PD-ABL-326

Best available copy

PD-ABL-326
95265

WORLD ENVIRONMENT CENTER

Waste Minimization Impact Project

Akmenes Cementas,
Akmene, Lithuania

Trip #1 and #2 Report

October 5 - 11, 1994 and
January 18 - 27, 1995

World Environment Center
419 Park Avenue South, 18th floor
New York, N.Y. 10016

June, 1995

DISTRIBUTION

Michael Kalinoski,	Senior Environmental Specialist, Bureau for Europe and New Independent States, United States Agency for International Development, Washington, D.C.
Patricia A. Swahn,	Acquisitions Manager, Document Acquisitions, United States Agency for International Development, Washington, D.C.
John J. Cloutier,	AID Representative, United States Agency for International Development, Vilnius, Lithuania
Nicholas Jenks,	General Development Officer, United States Agency for International Development, Vilnius, Lithuania
Simonas V. Anuzis,	General Director, Akmenes Cementas, Akmene, Lithuania

Antony Marcil, WEC
George Carter, WEC
Thomas J. McGrath, WEC
Romuald Michalek, WEC
Prabodh Shah, WEC
Jonas Kapturauskas, WEC Coordinator, Lithuania

Leonardos Rinkevicius, Manager, Pollution Prevention Center, Lithuania

Frank C. Stevens, Stevens Consulting Co.
Franklin A. Phillips, Phillips Environmental Training and Resource Associates, Inc.

(2) File

DISCLAIMER

The opinions expressed herein are the professional opinions of the author and do not represent the official position of the Government of the United States or the World Environment Center. This report is not for distribution without written approval from the U.S. Agency for International Development, Washington, D.C. or the World Environment Center, New York.

TABLE OF CONTENTS

I.	Introduction	1
II.	Executive Summary	2
III.	Appendix A ..... Frank C. Stevens-Report	3
IV.	Appendix B ..... Supplemental Technical Information	11

I. INTRODUCTION

Pursuant to the technical assistance program for Central and Eastern European countries funded by the United States Agency for International Development (USAID), the World Environment Center (WEC) team visited Akmenes Cementas (Akmenes) in Akmene, Lithuania on October 5 through 11, 1994 and January 18 through 27, 1995. The purpose of these visits was to assist Akmenes in implementing WEC's Waste Minimization Impact Project (WMIP). During the visits the WEC team identified several waste minimization opportunities for Akmenes and recommended equipment and process modifications.

II. EXECUTIVE SUMMARY

During October 5 through 11, 1994, volunteer experts, Frank C. Stevens and Franklin A. Phillips, and WEC Project Manager, Gretchen Mikeska, visited Akmenes Cementas (Akmenes) in order to review the work accomplished by Akmenes' Waste Minimization Committee (WMC) in regards to the Waste Minimization Impact Project (WMIP). A report on the WMC's accomplishments is provided in Appendix A and includes participation of the two cement consultants, A. Ivanauska and J. Kerzys, hired jointly by Akmenes and WEC in 1994.

During the January 18-27, 1995 visit, several waste minimization projects were discussed. The implementation of these proposed projects will result in savings on fuel, materials, and water, as well as reduce emissions.(Appendix B-3).

In September of 1994, the Lithuanian Environmental Agency (LEA) tested emissions by Akmenes. Results indicated that excessive particulates and gases were being emitted into the atmosphere. The WMC, volunteer experts, and WEC concluded that particulates and toxic gas (CO, NOx, and SO_2) emissions could be reduced while cutting cost by installing instrumentation and equipment designed to optimize the production process. Akmenes requested that WEC obtain quotations from manufacturers of O_2 and CO analyzers, as well as infrared pyrometers.

Purchase of a pyrometer and portable gas analyzer is scheduled for May 1995(Appendix B-5). The instrumentation is being financed by WEC and Akmenes. Further improvements are being considered for financing under USAID's pilot Environmental Action Program(EAP). Details of site visits by a USAID - EAP team to Akmenes was documented in a report which states that a $3.0 million USD expenditure for equipment would result in fuel savings of over $2.5 million USD annually. Improvements are estimated to reduce particulates, and gaseous CO, NOx, and CO_2 emissions by almost 50% and allow Akmenes to comply with LEA regulations. Funding for the improvements is currently being sought by USAID.

In May of 1995, WEC Project Manager, Prabodh Shah, and volunteer expert, Frank C. Stevens, plan to visit the plant to assist with the installation of the WEC/Akmenes purchased equipment and training.

III. APPENDIX A

Report of Frank C. Stevens, Stevens Consulting Co.

AKMENES CEMENTAS

Akmene, Lithuania

TABLE OF CONTENTS

1.0 Introduction 5

2.0 Findings and Observation 5

2.1 Description of the Plant 5

2.2 Waste Minimization Committee Activities 6

2.3 WEC Training Session 6

2.4 Asbestos Conversion 6

2.5 Alternative Fuels: Gas, Coal, Petroleum Coke Solid Wastes, and Tires 6

2.6 Proposed Plant Improvements 7

3.0 Conclusions and Recommendations 7

3.1 Akmenes Action Items 7

3.2 WEC Activity Items 7

3.3 Consultant Assignments 8

3.4 Other Recommendations 8

4.0 USAID - WEC Funding Program 8

4.1 Expenditures required for Emissions Reduction 9

1.0 Introduction and Background Information

The World Environment Center (WEC) is an independent, not-for-profit, non-advocacy organization headquartered in New York City. Established in 1974, WEC contributes to industrial development by improving industrial and urban environments, as well as health and safety practices. WEC provides "pro bono" assistance via environmental waste minimization programs to industries in developing countries using volunteer experts from industrial, academic, and governmental organizations.

This report describes the first (October 5-11, 1994) and second (January 18-27, 1995) visit by WEC managers and volunteer experts for implementation of the WMIP at Akmenes. Prior to WEC's WMIP activities, an eight day environmental assessment had been conducted at Akmenes in January, 1994. This project contributed greatly to WEC's understanding of the plant's operations, concerns, and waste minimization proposals.

Akmenes has been chosen as a competing candidate for AID's pilot Environmental Action Program (EAP) in Lithuania. From January 19 through 26, 1995, a USAID team visited Akmenes to identify suitable EAP projects that produce both economic and environmental benefits. The proposed EAP project, totaling $3.0 US million in capital expenditures, recommends purchase of pollution control instrumentation and the process optimization of two kilns in plant #2. For reasons of confidentiality regarding Akmenes' financial information, details of the EAP project have not been included in this report.

2.0 Findings and Observations

2.1 Findings and Observations

Akmenes was one of the largest cement plants built by the Soviet Union(USSR) prior to 1990. The plant was situated in Akmene because of its excellent supply of raw materials. The first plant was built during 1949 to 1959. Its four small wet process kilns and grinding mills averaged an annual production of 1.0 million tons per year. The plant was expanded in the years 1967 to 1974; a second plant was built adjacent to the first structure with larger kilns and grinding mills. Since then, Akmenes' production capacity has increased to 2.0 million tons per year.

Raw materials used in cement production include limestone(85%), clay(12%), iron oxides(1.5%), and silica(1.5%). To produce a kiln feed slurry, water is added to the raw materials after they have been crushed and ground into a fine powder. The slurry is fed into large rotary kilns of 5 meters(m) diameter and 185m length, which are lined

with refactory brick and turn at 1 revolution per minute. At the discharge end of the kiln, a white hot flame (2000°C) is ignited using heavy fuel oil. The heat goes upstream while the rotating kiln moves the slurry downstream, which takes about 2.5 hours to travel through the kilns. The raw materials are subjected to intense heat and clinkered, forming cement compounds of silica, iron, aluminum and calcium. This clinker is ground in cement grinding mills with 5 per cent gypsum to form a fine gray powder called cement. This product, when mixed with 2 parts sand, 3 parts crushed stone, and 1 part water, forms concrete, the basic building material for all types of construction. In 1991, Akmenes produced 3.1 million tons of cement. Decreased demand from the Russian market consequently lead to a sale drop to 723,000 tons/year at Akmenes after 1994.

The Nos. 7 and 8 kiln now produce 800,000 tons/year, but could be modified to produce 1.0 million tons per year. Updating and improving these two kilns provides the best opportunity for Akmenes to reduce emissions and lower fuel costs.

2.2 Waste Minimization Committee Activities

Much of the work of Akmenes' Waste Minimization Committee(WMC) is described in detail in Appendix B-3. As part of the WMIP, a number of in-plant projects will be implemented that focus on personnel health and safety training, preventive maintenance, improved level of dust control and spill minimization, better level of process control, water and heat conservation, and lower energy usage.

2.3 WEC Training Program

During May and in October, 1994, WEC conducted a training workshops together with Akmenes' WMC. Additional training is scheduled for 1995.

2.4 Asbestos Plant Conversion

By July 1995, the asbestos fiber used in corrugated building panels and pipes will be replaced by synthetic fiber. A German company supplied the know-how and financed the conversion. This has been a good investment for both parties in that it's profitable and environmentally safe.

2.5 Alternative Fuels, Tires and Solid Waste

The use of tires and solid organic waste as an alternative fuel source was researched in 1994. Akmenes plans to install these facilities, if and when money becomes available. A firm quotation has been received for a tire/waste organics shredding system with a conveying line to the burner pipe for about $400,000 USD. Shredded solid fuels will be blown into burning zone of the kiln parallel to main oil burner, and will reduce fuel costs by about 10 percent. Low sulfur content of these alternative fuels will result in reduced SO_2 emissions. Funding of this project is being pursued under USAID's EAP.

2.6 Other Proposed Improvements

Details on the purchase of a portable gas analyzer and pyrometer is shown in Appendix B-5. The equipment would cost approximately $56,000 USD, however, payback is expected in three months through fuel savings. WEC will assist Akmenes in the purchase of the equipment and contribute $10,000 as part of the WMIP.

3.0 Conclusions and Recommendations

Since the initiation of the WMIP in January of 1994, the progress made at Akmenes Cementas has been satisfactory. The management is very capable and has kept the plant profitable.

Utilizing a portable gas analyzer and infrared pyrometer will help decrease particulate emissions and toxic gases.

As discussed previously and in section 4.0, total compliance with environmental regulations, as well as lower operating costs, can be achieved with the expenditure of $3.0 million USD.

3.1 Akmenes' Action Items

Akmenes' WMC should prepare a report on their activities for the first quarter of 1995. This report should include a summary of activities of in-country consultants working at Akmenes. In addition, a further series of emissions testing should be performed at the plant.

3.2 WEC Action Items

Frank C. Stevens is expecting information on Orimulsion, in reference to a very heavy crude oil from Venezuela, for possible use in kilns at Akmenes. The crude is extracted with steam resulting in a fluid with the fine particles of the water emulsion and oil. Power plants are using Orimulsion and can be used in cement kilns. It should cost less than Russian oil, approximately $50 USD per ton.

Akmenes requested data on kiln gas and particulate emissions from U.S. cement plants using wet process for handling raw materials and feed slurry to kiln. During the WEC sponsored U.S. Study tour in May and June, 1994, representatives from Broceni Cement plant(Latvia) and Akmene Cement plant(Lithuania) visited three wet process plants.

3.3 Consultant Assignment

The In-Country consultant report of activities at Akmenes to date was sent to WEC and Akmenes in April of 1995.

3.4 Other Recommendations

Equipment quotations are to be finalized by early March 1995, and WEC will place an order for the portable gas analyzer (Testoterm), and pyrometer (Quadtex) (see Appendix B-7). Shipment is pending upon receipt of Akmenes' portion of the funds.

4.0 USAID - WEC Funding Program

In January 19-26, 1995, a USAID selected team met in Akmenes and Vilnius to collect further information required for the pilot EAP in Lithuania.

The following persons were introduced during the first meeting on January 19, 1995:

- Brandon Prater, USAID, Europe & New Independent States, Washington, D.C.
- Nicholas Jenks, Regional Development Officer, USAID, Vilnius Lithuania
- Veslev Stecevic, Project Specialist, USAID, Vilnius Lithuania
- Dr. Zina Gaidrene, Professor of Economics, Vistanto Didzioj, Vilnius, Lithuania
- Dr. Romas Lenkaitis, Chemical Engineer, Lithuania National Environmental Strategy, Vilnius, Lithuania
- Simonas Vutis Anozis, General Director, Akmenes Cementas, Akmene, Lithuania
- Dr. Algimantas Mituzas, Technical Director, Akmenes Cementas, Akmene, Lithuania
- Gretchen Mikeska, Project Manager, World Environment Center, New York
- Frank C. Stevens, Cement Technical Consultant and Volunteer expert for the World Environment Center; Stevens Consulting Co., Yucaipa, California

A condensed version of the technical summary written by the EAP team is presented by Frank C. Stevens, volunteer expert, with the contributions by Akmenes' management and equipment suppliers.

4.1 Expenditures Required for Emissions Reductions

According to numerous studies by the WEC team during 1994 and 1995, Akmenes' management, and the EAP team, it was determined that installation of certain equipment to reduce emissions to acceptable levels and equipping Akmenes with an alternative fuel system to reduce fuel usage, and in turn operating costs, might represent an acceptable EAP project.

The two kilns selected for improvement, Nos 7 and 8, were installed in 1974 using Russian technology and do not meet US environmental standards. Hence, proposed changes are modeled after wet process plants in the United States where emissions meet environmental standards and the fuel economy is more efficient.

Proposed expenditures required for these improvements are described below:

	US Dollars
• Instrumentation, process controllers, testing equipment, gas analyzers(CO_2 and CO), electrical modifications, recorders and alarms for the more efficient kiln operation and control.....	$ 600,000
• Modify electrostatic precipitators (ESP) for exit gases from the two clinker coolers and the two kilns to order to increase recovery of clincker dust and kiln dust.....	$ 800,000
• Install shredding system for tires and solid organic wastes for alternative kiln fuel	$ 400,000
• Modify and improve kiln chain system for better heat recovery and lower dust emissions, provide for reducing air filtration in kiln system and provide better controllers to reduce fuel usage and gas flow	$ 400,000
• Modify and improve first section of clinker cooler, install high efficiency burner pipe and controls to improve fuel efficiency.....	$ 800,000
Total cost estimate.....	$3,000,000

This investment does not include the plant's costs for engineering, fabrication, installation, and adjustments. The Akmenes engineers are qualified to install this equipment needed for improvements. USAID is currently investigating a five year loan of $3 million beginning July 1, 1995. The sovereign guarantee by the Lithuanian government is possible.

Estimated fuel cost savings will be about $3 million USD a year with a production level of 800,000 tons per year (equivalent of 1.6 kilns operating 300 days a year) and at a current fuel cost of $100 per ton for Russian oil. The use of solid wastes will reduce fuel costs further, as well as reduce emissions.

Emissions reduction from the clinker cooler electrostatic precipitators and the kiln electrostatic ESP will result from lower gas volumes through the ESPs and better heat exchange. In addition, this will lead to lower fuel usage, better combustion, and improved collection efficiencies. Test results have shown that lower emissions rates should allow Akmenes to comply with LEA regulations.

Improved burner efficiency will reduce carbon monoxide (CO); oxygen (0_2) control and burner design will reduce nitrogen oxides (N0x); and alternative fuel usage using lower sulfur containing materials will reduce sulfur dioxide ($S0_2$)emissions. Other improvements will reduce exit gas temperatures and volume.

Lower, more acceptable kiln emissions and lower fuel costs will increase Akmenes' profitability and competitiveness.

A separate comprehensive USAID - EAP report has been issued with distribution limited to WEC, USAID and Akemenes management.

Section IV

APPENDIX B
Additional Technical Information

B-1	Itinerary of WEC mission to Akmenes Cementas, October 5-11, 1994 and January 18-26, 1995
B-2	Waste Minimization Committee(WMC) Members and Roles
B-3	Waste Minimization Committee Meeting Minutes - proposed projects
B-4	Gas Analyzer and Pyrometer Equipment Proposals/ Comparisons
B-5	Equipment Orders - Quadetk Pyrometer and Testoterm
B-6	The Use of Alternative Fuels in the Cement Industry
B-7	Air Emissions associated with the combustion of scrap tires for Energy Recovery
B-8	Akmenes Cementas - Company Background
B-9	Curriculum Vitae of Frank C. Stevens and Frank Phillips

B-1

Itinerary of WEC mission to Akmenes Cementas,
October 5-11, 1994 and January 18-22, 1995

- October 5 and 6, 1994. Akmenes: Discussion of plant issues and waste minimization opportunities.
- October 7, 1994. Vilnius: attended Lithuanian Building and Products trade show and seminar.
- October 8, 1994, Akmenes: Plant presentation on operations and financial status.
- October 9, 1994, Akmenes: Continued discussions on waste minimization opportunities.
- October 10, 1994. Akmenes: Presentation by Franklin Stevens on alternative fuels.
- October 11, 1994, Riga: Travel back to the U.S.

January 18 through 27, 1995:Continued activities on WEC waste minimization project and discussions relating to potential EAP projects.

B-2

Waste Minimization Committee Members and Roles

- A. Wanauska - Consultant
- A. Mituzas - Technical Director
- J. Mituzas - Engineering
- V. Elzbergas - Maintenance
- V. Montvila - Production
- L. Antanelis - Environmental
- D. Binkuliene - Materials Control
  Quality Control

B-3

Waste Minimization Committee meeting minutes - Proposed Projects

STOCK COMPANY "AKMENĖS CEMENTAS"

THE MINUTES

of Waste Prevention Committee (WPC) meeting, held on the5of December, 1994

The members of WPC, present at the meeting:
Mr.A.Mituzas, leader of assessment group.
A.Ivanauskas and J.Keršys, leaders of contract work.
V.Elzbergas, manager of engineering.
V.Montvila, manager of operation.
G.Litvinovas, the chief of safety.
J.Mituzas, Rand D.
L.Antanėlis, the chief of environmental protection.

Discussed:

1.The projects of possible waste reducing ways at Stock Company "Akmenės cementas" were introducal by Mr.A.Ivanauskas and Mr.J.Keršys, WEC advisers. The projects were approved by the members of the committee.

2.The members listened to the text of the appeal to the employees of Stock Company "Akmenės cementas". The text was presented by Mr.A.Ivanauskas, member of WRC.

3.The general situation of environmental protection at the Stock Company "Akmenės cementas" was discussed and evaluated. Mr. L.Antanėlis introduced the members to the results of measuring control tests of hazardous wastes, that had been performed by Šiauliai regional agency.

4.The members of the committee approved Mr.J.Keršys' suggestion to meet with the chieves of workshops (departments) and discuss the shortcomings of waste reduction at tha place, estimating the real possibilities for eliminating defects.

5.It was decided to publish the material on problems of environmental protection, prepared by Mr.A.Ivanauskas and J.Keršys, in the local newspaper "Vienybė".

Mr.L.Antanėlis, secretary of the committee

Projects of Possible Waste Reducing Ways at Stock company "Akmenes Cementas"

I. Utilizing the redundant heat, produced while cooling clinker and reducing dust issues into the atmosphere.

Data:

redundant air amount $135000^{n}/m^{3}/h$

redundant air temperature $210^{o}C$

irrevocable clinker dust cleared away 8,12 kg/h

(from GIPROCEMENT report)

Variant 1.

We use 35084 $^{n}/m^{3}/h$ at $210^{o}C$ temperature, i.e.26 % as primary air into the kiln thus we reduce conventional fuel expenditure by 1,68 kg/h for one kiln, and at the same time we reduce cleared away clinker dust by 21,1 kg/h.

The Result:

a) economy of fuel and less poluting air by burned waste products;

b) reduced air polution by clinker dust.



1. Clinker cooler
2. Electrical precipitator
3. Ventilator
4. Kiln
5. Redundant air
6. Primary air
7. Fan

Variant 2

The heat of redundant heated air is utilised for heating up the premises of heating section (part/field) and for heating water for shower baths.

A collector, resistant to mechanical effect of clinker particles, is installed in the redundant air pipe-line that is between the cooler and eletrical precipitator. Water from water-supply is circulating in the collector. The water is heated up to 80°C and is being accumulated in 5 m^3 reservoir. This water is used for shower-baths. During the rest of the time water is used for heating up premises. There is a circulating pump equiped there.

360000 kcal/h would be needed to heat 5 m^3 of water up to 80°C. Thus using the redundant air heat we will save up 37 kg of fuel oil per 24 hours or 51,8 kg of comentional fuel per 24 hours.



1. Kiln
2. Cooler.
3. Redupdant air pipe-line, leading to electrical precipitators.
4. Water heating collector.
5. El.precipitator.
6. Pipe-line from el.precipitator to ventilator.
7. Fan.
8. Pipe-line out into the atmosphere.

Variant 3

The heat of redundant hot air is used for heating milling premises and for heating water for shower-baths.

The water is heated up to ↓ 80°C and is being accumulated in 5 m^3 reservoir (such amount of water is used for shower-baths per 24 hours). During the rest of the time premises are being heated up. The circulation of the water is kept going on by a separate pump. The loss of the water is recovered from

the water -supply. The collector is installed in the redundant air pipe-line behind the electrical filter.

The amount of saved up fuel makes up about 37 kg of fuel oil per hour (while burning it, there will be some hazardons burnt wastes).



1.Kiln
2.Clinker cooler
3.El.precipitator
4.Dedundant air pipe-line behind the filter
5.Water heating collector.
6.Fan
7.Pipe-line out into the atmosphere

II Utilization of kiln issued gases heat (average temperature ↓ 250°C).

Having installed ø 390 mm 2-way pipe-line in dust suppressing chambers and having lead those pipes to the premises situated above those dust chambers, it is possible to heat up 480 m^3 slur dosing premises by heated air. The heat conductivity factor of these premises is 0,28 . About 16700 kcal/ per hour would be needed for heating up these premises and for maintaining ↓ 10°C temperature.

We save up about 3000 kg of conventional fuel per year for heating slur dozing premises of one kiln.

Respectively the polution of atmosphere by burnt hazardons wastes is reduced.

And there is no need of expensive and complicated water or vapour heating system.



1.Kiln
2.Dust chamber
3.El.precipitator
4.Pipe-line-collector
5.Heated premises

III.Utilization of raw material milling waste in further production.

While operating raw material mills some kind of watery waste is being washed down into the pump pit sand then it goes down a perpendicular dirt pump to the milled slurry pits. Thus slurrymoisture is being increased. This can be avoided by installing 1 m^3 reservoir above the raw material supplying chutes at the end filling up the raw material mill. Watery waste will be returned from the reservoir back to the mill with the help of a special valve (damper). For this purpose it is nesessary to install an extra ø 100 mm pipie-line along the mill.
By reducing slurry moisture we will reduce expenditure of fuel necessary for clinker burning process, and at the same time the atmosphere polution will be reduced.



1.Perpendicular dirt pump.
2.Pipe-line
3.Reservoir
4.Special valve
5.Raw material mill

IV. Improvement of cement mills aspiration system work.

It is neccessary:

a) to install a sensing element for fixing and signalling rarefying changes in the chambers of bag filter;

b) to install a sensing element for fixing and signalling changes of dustiness in the pipe discharging waste into the atmosphere.

This would enable the supervisor of filters to notice holes in filter bags in time, to define worn out spots and eliminate the defect;

c) to install hermetic (tight) bolts under the cydone and thus make their work more effective.

These means will help to minimize the polution of the atmosphere in general, and, especially, they will minimize casual emission of waste.



1. Cement mill
2. Cyclone
3. Sensing elements in the chamber of the filter
4. Sensing element in the discharging pipe.
5. Bolt

V. Warming up of fuel oil by secondary (used) air (↓ 300°C).

It is worthwhile to utilize the heat of secondary (used) air for warming fuel oil up to its necessary parameters (↓ 110°C). This enables us to minimize heat energy for warming fuel oil up.

For this purpose we need to install pipe-line-collector in the pit of the cooler.

a) Heat losses in long vapour(steam) and fuel oil pipes will be reduced.

h)Fuel expenditure in vapour (steam) boiler house will be minimized.

At the same time less burnt waste will be issued into the atmosphere.



1-Cooler
2-pit
3-collector
4-kiln

VI.Heating up of premises in the I st production headquarters by utilizing of the heat of gases issued into the atmosphere by the cooler "Volga 35".

The aim is to heat the water up and warm the premises up by utilizing the heat of hot gas waste issued into the atmosphere. This could be done by installing water heating equipment, in redundant air discharging opening of the cooler "Volga 35". The fluctuation of issued gases temperature is 130° ÷ 280°C. 150.000 Kcal per hour are used for warming 5 m^3 of water up to 80°C, that will correspond to 15 kg of fuel oil.



1.Opening of the cooler.for discharging redundant air.
2.Water heating equipment.
3.Pipe-line
4.Water pump
5.Heating radiators

VII. Making hermetic dust emission junctions of electric precipitators by minimizing suction of cold air into electric precipitators.

The aim is to minimize suction of cold air into eletric precipitators. This will enable to reduce the amount of dust issue into the atmosphere and lengthen the period of precipitator usability.
It is necessary to optimize the operation of the levers of dust discharging equipment, as well as the planes of closing equipment itself in order to avoid suction of cold air.

VIII. Utilization of aspirated air from the cooler "Volga 35" for drying fuel in the coal mill and for supressing dust in the general system.

[illegible] of gases issued from the cooler [illegible] drying fuel in the coal mill and for supressing clinker dust in the general system.
The gases are cleaned in the cyclone and the extent of their cleaness is about 85 %. It is urgent to use this air in fuel burning process as it enables to avoid dust emission into the atmosphere.



1. Cooler
2. Cyclone
3. Fan
4. Coal mill
5. Coal milling cyclone
6. Fan
7. Screw conveyer of milled fuel
8. Bunker of milled fuel
9. Kiln
10. Clinker transporter
11. Dust discharging pipe
12. Fuel supplier

B-4

Gas Analyzers and Pyrometer Equipment Proposals and Comparison

1149 RARIG AVE.
COLUMBUS OH 43219

SIMCO controls

1149 RARIG AVE.
COLUMBUS OH 43219

NA108

QUOTATION NUMBER
1005056-0000-01

QUOTATION NUMBER
1005056-0000-01

NEW ACCOUNT

GREG CARSON

HARRY BHATT

MALCOLM PIRNIE
445 HUTCHINSON AVENUE
SUITE 350
COLUMBUS OH 43235-5667
HARRY BHATT

QUOTATION***QUOTATION******QUOTATION******QUOTATION******QUOTATION***

QUOTATION NUMBER	SLSMN.	QUOTE DATE	TAKEN BY	INQUIRY NUMBER/NAME		PAGE
1005056-0000-01	108	12/15/94	153	HARRY BHATT		1

QUOTATION

SHIPPING INFORMATION

SHIP BEST WAY ATTN: HARRY BHATT

FRT. P

QUANTITY			E D P NUMBER		MANUFACTURER • CATALOGUE NO. • DESCRIPTION	U/M	UNIT PRICE	AMOUNT
					**** 1984-1994 "10" YEARS **** ****** OF EXCELLENCE! ******			
1					*BA SMA21411 SMART O2 & COe ANALYZER W/1500 DEG F PROBE W/OPTIONAL DUAL FILTER W/120 VAC BLOWBACK SOLENOID => 220V / 50Hz W/2-STAGE AIR FILTER W/50-FOOT CABLE BAILEY CONTROLS	EA	8657.00	8657.00

plus spare parts

TERMS AND CONDITIONS

1. Our terms are [redacted], net 30.
2. This quotation is a firm quotation for a period of 30 days from above date. We reserve the right at any time to correct clerical errors.
3. Shipping promises or delivery promises date from receipt by us of complete specifications.
4. Material in stock is offered subject to prior sale
5. All claims for shortages and damages must be received by us within 30 days from date of invoice.
6. Simco Controls shall not be liable for any delay in the performance of this contract, or the delivery or shipment of goods, or for any damages suffered by the Buyer by reason of such delay when the delay is directly or indirectly caused by any cause beyond the control of Simco Controls.

TOTAL CONTINUED

THANK YOU FOR YOUR INQUIRY! MAY WE HAVE THE PLEASURE OF ENTERING YOUR ORDER?

If This Quotation Is Accepted, Please Sign And Return 1 Copy.

DATE

ACCEPTED BY

COLUMBUS • CINCINNATI • CLEVELAND

SIMCO CONTROLS

1149 RARIG AVE.
COLUMBUS OH 43219

NA108

QUOTATION NUMBER
1005056-0000-01

NEW ACCOUNT

GREG CARSON

HARRY BHATT

SIMCO controls

SIMCO CONTROLS

1149 RARIG AVE.
COLUMBUS OH 43219

QUOTATION NUMBER
1005056-0000-01

MALCOLM PIRNIE
445 HUTCHINSON AVENUE
SUITE 350
COLUMBUS OH 43235-5667
HARRY BHATT

QUOTATION***QUOTATION******QUOTATION******QUOTATION******QUOTATION***

QUOTATION

QUOTATION NUMBER	SLSMN.	QUOTE DATE	TAKEN BY	INQUIRY NUMBER/NAME		PAGE
1005056-0000-01	108	12/15/94	153	HARRY BHATT		2

SHIPPING INFORMATION

SHIP BEST WAY ATTN: HARRY BHATT

FRT.

QUANTITY			E D P NUMBER		MANUFACTURER • CATALOGUE NO. • DESCRIPTION	U/M	UNIT PRICE	AMOUNT
1					*BA SMA21511 SMART O2 & COe ANALYZER W/3000 DEG F PROBE W/120 VAC BLOWBACK SOLENOID W/2-STAGE AIR FILTER W/50-FOOT CABLE BAILEY CONTROLS ~~~~~~~~~~~~~~~~~~~~~~~~~~ TERMS: NET 30 DAYS FOB: COLUMBUS, OH FRT: PREPAY & ADD DELIVERY: 4-8 WEEKS ARO (TO DOMESTIC US DESTINATION) ~~~~~~~~~~~~~~~~~~~~~~~~~~ CONTACT INFO: HARRY BHATT PH: 614-888-4953 FX: 614-888-6295	EA	9025.00	9025.00

Don't need 3000°C probe

TOTAL 17,682.00

TERMS AND CONDITIONS

1. Our terms are [redacted] net 30.
2. This quotation is a firm quotation for a period of 30 days from above date. We reserve the right at any time to correct clerical errors.
3. Shipping promises or delivery promises date from receipt by us of complete specifications.
4. Material in stock is offered subject to prior sale.
5. All claims for shortages and damages must be received by us within 30 days from date of invoice.
6. Simco Controls shall not be liable for any delay in the performance of this contract, or the delivery or shipment of goods, or for any damages suffered by the Buyer by reason of such delay when the delay is directly or indirectly caused by any cause beyond the control of Simco Controls.

THANK YOU FOR YOUR INQUIRY! MAY WE HAVE THE PLEASURE OF ENTERING YOUR ORDER?

DATE

Bailey PRODUCT SPECIFICATION

E65-76

Smart Analyzer 90
Type SMA

SIMCO CONTROLS
1149 RARIG AVE.
COLUMBUS, OH 43219
614-253-1996



A1045

Figure 1. Type SMA Smart Analyzer 90

The Type SMA Smart Analyzer 90 is a combustion analyzer. It continuously samples and analyzes industrial flue gases. The Type SMA1 Smart Analyzer 90 monitors oxygen (O_2) only. The Type SMA2 Smart Analyzer 90 monitors both O_2 and carbon monoxide equivalent (CO_e).

Features/Benefits

New Rugged Industrial Design. The stainless steel heater block, extrusion honed metals and corrosion resistant plastics have hardened this rugged design. The Type SMA Smart Analyzer 90 is built to withstand demanding utility, petrochemical and other industrial applications.

Highly Accurate Sensors. The patented O_2 sensor is a reliable zirconium oxide design. It has built in contaminate protection and an integral self-controlled heater for longer life expectancies. A catalytic type, RTD based sensor is used for the CO_e measurement. The high sensitivity of the RTDs combined with the poison resistant catalyst provides improved performance. The accuracy of both O_2 and CO_e measurements are not affected by flue gas temperature, particulates or variations in either water vapor or carbon dioxide.

Self-Diagnostics and Alarming. The microprocessor based electronics continuously analyzes and monitors the operation of the sensors, analyzer and combustion process. Sensor calibration data is normalized against known test gas concentrations to warn of an impending sensor failure. Analyzer alarm messages display on the screen in English. Form C relay contacts are provided for alarms.

Patented Close Coupled Sample System. The close coupled sample system saves maintenance time and increases the life of the sensor when compared with in situ measurement techniques. The floppy filter removes flue gas particulates before analysis while the patented self cleaning action eliminates filter build up and plugging. The industry proven hot gas sample system uses heated passages to keep the process sample at a temperature above dew point to ensure trouble free operation.

High Temperature Operating Range. The analyzer assembly with the standard stainless steel probe and floppy filter assembly handles flue gas temperatures up to 649°C (1200°F). Other optional probe and filter assemblies are available for temperatures up to 1650°C (3000°F).

- **Easy Installation and Start up**. Flange mounting, plug in cable connectors and menu driven start up procedures significantly reduce installation, commissioning and operator training times.

- **Simplified In House Maintenance**. The sensors are field replaceable without having to remove the sensor assembly. Easy access is provided to all sensor components and electrical connections. Extensive self-diagnostics and optional filter blowback further reduce maintenance requirements

- **Automatic Sensor Calibration (Standard)**. The automatic calibration permits unattended operation and eliminates periodic labor intensive calibration checks required by other analyzers. Calibrations can be programmed to start automatically at specific intervals, manually via the operator interface or remotely by contact inputs. Contact outputs indicating calibration alarms and calibration in progress signal external control systems of the analyzer calibration status.

- **Low Cost Integrated Solution**. No other combustion analyzer provides both O_2 and low range CO_e measurements, automatic calibration and efficiency calculations in a single, low cost package.

- **On Line Combustion Efficiency Calculation (Standard)**. The Type SMA analyzer can work with existing boiler controls to achieve maximum fuel efficiency.

- **Remote Blowback (Optional)**. The analyzer may be fitted with an optional dual filter and remote blowback solenoid to offer added protection in applications with abnormally high levels of fine particulate (i.e., cement and lime kilns).

- **Distinctive Operator Interface**. A ten key keypad and a two line 80 character vacuum fluorescent display provide a highly visible, menu driven operator interface. Front panel mounted LEDs readily indicate the status of the analyzer.

Product Overview

The Type SMA Smart Analyzer 90 (see Figure 1) is a microprocessor based industrial grade combustion analyzer that continuously samples and analyzes industrial flue gases. The analyzer is designed for use on gas, oil or coal fired combustion processes. Typical applications include those found in the utility and petrochemical industries. The Type SMA1 analyzer monitors the oxygen (O_2) using a single sensor design. The Type SMA2 analyzer monitors both the O_2 and the unburned carbon monoxide equivalent (CO_e) using a dual sensor design.

The O_2 reading indicates the percent by volume measurement of the oxygen. Typically, the O_2 reading is the primary indicator for combustion applications. The CO_e measurement is often used to optimize combustion control in terms of efficiency and emissions.

The analyzer consists of a sensor assembly, probe and filter assembly, microprocessor based electronics assembly and interconnecting cable assembly (see Figure 2). Standard features include automatic and remote initiation of the sensor calibration, inlet/outlet temperature measurements for calculating combustion efficiency, integrated flashback protection, alarms with Form C relay contacts and isolated outputs.

See Figure 3 for the outline and clearance requirements of the sensor assembly. See Figure 4 for the outline and clearance requirements of the electronics assembly. See Figure 5 for the analyzer installation overview. Refer to Table 1 for the product specifications. Refer to Table 2 for the product nomenclature. Refer to Table 3 for a list of accessories.



Figure 2. Smart Analyzer Assemblies



Figure 3. Outline and Clearance Requirements (Sensor Assembly)



Figure 4. Outline and Clearance Requirements (Electronics Assembly)



Figure 5. Analyzer Installation Overview

VII. Pyrometer Comparison

1. The Davis M-400D unit is suspect regarding durability and application to constant cement kiln conditions. It's use is not advised without further information obtained from Davis, plus references from cement plant users.

2. The Everest 4000B and the Quantum Logic QL 3200F-3A units both should serve well as intermediate investment equipment selection. Use of these units requires understanding their operation, understanding their limitations, frequent parts cleaning and replacement, plus frequent visual inspection of the kiln flame to coordinate correctness of flame temperature readings (i.e., to make sure that it is the flame temperature that is being monitored, and not the side was (clinker) temperature). Frequent mechanical checks, calibration, and parts replacement is to be expected.

3. While the Quadtek Spyrometer is markedly higher in cost than non-scanning, non-imaging pyrometers, it is clearly the instrument of choice for advanced burner control / performance information. One distinct advantage is that if process changes should occur that would interfere with accurate temperature measurement, these changes would not only be displayed on the monitor, but remote repositioning of the pyrometer to the correct measuring point could be accomplished. Another advantage is the display of temperature measurement from up to six selectable points in the field of vision. The size of each of these six points is programmable, plus the system (unit) can determine the average temperature, peak (maximum) temperature, and minimum temperature within each region. Wide angle viewing of the field of interest is allowed.

Installation and application of this unit is not advised without employing either a Quadtek service professional, or WEC consultant familiar with the installation, operation and trouble-shooting of the Quadtek unit.

Instrument Manufacturer / Model	Portable, or Fixed	Calibration	Temperature Range / Accuracy	Field of View / Window Material / Microns / Scan Rate	Enclosure Material / Maximum Ambient Temperature	a. Focus Adjust / b. Video Level Adjust / c. Weight	Operating distance / Special features	Image Processor	Air cooling / Water cooling	Cost (shipping not included)
Quadtek M551 Integrated Scanning Pyrometer	Fixed: can be moved to second mounting	I.N.A.	759-1816 °C 1398-3250°F ± 1%	30:1 / Sapphire / Every 10 secs.	Nema 4 Waterproof Anodized Aluminum 20° F with vortex cooling	a. Screw, located on rear b. Auto-iris accessible from rear c. 30 lbs.		M201B x Targets: Min/Max/Ave t / on-screen graph of data	M405 at $1,250	$40,000 plus installation
Everest 4000B	Fixed mount	Model 1000 Kit at $765	30 to 1200 °C -22 to 2200 °F / I.N.A.	Fixed, selectable 2°, 15°, or 60° / Every 1 second	I.N.A. / 120°F	a. b. c.	2 cm to 300 m			$1,089 sensor 765 calib 435 trans 1,000 monit 500 cable $3,889 total
Quantum Logic QL3200F-3A	Fixed mount	I.N.A.	290 to 1650°C 550 to 3000°F / I.N.A.		I.N.A. / 140°F	a. b. c.			QL30R at $125 / QL303 at $150	$4,250 total
Davis M-406D	Fixed mount	I.N.A.	800 to 1500°C 1500 to 2700 °F / ± 1%	Fixed, selectable 1° or 4°	I.N.A. / 120 °F or add cooler	a. b. c.			AP 400 at $88 / yes	$ 630 sensor 73 frame 63 bracket 38 lock nut 88 air purge 248 water 403 linarizer 1,543 total

I.N.A. = Information Not Available

a - calibration kit b - transmitter c - monitor

Pyrometer Comparison & Quotes

Theory of Operation

The sensor assembly flange mounts to a duct or rocess wall so that the probe and filter assembly rotrudes into the flue gas stream. The probe and filter ssembly draws in the sample which is then analyzed by e sensor assembly. Electrical outputs from the sensors re fed through the interconnecting flexible cable to the lectronics assembly for analysis. The electronics ssembly analyzes the flue gas measurements and ansmits the resulting data accordingly.

ensor Assembly

The Type SMA Smart Analyzer 90 is based on 50 ars of proven reliability and expertise in analytical uipment development. These sensors provide a fast, curate and continuous percent by volume measurement alysis that is not affected by particulates or by mperature fluctuations.

The NEMA 4X sensor assembly mounts to a duct or ocess wall so that the probe and filter assembly otrudes into the flue gas stream. An air powered pirator creates a suction pressure to draw the process s through the patented floppy filter. The floppy filter's lf-oscillating motion filters the process gas sample and moves particulate build up from the filter.

The Type SMA analyzer uses a hot gas sample system at measures the flue gas samples on a wet basis by eping all metal parts at a temperature above dew point. is prevents acidic vapors from condensing on sampling rfaces. Once in the sensor assembly, the incoming ocess gas is split into two separate heated ssageways. One passageway diverts the sample to highly reliable zirconium oxide sensor where the ocess gasses are analyzed for net oxygen content. is patented O_2 sensor contains a built in heater to gulate its own temperature. The other passageway erts the sample to the catalytic combustibles CO_e nsor where the process gases are analyzed for mbustible content. As the sample passes through a heater mixing chamber, dilution air is added at a fixed e to ensure a repeatable and reliable combustibles asurement. The diluted sample then flows into the O_e sensor which consists of two RTD rods. One rod s as a reference and the other is coated with a catalyst t oxidizes or burns the combustibles on the rod surface. e temperature rise of the catalyzed RTDs (relative to reference RTD) represents the CO_e concentration.

After the process gas is analyzed by the sensors, it is nbined with the aspirating air and is sent back into the t through the aspirator exhaust filter. Electrical outputs n the sensors are fed through the interconnecting ible cable to the electronics assembly for analysis.

Electronics Assembly

The NEMA 4 electronics assembly provides the microprocessor based architecture and overall intelligence necessary to monitor sensor calibrations, field input/output (I/O) signals, and the operator interface. The electronics assembly controls the flange manifold and CO_e block temperature. The low level analog signals received from the O_2 and CO_e sensors are amplified and converted into 4 to 20 milliamp or 1 to 5 VDC outputs.

The field I/O signals consist of both analog and digital formats. Four analog outputs are available for O_2, CO_e, efficiency and temperature. Six digital Form C alarm contacts are available for oxygen, combustible, temperature, efficiency, diagnostics and calibration in progress. The electronics accepts two thermocouple inputs for combustion inlet air temperature and flue gas outlet temperature. Four digital inputs are available for remote calibration, blowback, check gas insert and fuel efficiency select.

The operator interface consists of a highly visible vacuum fluorescent display with two lines of 40 characters each. Setup options such as output ranges, alarm limits, calibration data and efficiency information are adjusted using the keypad. Modification of system parameters is security code protected with a three character user definable password.

Automatic Calibration (Standard)

The Type SMA analyzer contains an automatic sensor calibration feature which uses test gases of known concentrations to calibrate both sensors and ensure continual accuracy. Solenoids required to route calibration gases to the sensor assembly are incorporated into the electronics assembly.

All zirconium oxide O_2 sensors analyze flue gas samples by measuring the partial pressure of the oxygen in the sample with respect to an air reference. If the duct or process pressure changes, the partial pressure of oxygen also changes. Calibration of the sensor automatically corrects for sensor and duct pressure changes since the last calibration.

The automatic calibration is an eleven minute sequence that includes filter blowback (if ordered) as well as insertion of zero and span gas. Sensor calibration can be selected to occur as frequently or infrequently as desired and at any time of the day or night without operator or process intervention. Manual and remote calibrations can also be initiated via the operator interface or contact inputs.

Table 2. Product Nomenclature

Position	4	5	6	7	8	SMART ANALYZER 90	
Type SMA	☐	☐	☐	☐	☐		
						Measurement	
	1					O_2 only	
	2					O_2 and CO_e	
						Cable Length	
		1				Standard 15 m (50 ft)	
		2				Optional 30 m (100 ft)	
		3				Optional 46 m (150 ft)	
						Probe and Filter Type	**Probe and Filter Length**
			1			Standard Probe with Filter 649°C (1200°F)	1.5 m (4.8 ft)
			2			Standard Probe with Filter 649°C (1200°F)	2.4 m (7.8 ft)
			3			Standard Probe with Optional Dual Filter 816°C (1500°F)	1.8 m (5.8 ft)
			4			Standard Probe with Optional Dual Filter 816°C (1500°F)	2.7 m (8.8 ft)
			5			Optional High Temperature Probe with Filter 1649°C (3000°F)	1.6 m (5.1 ft)
						Blowback	
				0		None	
				1		120 VAC Solenoid	
				2		240 VAC Solenoid	
						Instrument Air Filters	
					0	None	
					1	Two Stage Filter System	

Table 3. Accessories

Accessory	Kit No.	Application
Blowback Solenoid	258525_1 (110 VAC) 258525_2 (220 VAC)	Performs a preventative maintenance activity to momentarily direct high pressure aspirating air to clean the probe and filter assembly.
Panel Mount Kit	258524_1	Allows for the electronics assembly to be panel or rack mounted.
Adapter Flange Kit	258407_1	Standard mounting uses a 2-in. flange. The kit contains an adapter piece for mounting to a 3-in. or 4-in. flange. This kit is included with the optional high temperature probe and filter assembly.
Probe Flange Kit	258536_1	Isolates probe and filter from the sensor assembly to ease maintenance in a positive pressure application.
Maintenance Kit	258432_1	Includes three-way valve and two pressure gauges used to measure suction and sample pressures.
Instrument Air Filters (ok - seems included)	258560_1	Recommended to clean instrument air before it enters the analyzer.
Test Gas Kit	258274_2	Portable maintenance test gas kit for one or two calibrations. Not meant to replace customer supplied test gas.

Table 4.
Plus Spare parts similar to Ametek

Table 1. Specifications

Property	Characteristic
Variable Analog Output Ranges ok	
O_2	Minimum 0 to 5 % Maximum 0 to 25 %
CO_e	Minimum 0 to 200 ppm (0 to 0.02 %) Maximum 0 to 20000 ppm (0 to 2 %)
Temperature	Minimum -18 to 260°C (0 to 500°F) Maximum -18 to 1649°C (0 to 3000°F)
Accuracy ok	
O_2	± 2.5 % of reading
CO_e	± 20 ppm of reading (span less than 1000 ppm) ± 2% of span (span greater than 1000 ppm)
Temperature	± 3.3°C (6.0°F)
ok **Ambient Temperature Effect**	
O_2	± 2.5 % of reading per 56°C (100°F)
CO_e	± 2.5 % of span per 56°C (100°F)
Temperature	1°C per 100°C (1°F per 100°F)
ok **Measurement Errors Due to Flue Gas Variables**	
CO_e	None
Water Vapor	None
Particulate	None
Temperature	None
ok **Sensor Response Time to 63% of Span**	
O_2	Less than 3 seconds
CO_e	Less than 18 seconds
Power Supply Requirements	
Supply Voltage	105 to 128 VAC, 47 to 63 Hz or 211 to 257 VAC, 47 to 63 Hz -220 V 50 Hz
Power (during start-up)	730 W
Power (operating)	310 W
Air Supply Pressure	208 kPa at 15.6 l/min (30 psig at 0.55 scfm)
Input Signals	
Two Analog	Type E, J, K, R, S or T (customer supplied, isolated[1])
Inlet T/C: Ambient Air Temperature	Biocini to supply 2 thermocouples
Outlet T/C: Flue Gas Temperature	
Four Digital	120/240 VAC, 50/60 Hz or 24 VDC
DI1: Remote Calibration	220
DI2: Remote Blowback	
DI3: Remote Check Gas	
DI4: Fuel Selection	
Output Signals	
Four Analog[2]	1 to 5 VDC or 4 to 20 mA (Isolated[3] or non-isolated)
AO1: Process O_2	
AO2: Combustibles (CO_e)	
AO3: Inlet/Outlet Temperature	
X AO4: Combustion Efficiency	
ok Six Isolated Digital[4]	Form C relay contacts rated for 2 A at 120/240 VAC, 50/60 Hz or 24 VDC (isolated)
DO1: Process O_2 Alarm	
DO2: Process CO_e Alarm	
DO3: Temperature Alarm	
DO4: Combustion Efficiency Alarm	
DO5: Analyzer Fault Alarm	
DO6: Calibration in Progress	

Table 1. Specifications (continued)

Property	Characteristic
Maximum Analog Output Loading	
Voltage Mode	250 kΩ, 600 mH
Current Mode	600Ω, 600 mH
Self Monitoring (Default Output)	
Digital Outputs	Alarm state: NC to COM is open and NO to COM is closed
Analog Outputs	Switch selectable to low or high output Low = 0 VDC or 0 mA High = 6.2 VDC or 25 mA
Probe and Filter Length	
Standard Probe and Filter	1.5 m (4.8 ft) or 2.4 m (7.8 ft)
Standard Probe and Optional Dual Filter	1.8 m (5.8 ft) or 2.7 m (8.8 ft)
Optional High Temperature Probe and Filter	1.6 m (5.1 ft)
Cable	
Standard Length	15 m (50 ft)
Optional Lengths	30 m (100 ft) 46 m (150 ft)
Minimum Bend Radius	17.8 cm (7 in.)
Maximum Diameter (Outside Diameter)	1.9 cm (0.75 in.)
Environmental	
Sensor Assembly (Pending)	NEMA 4X (indoor/outdoor)
Electronics Assembly (Pending)	NEMA 4 (indoor)
Maximum Probe and Filter Temperature	
Standard Probe and Filter	649°C (1200°F)
Standard Probe and Optional Dual Filter	816°C (1500°F)
Optional High Temperature Probe and Filter	1649°C (3000°F)
Ambient Temperature Limits	
Sensor Housing	-18 to 93°C (0 to 199°F)
Electronics Housing	0 to 60°C (32 to 140°F)
Cable	-18 to 93°C (0 to 199°F)
Humidity	
Sensor Assembly	95 % RH @ 93°C (199°F) non-condensing
Electronics Assembly	95 % RH @ 60°C (140°F)
Weight (Approximate)	
Cable Assembly	
Standard 15 m (50 ft)	7.3 kg (16 lbs)
Optional 30 m (100 ft)	14.5 kg (32 lbs)
Optional 46 m (150 ft)	21.8 kg (48 lbs)
Sensor Assembly	4.5 kg (10 lbs)
Electronics Assembly	9.1 kg (20 lbs)
Approvals/Certifications	
Factory Mutual (Pending)	Approved against flashback into duct
Factory Mutual (Pending)	Approved for use in Class I, division 2, groups B, C and D; and for use in Class II, division 2, groups E, F and G
Canadian Standard Association (Pending)	Certified for use in ordinary non-hazardous locations

An ungrounded or isolated thermocouple must be used. Cold junction compensation is provided.
AO2 (CO_2) defaults to 4 mA or 1.0 VDC when a Type SMA1 analyzer is installed.
Analog outputs can be selected for isolation in pairs. AO1 and AO2 define a pair and AO3 and AO4 define another pair.
DO2 (Process CO_2 alarm) defaults to normal state when a Type SMA1 analyzer is installed.

Specifications Subject to Change Without Notice

Ametex Quotation

MODEL WDG-HPIIC PPM

Item: 1
Quantity: 1
Ametek Model WDG-HPIIC Microprocessor Based Flue Gas Oxygen and Combustibles Analyzer for 115 VAC (230 VAC) 50/60 Hz operation in general accordance with Bulletin P-270 consisting of:

Sensor in stainless steel enclosure with lift-off cover and including:

1. Heaters to maintain components above the dew point of flue gas.
2. Convection flow loop with furnace and zirconia cell and catalytic combustibles detector.
3. Mounting plate for welding to vertical wall or onto 3 1/2" or 4" pipe nipple as flange.
4. 48" (60 cm) stainless steel sample probe/filter assembly to 1300°F (704°C).
5. 25 ft. (7.6 m) of interconnecting cable P/N 21185 JE.
6. 20 Micron SS filter - maximum 800°F.

Series 2000 Control Unit (Following features are standard)

1. 4 line x 20 characters/line vacuum fluorescent display shows combinations of oxygen (0-100%), combustibles (ppm or %), time & date, cell temperature, user-programmable text, T/C mV or cell mV.
2. Password protection, programmable pressure compensation and context-sensitive help are standard. Display line 4 is reserved for full text error and diagnostic messages.
3. Two isolated current outputs for oxygen and one for combustibles. Select oxygen, combustibles, cell temperature, T/C mV or cell mV as current output. Each can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA. Adjustable to correspond from 0-1% oxygen to 0-100% oxygen and from 0-200 ppm to 0-5% combustibles. Select hold or track during calibration.
4. Two oxygen alarms, each high or low selectable and energize or de-energize on alarm. Assign alarm 1 as Oxygen, Calibrate or verify. Two high Combustibles alarms.
5. Diagnostics includes watchdog timer, service alarms, system tests and a 10-entry event log.
6. RS-485 2-way addressable communications port.
7. Real-time clock/calendar.
8. Manual calibration or calibration verification.
9. Choice of general purpose wall mount, panel mount or 19" rack mount enclosure.
10. Meets requirements of Class I, Div. 2 hazardous area.

PRICE: $8010.00 net each

CO AND O2 ANALYZERS

VENDOR	EQUIPMENT	FEATURES	PRICE
BAILEY CONTROLS C/O SIMCO CONTROLS Columbus, OH 614-253-1996 X.148 Fax 614-253-2033 [illegible]	SMA 21411, Dual Filter (1500 F) SMA 21511 Filter (3000 F)	* Smart Analyzer 90 * Combustion analyzer which continuously samples and analyzes O2 and COs. * O2 Sensor: Zirconium oxide * CO Sensor: Catalytic type RTD based sensor * Automatic sensor calibration * Remote blowback * Nema 4 enclosure	SMA 21411 $8657 SMA 21511 $9025.00
McNEILL INTERNATIONAL 7041 HODGSON RD MENTOR, OH 44060 1-800-MCNEILL Fax: 216-953-1933 [illegible]	DAI Model 10600X 133 Sampling filter system Model 7612 Inconnel Probe 7'long	* Sensors: electrochemical, disposable minimum life - 1 year.Cost: O2-$140, CO-$276 * Calibrate once a month with cal gas * Filter replacement-once every six months * Power: 120VAC, 60 Hz, converter necessary * Local readout: Display - 3 1/2" analog meters * Nema 4 enclosure	$8868.75 Filter:$700.00 Probe:$1505 Total:$11073.75 Blowback to be provided by plant
ENVIROPLAN 3 BECKER FARM ROAD ROSELAND, NJ 07068 C/O D.J. SHINKLE 708-501-3579 [illegible]	CEMEX Extractive System	* Heated SS probe * Sample pump, peristaltic pump * Dragon Cement, Portland, ME * Sample control panel * Gas filter correlation CO Analyzer * Paramagnetic O2 Analyzer * O & M Manual - 2 copies * System drawings * NEMA1 instrument rack * 40 feet umbilical cord	$58000
SERVOMEX 90 KERRY PLACE NORWOOD, MA 02062-4733 617-769-7710 1-800-862-200 C/O JOHN DOLE, 216-631-0600 [illegible]	SERVOMEX 700B Zirconia analyzers	* Heated sensor unit * Aspirator (air or steam) for sampling * Wide range of probe options - temperature ranges - dust loading factors * Self-diagnostic indicators * Missouri Portland Cement Plant, Independence, MO * "Blowback" not required * Two-way communications possible between the analyzer and a computer or terminal * Easy calibration, once a month	$11000
ROSEMOUNT ANALYTICAL,INC 1201 N. MAIN ST,PO DRAWER 901 ORRVILLE, OH 44667 1-800-628-1200 X. 658		* In-situ type analyzer * 1300 F max, needs accessory for cooling down	O2 Analyzer: $4500 CO Analyzer:$15500 [illegible]
TELEDYNE ANALYTICAL INSTRUMENTS VICKI STEWART 818-961-9221	IN-SITU SYSTEM Model 9300	* Electrochemical microfuel cell for O2 * Infra-red sensor for CO * Both sensors being fed by a single probe * Installations in cement plants - Essroc Cement, Bessemer,PA * Blowback to clean the inside of probe * Vent-on pump for stack sampling	Model 9300: $18000 Dry type probe with wet wash to keep clear of particulate deposits: $5000.00 Total: $23000
AMETEK,INC Process and Analytical Inst. Div. Jim Wall, 614-889-2150 [illegible]	Oxygen- In Situ AMETEK WDG-In Situ CO - Infra Red EI - 20	* Screening, probe(9"-108"), electronics * Manual flow calibration * Measurement across the stack * Air blowing system to keep transducer lenses clean	$5,000 $12,500 Total: $17,500

Information required from Broceni for more accurate pricing:

Flow System: Temperature, pressure, constituents, What kind of outputs are needed - alarms, etc. indication, recording, process control - What do you want to do with the output?

bro2/hgb

[illegible]

FIRST CHOICE: [illegible] $8657 plus spare parts and [illegible] $9025 plus spare parts

THIRD CHOICE: TELEDYNE $23,000

Ametex Quotation

MODEL WDG-HPIIC PPM

Item: 1
Quantity: 1
Ametek Model WDG-HPIIC Microprocessor Based Flue Gas Oxygen and Combustibles Analyzer for 115 VAC (230 VAC) 50/60 Hz operation in general accordance with Bulletin P-270 consisting of:

Sensor in stainless steel enclosure with lift-off cover and including:

1. Heaters to maintain components above the dew point of flue gas.
2. Convection flow loop with furnace and zirconia cell and catalytic combustibles detector.
3. Mounting plate for welding to vertical wall or onto 3 1/2" or 4" pipe nipple as flange.
4. 48" (60 cm) stainless steel sample probe/filter assembly to 1300°F (704°C).
5. 25 ft. (7.6 m) of interconnecting cable P/N 21185 JE.
6. 20 Micron SS filter - maximum 800°F.

Series 2000 Control Unit (Following features are standard)

1. 4 line x 20 characters/line vacuum fluorescent display shows combinations of oxygen (0-100%), combustibles (ppm or %), time & date, cell temperature, user-programmable text, T/C mV or cell mV.
2. Password protection, programmable pressure compensation and context-sensitive help are standard. Display line 4 is reserved for full text error and diagnostic messages.
3. Two isolated current outputs for oxygen and one for combustibles. Select oxygen, combustibles, cell temperature, T/C mV or cell mV as current output. Each can be 4-20 mA, 0-20 mA, 20-4 mA or 20-0 mA. Adjustable to correspond from 0-1% oxygen to 0-100% oxygen and from 0-200 ppm to 0-5% combustibles. Select hold or track during calibration.
4. Two oxygen alarms, each high or low selectable and energize or de-energize on alarm. Assign alarm 1 as Oxygen, Calibrate or verify. Two high Combustibles alarms.
5. Diagnostics includes watchdog timer, service alarms, system tests and a 10-entry event log.
6. RS-485 2-way addressable communications port.
7. Real-time clock/calendar.
8. Manual calibration or calibration verification.
9. Choice of general purpose wall mount, panel mount or 19" rack mount enclosure.
10. Meets requirements of Class I, Div. 2 hazardous area.

PRICE: $8010.00 net each

OPTIONAL EQUIPMENT

Remote Calibration Unit (Optional)

This option includes the calibration box (Nema 4X) complete with valves, regulators, flowmeter, flow controller, check valve and auto calibration module for the Series 2000. This allows an automatic calibration (or verification) cycle to be performed; a) at a timed interval, b) remotely on demand either by contact closure or via the RS485 port or c) locally by manually pressing a key on the Series 2000. The calibration box should be mounted as close to the sensor as possible. Calibration gases to be supplied by customer. Refer to spare parts section for gases stocked by Thermox for resale. Includes 25 ft (7.6 m) interconnecting cable P/N 21194 JE - (Blenden No. 9773).

PRICE ADDER: $1260.00 net each

FS recommends no, because need worker to go up to unit every day + check unit.

Sensor Mounting Configuration

Floor mounting (LIFT OFF COVER ONLY). Uses 3" 150# mounting plate

X PRICE ADDER: $530.00 net each

Remote sensor board mounting for ambient temperatures from 160°F (71°C) to 392°F (200°C). Includes remote SS junction box (A203-333-1). Maximum distance sensor to box is 20 ft (6.1m). Includes 20 ft (6.1m) high temperature cable P/N 71971.

X PRICE ADDER: $525.00 net each

X Probe/Filter Assembly Option

48" (122 cm) Ceramic to 2800°F (1530°C)

PRICE ADDER: $505.00 net each

Options for Series 2000 Control Unit

X Wall-mount Nema 4

PRICE ADDER: $200.00 net each

X Wall-mount Nema 4X (stainless steel)

PRICE ADDER: $600.00 net each

X 60W heater and thermostat

PRICE ADDER: $210.00 net each

INTERCONNECTING WIRING

X **Control Unit to Sensor Unit**

P/N 21185 JE - (Belden No. 9774)
6-twisted pair 18 AWG each pair individually shielded and 20 AWG drain wire w/ PVC jacket. For use up to 1000' (304). Maximum temperature 176°F (80°C). (25 ft (7.5 m) of cable is included with sensor).
PRICE: $ 2.20/ft

Only 10 feet from sensor to control unit

X **Control Unit to Remote Calibration Unit**

P/N 21194 JE - (Belden No. 9773)
3-twisted pair, 18 AWG. Each pair individually shielded and 20 AWG drain wire. PVC jacket. For use up to 1000 ft. (304 m). Maximum temperature 176°F (80°C). (25 ft (7.5 m) of cable is included with calibration unit).
PRICE: $ 1.45/ft.

220V / 50 Hz

SPARE PARTS

Sensor Unit

Part #70409SE Furnace Assembly
PRICE: $250.00 net each
Part #71697KE Type "K" Thermocouple
PRICE: $125.00 net each
Part #80418SE Sensor Board
PRICE: $215.00 net each
Part #71063SE Zirconium Oxide Cell
PRICE: $435.00 net each
Part #72396KE Thermostat (lift-ff enclosure)
PRICE: $170.00 net each
Part #72326KE Thermostat (hinged enclosure)
PRICE: $170.00 net each

Remote Calibration Unit

~~$1366~~ 1025

Part #39003JE Air Regulator
PRICE: $110.00 net each
Part #37013JE Regulator Gauge
PRICE: $ 25.00 net each
Part #36023JE Calibration Gas Solenoid Valve
PRICE: $ 65.00 net each
Part #37020JE Flowmeter
PRICE: $120.00 net each

Series 2000 Control Unit

Part #90219VE Display Module
PRICE: $1215.00 net each
Part #90253VE Power Supply/Keypad Module
PRICE: $370.00 net each
Part #80436SE Calibration Card
PRICE: $225.00 net each
Part #80449SE Combustibles Card
PRICE: $885.00 net each
Part #80439SE Backplane Assembly
PRICE: $165.00 net each
Part #80445SE Wiring Board
PRICE: $375.00 net each
Part #80440SE Processor Board
PRICE: $810.00 net each
Part #42373JE Display
PRICE: $290.00 net each

$4335

SPARE PARTS

Sensor Unit

Part #70409SE Furnace Assembly
PRICE: $250.00 net each
Part #71697KE Type "K" Thermocouple
PRICE: $125.00 net each
Part #80418SE Sensor Board
PRICE: $215.00 net each
Part #71063SE Zirconium Oxide Cell
PRICE: $435.00 net each
Part #72396KE Thermostat (lift-ff enclosure)
PRICE: $170.00 net each
Part #72326KE Thermostat (hinged enclosure)
PRICE: $170.00 net each

Remote Calibration Unit

~~$1366~~ 1025

Part #39003JE Air Regulator
PRICE: $110.00 net each
Part #37013JE Regulator Gauge
PRICE: $ 25.00 net each
Part #36023JE Calibration Gas Solenoid Valve
PRICE: $ 65.00 net each
Part #37020JE Flowmeter
PRICE: $120.00 net each

Series 2000 Control Unit

Part #90219VE Display Module
PRICE: $1215.00 net each
Part #90253VE Power Supply/Keypad Module
PRICE: $370.00 net each
Part #80436SE Calibration Card
PRICE: $225.00 net each
Part #80449SE Combustibles Card
PRICE: $885.00 net each
Part #80439SE Backplane Assembly
PRICE: $165.00 net each
Part #80445SE Wiring Board
PRICE: $375.00 net each
Part #80440SE Processor Board
PRICE: $810.00 net each
Part #42373JE Display
PRICE: $290.00 net each

$4335

TELEDYNE ANALYTICAL INSTRUMENTS

BAKER INDUSTRIAL EQUIPMENT, INC.
2475 State Road • P.O. Box 1208
Cuyahoga Falls, Ohio 44223-0208
Phone: 216-928-8877
Fax 216-923-0615 • (213) 28[illegible]

APPLICATION INFORMATION

Please supply complete answers to the following questions so that Teledyne Analytical Instruments can correctly evaluate your application and propose instrumentation best suited to solve your analysis problem.

INQUIRY FROM: DATE 13 Jan 1993

Name: FRANK C. STEVENS
Title: President
Company: Stevens Consulting Co
Address: 13620 Oak Mann. Rd
Lakeside Calif 92399
Telephone Number: 619-390-4033

SEND RESPONSE TO: FRANK C. STEVENS
and Gordon McKeehan
World Environment Center

PURPOSE OF INQUIRY: FAX 619-390-4031

Feasibility of Application ☐ Budget Estimate ☐ Quote for Possible Purchase ☒

PROCESS CONDITIONS:

1. Nature of Process: Wet Process Cement Kiln, Sample feed end of Kiln
2. Number of Sample Streams to be Monitored: One
3. STREAM COMPOSITION(S): (List Everything)

COMPONENT	TO BE MEASURED	REQUIRED ACCURACY	RANGE	CONCENTRATION UNITS	MAXIMUM	NORMAL	MINIMUM
O_2	O_2	0.5 to 1.0% of Scale	0-5%	Percent	10%	2.63%	0.0%
			0-10%				
CO	CO		0-2000	ppm	2000 ppm	200 ppm	0.0%
			0-20000	ppm	2%	200 ppm	

4. STREAM OPERATING CONDITIONS: VACUUM -4" H_2O -3" H_2O -2" H_2O

a. Physical Properties

Temp.: °F ☐ °C ☒ Max. 400°C Normal 300°C Min. 200°C

VACUUM ~~Press.~~: psig ☐ psia ☐ Inches of H_2O ☐ Max. -4" H_2O Normal -3" H_2O Min. -2" H_2O

Phase: Vapor ☐ Liquid ☐ Mixed ☐ Contains Solids? Yes ☒ No ☐ Describe: PORTLAND CEMENT DUST HEAVY CONCENTRATION

Amount and Particle Size: 2-2 grams/cubic meter minus 100 mesh

b. Chemical Properties

Corrosive? Yes ☐ No ☒ Acid ☐ Basic ☒ Neutral ☐

What materials withstand contact with sample? STAINLESS STEEL

Stability: HYDROSCOPIC, CONTAINS CaO AND MOISTURE

Polymerizing Tendency: No

METHODS OF ANALYSIS:

1. What methods of lab analysis are used to measure component(s) of interest? ORSAT, TESTO EKM
2. What TAI instrument or literature prompted inquiry? TAI

APPLICATION DATA AVAILABLE

1. Are samples available for evaluation by TAI? Yes ☒ No ☐ If so, please describe: TYPICAL FEED END CEMENT KILN GASES AND DUST
2. Are spectrograms of sample available? Yes ☐ No ☒ If so, please attach. WET CHEMICAL ANALYSIS ARE AVAILABLE
3. Please attach any other data that might be useful, such as sketch of sample system, etc. WILL USE TYPICAL CEMENT PLANT SAMPLE SYSTEM FOR FEED END WET PROCESS KILN

BAKER

BAKER INDUSTRIAL EQUIPMENT, INC., • 2475 STATE RD. • P. O. BOX 1208 • CUYAHOGA FALLS, OH 44223 (216) 928-
FAX: (216) 923-

December 16, 1994

Malcolm Pirnie, Inc.
445 Hutchinson Avenue
Columbus, OH 43235

Attention: Mr. Harry Bhatt - Project Manager

Gentlemen:

Subject: Teledyne Analytical Instruments Cement Kiln Sample Systems and Analyzers

Teledyne has been very successful in providing kiln sampling and gas measuring systems. Essroc Cement located in Poland, Ohio has been using a Teledyne cement kiln sampling system with oxygen and carbon monoxide analyzers for a number of years with success. I am gathering a list of other installations and will forward them in another correspondence.

We discussed a wet cement manufacturing process in which your customer would like to monitor oxygen and carbon monoxide. The Teledyne Model 9300 combines oxygen and carbon monoxide analyzers with a relatively simple maintenance-free sampling system. A budgetary cost for analyzers, sample system and probe is $24,128.00.

In the price, we have included a water-cooled and water-washed probe for temperatures up to 3,000°F (1,650°C), and an air blowback system to purge the probe and sample lines. Temperatures below 2,100°F (1,150°C) may allow us to use a dry type probe with water-wash.

Because cement kiln sampling systems are so critical, I have included several application bulletins and cut sheets on Teledyne's Model 9300 oxygen and carbon monoxide analyzer and flue gas probes.

Please free to contact me if you have any questions. Also, have your customer fill out our application data sheet so that we may provide a quote.

Sincerely,

BAKER INDUSTRIAL EQUIPMENT

Richard F. Werren
Sales Engineer

MlcmPrRF.doc
Enclosures

RECEIVED
DEC 20 '94
MALCOLM PIRNIE
COLUMBUS
JOB #
FILE:

VII. Pyrometer Comparison

1. The Davis M-400D unit is suspect regarding durability and application to constant cement kiln conditions. It's use is not advised without further information obtained from Davis, plus references from cement plant users.

2. The Everest 4000B and the Quantum Logic QL 3200F-3A units both should serve well as intermediate investment equipment selection. Use of these units requires understanding their operation, understanding their limitations, frequent parts cleaning and replacement, plus frequent visual inspection of the kiln flame to coordinate correctness of flame temperature readings (i.e., to make sure that it is the flame temperature that is being monitored, and not the side was (clinker) temperature). Frequent mechanical checks, calibration, and parts replacement is to be expected.

While the Quadtek Spyrometer is markedly higher in cost than non-scanning, non-imaging pyrometers, it is clearly the instrument of choice for advanced burner control / performance information. One distinct advantage is that if process changes should occur that would interfere with accurate temperature measurement, these changes would not only be displayed on the monitor, but remote repositioning of the pyrometer to the correct measuring point could be accomplished. Another advantage is the display of temperature measurement from up to six selectable points in the field of vision. The size of each of these six points is programmable, plus the system (unit) can determine the average temperature, peak (maximum) temperature, and minimum temperature within each region. Wide angle viewing of the field of interest is allowed.

Installation and application of this unit is not advised without employing either a Quadtek service professional, or WEC consultant familiar with the installation, operation and trouble-shooting of the Quadtek unit.

B-5

Equipment Orders - Quadetek Pyrometer and Testoterm Gas Analyzer

QUADTEK

Innovative imaging technology for process industries

June 17, 1994

AKMENES CEMENTAS
J. Dalinkeviciaus 2.
5464 Naujoji Akmene
Lithuania

Attention: Algimantas Mituzas

Subject: Your June 17, Fax And Questions
Quote # 94-0617-RAL/01

Dear Mr. Mituzas,

I have attached the quote you requested. This quote allows for final selection of the correct QUADTEK Spyrometer ™ standard lens tube length and optical Field of View(FOV) for your kiln application without the need for additional pricing. Our normal proceedure is to discuss your needs for viewing area and distance prior to finalizing the design for your kiln.

I have also quoted optional installation and startup service which would be a minimum of one week plus our technicians travel and living expenses during that time. Note that we supply excellent installation manuals. Skilled instrument technicians who are familiar with cameras or computers can successfully install our product.

QUADTEK has developed the designs and features which give our cameras good quality pictures and reliability over ten years of continuous engineering and design effort. Over that time, our products have evolved and the Spyrometer™ is the latest design and includes the latest and best features. While it is not inexpensive, we made a special effort to include a valuable package of features at pricing that is good for the combination of features that are included. Those features include:

- High quality video image.
- Color kiln video display
- 6 point operator targeted scanning pyrometer
- 6 scaleable 4-20 ma outputs
- configurable trend display with 24hr. memory of a points

15241 NE 90th Street • Redmond, WA 98052
(206) 881-0778
Fax (206) 869-0667

Our payment requirements are for prepayment or to use an international Letter of Credit. Our agent here can work with an international bank with offices in the US.

Our freight and shipping policy is to ship FOB our factory in Redmond, WA. Extra charges such as fees, duty and taxes are the responsibilty of the purchaser. As an estimate on freight, we recently received an airfright price for a complete system to be shipped to Greece for under $800. USD. If it is helpful, we prepay freight expenses and bill our customers at actual cost without markup.

With best regards,

Dick Ludwig
Manager of Sales and Marketing

QUADTEK SPYROMETER™ SCANNING PYROMETER SYSTEM
High Temperature Ratio Pyrometer Version
Temperature measurement range
(602-1816) °C

Item	Qty	Part Number	Description	Unit Price US $
1.	1	**M551B** **/TRx** **/L24** **/VC** **/Fxx** **/Mx**	**Model 551integrated scanning pyrometer/camera sensor** -M500 series NEMA-4 type high temperature resistant enclosure -Solid state MOS CCTV electronics -integrated scanning ratio pyrometer -measuring range: specify /TR1: (602-1289°C), /TR2: (759-1816°C) or/TR3: (760-2190 °C) -high temperature air cooled optics(18, 24, 30 or 42 inch length) -enclosure mounted vortex cooler -optics horizontal Field of View: (specify 40°,60° or 80°) -camera mount MB, braclet type or MF, flanged type requirement when ordering automatic camera retract	**$18300**
2.	1	**M201B**	**Model 201 SPYROMETER™ scanning pyrometer processor** -user-selectable sensor wavelengths: 1.6 or 0.8 micron, 1.6/0.8 ratio -six (6) user-selectable scan measurement locations -user-selectable scan target size -graphical overlays indicating location, scan area, temperature -six (6) 4-20 mA DC outputs -mouse controlled set-up functions -sealed mouse for harsh enviroment -color VGA display monitor output	**$12650**
3.	1	**PS6374-039**	**High resolution 13" VGA monitor** with 6 foot (1.8m) 9221 connector cabling	**$850**

SYSTEM OPTIONS

Item	Qty	Part Number	Description	Unit Price US $
1.	1	**M353(RC)**	**Remote mounted automatic retract controller actuator switch**	**$450**
2.	1	**M40x(AC)**	**Loss of cooling air alarm output**	**$450**
3.	1	**MANUALS**	**Additional sets of service manuals** (two sets of manuals are included with each system purchased)	**$25ea**
4.	1	**TAGS1**	**Stainless steel tags** -per tag	**$25**

RECOMMENDED SPARE PARTS

Item	Qty	Part Number	Description	Unit Price US $
1.	1	**KT7171-998**	**M500 series lens cleaning kit**	**$100**
2.	1	**PS6374-033**	**Hand-held 3$^1/_2$" B&W monitor** (use- camera installation and troubeshooting)	**$450**
3.	1	**AS6108**	**M330/M550 power cable asmbly**	**$86**
4.	1	**KT6929**	**M405 replacement cartridge kit** (replace ecvery three months)	**$250**

INSTALLATION AND START-UP ASSISTANCE

Item	Qty	Part Number	Description	Unit Price US $
1.	1	**START-UP DAY1**	**Installation & startup supervision** -first day (travel and living expenses to be billed at actual cost)	**$1200**
2.	1	**START-UP DAY2**	**Installation & startup supervision** -per day, consecutive with first day of start-up (travel and living expenses to be billed at actual cost)	**$850**

QUADTEK SPYROMETER™ SCANNING PYROMETER SYSTEM
High Temperature Ratio Pyrometer Version
Temperature measurement range
(602-2190) °C
continued

Item	Qty	Part Number	Description	Unit Price US $
4.	1	**M405**	**Model M405 three-stage heavy duty air filter system complete with hoses** (Instrument quality air recommended)	**$1250**
5.	1	**PS6082-084**	**500 foot RG-59/U video cable** (for over 1000 feet, utilize RG-11/U type cable)	**$350**
6.	1	**KT6109**	**Video cable connector kit** (2) RG-59/U to UHF connectors (1) UHF to BNC adapter	**$60**
7.	1	**M353**	**Model 353 pnuematic automatic camera retract system**	**$4000**

TOTAL SPYROMETER SYSTEM SHIP DATE 10-12 WEEKS FOB Redmond, WA. Freight, Prepay and add. QUOTE # 94-0607-RAL/01	**$37460**

TERMS OF SALE

1. Prices and specifications are subject to change without notice.
2. Payments shall be due net 30 days after date of invoice. Interest at the rate of 1 1/2% per month shall accrue on balances unpaid after 30 days.
3. Reasonable attorney's fees and costs of collecting payment from buyer shall be reimbursed to seller.
4. Limit of liability - In no event will Quadtek be liable for business interruptions, loss of profits or savings, costs of delay, or for any other special, indirect, incidental or consequential losses, costs or damages, associated with the use of its products.
5. Unless otherwise specified, prices quoted are FOB Redmond, Washington, and do not include taxes and tariffs.
6. Customer's non-acceptance of a shipment or cancellation of an order after Quadtek has received a bonafide purchase order will entitle Quadtek to recover a cancellation fee equal to 25% of the price of the ordered product.

Receipt of purchase order for any of Quadtek's products constitutes acceptance of Quadtek's terms of sale and warranty. The provisions contained in the terms of sale and warranty may not be modified, amended or waived except in writing by Quadtek's authorized representative. Quadtek hereby objects to any additional or different terms or conditions, contained in any purchase order for Quadtek's products.

LIMITED WARRANTY

Except as provided below, Quadtek warrants its video imaging systems to be in good working order for a period of one year after receipt of the system by the customer. Quadtek warrants the added content of its video imaging system upgrades to be in good working order for a period of ninety days after receipt of the system by the customer. Quadtek warrants its factory repairs for materials and workmanship for a period of ninety days after receipt of the system by the customer. If at any time during the specified warranty period a system fails to be in good working order, Quadtek will, at its option, replace or repair the system at no additional charge except as set forth below.

To request a system repair under the terms of this warranty, a customer should contact Quadtek by fax (206-869-0667) with a description of the problem. Quadtek will evaluate the information received by fax and either advise customer of the next step in the repair process or seek additional information in order to pinpoint the components requiring repair or replacement. Upon determination of the best approach to resolve the warranty problem, Quadtek will do one of several service options as mutually agreed between Quadtek and the customer.

1) request that customer return the equipment (at customer's expense) to factory for repair or replacement (customer will be responsible for reinstallation of repaired or replaced system), 2) send new parts of small value for customer to install or, 3) send new parts of large value (in excess of $500US list price and require the return of same defective parts to seller within 45 days at seller's expense unless deemed customer's responsibility). Defective parts must be returned to seller using seller's preferred shipping instructions.

This warranty does not apply to the following conditions:

1. Damage to the lens tube caused by running the lens with inadequate cooling air.
2. Damage that occurs because of flame or hot gases impinging on the system due to positive pressure at the camera installation port. (Applies only to systems installed with open ports in negative draft furnaces.)
3. Breakage of internal optical components in the lens caused by excessively rough handling of the lens by persons cleaning the lens or access port.
4. Damage to the image tube from burn-in caused by leaving the camera with only a fraction of the field of view in use or by exposure to sunlight or other bright light source.
5. Picture deterioration due to neglect of recommended maintenance.
6. If the customer has abused, misused, modified, or attempted repairs on the equipment.
7. Damage due to violation of storage requirements. We require that the equipment be stored indoors in the original shipping cartons in a controlled atmosphere such as a warehouse not subject to temperatures below -15øC or above 45øC.

Quadtek furnishes the above warranties in lieu of all other warranties, expressed or implied, including warranties of merchantability and fitness for a particular purpose.

QUADTEK, INC.
15241 NE 90th Street
Redmond, WA 98052
206-881-0778

QLN1001R1

1994 PRICES

TESTO 350

Description	Part #	Price
Testo 350 Basic Analyzer unit for Temperature, O2, CO2, efficiency	0632.3500	$ 1799.00
CO Module 1, measuring range 0 to 10,000 ppm H2 compensated	0440.3503	795.00
CO Module 2, measuring range 0 to 20,000 ppm	0440.3502	695.00
CO Module 3, measuring range 0 to 40,000 ppm	0440.3503	1199.00
NO Module 4, measuring range 0 to 3,000 ppm	0440.3504	800.00
NO2 Module 5, measuring range 0 to 500 ppm	0440.3505	900.00
SO2 Module 6, measuring range 0 to 5,000 ppm	0440.3506	900.00
CO measuring cell shut off & rinse function	0470.0350	329.00
Control Module for use with the Testo 339	0470.0351	329.00
Testo 350 Basic Handheld unit with additional temp probe input, RS 232 and infrared interface	0560.3510	885.00
Testo 350 Comfort Handheld unit with above features plus integrated memory, input for FPM & %RH, & isolated RS 232	0560.3520	1449.00
Power Supply / Recharger	0554.0077	46.00
Connection Cable between unit & analyzer coiled cable	0409.0350	42.00
Connection Cable between unit & analyzer 15'	0409.0351	
Connection Cable between unit & analyzer 30'	0409.0352	119.00
Connection Cable between unit & analyzer 60'	0409.0353	161.00
Flue Gas Probe 30" length, Tmax = 1832 F	0600.8520	745.00
Flue Gas Probe 30" length, Tmax = 1832 F for improved SO2 & NO2	0600.8521	945.00
Flue Gas Probe 13" length, Tmax = 1832 F	0600.8720	665.00
Flue Gas Probe 13" length, Tmax = 1832 F for improved SO2 & NO2	0600.8721	875.00
Flue Gas Probe 13" length, Tmax = 932 F	0600.9522	359.00
Ambient Air probe 3" length, Tmax = 176 F	0610.3613	49.00
Ambient Air probe 12" length, Tmax = 212 F	0610.9713	144.00
Pressure Probe 4" H2O	0638.1445	489.00
Pressure Probe 40" H2O	0638.1545	449.00
Magnetic Holder for Pressure Probe	0554.0226	39.00
Silicon Hose for Pressure Probes	0554.0440	27.00
Pitot Tube 20"L , Tmax= 662 F	0635.2045	119.00
Pitot Tube 14"L , Tmax= 662 F	0635.2145	115.00
Pitot Tube 12"L , Tmax= 932 F	0635.2245	250.00
Humidity & Temperature Probe 0-100% RH, Tmax- 160 F	0636.9767	439.00
Humidity & Temperature Probe 0-100% RH, Tmax- 290 F	0636.2167	765.00
Infrared Printer with Alkaline batteries and 1 Roll of Thermal Paper	0554.0345	285.00
Rolls of Thermal Paper	0554.0115	23.00
Plastic Bags with adhesive labels to mount readings on boiler	0554.0116	39.00
RS 232 Interface Cable	0409.0154	25.00
Nice Case for Testo 350 (leather)	0516.0130	240.00
Carrying Strap for Analyzer	0516.0060	21.00
Aluminum Case for the Testo 350 & 330 together	0516.0139	650.00
Aluminum Case for the Testo 350	0516.0350	

ГАЗОАНАЛИЗАТОР ДЫМОВЫХ ГАЗОВ– ОПТИМИЗАТОР ГОРЕНИЯ

testo term

testo 33

ВЫСОКОТОЧНЫЙ ПРИБОР ДЛЯ ИЗМЕРЕНИЙ

температуры,

давления,

концентрации O_2, CO_2, CO, NO_x, SO_2

коэффициента избытка воздуха

потери тепла с уходящими газами.

С ЗАПОМИНАЮЩИМ И ПЕЧАТАЮЩИМ УСТРОЙСТВОМ

testo® 33

...ИЗМЕРЯЕТ, ...ЗАПОМИНАЕТ, ...ПЕЧАТАЕТ

testo term

ОТЛИЧИТЕЛЬНЫЕ ОСОБЕННОСТИ

- Индикация на дисплее параметров:
  температуры
  разрежения
  концентрации O_2 / CO_2
  CO
  $NO_{(x)}$ / NO_2
  SO_2
  потери тепла с уходящими газами
  коэффициента избытка воздуха
- Быстрая замена датчиков
- Сохранение в памяти вводимых и измеренных данных
- Одновременная индикация трех параметров
- Устройство для запоминания и печати



testo-33 состоит из двух отдельных блоков: командно-измерительного ("Измеритель") и анализирующего ("Анализатор"). Первый измеряет и рассчитывает значение параметров, второй содержит датчики, в том числе электрохимические – для анализа газов

В базовом варианте Анализатор включает датчики O_2, CO, температуры и разрежения Концентрация CO_2, коэффициент избытка воздуха и потери тепла определяются расчётом. По желанию заказчика Анализатор может быть оборудован датчиками $NO_{(x)}$, NO_2, SO_2

Микропроцессор Измерителя хранит в памяти характеристики наиболее распространённых топлив; в него оператор может ввести дополнительные данные Все данные сохраняются в памяти и после отключения прибора

Прибор может быть укомплектован принтером, который способен запомнить и распечатать данные, поступающие примерно от 30 источников Данные можно распечатать индивидуально, по группам или все вместе Данные могут быть также переданы на внешнюю ЭВМ через **стандартный интерфейс типа RS 232**

Имеются 2 **аналоговых выхода**

Измеритель с принтером или без него укладывается в специальное ложе анализатора Это позволяет **testo 33** быть весьма компактным, портативным

КОМПЛЕКТ ПОСТАВКИ

Измеритель с кабелем для подключения к анализатору длиной 1,8 м

Анализатор

Газозаборный зонд со шлангами и соединительным кабелем длиной 2,2 м

Принтер со штекером для подключения к измерителю, 4×1,24 V аккумулятора и

testo term

testo® 33

...ИЗМЕРЯЕТ, ...ЗАПОМИНАЕТ, ...ПЕЧАТАЕТ

Принтер

ключения
ней ЭВМ

Разъем для подключения принтера

Встроенный аккумулятор

Четырехстрочный дисплей

змеритель

Сенсорная клавиатура

Кабель для подключения ИЗМЕРИТЕЛЯ к АНАЛИЗАТОРУ

ТЕХНИЧЕСКАЯ ХАРАКТЕРИСТИКА

Дополнительные сведения

На ДИСПЛЕЙ одновременно выводятся 3 параметра. Все параметры, группами по 3, можно вызвать на дисплей. В отдельной стр на дисплее указывается текущий режим работы прибора.

ПРИНТЕР очень легко стыкуется с ИЗМЕРИТЕЛЕМ



ИЗМЕРИТЕЛЬ имеет 2 АНАЛОГОВЫХ ВЫХОДА, через которые можно вывести любые выбранные оператором параметры



АНАЛИЗАТОР может быть снабжен необходимыми датчиками по индивидуальному заказу. Компоновка прибора обеспечивает

testo® 33

testo term

...ЭТО ПРОСТОТА УПРАВЛЕНИЯ

① Включение прибора

Производится автоматическая калибровка датчиков, затем автоматическое переключение на программу выбора топлива.

② Выбор вида топлива

ENTER — Ввод в программу вида топлива, после чего происходит переход к программе измерений.

③ START STOP — Измерение Включение насоса

Вызов параметров на дисплей

Дополнительные функции прибора

M — Измерение

Индикация на дисплее измеряемых и расчётных величин. Сохранение параметров в памяти.

Вызов необходимой программы, переход к перечню вводимых параметров

- Выбор топлива
- Программа
- Ввод "механедожёга" (числа Russ)
- Сервисрограмма (состояние прибора, рабочие параметры, аналоговые выходы, RS 232 и др.)

Образец печати протокола

13-03-89	Дата
06:58:01	Время
No 0012	№ измеряемого параметра
Heizöl EI	Вид топлива
214.0 C AT	Температура газов C°
7.3 % O2	Концентрация O_2, % об.
11 % qA	КПД по Q^{P}_{A}, %
	КПД по Q^{P}_{H}, %
10.1 %CO2	Концентрация CO_2, %
1.5 λ	Коэффициент избытка воздуха
-0,25 hPas	Разрежение, мбар или гПа
25.0 C U1	Температура воздуха, C°
35 p CO	Концентрация CO, ppm или мг/м³
79 p NO	Концентрация NO_x, ppm или мг/м³
0 p NO2	Концентрация NO_2, ppm или мг/м³
18 p SO2	Концентрация SO_2, ppm или мг/м³

Для топливосжигающих установок в быту

...надежный способ измерений потерь тепла с уходящими газами

На теплоцентралях



...для быстрой и безопасной настройки работы горелок

Настройка режима горения, эксплуатация топливосжигающих установок

Необходимые измерения: O_2 (CO_2), CO, разрежение, температура дымовых газов, потери тепла с уходящими газами, коэффициент избытка воздуха.

Чтобы настроить оптимальный режим горения, необходимо знать значение потерь тепла с уходящими газами и коэффициент избытка воздуха, которые при известных характеристиках топлива определяются по температуре газов и концентрации в них O_2 (CO_2). Оптимальное соотношение температуры газов и коэффициента избытка воздуха обеспечивает минимальные потери тепла с уходящими газами (максимальный КПД).

В тяжелой промышленности



...непрерывные измерения необходимых параметров при настройке горелок, которые могут считываться с дисплея или печататься в протоколе

Испытания, контроль за вредными выбросами топливосжигающих установок

Необходимые измерения: O_2 (CO_2), CO, NO_{tot}, NO_2, SO_2, разрежение, температура дымовых газов, потери тепла с уходящими газами, коэффициент избытка воздуха.

Прибор позволяет контролировать вредные для окружающей среды выбросы по результатам измерений их содержания в уходящих дымовых газах или отработавшем воздухе различных установок, работающих, например, в нефтехимической промышленности, в энергетике и т.д. При этом следует руководствоваться допустимыми нормами вредных выбросов, принятыми в каждой конкретной стране.



РЕКОМЕНДУЕТСЯ:

при сжигании жидкого топлива:	поддерживать O_2 на минимальном уровне, число Russ — от 0 до 1;
при сжигании газа:	поддерживать O_2 на минимальном уровне, CO — не менее 1000 ppm

Bestelldaten testo® 33

testo term

Газозаборный зонд



Газозаборный зонд
с присоединительными шлангами
и кабелем





Заказные данные

	Наименование	№ по каталогу	Цена, марки ФРГ
Анализатор	(1) ИЗМЕРИТЕЛЬ на рабочее напряжение 220 V с кабелем для подключения к АНАЛИЗАТОРУ длиной 1,8 м	3300	1.285,--
	(2) АНАЛИЗАТОР, базовый комплект с аккумулятором для измерения температуры, разрежения, коэффициента избытка воздуха, O_2, CO_2, CO, O_2	0632.9433	2.740,--
	То же плюс NO_x	0632.9533	4.825,--
	То же плюс NO_x и NO_2	0632.9633	7.220,--
	То же плюс NO_x, NO_2 и SO_2	0632.9733	9.875,--
Газозаборный зонд	(3) Газозаборный зонд, $T_{макс}$ – 400° C, длина 335 мм со шлангами длиной 2,2 м и кабелем	9510	520,--
	(5) То же, $T_{макс}$ – 1000° C, длина 335 мм	8710	685,--
	(6) То же, $T_{макс}$ – 1000° C, длина 655 мм	8510	820,--
Вспомогательные принадлежности	(7) Кабель для подключения ИЗМЕРИТЕЛЯ к АНАЛИЗАТОРУ длиной 5 м (вместо указанного в поз. 1)	0409.3301	175,--
	(8) Устройство для установки зонда в газоход с матерчатым поясом	0554.0094	171,--
	(9) Кабель для подключения внешних устройств к аналоговому выходу	0409.0084	110,--
	(11) Принтер с запоминающим устройством	0554.0070	820,--
	(12) Аккумуляторные батареи к принтеру	0515.0088	35,--
	(13) Бумага для печати, 1 упаковка (5 рулонов)	0554.0149	15,--
	(16) Кейс для прибора с комплектующими	0516.0130	280,--

Мы рекомендуем:

— **testo 33** базовый комплект, включая:

(1) ИЗМЕРИТЕЛЬ с кабелем для подключения к АНАЛИЗАТОРУ

(2) АНАЛИЗАТОР с аккумулятором для измерения температуры, разрежения, O_2 и CO, расчета CO_2, потерь тепла с уходящими газами и коэффициента избытка воздуха (0632 9433)

(3) Газозаборный зонд со шлангами и кабелем (9530)

(17) Футляр для прибора

Стоимость марок ФРГ

— **testo 33** базовый комплект с принтером **(0554.0070)**

Стоимость марок ФРГ

Возможны некоторые изменения без предварительного извещения

Газозаборный зонд

Газозаборный зонд с присоединительными шлангами и кабелем

testo

Electronic measurement
of physical and chemical values

testo 350

Precision measurements for flue gas analysis and emissions monitoring

ISO 9001 TESTO QUALITY certified



0986.2223/vc/R/08.94

Quality

Testo has been developing and manufacturing portable flue gas analyzers for over 15 years. Over this time, our research and development engineers have evolved our products based on customer experience and ideas. This way we provide you with a quality product that meets your needs.
High standards, a favorable price performance relationship and customer-orientated service has made testo the worldwide market leader of portable combustion analyzers.

Summary of flue gas analyzers	testo 342	testo 350	testo 350 + testo 339
°C/°F, O_2, CO_2, qA	X	X	X
NO_2, SO_2		X	X
CO, NO, NO_x	X	X	X
Battery operation	X	X	
RS-232 interface		X	X
Printer connection	X	X	X
Infrared interface for Palmtop PC		X	X
CO cell overload shut-off	X	X	X
Remote operation of analyzer		X	X
Long-term measurement up to 12 hours			X
Flue gas probes up to +1830°F	X	X	X
Continuous meas. of flue gas and ambient temperature	X	X	X
CO measuring range 0 to 4000 ppm	X	X	X
CO measuring range 0 to 40000 ppm		X	X
Datalogging capability		X	X
Test Gas Calibration	X	X	X
Integrated humidity and velocity meas		X	X

The Company Background

In 35 years Testo has developed from a workshop to a successful medium-sized company wiht 500 employees worldwide. Testo is privately owned and financially secure. Only by internal growth and without acquisition, Testo has achieved the position of a worldwide market leader and still lives by the original success philosophy.

- [illegible]
- Humidity
- [illegible]
- Flue gas
- Water
- Analysis
- Lux/sound
- rpm

Company innovations

The company has 65 research and development engineers that are dedicated to develop future measurement technology.

Quality standards

Testo products are manufactured under the official quality assurance standards of ISO 9001. Being one of the first in this industry, Testo again sets standards for the entire market.

Measuring Industrial and Residential Combustion Sources

Testo 350 Qualifies for Many Applications

The extreme versatility of the testo 350 allows it to be used in numerous industrial and residential applications. When combined with the testo 339 Gas Conditioning Unit, the applications become limitless.

Possible Applications Include:

1. Professional burner/ boiler maintenance.
2. Tuning industrial/ residential burners to optimum. efficiency
3. Frequent internal audits of installed-CEMS.
4. Avoid unnecessary costs due to additional RATA tests through internal audits.
5. Internal emissions inventory survey.
6. Fine tune process heaters.
7. Measure and report according to certain requirements from various State EPA's. [call to find out if your source qualifies]



Application of the Testo 350 - Three Scenarios





Burner Tuning & Maintenance

The testo 350 provides all the required readings for burner optimization. All necessary parameters are measured separately and combined into one true efficiency value according to ASME standards. Parameters to calculate efficiency via differential pressure or differential temperature are provided.



Emissions Testing

Fast, accurate, and economic emissions testing is a valuable tool for all environmental professionals. Set-up and ready to operate in a few minutes, the system can measure and record data for up to 12 hours. The measured results are not affected by high condensate levels, dust, or soot. The accurate measurement of NO_x emissions is becoming increasingly more important. By combining an actual air velocity and relative humidity measurement, the testo 350 provides emissions values in either pounds per hour or tons per year.

Industrial Process Optimization

In processes such as glass or ceramic furnaces very high gas concentrations are reached. The testo 350 can tolerate these measuring ranges. Thanks to it's memory chip, each cell comes pre-calibrated. As a result, field replacement of cells is as easy as and takes as long as changing a battery.

esto 350 at a glance

Flue gas probe

Moisture trap



CO
NO
NO_2
NO_x

The analyzer unit:

- Basic set-up
  O_2, CO_2, °F/°C, "H_2O, excess air, efficiency

PC software: ▶
- Display & evaluate measured data with Windows® Software

Infrared printer: ▶▶
- Document measured values with the small & rugged printer
- Wireless infrared data transmission to eliminate cumbersome printer cables





Gas conditioning unit (optional): ▲
- Removal of the moisture from the flue gas for more accurate and long-term measurements

Measuring modules:
- Can be easily added
- Allows individual set-up of analyzer with any combination of CO, NO, NO_2, SO_2



The Comfort hand-held instrument ▶
- To control the analyzer unit
- Integrated datalogger
- Displays humidity and velocity measurement


Intake air temperature
Ambient Humidity & Temperature
Pressure
Flue gas velocity

Infrared printer: ▶
- Control via infrared beam
- Simple, compact documentation
- No awkward cable connections

PC software: ▶▶
- To display and process the measured values









Measuring modules:
- Can be easily added
- Allows individual set-up of analyzer with any combination of CO, NO, NO_2, SO_2

The basic hand-held instrument ▶
- to operate the measuring unit

The hand-held instruments

A choice of two versions



Functional description

The entire control of the system is performed by the hand-held instruments. The remote instrument comes with a 60 foot cable. This allows simultaneous stack gas measurements while tuning the burner.

The advantages of the hand-held instrument include:

- 4 line, easy-to-read LCD display
- Output of measured values in ppm or lbs/Mbtu
- Sealed key pad
- User-friendly operation
- Test gas calibration via user-menus
- Lockable plug-in connection



e basic hand-held instrument

Second temperature probe input for simultaneous measurement of intake air & stack gas temperature
Infrared data transmission to remote printer
RS 232 (V24) interface for data transmission to PC
20 selectable fuels
CO_2 max.value for all fuels freely selectable

Additional features of the Comfort hand-held instrument

- Integrated memory for approx. 500 sets of data
- RS 232 (V24) interface for data transmission to PC
- Galvanically separated
- Measurements can be saved with comments
- Pressure or differential pressure meas. with an external probe
- Measurement of flue gas velocity using Pitot tube
- Humidity measurements using the testo humidity probe
- Optional interface to control the **testo 339** Gas Conditioning Unit, which allows programming of fresh air and flue gas cycles, self-tests, automatic zero point and drift monitoring.

The analyzer unit

The heart of the measuring system

Features

- The pump draws against negative pressures of up to 40 inches of water
- AC/DC operation
- 3 different CO measuring cells cover different measuring ranges up to 40.000ppm
- Integrated draft measurement
- CO cell overload shut-off system to protect CO cell against hazardous gas concentrations Other cells remain in use.
- Field replaceable measuring cells without test gas calibration (like changing batteries)

Description of the Unit

The gas analysis is performed in the analyzer unit.
The flue gas is drawn in by a pump and passed along the sensors (electrochemical cells).The actual gas concentrations are transformed into electrical signals which can be measured and transmitted to the hand-held instrument.

User-friendly upgrades

The basic analyzer box can be upgraded with modules. The upgrades are possible in the field at any time without test gas calibration

Analyzer box-basic set-up
O_2, CO_2, °F/°C, hPa/"H_2O, efficiency & excess air in flue gases

Upgrade modules CO, NO, NO_2, SO_2, RH, fpm

testo

The probe selection

... to suit your individual needs

Flue gas probes

- Easy to clean
- Easy replacement of tubes & thermocouples
- Testo patented, reliable moisture trap
- Immersion depths 12 and 28". Other lengths available
- High-quality hose for NO_2 & SO_2 measurements available. Separate gas & draft hoses eliminates interference of moisture on draft measurement

Humidity probes

- Capacitive **testo•** humidity sensor
- Sensor drifts < 1% per year
- Highly accurate < ± 2%
- Temperature stable up to 280°F

Pressure probe, Pitot tube

- Measurement of differential pressure up to 40" H_2O
- Flue gas velocity up to 6000 fpm
- Pitot tubes available in various lengths, diameters and materials

Application	Comfort probe for flue gas measurement	Comfort probe for flue gas measurement	Compact probe for flue gas measurement (not used with the gas sampling unit)	Monitoring ambient humidity
In connection with...	Analyzer box and basic or Comfort-hand-held instr.	Analyzer box and basic or Comfort hand-held instr.	Analyzer box and basic or Comfort hand-held instr.	Comfort hand-held instrument
Measuring range	T_{max} = +1830°F	T_{max} = +1830°F	T_{max} = +932°F	0 to 100% RH (probe tip) -4 to +158°F
Temperature sensor	NiCr-Ni	NiCr-Ni	NiCr-Ni	NTC
Immersion depth	28"	16"	12"	10"
Ø probe hose	0.032"	0.032"	0.032"	0.063"
Gas outlets	2	2	2	
Cable length	7.22'	7.22'	7.22'	5.0'
Probe	Flue gas probe with standard gas sampling hose*) 0600.8520	Flue gas probe with standard-gas sampling hose*) 0600.8720	Compact probe with standard-gas sampling hose*) 0600.9522	Humidity / temperature probe 0636.9767
	Flue gas probe with advanced gas sampling hose*) 0600.8521	Flue gas probe with advanced gas sampling hose*) 0600.8721	Compact probe with advanced gas sampling hose*) 0600.9523	

The correct gas sampling hose for your application		
	Measurement of °C, O_2, CO, NO	Standard gas sampling hose with moisture trap, L 7.22'
	Short-term measurement of NO_2, SO_2	High-quality gas sampling hose with separator and moisture trap, L 7.22'
	Long-term meas. of °C, O_2, CO, NO, NO_2, SO_2	Heated gas sampling hose in connection with gas sampling unit, L 7.22 or 13' (Refer to Accessories)

*) For the heated gas sampling hose refer to the Ordering data for the sample conditioning unit

Monitoring of waste gas humidity to 284°F	Measurement of pressure and differential pressure		Measurement of the flue gas velocity in combination with pressure probe			Separate measurement of combustion air temperature
Comfort-hand-held instr.	Comfort hand-held instrument		Comfort hand-held instrument			Basic or comfort-hand-held instrument
0 to 100% RH -4 to +284°F	40"r	4"	T_{max} = 662°F 200 to 6000 Fpm	T_{max} = 662°F 200 to 6000 fpm	Tmax = 932°F 200 to 6000 fpm	T_{max} = 212°F
NTC	–	–	–	–	–	NTC
12"	–	–	20"	14"	12"	12" with cone
0.047"	Pitot tube connection 0.02"	Pitot tube connection 0.02"	0.03"	0.03"	0.015"	0.02"
–	–	–	–	–	–	–
5.0'	5.0'	5.0'	–	–	–	5.0'
Humidity / temperature probe 0636.2167	Pressure probe 0638.1545	Pressure probe 0638.1445	Pitot tube, brass 0635.2045	Pitot tube brass 0635.2145	Pitot tube, stainless steel 0635.2245	Air probe 0610.9713



The gas conditioning unit

For long-term measurements up to 12 hours



In order to obtain long-term measurements, moisture has to be removed from the stack gas sample. Otherwise the moisture increases in the system and leads to chemical reactions with NO_2 & SO_2, which affects the results significantly.

The compact **testo 339** gas conditioning unit removes the moisture from stack gas samples, which ensures an accurate reading.

Simply connect the testo 339 between the stack and the **testo 350** analyzer whenever gas conditioning is required. The entire system is ready for measurements in less then five minutes.

The testo 339 is designed to work with the testo 350. The system functions automatically and it is self-controlled. The testo 339 controls the temp. of the stack gas sample, the removal of the moisture, sampling time and fresh air purge cycles.

The gas conditioner also protects the analyzer from possible damage as a result of hazardous gas concentrations by interrupting the flow of the stack gas sample and by purging with fresh air.



Features

- Weighs only 10.5 lbs
- Automatic operation for long-term measurements
- Easy to maintain and clean with auto-purge button
- Ensures accurate NO_2 & SO_2 measurements
- For unattended long-term meas. up to 12 hours
- Handles sample moisture up to 140°F dew point

Comprehensive documentation of the measured data

with printer or PC

The Testo® Comfort Software...

In the PC the measuring values can be reviewed, analyzed, and stored with the testo Comfort Software. testo Comfort Software provides a great variety of statistical functions to analyze the measured values. Maximum & minimum calculations are provided as well as mean values, standard deviations, and variances. For compliance purposes each parameter can be averaged at 1, 5, 15 minutes and 1 hour averages. The data can be linked to a specific stack identification number. Calculations of ppm, lbs/hr or tons/yr can also be easily executed with the testo Comfort Software. Comments (e.g. fuel type / operating times) can be attached to the data sets. The export function of the testo Comfort Software provides the data sets in ASCII format for further evaluation in other spreadsheets or databases. The original set of data, however, cannot be altered, which ensures manipulation-free emissions values.

Infrared printer

In most applications a print-out is needed to document the measured values. To avoid tedious cable connections between the analyzer and printer, testo has invented a transmission technology completely new to the market. Testo uses a wireless infrared data transmission system, which works like a TV remote control. Measured values are transmitted dependably over distances of up to 20 feet. Especially in a burner environment, the cable-free data transmission makes documentation convenient, time-saving, error free, and easy to manage. Two freely programmable lines allow users to comment on the measured values or to add information.

Data Transmission to the PC

The measured values can be downloaded to a PC with a standard RS-232 cable. This can be performed real-time while collecting the data without interrupting the measurement. In addition the Comfort Software version of the instrument allows the contents of it's memory to be downloaded at anytime. The memory contains up to 500 sets of measurements which are accessible during or after completion of the tests.

ıccessories

ared printer

measured data is transmitted ctly from the hand-held rument via an infrared beam. data is printed quickly and ably on-site without any tedious le connections. One comment ihanumeric) per measurement be printed.



Accessories for gas conditioner

1 Moisture trap
2 preliminary filter for operation in dirty ambient air
3 set of hose filters

Maintenance kit for testo 339

1 pump head for hose pump, 5 air filters, 5 fuses including assembly instructions.

Circuit board for remote operation of conditioner

To control the gas conditioner from the Comfort hand-held instrument, an additional circuit board with interface can be mounted. Averaging function & pump control are benefits of this accessory.

ıperature-controlled sampling hose

temperature-controlled, heated e (up to 13") with an integrated, particle filter maintains the flue at 300°F. This feature inates potential chemical tions of condensation with NO_2, SO_2 to ensure accurate and -term stable measurements of & SO_2 parameters.



Carrying Case

1 Carrying case for the complete measuring system, 7.2" hose, flue gas probe and accessories.
2 Service case for hand-held instrument, analysis box, flue gas probe and tools
3 Service case with shoulder strap
Not shown: carrying case for analyzer or gas conditioner (same design as 1)



Calibration certificates

Every testo 350 analyzer comes with factory calibrated measuring cells. A full calibration of the ordered configuration prior to delivery is available upon request. NIST traceable calibrations of the humidity, air velocity, & pressure probes are also available.

Technical data

testo 350

Temperature measurement:

Measuring range:	- 40 to + 1800°F
Accuracy	± 32.9°F (32 to + 212°F) ± 0.5% of m.v.(from+212°F)

Draft/pressure measurement:

Measuring range:	± 20" H_2O
Resolution:	0.04" H_2O

O_2 measurement:

Measuring range:	0 to 21 vol. %
Accuracy	± 0.2 vol %
Measuring method:	Electrochemical meas. cell
Response time t_{95}:	Approx. 20s

CO_2 calculation :

Display range:	0 to CO_2max
Calculation:	Digital calculation from O_2

CO measurement (without H_2 compensation):

Measuring range:	0 to 20000 ppm
Accuracy:	± 20 ppm (to 400 ppm) ± 5% of m.v. (to 2000 ppm) ± 10% m.v. (to 20000 ppm)
Response time t_{90}:	Approx. 40s
Measuring range:	0 to 40000 ppm
Accuracy:	± 50 ppm (0 to 1000 ppm) ± 5% of mv(1000 to 10000 ppm) ± 10% of mv (>10000 ppm)
Response time t_{90}:	Approx. 40s

CO measurement (with H_2 compensation):

Measuring range:	0 to 10000 ppm
Accuracy:	± 20 ppm (to 400 ppm ± 5 % of m.v. (to 2000 ppm) ± 10 % of m.v. (to 10000 ppm)
Response t_{90}	Approx. 40 s

NO measurement:

Measuring range:	0 to 3000 ppm
Accuracy:	± 5 ppm (to 100 ppm) ± 5 % of m.v. (to 2000 ppm) ± 10 % of m.v. (to 3000 ppm)
Measuring method:	Electrochemical meas. cell
Response time t_{90}:	ca. 20s

NO_2 measurement:

Measuring range:	0 to 500 ppm
Accuracy:	± 10 ppm (to 100 ppm) ± 5 % of m.v.(> 100 ppm)
Measuring method:	Elektrochemical meas. cell
Response time t_{90}:	Approx. 40s

SO_2 measurement:

Measuring range:	0 to 5000 ppm
Accuracy:	± 20 ppm (to 400 ppm) ± 5 % of m.v. (to 3000 ppm) ± 10 % of m.v. (to 5000 ppm)
Measuring method:	Elektrochemical meas. cell
Response time t_{90}:	Approx. 40s

Humidity measurement:

Meas. range, humidity:	0 to 100 %RH
Meas. temperature:	- 4 to + 284°F

Velocity measurement:

Meas. range, velocity:	197 to 1970 (5906) fpm
Application, temperature:	32 to + 932°F

Differential pressure measurement:

Measuring range:	± 40" H_2O
Accuracy:	± 0.04" H_2O (0 to 8" H_2O) ± 0.5% of mv (8 to 40" H_2O)
Resolution:	0.004" H_2O
Measuring range:	± 4" H_2O
Accuracy:	± 0.012" H_2O
Resolution:	0.004" H_2O

testo 350

Dimensions:

Hand-held instrument:	7.7 x2.1 x 1.7"
Analyzer:	11.5 x 6.4 x 6.2"

Weight:

Hand-held instrument:	Approx. 0.5 lbs
Analyzer:	Approx.6.17 lbs

General data:

Housing:	Plastic (ABS) (instrument and analyser)
Max. operating temp.:	+ 39.2 to + 104°F
Max. storage and transport temperature:	- 4 to +122°F
Power supply:	System or integr. batt. block

Gas conditioning unit

Functional principle:

Peltier cooler

Power supply:

Instrument: 90 to 260 V, 47 to 63 Hz
Hose: 110 V or 230 V

Max. smoke load:

20 g/m³ smoke in flue gas

Max. humidity load:

+140 °F dew point temperature at inlet

Operating temperature:

+41 to +104 °F

Max. flow:

0.06 ft³/min

Storage and transport temperature:

-4 to +122 °F

Housing:

Aluminium, 7.1 x 6.7 x 12" with handle

Hose:

O 1.2" temperature-controlled +302°F...+338°F

Weight:

Instrument: Approx. 10.5 lbs
Hose: Approx. 2.65 lbs / 7.2" long

Printer

Type of printer:

infrared-controlled thermal printer, adjustable contrast

Printing capacity:

Approx. 300 printouts per roll

Reception radius:

Max.7.0'

Dimensions:

7.3 x 3.6 x 2.4 "

Weight:

0.95 lbs (incl. batteries)

Operating temperature:

32 to + 122 °F

Storage temperature:

- 8 to + 140 °F

Power supply:

4 AA, 1.5 V or NC rechargeable batteries

Flue gas probes

Length:

12 - 28"

t_{max}:

900 / 1800 °F

Weight:

Flue gas probe 0600.8520	2.0 lbs
Flue gas probe 0600.8720	1.8 lbs
Flue gas probe 0600.9522	0.9 lbs

Warranty:

Measuring instrument:

(expendable parts exempted)
such as measuring cells, filter, pump, rechargeable batteries.) 24 months

Probes:

12 months

Hose, can be heated:

6 months

O_2 cell:

18 months

CO, NO, NO_2, SO_2 module:

6 months

Monitoring industrial burners

he **testo 350** is the right measurement system.







1 Adjustment of the oxygen content in an anthracite conveyor and measurement of SO_2 and NO_x. Measurements are taken at various points with a 65' length cable connected to the instrument.

2 Tuning of a cogen[illegible]or.

3 Monitoring the SO_2 content before and after a scrubber.

testo 350
Order form

Description	Order No.
Analyzer unit / Module / Options	
Analyzer unit, basic version testo 350: °F, draft, O_2, CO_2, excess air, efficiency	0632.3500
CO module 1①,measuring range 0 to 10.000 ppmH_2 compensated	0440.3503
CO module 2①,measuring range 0 to 20.000 ppm	0440.3502
CO module 3①,measuring range 0 to 40.000 ppm	0440.3507
NO module 4, measuring range 0 to 3.000 ppm	0440.3504
NO_2 module 5, measuring range 0 .to 500 ppm	0440.3505
SO_2module 6, measuring range 0 to 5.000 ppm (if the NO_2 content in the waste gas > 20 ppm please order NO_2 module)	0440.3506
CO measuring cell switch-off and rinse function	0470.0350
Control module for gas conditioning testo 339 (only with Comfort hand-held instrument 0560.3520) incl. averaging and pump monitoring (also order connection cable 0409.0154 - Refer to back page)	0470.0351
Hand-held instruments	
Basic hand-held instrument testo 350, with additional temperature probe input, RS 232 (V24) and infrared interface	0560.3510
Comfort hand-held instrument testo 350, with additional temp. probe input, integrated memory, input for fpm, %RH, Δ P measurements, RS 232 (V24) electrically isolated and Infrared interface	0560.3520
Accessories	
Ac adapter testo 350	0554.0085
Connection cable, spiral cable for connection between hand-held instrument/analyzer unit	0409.0350
Connection cable 16' for connection between hand-held instrument/analyser unit	0409.0351
Connection cable 32' (as above)	0409.0352
Connection cable 65', (as above)	0409.0353
Flue gas probes	
Flue gas probe*) T_{max} = +1830°F, immersion depth 28", (incl. 7.22' conn. hose and cable)	0600.8520
Flue gas probe as above, but with high quality hose material and moisture trap for short-term NO_2, SO_2 measurements	0600.8521
Flue gas probe*) T_{max} = +1830°F, immersion probe 12", (incl. 7.22' conn. hose and cable)	0600.8720
Flue gas probe as above,but with high-quality hose material and moisture trap for short-term NO_2, SO_2 measurements	0600.8721
Compact probe*) T_{max} = +930°F, immersion probe 12", (incl. 7.22' connection hose and cable) not for use with gas conditioning option	0600.9522
Compact probe as above, but with high quality hose material and moisture trap for short-term NO_2, SO_2 measurements	0600.9523
Probes	
Air probe, NTC for separate measurement of the combustion air temperature, T_{max} = + 140°F L 2.36" in total	0610.3613
Air probe, T_{max} to + 212°F, L 11.82", Ø 19" with a cone to attach the probe	0610.9713
Pressure probe②, 4" H_2O	0638.1445
Pressure probe②, 40" H_2O	0638.1545
Magnetic holder for pressure probes	0554.0225
Silicon hose for pressure probes, L 16"	0554.0440
Pitot tube②, for flue gas velocity, Chromed brass, Ø 28", L 19.7", max.temperature 662 °F	0635.2045
Pitot tube②, for flue gas velocity, Chromed brass, Ø 28", L 13.8", max. temperature 662 °F	0635.2145
Pitot tube②, for flue gas velocity, Stainlies steel, Ø 15", L 11.8", max. temperature 932 °F	0635.2245
Probe to measure humidity and temperature②, 0 to 100 %RH, T_{max} = + 158°F	0636.9767
Probe to measure humidity and temperature②, 0 ... 100 %RH, T_{max} = + 284°F	0636.2167

① only one CO module can be built in. ② only with Comfort hand held instrument 0560.3520

Attention, do not forget to order the connection cable and the AC adapter

How to order

Example

testo 350, basic set

Basic hand-held instr.	0560.3510
Analyzer unit, basic version **testo 350**	0632.3500
CO module 2	0440.3502
Infrared printer	0554.0345
Coiled cable	0409.0350
System	0554.0085
Service case	0516.0130
Compact probe	0600.9522

testo 350, complete set (with optional gas cond. unit)

Comfort hand-held instr. **testo 350**	0560.3520
Analyzer unit, basic version **testo 350**	0632.3500
CO module 1	0440.3503
NO module 4	0440.3504
NO_2 module 5	0440.3505
SO_2 module 6	0440.3506
Connection cable, Hand-held instr. → PC	0409.0154
Connection cable, Analyzer box → Gas cond. unit	0409.0154
System	0554.0085
Coiled cable, Hand-held instrument → Analyzer unit	0409.0350
Flue gas probe	0600.8720
Infrared printer	0554.0345
Transport case	0516.0139
Gas conditioning unit **testo 339**	0563.3390
Control module for gas conditioning unit **testo 339**	0470.0351
Moisture trap	0554.0391
Gas sampling hose, heated	0401.0390

How to order

Please fill out a separate ordering form for each analyzer configuration. You can order as described according to the following examples:

Ordering examples for 3 analyzer unit configurations:

Each configuration must include:
- Hand-held instr. of your choice
- Flue gas probes of your choice
- Connection cables of your choice and AC adapter

Combination 1:

Analyzer unit, basic version, **testo 350**	0632.3500
CO module 1	0440.3503
NO module 4	0440.3504

Combination 2:

Analyzer unit, basic version **testo 350**	0632.3500
CO module 2	0440.3502
CO meas. cell switch-off function	0470.0350

Combination 3:

Analyzer unit, basic version **testo 350**	0632.3500
CO module 3	0440.3507
NO module 4	0440.3504
CO meas. cell switch-off function	0470.0350

testo 350

Description	Order no.	Price	Please tick
Accessories / Printer			
Infrared thermal printer to printout measured values incl. 4 round cell batteries, 1 roll of thermal paper	0554.0345		
Comfort software	On request		
Battery charging unit for infra-red printer, incl. 4 NC-rechargeable batteries	0554.0110		
Additional thermal paper (6 rolls)	0554.0115		
Self-adhesive bags, (50 off) to attach the print-out to the boiler	0554.0116		
Connection cable, hand-held instr. → PC or analyzer box → gas conditioning unit, L 6'	0409.0154		
Analog output with 6 channels in an external housing, connection via RS 232 interface	On request		
Cases			
Service case, leather, for hand--held instr., analyzer, flue gas probe (short) and tools	0516.0130		
Carrying strap for the analyzer	0516.0060		
Transport case, aluminium edges, for gas conditioning unit, hand-held instrument, analyzer box, heated hose, probe and accessories	0516.0139		
Transport case, aluminium edges, for analyzer, complete or gas conditioning unit, complete	0516.0350		
Case incl. carrying strap	0516.0038		
Gas conditioning unit / Accessories			
Gas conditioning unit testo 339, incl. power cable, 2 spare fuses, Connection cable to the analyser **testo 350** (L 1.31'), service hose	0563.3390		
Gas sampling hose, heated, L. 7.22', 230 V version, incl. filter insert	0401.0390		
Gas sampling hose, as above, 110 V version	0401.0396		
Gas sampling hose heated, L 13.12', 230 V version, incl. filter insert	0401.0395		
Condensate container for attachment to the gas conditioning unit	0554.0391		
Spare parts pack for gas conditioning unit: 1 pump head for hose pump, 5 ventilator filters, 5 fuses incl. assembly instructions	0554.0392		
Hose filter insert for gas sampling hose (5 pack)	0554.0393		
Preliminary filter to protect gas paths (gas conditioning unit) in fresh air (dust load)	0554.0394		

For calibration certificates order our special brochure

Subject to change.

Address

Company

Department

Name

Street

Town/ County/ Zip code

Telephone

Date

Signature

Testo Inc.

230 Route 206
Flanders, N.J. 07836
Phone 201-252-1720
Toll Free 800-227-0729
Fax 201-252-1729

Jerry

B-6

The use of Alternative Fuels in the Cement Industry

SEMINAR

THE USE OF ALTERNATIVE FUELS IN THE CEMENT INDUSTRY IN LITHUANIA

AKMENES CEMENT PLANT
AKMENE, LITHUANIA
OCTOBER 10, 1994

PRESENTED BY WEC VOLUNTEER CONSULTANTS

FRANK C. STEVENS
AND
FRANKLIN A. PHILLIPS

A TECHNICAL ASSISTANCE PROJECT OF
WORLD ENVIRONMENT CENTER
NEW YORK, N.Y. 10016

EXECUTIVE SUMMARY

Innovative ideas and new technologies are continually needed to manage hazardous waste. At present, one of the more controversial options in waste management is the burning of hazardous waste in cement kilns. This practice can result in the following benefits:

- energy recovery from combustible wastes with a high energy, low chlorine, and low metals content
- conservation of fossil fuels, such as coal and oil
- reduction in cement production costs
- destruction of hazardous organic waste.

The issues associated with burning hazardous waste in cement kilns are not generally reported in publicly accessible literature. This document has been written as a resource to help answer many of the questions that arise when evaluating this technology.

In presenting a comprehensive overview of the technical and regulatory issues surrounding the use of hazardous waste as a supplemental fuel in cement kilns, this document addresses the following topics:

- the cement production process
- restrictions on the wastes that can be used by the cement industry
- characteristics of a cement kiln that make it a suitable combustion device for the treatment of hazardous waste
- federal regulations that govern cement production facilities burning hazardous waste
- the fate of the constituents in the hazardous waste fuel
- the potential for adverse human health effects.

This analysis concludes that the organic and metal emissions of a well-designed and properly operated cement kiln burning hazardous waste are not substantially different from the emissions of a cement kiln burning only conventional fuel. In addition, the byproduct of the production process (i.e., cement kiln dust) and the final product (i.e., cement) do not appear to differ substantially as a result of burning hazardous waste as a supplemental fuel.

Because no substantial increases in organic and metal components have been observed in emissions, in cement kiln dust, or in cement when hazardous waste is burned as a supplemental fuel, no increases in adverse health effects due to the use of hazardous waste are expected. Assessments of health risks from emissions and cement kiln dust from kilns in the U.S. have supported this conclusion. Thus, properly operated cement production facilities under current (1991) regulations do not pose a greater risk to public health when a portion of the conventional fuel is replaced by hazardous waste.

THE USE OF ALTERNATIVE FUELS IN THE CEMENT INDUSTRY IN LITHUANIA

1. THE CEMENT INDUSTRY

   Overheads 1-6

2. ALTERNATIVE FUELS HISTORY IN CEMENT PLANTS

   Overheads 1-3

3. TYPES OF WASTE STREAMS AVAILABLE, AND THEIR SOURCES

   Overheads 1-8

   A. Tires: Municipalities, landfills, neighborhoods, import from U.S.A.

   B. Used oil: Vehicle maintenance and service, hydraulic systems

   C. Flammable solvents: Line flush material, tank cleaning, off-specification material, adhesive manufacturers, paint and coatings formulators, furniture manufacturing, laboratories, waste ink and printing, solvent still bottoms, rubber cements, marine glues, epoxies

   D. Chlorinated solvents: Vapor degreasers, carburetor cleaner, paint remover, laundries, dry cleaning

   E. Industrial sludges and filter cakes: Oil refineries, metal plating

   F. Contaminated soils: spills, releases, refineries

   G. Polychlorinated biphenyl (PCB) containing oil: Transformers and capacitors from electric power equipment

F.S. 4. BENEFITS OF BURNING WASTE MATERIAL AS FUEL

Overhead 1

A. Savings on fuel costs

B. Conserve coal supply

C. Clean up contaminated areas and waste materials from your facility

D. Help prevent soil contamination by decreasing indiscriminant dumping by waste generators

E. Help prevent aquifer contamination (ground water and water wells)

F. Help prevent air pollution from evaporating liquids

F.P. 5. CONTROLLED VS. UNCONTROLLED CLINKERING PROCESS

Overheads 1-3

A. Elevated temperature plus mixing action and residence time

B. Large heat mass in the clinker in kiln

C. Limit the percent of excess oxygen to 1-2%

D. Use continuous kiln emission monitoring instruments

E. Process analyzer

F. Process control computers for kiln operation

G. Automated controls

F.P. 6. COMBUSTION PRODUCTS AND CLINKERING ACTION

Overheads 1-3

A. $CaO + Al_2O_3 + Fe_2O_3 + SiO_2 \longrightarrow$ Cement compounds

B. Organic hydrocarbons $+ O_2 \longrightarrow CO_2 + H_2O$

C. Organics containing nitrogen $\longrightarrow NO_x$

D. Organics containing sulfur $\longrightarrow$ SO_x

E. Organics containing halogens $\longrightarrow$ HCl , However, there are no HCl vapors emitted from cement kilns since they are absorbed by the alkali atmosphere in the kiln.

F. Organics containing metals

Metals + O_2 + SiO_2 $\longrightarrow$ metal silicates

Toxic metals are lost in the large mass of produced clinker

7. REQUIREMENTS FOR USING ALTERNATIVE FUELS

A. Destruction and removal efficiency (DRE) of 99.99% for RCRA hazardous wastes

B. Demonstrate 99.99% DRE while burning principal organic hazardous constituents (POHCs)

C. Particulate matter emissions are limited to 0.08 Gr/DSCF, corrected to 7% oxygen

8. PUBLIC RELATIONS

Overheads 1-2

9. AGREEMENTS WITH GOVERNMENT, SUPPLIERS, AND TRANSPORTERS

Overhead 1

10. SAFE TRANSPORTATION

A. Trucks are properly designed, inspected, and maintained

B. Drivers are trained in hazardous materials

C. Drivers are trained in spill and fire response

11. PROTECTION OF EMPLOYEES

A. Proper personal protective equipment is worn whenever needed: Splash protection, eye protection, hand protection

B. A respiratory protection program is developed and implemented at the plant

F.P. 12. PREQUALIFICATION OF WASTE SUPPLIERS AND THEIR WASTE STREAMS

A. Obtain a representative sample of the waste stream from the prospective supplier

B. Analyze the waste stream for standard parameters:

1. Specific gravity

2. pH

3. Thermal energy content (KCal/kgm, or BTU/lb)

4. Water content

5. Halogen content

6. Toxic metals content

Perform an extractable metals analysis to determine if the waste stream is regulated as a hazardous waste or not. An extractable metals analysis is also performed on the kiln dust occasionally to verify that toxic metals are not being emitted from the stack

Perform a total metals analysis to determine the metals (waste stream) feed rate into the kiln

C. Sample and analyze the blended waste stream prior to feeding it into the kiln

F.S. 13. PLANT FACILITIES MODIFICATIONS FOR USING ALTERNATIVE FUELS

Overheads 1-2

F.S. 14. CONTROL OF CEMENT QUALITY DURING WASTE BURNING

F.S. 15. AIR EMISSIONS AND CONTROL DURING BURNING

A. Accomplished through continuous emission monitoring (CEM) data to help control combustion conditions

F.P. 16. HEALTH AND SAFETY OF ALL PLANT WORKERS

A. Establish safe working conditions

B. Train workers in the principles of safe work practices

17. HEALTH AND SAFETY OF ALTERNATIVE FUELS HANDLERS

A. Training of waste fuel site workers

1. Principles of safety applied to unloading. storing, transferring, and injecting into the kiln

2. Hazardous characteristics of wastes:

Ignitability

Corrosivity

Reactvitiy

Toxicity

B. Training of the emergency response team members

1. Spill response principles, techniques and equipment

2. Fire response principles, techniques, and equipment

C. Secondary containment requirements for storage areas and material off-loading areas

D. Site security for waste storage and handling areas

E. Preparedness and Prevention Plans and required safety equipment

F. Contingency Plans for hazardous wastes incidents

18. IMPORT AGREEMENTS

19. TIME FRAME TO IMPLEMENT WASTE PROGRAMS

20. INITIAL CAPITAL INVESTMENTS REQUIRED

A. Engineering

B. Purchasing

C. Construction

D. Training

21. SUMMARY

CEMENT INDUSTRY

- Manufacturing is energy intensive
  - Electricity used for operating process equipment and controls
  - Fuels used for firing cement kilns
  - Cost of energy 60 to 70 per cent of manufacturing cost

Table 1 Cement Industry Energy Efficiency
Table 1.1 Average Energy Intensities of Building Materials
Table 1.2 Comparison of Energy Intensities in End Products
Table 2.1 Energy Consumption by Manufacturing steps
Table 3.1 Comparative Thermal Energy Consumption in Various Pyroprocessing systems
Table 3.2 Comparative Features of Different Cement Producing Technologies
Diagram 1 Dry and Wet Process Flows
Diagram 2 Precalciner Process Flow

- Fuel Costs are Expensive
  - Fuel for cement kilns
  - Fuel for electric power generating plants
  - Cogeneration plants using process heat

- Use of energy is 1000 to 2000 megacalories per ton of cement

  - Electricity 90 to 140 kWh / ton cement

  - Fuel 800 to 1500 kcal/kg clinker

(kcals/kg of clinker)



Process	Total Energy Consumption	Energ Efficien (%)
Wet	1,400	30
Semi-Wet (Grate Preheater)	950	44
Semi-Dry (Grate Preheater)	835	50
Dry (Long Rotary Kiln)	965	43
4-Stage Preheater	750 – 850	49 – 5
4-Stage Preheater/ Precalciner	750 – 850	49 – 5

Dry and Wet Process Flows




Primary Crusher
Screen
Secondary Crusher
LIMESTONE QUARRY & CRUSHING
Sampling Tower
Elevator
Reclaiming
Stacking
PRE-BLENDING
Elevator
Separator
Sampling
Raw Mill
RAW GRINDING
KILN FEED
Electrostatic Dust Collector
DUST COLLECTION
Kiln
PYRO PROCESSING
Clinker Cooler
Clinker
Packing Machine
BULK LOADING
Gypsum
Clinker Storage
CLINKER STORAGE
Finish Mill
FINISH GRINDING

ALTERNATIVES FUELS HISTORY IN CEMENT PLANTS

- Year 1973. OPEC Nations. High Fuel Costs
- Change to alternative fuels
  - Types and sources, typical history
  - Specifications - Chart
- Operating history of cement kilns, chart
- Updates on cement kilns using alternative fuels
- Definition of alternative fuels picture
  - Ignitability
  - Corrosivity
  - Reactivity
  - Toxicity
- Described as hazardous only if the alternative fuel exhibits one or more of the characteristics

- World Wide Usage by Many Cement Companies:
  - Holderbank
  - Lafarge Copee
  - Italcement and Ciments Français
  - Cementos Mexicanos
  - Blue Circle
  - CBR and Heidelburg
  - Ask Grove
  - Unincem and River Cement
  - Scancen and Continental Cement
  - Onada Cement and other Asian Countries
- Alternative fuels include organic liquids, sludges and solids. Rubber tires usage in cement kilns is expanding

- World Wide Usage by Many Cement Companies:
  - Holderbank
  - Lafarge Copee
  - Italcement and Ciments Français
  - Cementos Mexicanos
  - Blue Circle
  - CBR and Heidelburg
  - Ask Grove
  - Unincem and River Cement
  - Scancen and Continental Cement
  - Onada Cement and other Asian Countries
- Alternative fuels include organic liquids, sludges and solids. Rubber tires usage in cement kilns is expanding

Summary:

- Use of hazardous wastes as fuel substitutes in cement kilns is a "fundamentally sound" technology
- Preferred alternatives to incineration
- Long residence times and high temperatures in cement kilns maximing combustion efficiencies. At hottest point 99.9999 to efficiency
- Available data on cement kilns very complete
- Produces quality product not harmful to health of public and environment

USE OF TIRES AS AN ALTERNATIVE FUEL

1. USED IN :

- CEMENT KILNS
- PULP AND PAPER MILLS
- ELECTRIC UTILITIES
- DEDICATED TIRE TO ENERGY FACILITIES
- ENVIRONMENTALLY ACCEPTABLE
- ECONOMICALLY FEASABLE

II. SCRAP TIRES ARE RESOURCE

- BETTER HEAT CONTENT THAN COAL
- LOWER NITROGEN AND SULFUR CONTENT
- LOWER GAS EMISSIONS

III. TIRE CHARACTERISTICS

- PHYSICAL, CHEMICAL

IV. COMBUSTION PROCESS IN CEMENT KILN

- SHREDDED OR WHOLE
- AIR QUALITY

V. CEMENT KILN USAGE

- U.S
- EUROPA
- ASIA
- MOROCCO AND OTHER COUNTRIES

VI. AVAILABILITY FOR EXPORT TO [redacted] THE BALTIC STATES

EMENT FACILITIES WHICH HAVE TEST–BURNED OR ARE BURNING TIRES

ANY NAME	PLT/MILL	CITY	STATE	APPX. SIZE TIRE BURNED
Portland Cement Co.	Rillito	Rillito	Arizona	2" X 2"
ve Cement West, Inc.	Durkee	Durkee	Oregon	2", wire free
cle, Inc	Atlanta	Atlanta	Georgia	
w Cement Co.	Boxcrow	Midlothian	Texas	2" X 6"
a Portland Cement	Mojave	Mojave	California	2.5" X 2.5"
ment–Calaveras Cement Co.	Redding	Redding	California	shredded
Cement		Dundee	Michigan	
aterials, Inc.		Nazareth	Pennsylvania	
Crushed Stone Co.		Leesburg	Florida	
source Recovery		Harleyville	South Carolina	
Hill Cement Co		Harleyville	South Carolina	whole
Hill Cement Co.		Midlothian	Texas	
M, Inc.	Main office	Dundee	Michigan	
M, Inc. for Ideal Basic Ind., Inc.		Dundee	Michigan	2" X 2"
ment		Seattle	Washington	2", wire free
Cement Co.		LaSalle	Illinois	
Cement Co.		Kosmosdale	Kentucky	shredded
Corp.	Main ofc.	Dallas	Texas	
Corp.	Balcones	New Braunfels	Texas	2", wire free
Portland Cement Co.		Allentown	Pennsylvania	
Cement		Charlevoix	Michigan	
Cement Co.		Cleveland	Ohio	
Concrete		Clinchfield	Georgia	
r Cement Co		Humboldt	Kansas	
s Peerless Cement		Detroit	Michigan	
ement Co.	Selma	Festus	Missouri	
one Star		Davenport	California	
e Cement Co.		Roanoke	Virginia	whole
wn, Inc. (Southwestern)	Lyons	Lyons	Colorado	3" x 3"
stern Portland Cement Co.		Fairborn	Ohio	whole–36"
GN FACILITIES:				
erger Cement Plant			W. Germany	
cle Dry Process Cement Works		Hope	England	whole
no Cement Co.			Japan	
Cement Co.			Japan	
u Cement Co.			Japan	
Cement Co.			Japan	

May 3, 1991

ANALYSES OF VARIOUS TIRES

TIRE TYPE	SOURCE	ENERGY CONTENT (BTU/LB)	COMPONENTS, PERCENT BY WEIGHT						
			MOISTURE	ASH	SULFUR	CARBON	HYDROGEN	NITROGEN	OXYGEN
FIBERGLASS	POPE, 1991	13,974	0.00	11.70	1.29	75.80	6.62	0.20	4.39
STEEL-BELTED	POPE, 1991	11,478	0.00	25.20	0.91	64.20	5.00	0.10	4.40
NYLON	POPE, 1991	14,908	0.00	7.20	1.51	78.90	6.97	< 0.10	5.42
POLYESTER	POPE, 1991	14,752	0.00	6.50	1.20	83.50	7.08	< 0.10	1.72
KEVLAR-BELTED	POPE, 1991	16,870	0.00	2.50	1.49	86.50	7.35	< 0.10	2.11
UNSPECIFIED TIRE	HALEY, 1984	16,146	0.00	1.50	1.80	89.20	7.30	0.20	NR
UNSPECIFIED TIRE	RYAN, 1989	15,550	0.50	5.70	1.20	83.20	7.10	0.30	2.50

NR - NOT REPORTED

May 3, 1991

TYPICAL COMBUSTIBLE WASTES

- Halogenated solvents (e.g., tetrachoroethylene)
- Non-halogenated solvents and the still bottoms from the recovery of such solvents (e.g., acetone, benzene, MIBK, cresols, toluene, isobutanol, etc.)
- Distillation bottom tars from the production of phenol/acetone from cumene
- Slop oil emulsions, tank bottoms, and sludges from the petroleum refining industry
- Distillation bottoms from the production of chlorobenzenes, trichloroethane, etc.
- Used or contaminated organics (e.g., aldehydes, alcohols, aromatics, cutting oils, lubricating oils, engine oils, lacquers, varnishes, etc.)
- Herbicides, pesticides, and insecticides
- Gasoline, kerosene, diesel, fuel, oil sludges, and API wastes
- Light fractions of petroleum refinery products contaminated with water, dirt, and organic wastes
- Pulverized plastics from the packaging industry
- Carbon black and activated carbon

Examples of Hazardous Waste Generated by Businesses and Industries

Waste Generators	Waste Type
Chemical Manufacturers	Strong Acids and Bases Spent Solvents Reactive Wastes
Vehicle Maintenance Shops	Heavy Metal Paint Wastes Ignitable Wastes Used Lead Acid Batteries Spent Solvents
Printing Industry	Heavy Metal Solutions Waste Inks Spent Solvents Spent Electroplating Wastes Ink Sludges Containing Heavy Metals
Leather Products Manufacturing	Waste Toluene and Benzene
Paper Industry	Paint Wastes Containing Heavy Metals Ignitable Solvents Strong Acids and Bases
Construction Industry	Ignitable Paint Wastes Spent Solvents Strong Acids and Bases
Cleaning Agents and Cosmetics Manufacturing	Heavy Metal Dusts Ignitable Wastes Flammable Solvents Strong Acids and Bases
Furniture and Wood Manufacturing and Refinishing	Ignitable Wastes Spent Solvents
Metal Manufacturing	Paint Wastes Containing Heavy Metals Strong Acids and Bases Cyanide Wastes Sludges Containing Heavy Metals

SPECIFICATIONS OF SUPPLEMENTAL FUEL[1]

Heat Content	8,000 Btu/lb. minimum (5,000 Btu/lb. with supplemental fuel) 12,000 Btu/lb. preferred
Viscosity	Less than 3,000 centipoise
Odor	Characteristic of solvents Reference ASTM 1296-69
Suspended Solids[2]	30% maximum
Sulfur	3% maximum
Nitrogen	1% maximum
Halogens	10% maximum (normally 2 - 4%)
Inorganic Acids & Bases	Extractable pH of 4 - 11
Water	20% maximum (10% as separated phase)

SPECIFICATIONS OF SUPPLEMENTAL FUEL[1]

(continued)

Ash content	30% maximum	
Heavy Metals (barium, chromium, lead, zinc)	Barium	1,000 ppm
	Cadmium	300 ppm
	Chromium, total	2,000 ppm
	Lead	750 ppm
	Mercury	1.0 ppm
	Zinc	3,000 ppm
	Beryllium	0.4 ppm
	Silver	5.0 ppm
	Arsenic	5.0 ppm
	Selenium	1.0 ppm
PCB	Less than 50 ppm	
Benzene	Exclusion Level maximum 3	

1. All standards contained in this schedule are subject to change in the light of regulatory requirements.

2. Materials otherwise meeting the requirements for Acceptable Materials under this Agreement will be deemed to be Acceptable Materials with regard to size or particulates and solids if they have been pre-screened by a screening device, owned and maintained by Continental Cement and located at the plant, which has screening holes no larger than 1/8" in diameter.

3. In the absence of an Exclusion Level for Benzene, the maximum level shall be 0.5%.



A waste is hazardous if it exhibits any of these four characteristics.

- Reduction of energy usage and cost
  - Better housekeeping and pollution controls
  - Preventive maintenace and production procedures
  - Operations improvements
  - Personnel training and supervision
  - Improved monitoring and controls
    - Control room automation
    - Laboratory automation
  - Capital investments for modifications to existing plant and equipment
  - Capital investments (large) for more energy efficient processing and equipment
  - Use of blended cements with slag, fly and/or pozzolan
  - Use of lower cost alternative fuels instead of coal, oil, and/or gas.

CONTROLLED VERSUS UNCONTROLLED CLINKERING WITH ALTERNATIVE FUELS

- Has to be controlled
  - High temperatures
  - Mixing and long gas residence time
  - Heat mass 900°C to 1500°C
  - Excess air, to 2 per cent oxygen
  - Sufficient burning zone temperatures for good quality clinker, with less than 2% Free lime
  - Continuous emission monitors for O2, CO, SOx NOx, NH4CL, H2O, CO2 and THC

- Controls include
  - Process control computers
  - Quality control laboratory
  - Microscopie analyses
  - Manufacture quality controlled and acceptable clinker and cement all the time
- Results
  - Good quality clinker
  - Better production
  - Lower operating costs
  - Longer refractory life
  - Lower fuel usage and costs

Data pertinent to incineration of chemical wastes

Critical waste incineration parameters	Physical and chemical properties
Ultimate analysis	C, H, O, N, S, ash, and moisture
Metals	Ca, Na, K, Cu, V, Ni, Fe, Pb, Hg, Cr, Cd, As, etc.
Halogens	Chlorides, bromides, fluorides
Heating value	Btu/lb or cal/gram
Solids	Size, form, and quantity to be received
Liquids	Viscosity, specific gravity and impurities, H_2O
Gases	Density and impurities
Organic portion	Percent total organic carbon
Special characteristics	Corrosiveness, reactivity, flammability
Toxicity	TLV (Toxic Limit Value), carcinogenicity, aquatic toxicity, etc.

Sources: Lauber (1982).
Branscome et al. (1985).

COMBUSTION, PRODUCTS AND CLINKERING ACTION

High temperatures, long residence times, excess oxygen, 1 to 2 per cent, mixing action, and excess heat mass yields complete organic and metal destruction

- Organic hydrocarbons ⟶ CO_2 + H_2O
- Nitrogen in organics ⟶ NO_x
- Sulfur in organics ⟶ SO_x
  (Note: Less than 0.5 % S in most waste fuels)
- Halogens in organics ⟶ HCl
  + Ca, Na and K in cement
  Yield $CaCl_2$, NaCl and KCl
- Metals in organics ⟶ Metal silicates
  as part of C_3S, C_2S, C_3A and C_4AF
- Plastics and other organic products ⟶ CO_2



Schematic drawing of a typical cement kiln (Source: Lauber 1982. Reprinted by permission of the publisher.)

PUBLIC RELATIONS

- Cement plant must be neighbor friendly
- Good housekeeping, neat and green appearance, minimum fugitive, dust and clean stack emissions
- Must answer immediatly concerns of employees, neighbors, customers, share-holders and government officials
- Plant must have acceptances of alternatives fuels program before, during, and after start of program
- Criteria are what the public perceives, sees, hears, understands and believes
- Company must tell, explain, show and demonstrate credibility

- Right of refusal must be obtained by cement plant if alternative fuel does not meet chemical and physical test requirements
- Generator, supplier, blender, and transporter must retain full ownership and responsibility of alternative fuel until sampled, tested, and accepted by cement plant
- Generator, supplier, blender and transporter must have financial responsibility and insurances to handle their responsibilities in cases of misrepresentation, accident, liability and/or contamination
- Testing by generators, suppliers, and transporters must be performed by accredited and qualified personnel and laboratories

AGREEMENTS WITH GOVERNMENTS, GENERATORS, SUPPLIERS, AND TRANSPORTERS

- Must be excellent legal document giving full protection to the cement plant
- Terms and conditions must give the cement plant flexibility to meet changing requirements in plant operations, government restrictions, quantities, and revenues
- Full insurance coverage must be obtained to protect plant and personnel against fire hazards accidents and other liabilities

PLANT FACILITIES

- Unloading alternative fuels at plant
  - Concrete pad and containment area
  - Sampling station
  - Fire protection
  - Venting of vapors to thermal oxydizer, kiln burner, or carbon canisters
  - Covering
  - Filters, pumps, and unloading equipment
  - Use of containers from suppliers and generators
- Laboratory
  - Complete, testing equipment and trained personnel
  - Audit and control of sampling testing and storage of alternative fuel samples, kiln feed samples, clinker samples and cement samples

- Fire and safety protection
  - Adequate fire fighting equipment, water storage, foam generators and fire extinguishers
  - Trained personnel in alternative fuels facility and plant
  - Safety equipment, protective clothing and trained personnel
- Processing and blending
  - Liquids and sludges. Filters, screens, schredders, grinders, and conveying facilities, storage tanks, venting
  - Solids Unloading equipment, conveying, screening, shredding, Vented storage buildings
  - Blending for alternative fuels
  - Volumetric metering and controls for liquids and sludges
  - Gravimetric Weighing feeders for solids
  - Fail safe controls for alternatives fuels and kiln systems
  - Cut-off alternatives fuels when kiln operating parameters are not met
  - Operating procedures and combustion controls

B - 7

Air Emissions Associated with the combustion of scrap tires for Energy Recovery

OHIO AIR QUALITY
DEVELOPMENT AUTHORITY

AIR EMISSIONS ASSOCIATED WITH THE COMBUSTION OF SCRAP TIRES FOR ENERGY RECOVERY

MALCOLM PIRNIE, INC.
6161 Busch Blvd.
Columbus, Ohio 43229

May, 1991

This report was conducted under contract to the Ohio Air Quality Development Authority. Funding was provided by the Ohio Air Quality Development Authority and the Scrap Tire Management Council.

ACKNOWLEDGEMENTS

Thanks are due to several individuals who reviewed and contributed to the development of this report. Under the direction of the Ohio Air Quality Development Authority, a technical advisory panel was assembled. The members of the panel and their respective affiliation are provided below:

Mark R. Shanahan, Ph.D.
Executive Director
Ohio Air Quality Development Authority

Michael Blumenthal
Executive Director
Scrap Tire Management Council

Robert Hall, Chief
Combustion Research Branch
U.S. Environmental Protection Agency

Charles R. McGowin
Technical Manager
Generation and Storage Division
Electric Power Research Institute (EPRI)

John D. McKenna
President
ETS, Inc.

Ned E. Williams, P.E.
Burgess and Niple, Ltd.

OHIO AIR QUALITY DEVELOPMENT AUTHORITY
AIR EMISSIONS ASSOCIATED WITH THE
COMBUSTION OF SCRAP TIRES FOR ENERGY RECOVERY

TABLE OF CONTENTS

		Page
ACRONYMS AND ABBREVIATIONS		
GLOSSARY AND DEFINITION OF TERMS		
	EXECUTIVE SUMMARY	E
1.0	INTRODUCTION	1-1
2.0	TIRE CHARACTERISTICS	2-1
2.1	Physical	2-1
2.1	Chemical	2-1
3.0	SCRAP TIRE ISSUES	3-1
3.1	Landfill Problems	3-1
3.2	Tire Fires	3-1
3.3	Tires as Breeding Grounds for Insects	3-2
3.4	Rodents	3-3
3.5	Waste Tire Legislation	3-3
3.6	Tires as a Fuel Source	3-3
4.0	COMBUSTION SOURCES	4-1
4.1	Boiler Types	4-2
4.2	Types of Combustion Facilities	4-3
4.2.1	Cement Kilns	4-3
4.2.2	Pulp and Paper Mills	4-5
4.2.3	Electric Utilities	4-5
4.2.4	Dedicated Tire to Energy Facilities	4-5
5.0	AIR QUALITY ISSUES	5-1
5.1	Regulatory Requirements	5-1
5.2	Types of Air Emissions	5-1
5.3	Air Pollution Control Equipment	5-2
5.3.1	Dry Scrubbers	5-3
5.3.2	Wet Scrubbers	5-3
5.3.3	Fabric Filters (Baghouse)	5-4
5.3.4	Electrostatic Precipitators	5-5
5.3.5	Selective Non-Catalytic Reduction	5-6

TABLE OF CONTENTS (Continued)

6.0	SUMMARY OF AIR EMISSIONS DATA	6-1
6.1	Sources of Information	6-1
6.2	Air Emissions Data from Cement Kilns	6-1
6.3	Air Emissions Data from Pulp and Paper Mills	6-2
6.4	Air Emissions Data from Utility Boilers	6-8
6.5	Air Emissions Data from A Dedicated Tire-To-Energy Facility	6-9
6.6	Air Emissions Data from Other Industries	6-10
6.7	Additional Observations	6-13
7.0	SCRAP TIRES IN OHIO	7-1
7.1	Mosquitoes	7-1
7.2	Scrap Tire Legislation	7-2
7.3	Coal Reserves	7-4
7.4	Industries Currently Burning Scrap Tires for Energy Recovery	7-5
7.5	Summary of Air Emissions Tests at Ohio Edison Company	7-7
7.6	Southwestern Portland Cement Company	7-8
8.0	SUMMARY	8-1
9.0	CONCLUSIONS AND RECOMMENDATIONS	9-1
10.0	REFERENCES	10-1

LIST OF TABLES

Table No.	Description
1-1	Potential Uses for Scrap Tires in Illinois
2-1	Analysis of Various Tires
2-2	Analysis of Various Tire-Derived Fuel (TDF)
2-3	Analysis of Various Coal
2-4	Major Chemical Elements in Ash of the Coal and Three Rubber Samples
3-1	Applicable State Laws
4-1	Types of Combustion Sources
4-2	Major Chemical Elements in Ash of the Coal and Three Rubber Samples
4-3	Cement Facilities Which Have Test-Burned or Are Burning Tires

TABLE OF CONTENTS (Continued)

LIST OF TABLES (Continued)

Table No.	Description
4-4	Pulp and Paper Mills Which Have Test-Burned or Are Burning Tires
4-5	Utility Facilities Which Have Test-Burned or Are Burning Tires
6-1	Cement Companies Contacted
6-2	Summary of Returned Questionnaires from Companies Which Have Test-Burned or Are Burning Scrap Tires
6-3	Summary of Air Emission Results for Nekoosa Packaging
6-4	Emissions of PNAs and Metals from Burning Auxiliary Fuels, Port Townsend Paper Company
6-5	Summary of Air Emission Rates from Burning Tires, Great Southern Paper Company
6-6	Summary of Emissions from the TDF-Sludge Test-Burn, Inland-Rome, Inc., Rome, Georgia
6-7	Summary of Air Emissions from Burning Tires, Crown Zellerbach Pulp Mill
6-8	Average Emission Data from Burning TDF and Coal, Willamette Industries, Inc., Portland, Oregon
6-9A	Average Air Emissions Summary for Each Test Condition, Champion International, Sartell, Minnesota
6-9B	Emission Rates of Materials Measured in Tests, Champion International, Bucksport, Maine
6-10	Average Air Emission Test Results, Smurfit Newsprint, Newberg, Oregon
6-11	Emissions Test Results Summary from Study I, United Power Association, Elk River, Minnesota
6-12A	Modesto Energy Company, Summary of Measured Emissions by Radian Corporation
6-12B	Modesto Energy Company, Summary of Measured Emissions by The Almega Corporation
6-13	Air Emissions Summary from Burning TDF, Dow Corning Corporation, Midland, Michigan
6-14	Metal Emissions Summary from Burning TDF, Dow Corning Corporation, Midland, Michigan
6-15	Summary of Emission Compliance Test Results, Uniroyal Goodrich Tire Company, Eau Claire, Wisconsin
6-16	Summary of Average Emission Results, Virginia Polytechnic Institute and State University
6-17	Summary of Preliminary Average Emission Rates, Monsanto Company
6-18	Emissions Data from Tire and Refuse Derived Fuel (RDF) Combustion Testing
7-1	Sulfur and Ash Data for the Most Productive Coal Beds in Ohio
7-2	Pulp and Paper Mills in Ohio
7-3	Tire Feed Rates for Test-Burns at the Ohio Edison Toronto Plant
7-4	Emission Rates During the Ohio Edison Tire Burn Test
7-5	Tire Burn Bottom Ash Transport Water, Dissolved Metals Analysis
7-6	Tire Burn Bottom Ash Transport Water, Total Metals Analysis

TABLE OF CONTENTS (Continued)

LIST OF FIGURES

Figure No.	Description
1-1	Japan's Use of Scrap Tires
3-1	Applicable State Laws
4-1	Diagram of Hope Works Waste Tire Burning System, Hope, England
4-2	Schematic Diagram of the Modesto Energy Company Plant
7-1	Questionnaire, Scrap Tire Use

Appendices	Description
A	Questionnaire
B	Request for Information
C	Completed Questionnaires

ACRONYMS AND ABBREVIATIONS (Continued)

Acronym	Term
km	Kilometer
lb	Pound
m	Meter
M	Million
Mn	Manganese
MW	Megawatt
N_2	Nitrogen
ng	Nanogram, one-billionth of a gram ($1x10^{-9}$ g)
ng/dscm	Nanograms per dry standards cubic meter
NH_3	Ammonia
Ni	Nickel
NIOSH	National Institute for Occupational Safety and Health
NO	Nitric Oxide
NO_x	Nitrogen Oxides
O_2	Oxygen
OEPA	Ohio Environmental Protection Agency
PAH, PNA	Polynuclear Aromatic Hydrocarbons
Pb	Lead
PCB	Polychlorinated Biphenyls
PCDD	Polychlorinated Dibenzo (p) Dioxins
PCDF	Polychlorinated Dibenzofurans
PM	Particulate Matter
PM-10	Particulate Matter with an aerodynamic diameter less than 10 microns
ppb	Parts per billion
ppm	Parts per million
ppmdv	Parts per million in dry volume
ppmv	Parts per million on a volume basis
psig	Pounds per square inch - gauge
RCRA	Resource Conservation and Recovery Act
RDF	Refuse-Derived Fuel
Sn	Tin
SNCR	Selective Noncatalytic Reduction
SO_2	Sulfur Dioxide
SO_3	Sulfur Trioxide
sq. in.	Square Inch
SWMP	Solid Waste Management Plan
TCDD	All isomers of tetrachlorodibenzo-p-dioxin
TCLP	Toxicity Characteristic Leaching Procedure
TDF	Tire-Derived Fuel, exclusive of whole tires

ACRONYMS AND ABBREVIATIONS

Acronym	Term
ACFM	Actual Cubic Feet Per Minute
As	Arsenic
B(a)P	Benzo-a-pyrene
BACT	Best Available Control Technology
Be	Beryllium
Btu	British Thermal Unit
°C	Degrees Celsius
CAA	Clean Air Act
$CACO_3$	Limestone (Calcium Carbonate)
$CaSO_3$	Calcium Sulfite
$CaSO_4$	Calcium Sulfate
Cd	Cadmium
CEM	Continuous Emission Monitoring
CH_4	Methane
CO	Carbon Monoxide
CO_2	Carbon Dioxide
Cr	Chromium
Cu	Copper
DNR	Department of Natural Resources
EPRI	Electric Power Research Institute
ESP	Electrostatic Precipitator
°F	Degrees Fahrenheit
ft	Feet
FGD	Flue Gas Desulfurization
g	Gram
gr/dscf	Grains Per Dry Standard Cubic Foot
H	Hydrogen
HB	House Bill
HCl	Hydrogen Chloride
HF	Hydrogen Fluoride
Hg	Mercury
HHV	Higher Heating Value
H_2O	Water
H_2SO_4	Sulfuric Acid
hr	Hour
kcal	Kilocalorie
kg	Kilogram

ACRONYMS AND ABBREVIATIONS (Continued)

Acronym	Term
THC	Total Hydrocarbons
TPD	Tons Per Day
TPY	Tons Per Year
TSP	Total Suspended Particulate Matter
TWA	Time-Weighted Average
ug	Microgram, one-millionth of a gram ($1x10^{-6}$ g)
USEPA	United States Environmental Protection Agency
USGS	United States Geological Survey
ug/m^3	Micrograms per cubic meter
VOC	Volatile Organic Compounds
yr	Year
Zn	Zinc
ZnO	Zinc Oxide

GLOSSARY AND DEFINITION OF TERMS

Ash Residue:

A mixture of bottom ash and fly ash.

Baghouse:

Air pollution control equipment used for removing particulates from the flue gas stream by means of filtration through tubular fabric filters (bags).

Bottom Ash:

Ash and unburned material remaining on grates (stoker) after the waste is combusted in the furnace.

Dry Scrubber:

Air pollution control equipment that injects a lime slurry into a flue gas stream containing acid gases, producing a neutralized dry residue that can then be removed by a particulate control device. They are also commonly called spray dryer absorbers.

Electrostatic Precipitator:

An air pollution control device which removes particulates from the flue gas stream by charging the particulates and collecting these particles on an oppositely charged plate. The particulates are then removed from the plate by a mechanical rapper and collected as fly ash for disposal.

Flue Gas Desulfurization:

The operation of removing sulfur oxides from exhaust gas streams of a boiler or industrial process.

Fly Ash:

Airborne combustion residue collected in the steam generator economizer, dry scrubber and the fabric filter system. This includes excess lime and acid gas reaction products.

PCDD:

Short for polyclorinated dibenzo-p-dioxins (dioxins), a family of chemical compounds whose molecular structure consists of three rings, two of which are benzene rings connected by a pair of oxygen atoms, with from one to eight chlorine atoms attached to the benzene rings in any of 75 different combinations (isomers) in a number of groups (homologs).

Homolog defines a group of isomers with the same number of chlorine atoms. Homolog nomenclature is as follows:

T_4CDD	tetrachlorodibenzo(p)dioxin containing four chlorine atoms
P_5CDD	pentachlorodibenzo(p)dioxin containing five chlorine atoms
H_6CDD	hexachlorodibenzo(p)dioxin containing six chlorine atoms
H_7CDD	heptachlorodibenzo(p)dioxin containing seven chlorine atoms
O_8CDD	octachlorodibenzo(p)dioxin containing eight chlorine atoms

An isomer is defined by the arrangement of chlorine atoms within the homolog. Isomer nomenclature is as follows:

2,3,7,8-T_4CDD: 2,3,7,8-Tetrachlorodibenzo(p)dioxin, that is, an isomer with a chlorine atom at the 2,3,7, and 8 lateral ring positions

PCDF:

Short for polychlorinated dibenzofurans (PCDFs) (furans), a family of 135 possible isomers that are structurally similar to the dioxins, containing two benzene rings attached to a central furan ring. The PCDF nomenclature is as described under dioxins.

PM-10:

Particulate matter including only those particles with aerodynamic diameters less than or equal to a nominal 10 micrometers and representing that fraction of total suspended particulates (TSP) available for bio-uptake and retention via inhalation.

Polynuclear Aromatic Hydrocarbons (PAH, PNA):

A group of chemicals that may be formed during the incomplete combustion of coal, oil and gas, garbage, or other organic substances. PAHs can be derived from both man-made and natural sources. The structure of PAH compounds are based on multiple benzene rings. The compounds range in complexity from naphthalene, consisting of two benzene rings, to benzo(a)pyrene, consisting of five benzene rings. Naplithalene is the lightest of the PAHs and is one of the lease toxic, whereas benzo(a)pyrene is one of the heaviest PAHs and is the most hazardous. Benzo(a)pyrene is a known carcinogen.

Solid Waste Management:

The systematic administration of activities which provide for the collection, source separation, storage, transportation, transfer, processing, treatment, and disposal of solid waste.

Ton:

A "short ton" equal to 2,000 pounds.

Waste Management:

The total process of the collection of waste at its point of generation, transportation, treatment and final disposal in an acceptable manner.

EXECUTIVE SUMMARY

An estimated 2 to 3 billion scrap tires are presently stockpiled in numerous locations around the United States, and at least 170 million tires are added to these storage piles or landfilled each year. As more scrap tires are added to unregulated dumpsites, they present a solid waste management problem. Scrap tires create potential fire hazards as they accumulate in stockpiles, as well as contributing to environmental, public health, and safety problems. Legislation governing scrap tire disposal has been enacted in over half of the states to regulate/ban landfilling of tires.

A number of technically feasible alternatives exist to utilize scrap tires other than landfilling or stockpiling. In particular, scrap tires have an attractive heat content, and as a result, are a potential energy resource. Tires generally have more heat energy by weight than coal and have the highest heating value per pound of any potential waste fuels of interest today. In addition, combusting tires or tire-derived fuel (TDF) is relatively inexpensive compared to coal.

Under the appropriate operating conditions, feed rates and pollution control equipment configurations, scrap tires have a significant potential as a supplemental or dedicated fuel source. Four types of combustion facilities which can substantially decrease the number of tires disposed in landfills and stockpiles are cement kilns, pulp and paper mills, electric utilities, and dedicated tire-to-energy facilities. Although published air emissions data regarding the combustion of scrap tires are limited, compared to the available literature for municipal wastes, biomass, and coal combustion, these four combustion sources have the potential to be operated in an environmentally acceptable and economically sound manner.

This report presents a compilation of available air emissions data from sources which combusted scrap tires as a fuel source. Air pollution control equipment requirements and air emissions testing protocols vary from state to state, resulting in a wide range in reported emissions. Although this air emissions data base is limited, enough information is available to suggest that scrap tires for energy recovery be explored as a possible solution to the scrap tire management problem.

As a result of reviewing the available literature of air emission data associated with the combustion of scrap tires for energy recovery, several conclusions are possible:

1. Scrap tires should be considered a resource rather than a waste material;
2. Scrap tires in either a shredded, chipped, or whole condition have been combusted in an environmentally sound manner; and
3. Scrap tires have a significant heat content, and under controlled conditions this heat can be extracted for a beneficial use.

Several other issues, however, must be addressed concerning the use of scrap tires for heat recovery. These include the issues of chipping or shredding technology reliability, regulatory review, uniformity of air emissions data and test methodologies, and ash characteristics.

1.0 INTRODUCTION

This document addresses the final disposition of automotive tires which have been discarded (scrap tires). Adverse environmental effects and threats to public health and safety may develop if scrap tires are not properly managed. A number of technically feasible alternatives exist for disposing of scrap tires, other than landfilling or illegal dumping. Table 1-1, for example, lists various potential uses for scrap tires in Illinois.

Some options for the more than 240 million tires discarded in the U.S. each year include: resale, exporting, retreading, and processing into products such as remanufactured tires, reclaim rubber, industrial floor mats, and railroad crossings. Tires can also be burned for energy recovery, shredded or chipped for use as fill or road surfacing material, and melted to allow recovery of the metal in steel-belted tires. Only about 35 million, or approximately 15% of the scrap tires generated each year, are retreaded (Pope, 1991). Rubber reclamation operations consume 12 million tires per year, and 13 million tires per year are used as supplemental fuel (Pope, 1991). Tires are utilized in asphalt production, as railroad ties, and as artificial reefs when tied together to form groin/dock bumpers.

In addition, various technologies, which utilize these scrap tires, also exist. For example, melting scrap tires and separating the residue to reclaim the ingredients for recycling have been previously studied, as the technology is not new (Haas, 1990). Although these options may be technically feasible, the economic viability of any alternative is the ultimate factor which determines its success. For example, studies have shown that rubberized asphalt has a greater degree of integrity than conventional asphalt. However, processing costs to produce rubberized asphalt, which can potentially be doubled, have limited the expanded use of the rubberized asphalt (Burger, 1991).

Haas (1990) indicates that it is time that scrap tires be used as a source of energy recovery in addition to recycling or reclaiming tire parts. Assessing the feasibility of energy recovery through the use of scrap tires as a fuel is an area of interest to industry and policy makers. A study on scrap tire management by the Illinois Department of Energy and Natural Resources (IDENR) concluded that a "cost effective method of utilizing scrap tires in large volumes in the near term is to use scrap tires as fuel" (Burger, 1991). Other authors concur with this conclusion that energy recovery from scrap tires is a viable alternative (Pope, 1991).

A recent article in Scrap Tire News (January, 1991) describes a Japanese facility which incinerates tires. In Japan, approximately 35 percent of all scrap tires are burned for

fuel. Figure 1-1 illustrates Japan's use of scrap tires and the extent that each option is used. Japan is currently looking at alternative fuel sources due to the ongoing unrest in the Middle East, which is the source of approximately 60 percent of the country's energy requirements. As a result of the oil crisis in the 1970's, a Japanese tire company, Yokohama Rubber Company, Ltd., installed a tire incinerator at its Mie Plant. This incinerator has been in operation since November, 1974, and provides eight percent of the facility's energy requirements.

The tires are burned whole at Yokohama and range from minimum vehicle to truck size tires. Depending on the tire size, an average of 10,000 tires are burned each month. The use of these tires results in a considerable savings in fuel consumption. The company has estimated a savings of 18,850 tons of petroleum which is equivalent to $439,000. The scrap tire supply at the Mie plant comes from the plant itself, which produces truck tires. Tires are also transported from two other Yokohama plants, which provide a total of 75 percent of the supply. Six percent of this supply is from racing tires. Although a Yokohama engineer, Osuke Kojima, cites that the system is old and generates too much smoke for today's environmental standards, he estimates that the cost to update the facility would be three times the cost to build the incinerator in 1974 (original construction cost: $950,000).

The chamber burns tires at approximately 900°C (1600°F) within the current incinerator, and generates 10,240 cubic meters of gas per hour. This gas flows into an adjacent boiler and then to an economizer or heat exchanger, where it is desulfurized and goes up the stack. The system is computer-controlled.

The availability of scrap tires for energy recovery appears not to be a concern. In addition to the 240 million tires scrapped each year in the U.S., 2 to 3 billion scrap tires are estimated to be presently stockpiled at disposal sites, a majority of which are illegal sites. As these tires are awaiting some removal/disposal action, a great potential exists that the tire pile will catch fire.

According to several sources, only 25 to 30 percent of the waste tires discarded each year are used productively, i.e., either re-used or re-processed (McGowin, 1991). Approximately 10 percent of the scrapped tires are landfilled, with the remaining 60 to 65 percent stockpiled and/or dumped. Thus, at least 150 million tires are made available each year for energy recovery.

Reliability of a continuous tire supply can be a concern, especially for facilities located in remote areas (e.g., Midlothian, Texas). For these facilities, scrap tires are not as easily accessible, and/or have higher transportation costs compared to facilities located in

large, metropolitan communities. Thus, if the reliability of a long term tire supply decreases, the risk of recovering capital investment required for permit and feed system modifications increases. Because many pulp and paper mills are located at or near raw material supplies, these mills are at long distances from metropolitan cities, where tire generation is most common. Transportation costs are a price disadvantage.

The primary reason for burning waste tires is to save fuel costs. Burning tires as an alternative fuel will only be feasible if it is economically competitive with the other fuels. The feasibility of co-firing tires/TDF is dependent on various factors, particularly the degree of processing/fuel specifications. Substituting tires for coal can decrease the cost of fuel substantially. For example, if the relative cost of coal, the primary fuel, is assumed to be 1, then according to Juell (1984), the relative costs of the other fuels are as follows:

Natural gas	-	2.5
Rice hulls	-	0.9
Wood shavings	-	0.7
Coke	-	0.6
Chipped tires	-	0.6

The use of TDF could potentially reduce the cost of fuel by as much as 40 percent.

The cost to produce 2 inch tire fuel is relatively low compared to processing tires into new products. However, the energy required to reduce the size of the tire chips increases dramatically as the size of the tire chip decreases. Thus, the smaller a tire chip size is needed, the more expensive the price is to obtain it. Approximately 40 Btus are expended to produce one pound of 6" x 6" tire shreds, whereas 750 Btus are required to produce one pound of 1" x 1" tire chips (Burger, 1991). Boilers requiring wire-free crumb rubber material, 20-30 mesh, may pay an average of $160/ton (Scrap Tire News, March, 1988, from Burger, 1991). However, 2" TDF with steel may only cost $20/ton. Boiler types can determine the tire chip size requirement. Co-firing pulverized coal or cyclone-fired boilers require 1" x 1" or less TDF, whereas stoker-fired and fluidized-bed boilers can accept 2" x 2" to 4" x 4" size shredded tires (McGowan, 1991). Burning tires in pulverized coal or cyclone-fired boilers may not be cost-effective, whereas burning tires in stoker-fired or fluidized bed boilers may result in a cost savings. Keystone Cement Company in Bath, PA, currently has a permit to burn scrap tires; however, the tire shred must be less than 1/8" and Keystone has not found a supplier who can grind tires small enough and keep it cost-effective for Keystone to utilize tires as a fuel (Luybli, personal communication).

For a cement kiln to burn scrap tires economically, the cost to obtain the tires must be less than $45.00 per ton (Kearney, 1990). An initial cost of $60,000 to $500,000 for modification of the feed system must be invested prior to burning scrap tires. Additional costs for test burns are required for permitting. Thus, for a facility to recover some of the investments, the cost for TDF must be considerably less than coal to be economically viable.

According to the Scrap Tire Use/Disposal Study by Kearney (1990), the typical cost of coal for cement kilns is $38 - $48 per ton and for TDF, $30-50 per ton. However, because TDF has a higher Btu content, TDF can generally be cheaper per MBtu than coal ($1.10-$1.80 per MBtu for TDF vs. $1.60-$2.00/Mbtu for coal). However, initial capital costs and costs for shredding and transportation may increase the net cost for TDF. Blue Circle Cement, Inc. in Hope, England has demonstrated a 15 percent savings in primary fuel cost for one kiln without noticeable production loss nor adverse effects on the quality of the cement.

Costs for shredding tires range from 27 to 37 cents per tire. Pulp and paper mills require tires to be wire-free prior to burning. Dewiring increases the cost of TDF by 25-50 percent. Additional costs for dewiring TDF range from $1.00 to $1.70 per Mbtu.

A scrap tire management study in Illinois found that one facility using existing boilers and four processing sites had total collection, transportation and processing costs of $1.19 per tire (Burger, 1991). The facility could maintain economic viability if the combined income from the tipping fee and sale of tire fuel would be at least $1.19 per tire. If tire fuel suppliers charge tipping fees comparable to landfills ($1 - $5 per tire), the suppliers could offer the fuel to customers for approximately $1 per tire or less. Thus, tire fuel could be approximately $20 per ton, assuming tire chip sizes are between 1.5" and 2".

The town of Manitowoc, Wisconsin has offered to provide shredded tires to Manitowoc Public Utilities (MPU) and would pay $3 for each ton of tires burned by MPU. The disposal fee of + $3 per ton for tires when compared to the costs of coal ($35 - 48/ton) and coke ($26/ton) presents a compelling economic argument for burning scrap tires.

The states of Minnesota, Wisconsin, and Illinois have initiated programs which subsidize some of the costs of burning TDF, thus, encouraging the use of TDF as a supplemental energy source. Specifically, the Wisconsin Department of Natural Resources (DNR) will pay for stack test during source test-burns to obtain quality emissions data and for permitting. The Wisconsin DNR has contributed monies for environmental testing to Nekoosa Packaging and Wisconsin Power and Light. In addition, the Wisconsin Waste Tire Management and Recovery Grant Program will fund projects intended to research new uses

and expand existing uses for scrap tires. Wisconsin's grant program is funded by monies generated from a $2 per tire fee on vehicle titles.

The state of Minnesota requires a $4 tax on vehicle title transfers to fund a stockpile cleanup and a grant/loan program. The Minnesota Pollution Control Agency will provide grants and loans to facilities recycling, reusing, or processing tires. These grants and loans help companies that use tire-derived material, such as crumb rubber, to manufacture products incorporating these waste tire products.

Illinois also funds TDF test-burns and provides low interest loans to industries planning to burn scrap tires. These loans allow the industries to retrofit existing equipment or make improvements to facilitate the use of TDF. Illinois is currently funding five TDF test-burns in 1991. This fund is supported by a $0.50 revenue received per vehicle title, and is used to establish the Used Tire Management Fund.

Other states which provide grants/loans to industries, or subsidize markets for waste tires or TDF, include Arizona, California, Missouri, and Oregon. Virginia is currently planning to implement a program to subsidize costs for burning TDF in cement kilns and pulp and paper mills.

The purpose of this study is to compile and analyze available air emissions data on the use of scrap tires as a fuel source for combustion. The consequences of scrap tire combustion on air quality, and the identification of areas in which additional information is necessary are presented in this document. This report does not address potential associated issues, including shredding or chipping technology, economics, ash handling, transport or storage issues. A comprehensive understanding of the impact on air quality resulting from burning scrap tires is required so that industry, policy makers and the general public can make informed decisions on this topic.

Published air emissions data regarding the combustion of scrap tires are limited compared to available literature for municipal wastes, biomass, and coal combustion. Literature which is available concentrates primarily on the methods and feasibility of the processes. Unfortunately, data available regarding air emissions associated with scrap tire combustion are widely scattered and inconsistent. Since few data associated with scrap tire combustion are readily available, there is a relatively low level of understanding regarding use of scrap tires as a fuel source. Information that is available is highly variable. Air emission testing methods are not standardized, and air emission limits vary from state to state.

TABLE 1–1 (Page 1 of 2)

POTENTIAL USES FOR SCRAP TIRES IN ILLINOIS

POTENTIAL USES	Est. % of IL Tires Use	ADVANTAGES	DISADVANTAGES	MARKETABLE PRODUCT
Artificial Reefs	5	Increases Fish Habitation Long Life Ease of Configuration	Costly to Install May Move	Reefs
Breakwaters	1–2	Perform Well Durable Low Cost	Limited Number of Tires Used	Breakwater
Construction	5	Perform Well Low Cost	Limited Number of Tires Used	Retaining Walls Erosion Control Crash Attenuation Structrual Fill Material
Crumb Rubber	Up to 100%	Marketable Commodity Reclaims Raw Material Marketable Applications	High Cost	Crumb Rubber
Rubberized Asphalt	Up to 100%	Longer Wear Noise Buffer	Mixed Test Results Requires Special Equipment Not Proven Economical	Asphalt
Sealants	5	Proven Effective	Limited Number of Tires Used	Roof/Road Sealant
Railroad Crossings	5	Proven Effective Reduces Supply	Limited Number of Tires Used	Railroad Crossings
Sport Surfaces	1–2	Better Surface Lessens Impact	Limited Number of Tires Used	Running Tracks Playgrounds
Stampings	1–2	Proven Effective	Limited Number of Tires Used Not Economical Fragmented Market	Dock Bumpers Farm Machinery Rollers Pipe Rollers
Soil Additives	1–2	Improves Soil Quality Improves Air Circulation	Limited Number of Tires Used Fixed Sales for Compost	Tire Chips
Sheet Goods	1–2	Proven Effective	Limited Number of Tires Used Limited Uses	Floor Mats, Carpet Pads Mud Guards

(From Burger, 1991)

TABLE 1–1 (Page 2 of 2)

POTENTIAL USES FOR SCRAP TIRES IN ILLINOIS

POTENTIAL USES	Est. % of IL Tires Use	ADVANTAGES	DISADVANTAGES	MARKETABLE PRODUCT
Molded Products	5–10	Wide Variety of Uses	Saturated Market	Truckbed Liners Pots, Buckets, Etc.
Tire Retreading	10	Historically Proven Reduction of Supply	Declining Market	Retreaded Tires
Dedicated Whole Tire Boilers	90–100	Completely Disposes Tire Produces Energy Appears Environmentally Clean	Long Pay–back Period Community Acceptance New Boiler Construction Requires Large Stockpile for Continued Use	Energy
Municipal Solid Waste to Energy	50–80	Reduction of Supply Compatible with Existing Fuel Can Boost Btu Content	Limited Use Tires My Burn Too Hot Limited MSW WTE Facility	Energy
Pulp/Paper Plants	Unknown	Reduction of Supply Compatible wiht Existing Fuel Can Boost Btu Content	Limited Use in Illinois Increases Air Emissions Required Stockpiles	Energy
Utility Boilers	10–20	Reduction of Supply Compatible with Existing Fuel	Requires Stockpiles Increases Air Emissions	Energy
Cement Kilns	Unknown	Reduction of Supply Compatible with Existing Fuel	Requires Clean TDF	Energy
Fluidized Bed Boilers	50–100	Reduction of Supply Compatible with Existing Fuel	Requires Clean TDF Requires Stockpiles Increases Air Emissions	Energy
Pyrolysis	Unknown	Minimal Environmental Impac Anticipated	Unproven Markets Requires Stockpiles	Oil & Combustible Gas Carbon Black

(From Burger, 1991)

Japan's Use of Scrap Tires

(unit: 1,000 tons)



Source: JATMA

MALCOLM PIRNIE	1737-01-1	Japan's Use of Scrap Tires (From Scrap Tire News, Jan., 1991)	Rev. 2, May 3, 1991	FIGURE 1-1

2.1 PHYSICAL

Although automobile and truck tires manufactured today are primarily steel-belted radial ply type, other types of tires are available. Some tires are made with Fiberglas, Aramid, and/or Rayon. Table 2-1 lists five different types of tires and their properties. Most modern tires have a complex composition of natural and synthetic rubbers, other chemicals, minerals, and metals. Steel-belted radial ply tires may also contain polyester, steel, or nylon cords.

Some radial tires have a fine carcass wire, whereas bias ply tires do not. Radial and bias ply tires contain bead wire. The bead wire in these tires consists of numerous strands of high tensile strength steel. This steel is used to assure that the tire remains on the rim. In the past, both auto and truck tires have been either radial or bias ply type. Some bias ply tires are still manufactured in the U.S., but they are primarily truck tires. Approximately one-half of the truck tires present in the market today are radial and one-half are bias ply types.

2.2 CHEMICAL

Table 2-2 lists properties of various sizes and qualities of tire-derived fuel (TDF). In general, tires have more heat energy by weight than coal (8970 kcal/kg vs. 6500 kcal/kg). Tires have the highest heating value per pound of potential waste fuels of interest today (Howe, 1991). The average higher heating value of tires is 14,000 Btu/lb. One average tire contains over 300,000 Btu of heat energy. Discarded tires, however, can lose their volatility, dropping from as high as 50 percent to as low as 20 percent, as they age in a scrap tire pile (Granger & Clark, 1991). This finding is disputed by the tire industry. As an example, tires do not volatilize at highway or ambient temperatures and, (J. Zimmer, personal communication, 4/18/91) therefore, it is unlikely to occur from pile storage. In general, the heating value of TDF generally decreases with increasing steel content (Table 2-2).

The main constituents of rubber in tires are carbon and oil (hydrocarbons), hence

the combustible nature of tires. When tires burn in uncontrolled environments, the black smoke that escapes contains fine particles of carbon. Carbon and hydrogen can make up as much as 96.5 percent of the tire. However, the percentage of ash can be as high as 25 percent, especially if the rubber contains steel (Granger & Clark, 1991). Although tires contain a significant amount of sulfur, they are generally lower in sulfur than oil and U.S. coal (except low-sulfur coal). In addition, coal generally has a higher percentage of ash than TDF. Table 2-3 lists various types of U.S. coal and their properties. The ash resulting from burning coal or TDF is comprised mainly of metals. Zinc is the main constituent in TDF fly ash, but lead, arsenic, chromium, and cadmium are also present (Granger & Clark, 1991). Table 2-4 lists the major chemical elements in ashes of coal and TDF and their concentrations.

TABLE 2-1

ANALYSES OF VARIOUS TIRES

TIRE TYPE	SOURCE	ENERGY CONTENT (BTU/LB)	COMPONENTS, PERCENT BY WEIGHT						
			MOISTURE	ASH	SULFUR	CARBON	HYDROGEN	NITROGEN	OXYGEN
FIBERGLASS	POPE, 1991	13,974	0.00	11.70	1.29	75.80	6.62	0.20	4.39
STEEL-BELTED	POPE, 1991	11,478	0.00	25.20	0.91	64.20	5.00	0.10	4.40
NYLON	POPE, 1991	14,908	0.00	7.20	1.51	78.90	6.97	< 0.10	5.42
POLYESTER	POPE, 1991	14,752	0.00	6.50	1.20	83.50	7.08	< 0.10	1.72
KEVLAR-BELTED	POPE, 1991	16,870	0.00	2.50	1.49	86.50	7.35	< 0.10	2.11
UNSPECIFIED TIRE	HALEY, 1984	16,146	0.00	1.50	1.80	89.20	7.30	0.20	NR
UNSPECIFIED TIRE	RYAN, 1989	15,550	0.50	5.70	1.20	83.20	7.10	0.30	2.50

NR - NOT REPORTED

TABLE 2–2

ANALYSES OF VARIOUS TIRE–DERIVED FUELS (TDF) [7]

TDF TYPE	SOURCE	ENERGY CONTENT (BTU/LB)	COMPONENTS, PERCENT BY WEIGHT								
			MOISTURE	ASH	SULFUR	CARBON	HYDROGEN	NITROGEN	OXYGEN	CHLORINE	VOLATILES*
CRUMB RUBBER	EIRSCHELE, 1991	16,300	0.20	4.20	1.90	**28.90	NR	NR	NR	NR	64.80
1/2" "FUZZ"	GRANGER & CLARK, 1991	13,813	2.26	16.48	1.30	69.74	6.30	0.45	3.40	0.07	64.66
1/2" X 1/2" W/O STEEL	EIRSCHELE, 1991	15,560	0.80	9.50	1.50	**27.30	NR	NR	NR	NR	60.90
1" X 1" W/ STEEL	EIRSCHELE, 1991	14,860	2.40	13.20	1.30	**22.40	NR	NR	NR	NR	60.70
1" X 1" W/O STEEL	EIRSCHELE, 1991	15,690	1.30	6.80	1.40	NR	NR	NR	NR	NR	NR
1" X 1" W/O STEEL	MC GOWIN, 1991	12,572	8.55	14.76	1.19	NR	NR	NR	NR	NR	NR
2" SHREDDED W/ STEEL	PHALEN ET AL., 1991	15,787	0.39	8.32	1.62	77.37	6.81	0.37	5.12	NR	62.72
2" RUBBER W/ METAL	GRANGER & CLARK, 1991	13,362	0.75	23.19	1.33	67.00	5.81	0.25	1.64	0.03	54.23
2" RUBBER W/O METAL	GRANGER & CLARK, 1991	14,019	1.02	8.74	1.23	72.15	6.74	0.36	9.67	0.09	67.31
1–1/2" UNSPECIFIED TDF	HOWE, 1991	12,572	8.55	14.76	1.19	62.02	5.96	0.25	7.27	NR	54.33
UNSPECIFIED TDF	POPE, 1991	14,500	0.00	4.81	1.24	84.40	7.13	0.24	2.18	NR	NR
UNSPECIFIED TDF	BURGER, 1991	14,500	0.80	10.00	1.40	78.00	NR	0.02	NR	0.15	65.00
UNSPECIFIED TDF	SCHREURS, 1991	14,500	1.00	5–22	1.60	NR	NR	NR	NR	NR	NR
SHREDDED TDF	GAGLIA ET AL., 1991	16,250	0.62	4.78	1.23	83.87	7.09	0.24	2.17	NR	NR

NR – NOT REPORTED

* – PROXIMATE ANALYSES

** – FIXED CARBON ONLY

TABLE 2–4

MAJOR CHEMICAL ELEMENTS IN ASH OF COAL AND THREE RUBBER SAMPLES

ASH ANALYSIS (%)	COAL	RUBBER 1/2" "FUZZ"	RUBBER 2" W/O METAL	RUBBER 2" W/METAL
Silicon as SiO_2	47.98	18.21	22.00	5.16
Aluminum as Al_2O_3	20.70	6.99	9.09	1.93
Iron as Fe_2O_3	18.89	30.93	1.45	0.35
Titanium as TiO_2	0.82	6.01	2.57	0.14
Calcium as CaO	3.30	5.99	10.64	0.56
Magnesium as MgO	0.79	0.73	1.35	0.10
Sodium as Na_2O	0.48	1.07	1.10	0.13
Potassium as K_2O	2.06	0.55	0.92	0.14
Sulfur as SO_3	4.33	8.35	15.38	0.99
Phosphorous as P_2O_5	0.62	0.56	1.03	0.10
Zinc as ZnO	0.02	20.60	34.50	5.14
Metal				85.28
Total	100.00	100.00	100.00	100.00
Base/Acid Ratio	0.37	1.26	0.46	*11.98

* Counting metal as Fe_2O_3
All values normalized to 100%
Ash and coal samples laboratory–prepared.

(From Granger and Clark, 1991)

TABLE 2-3

ANALYSES OF VARIOUS SOURCES OF COAL

COAL TYPE	SOURCE	ENERGY CONTENT (BTU/LB)	COMPONENTS, PERCENT BY WEIGHT								
			MOISTURE	ASH	SULFUR	CARBON	HYDROGEN	NITROGEN	OXYGEN	CHLORINE	VOLATILES
UTAH COAL	CALIFORNIA AIR RESOURCES BOARD, 1984	12,771	3.59	8.44	0.79	71.45	5.00	1.37	9.64	0.04	NR
UNSPECIFIED WESTERN COAL	CALIFORNIA AIR RESOURCES BOARD, 1984	12,000	18.00	9.00	1.00	54.50	4.00	1.00	12.50	NR	NR
WYOMING SUB-BITUMINOUS COAL	CALIFORNIA AIR RESOURCES BOARD, 1984	6,900	26.95	11.00	0.37	30.68	5.04	0.34	25.63	NR	NR
WEST VIRGINIA BITUMINOUS COAL	MC GOWIN, 1991	11,680	6.60	16.04	0.85	NR	NR	NR	NR	NR	NR
CLINTWOOD BED VIRGINIA COAL	VIRGINIA POLYTECHNIC INSTITUTE, 1990	14,120	2.00	6.70	1.30	78.80	5.20	NR	6.40	NR	31.90
NORTH DAKOTA LIGNITE	SCHREURS, 1991	6,100	40-43	9.00	0.85	NR	NR	NR	NR	NR	NR
UNSPECIFIED COAL	BURGER, 1991	12,400	6.30	8.00	2.70	77.00	NR	1.50	NR	0.01	37.00
UNSPECIFIED COAL	HALEY, 1984	11,700	2.60	15.20	0.40	69.00	4.00	1.30	NR	NR	NR
UNSPECIFIED COAL	TRAVERSE CITY LIGHT & POWER, 1984	11,800	11.39	8.13	0.92	66.10	4.49	1.35	7.62	NR	NR
UNSPECIFIED COAL	GRANGER & CLARK, 1991	12,148	7.76	11.05	2.30	67.69	4.59	1.13	5.47	0.01	34.05
UNSPECIFIED COAL	GAGLIA, ET AL., 1991	NR	6.50	14.00	2.30	70.50	4.00	1.30	1.40	NR	NR
UNSPECIFIED COAL	PHALEN, 1991	10,527	9.76	18.02	2.08	60.71	3.64	1.50	4.29	NR	20.97

NR - NOT REPORTED

3.1 LANDFILL PROBLEMS

The accumulation of scrap tires at landfills, above ground stockpiles, and illegal dumps creates potential environmental, safety and health hazards. Air and water, which become entrapped in the tires buried in a landfill, make the buried tires buoyant. These tires rise to the top of the landfill and eventually rupture the clay cap that protects the buried refuse. A rupture in the clay cap allows landfill gases to escape and allows for infiltration of rain or surface water which may then increase the production of leachates which can contaminate surrounding soils and/or ground water. The ruptured landfill cap is a potential health risk, creating an avenue into the landfill for rodents, insects, and birds. In addition, tires take up a significant amount of volume in landfills and do not biodegrade. As few as 13 tires can occupy one cubic yard of landfill space (Culviner, 1990). Many landfill owners refuse to accept scrap tires due to these various disposal problems. Those landfill owners who do accept tires usually charge a higher disposal fee due to increased handling requirements. For example, a survey revealed that 12 of the 35 landfills in Illinois would not accept tires, and the average cost to dispose of tires in Illinois landfills in July, 1990 was $2.32 per tire (Burger, 1991).

3.2 TIRE FIRES

As scrap tires accumulate at stockpiles and dumps, they create potential fire hazards. Arson is the number one cause for tire fires (Blumenthal, personal communication). On October 31, 1983, a fire began in Winchester, Virginia and burned for nearly nine months. This fire began in a dump containing approximately 5 million truck and automobile tires. On November 4, 1983 air samples were collected in the fire smoke plume, and analyzed to determine the types and magnitude of contaminants and other emissions comprising the smoke. Samples were analyzed for nitrosamines, metals, total particulates, polynuclear aromatic hydrocarbons (PAHs), and other organic vapors. Results indicated that potentially hazardous levels of carbon monoxide (CO) and PAHs were present in the fire smoke plume. CO levels ranged from 15 to 65 ppm above the National Institute for Occupational Safety and Health (NIOSH) recommended exposure limit for a 10-hr time-weighted average (TWA) (NIOSH, 1984). At least seven PAH compounds were detected at concentrations ranging from 3 to 461 ug/m^3. These concentrations, which may require additional regulatory

154

review, could result in potential health problems. The residue resulting from the combusting of tires was 100 feet thick, and composed of char, carbon black, metal and some remaining rubber. Another major fire in Ontario burned at least 13 to 14 million tires. This uncontrolled fire, which began on February 12, 1990, is considered the largest fire in North America (Tire Business, 1/26/90).

The effect of open, uncontrolled scrap tire fires on air quality has become a major concern as more uncontrolled fires occur. To determine air emissions from open combustion of scrap tires, a small scale study guided by USEPA was conducted by Acurex (Ryan, J.V., 1990). During this study, more than 50 volatile organic compounds (VOCs) were identified. Results indicated that the main emission products identified due to incomplete combustion were mono and polyaromatic hydrocarbons. At least one of these compounds, benzo(a)pyrene, is a known carcinogen. Data also indicate that approximately 12-50 grams of semi-volatile organics can be emitted for every kilogram of tire burned. In addition, zinc was identified to comprise nearly 50 percent of the total ash residue.

3.3 TIRES AS BREEDING GROUNDS FOR INSECTS

In addition to creating potential fire hazards, stockpiles and dumps of tires are ideal breeding places for rodents and insects, especially mosquitos. The water that collects in the tires is warmed by the sun's rays which are absorbed by the dark surface of the tire. These conditions create an excellent habitat for mosquitos, and when coupled with an absence of natural predators and protection from the effects of insecticides, allows mosquitos to breed up to 4,000 times faster than in their natural habitat.

The introduction and infestation of several mosquito species is directly attributed to the importation of used tires from other continents to the U.S. The invasion of the Asian Tiger Mosquito (Aedes Albopictus), for example, was caused by the presence of these insects in a shipment of used tires, as the tires were transported from Asia to the U.S. Data from the U.S. Public Health service reveal these mosquitos can transmit Dengue Fever, Yellow Fever and at least 15 other viruses. Efforts to extinguish or control the spread of the Asian Tiger mosquito have failed.

3.4 RODENTS

Tires also supply a warm, dark harbor for rodents. For example, tires with an adequate water supply are an ideal habitat for Rattus norvegicus (Norwegian Rat). These rats either burrow under scrap tires or breed within the tires. The Norwegian Rat is the most common species of rats in landfills and can have as many as 12 offspring in one litter. They can transmit diseases as they are omnivors and feed on either dead or live animals.

3.5 WASTE TIRE LEGISLATION

Legislation governing used tire disposal has been enacted in many states (Pillsbury, 1991, personal communication). Table 3-1 lists these states and a summary of their applicable waste tire regulations. Minnesota currently bans whole as well as cut tires from disposal at landfills. Illinois passed the Vector Control Act in 1989, which places a ban on land disposal of whole tires, effective July 1, 1994. According to this law, whole tires can only be accepted at landfills which have the capabilities to shred, chop, or slit the tires, and which have implemented programs to actively seek other disposal options for the processed tire material (Burger, 1991). A discussion of legislative activities in the state of Ohio is contained in Section 7.

3.6 TIRES AS A FUEL SOURCE

The major reason for combusting tires is to decrease the number of waste tires disposed of in landfills and dumps, thereby reducing the potential for fires, and environmental, health, and safety hazards. However, other reasons exist for combusting tires or tire-derived fuel (TDF) for energy recovery. First, combusting tires or TDF would reduce the dependency on oil for fuel. When comparing the heating value of tires to gasoline, Pope (1991) concludes that one tire has the energy equivalent of approximately 2.4 gallons of gasoline. If a car is assumed to get 25 miles per gallon of gasoline, then one tire has enough energy to move the car 60 miles. Although tires cannot be used to run cars, tires are a valuable fuel when burned completely in the proper environment. Tires can be combusted to generate electricity, steam or hot gases. Other methods of reusing tires for purposes such as an asphalt-reducing admixture in road construction can save millions of barrels of imported oil. According to one rubber industry source, approximately 63 million

barrels of oil could be saved as well as 440 million scrap tires used when incorporating scrap tires in asphalt paving (Culviner, 1990). Note: Rubber is used as an asphalt extender or aggregate replacement, but it does not replace asphalt cement (Chapman, personal communication).

STATE	FUNDING SOURCE	STORAGE REGS	PROCESSOR REGS	HAULER REGS	LANDFILL RESTRICTIONS*	MARKET INCENTIVES
AZ	2% sales tax on retail sale		✓		bans whole tires	
CA	$.25/tire disposal fee	✓	✓			grants
CO		✓	✓			
CT		✓				
FL	$1/tire retail sales	✓	✓	✓	tires must be cut	R&D grants
IL	$.50/vehicle title	✓	✓	✓		grants/loans
IN	permit fees/tire storage sites	✓			tires must be cut	grants
IA					bans whole tires	
KS	$.50/tire retail sales	✓	✓	✓	tires must be cut	grants
KY	$1/tire retail sales	✓			tires must be cut	
LA		✓			tires must be cut	
ME	$1/tire disposal fee	✓	✓	draft		grants/loans
MD	state budget appropriations	✓	✓	✓		
MI	$.50/vehicle title fee	✓	✓	✓		grants
MO	$.50/tire retail sales	✓		✓	bans whole tires	funds/testing
MN	$4/vehicle title transfer	✓	✓	✓	bans whole and cut tires	grants
NB	$1/tire retail sales					grants
NH	town graduated vehicle registration fee	✓				
NC	1% sales tax on new tires	✓	✓	✓	tires must be cut	funds county tire collection
OH					tires must be cut	
OK	$1/tire surcharge new tire sales	✓	✓		tires must be cut	grants
OR	$1/tire disposal tax on new tire sales	✓	✓	✓	tires must be cut	$.01/lb.
PA		✓				R&D grants
RI	$.50/tire tax on new tire sales	✓	✓			
SD		✓	✓		tires must be cut	
TN					bans whole tires	
TX		✓			bans whole tires	
UT	graduated tax per tire size					$20/ton
VA	$.50/tire disposal fee on new tire sales					funds/testing
VT					tires must be cut	
WA	$1/vehicle registration	✓	✓	✓		grants
WI	$2/tire per vehicle title fee	✓	✓	✓	tires must be cut	$20/ton

* Majority of states have imposed regulations that require tires to be cut, sized or shredded prior to landfilling. Some allow for above-ground storage of shreds at landfills. OH, NC, CO are considering or allowing monofills for tire shreds. Whole tires are discouraged from landfills in most cases by law or by high disposal fees. STN – Jan. 1991

MALCOLM PIRNIE

Applicable State Laws
(From Scrap Tire News, 1991)

1737-01-1

REV. 2, May 3, 1991

FIGURE 3-1

Communications with various industries indicate that several types of combustion sources are typically used in scrap tire combustion. Table 4-1 summarizes four types of combustion facilities which are not only effective in decreasing the number of tires disposed in landfills or stockpiles, but also appear to be operating in an environmentally acceptable and economically sound manner. Some combustion sources are limited to the percent of tires that can be combusted due to limitations on emissions of VOCs, metal oxides, and SO_2. In addition, many combustion sources are operationally limited because they cannot handle the high concentration of bead wire and steel-belting in the tires due to boiler feed rates, fuel specifications and other technical reasons. Combustion sources which require shredded tires have experienced handling problems due to the poor quality of TDF. Utility facilities in particular, have expressed the need for standards in the quality of the TDF. A quality standard could avoid the handling problems many companies experience from the large TDF pieces and wire in the TDF.

In order to evaluate the suitability of TDF as a supplemental fuel with coal in a cyclone furnace, the Babcock & Wilcox Company performed chemical and physical evaluations on eastern, bituminous coal and three samples of TDF (Granger and Clark, 1991). The car and truck tires were shredded into three categories for the tests: 1/2 inch rubber "fuzz", 2 inch rubber with metal, and 2 inch rubber without metal. Results of the analyses showed that, compared to coal, the tire samples had less moisture, significantly more combustible matter, and significantly less fixed carbon. The heating content of the shredded tire samples tested was 10 to 16 percent higher than the coal alone. The most significant differences observed between combusting TDF and coal were the ash characteristics and sulfur content of the fuel. The sulfur content of the TDF samples was 1.2 percent to 1.3 percent, or approximately one-half of the sulfur content of eastern coal. However, there should be no significant change in the sulfur content when comparing TDF with low sulfur, western coals.

The ash contents from the three TDF samples were 16 percent, 9 percent, and 23 percent, respectively. The high ash percent was due to the steel content of the TDF. Combusting coal only with no TDF resulted in 11 percent ash. The ash chemistry between the TDF and coal also varied significantly. Table 4-2 shows the major constituents and concentrations, expressed as oxides, in the coal and TDF ash samples. Zinc oxide (ZnO)

is added during the rubber compounding process to control the rate of vulcanization, and appeared to be the cause of the high zinc concentration in the fly ash.

Although most combustion facilities may viably burn TDF, boiler types can also determine whether combusting tires is economically feasible. Test burns on several boiler types (pulverized coal-fired, stoker-fired, cyclone-fired, fluidized bed boilers and wet-bottom boilers) indicate that not all boiler-types combust tires with the same degree of success. The following section provides a review of these four boiler types.

4.1 BOILER TYPES

Pulverized coal-fired boilers require coal to be finely ground into the consistency of face powder. The ground coal is blown into the fire box where it is combusted. The cost to grind TDF into a similar consistency is very high and generally not considered economically feasible, (Stopek, et al.).

Stoker-fired boilers typically combust 3/4-inch minus coal and can readily burn TDF. Combusting 1-inch minus TDF in stoker-fired boilers is generally feasible up to about 10 percent TDF. Stoker-fired boilers are common in industrial applications, but are rare in utility systems.

Cyclone-fired boilers combust coal that is crushed to a size such that 95 percent of the material is less than 1/4-inch. Several utility boilers are currently undergoing studies to determine the maximum TDF size that cyclone burners, which are attached to the outside of the boiler, can effectively and efficiently combust. Coal and TDF are fed into one end of the cylindrical cyclone, and combusted at high temperatures (2500°F - 3000°F). Ottertail Power Company determined that the largest size tire shreds which can be combusted at their South Dakota facility is 2" x 2" TDF with all loose wire removed (Rolfus, 1991, Personal Communication).

Fluidized bed boilers are also capable of combusting scrap tires. The number and capacity of fluidized bed boilers for generating power have increased significantly in the past decade. Tires are shredded or chipped prior to being fed into the combustor to prevent "hot spots" that could occur if a whole tire was combusting in one small area (Pope, 1991). Fluidized bed boilers have emission control advantages as a result of more complete combustion of fuels and thus, have the flexibility of combusting various fuel types, including waste fuels. Test results indicate that the SO_2 and NO_x emissions usually decrease during

the combustion process. Emissions of dioxins and furans are also minimized due to the extremely high temperatures within the combustor.

The wet-bottom boiler has a slag layer on the bottom that keeps temperatures at about 3,000°F. This temperature is hot enough to vaporize whole tires immediately without producting environmental effects (The Herald-Star, 1990). In wet-bottom boilers, the ash-handling system can accommodate the slag produced by the steel from the tire beads and belts. Wet-bottom boiler furnaces have lower and upper sections. The lower portion of the furnace maintains a high, constant gas temperature, allowing molten slag to fall onto the floor bottom where a pool of liquid slag is maintained and trapped in a slag tank containing water. The lower temperature in the upper portion of the furnace allows gases to cool below the ash fusion point. Ohio Edison Company has test-burned whole tires (up to 32") in their 42 megawatt coal-fired, wet-bottom boiler, the only one of its kind in Ohio, with decreased air emissions (See Section 7.5).

4.2 TYPES OF COMBUSTION FACILITIES

Scrap tire combustion methods are discussed in detail in a report by the Scrap Tire Management Council (Kearney, 1990). Various barriers to the expanded use of these tire combustion methods were also discussed. The following sections summarize four of the most combustion methods.

4.2.1 CEMENT KILNS

The basic elements of cement are calcium, silicon, aluminum, and iron. Mixtures of finely ground calcareous material (e.g., limestone), argillaceous material (e.g., clay, shale), and siliceous material (e.g., sand) provide the required elements for cement. Cement is manufactured through the controlled heating of a mixture of these materials to approximately 1500°C - 1600°C (2700°F - 2900°F) in a rotary kiln. Decarbonation of lime results from the high temperature, and subsequent reaction with silica forms calcium silicates, or "clinker". The clinker is ground with gypsum to produce cement.

Combusting waste tires for energy recovery in cement kilns has been widely used in Europe and Japan since about 1974 (Haley, 1984). The cement kiln has proved to be successful for disposing of whole scrap tires or rubber dust. The extremely high temperature in the kiln allows for complete combustion of tires, as well as oxidation of the steel reinforcements. Because the steel beads/belts react as a component of the cement clinker, these wires do not need to be removed from the tires prior to combustion. This clinkering

process is an efficient method of trapping the metal present in modern tires (e.g., steel-belted radials) as well as trapping ash. These by-products become a constituent of the clinker and are eventually incorporated into the finished product. As a result, this consumption of iron from combusting tires has reduced the costs for supplemental iron for some cement manufacturers. Advantages to combusting waste tires as a supplemental fuel in cement kilns are as follows:

1. Nitrogen and sulphur emissions and ash quantities are lower than typical coal values;

2. The steel content provides supplemental iron for the cement; and

3. The ash is incorporated into the product (cement) and thus, is totally consumed.

Approximately 240 cement kilns are currently in operation in the U.S. The primary requirement for a cement kiln to combust scrap tires/TDF is the installation of a separate fuel feed system. This fuel feed system introduces the tires into the process. Several different types of tire feeding systems are currently available. The type of system is generally dependent on the selected application. The purpose of this separate fuel feed system is to control the rate at which TDF is fed into the combustion system.

TDF can be fed into the combustion system using either a mechanical or pneumatic system. The configuration of the kiln determines whether whole tires or only TDF can be used as an auxiliary fuel. Larger kilns with preheaters can effectively combust whole tires. However, Ash Grove Cement, Inc. has patented a process whereby whole tires are combusted in long kilns without preheaters (E. Hansen, personal communication). Most other cement plants usually combust TDF in kilns without preheaters. The size of the TDF is generally 2" x 2" or 4" x 4". Figure 4-1 is a diagram of a waste tire combustion system in Hope, England, where whole tires are combusted.

Table 4-3 lists facilities in the U.S., Japan, and Europe which have tested or are currently combusting scrap tires in their cement kilns as a supplemental fuel, and the approximate size of tire or TDF it can combust, if known. According to Kearney (1989), over 69,000 tires are combusted in Japan each year as fuel in cement kilns. Japanese cement companies typically combust whole tires in their kilns.

An estimated 40-50 kilns in the U.S. are presently equipped with preheaters/pre-calciners, which can efficiently combust scrap tires. In general, the existing emission controls on kilns are suitable for flue gas cleaning when combusting waste tires. Emission standards

can generally be maintained when using TDF as an auxiliary fuel, if the TDF does not exceed 20 percent of the total heat value of the fuel used in the kilns. However, according to Hansen (personal communication), Ash Grove Cement, Inc. can combust up to 40 percent whole tires of the total fuel in their kilns without preheaters when utilizing their patented process.

4.2.2 PULP AND PAPER MILLS

Hog fuel (wood waste) boilers are normally used at pulp and paper mills. These boilers generally have stoker grate feeding system designs, which can combust solid waste such as TDF. Mills combusting TDF normally mix the TDF with the hog fuel on a conveyor which feeds the furnace. The only primary equipment modification required to combust scrap tires in hog fuel boilers is the installation of a metering system capable of handling the high heat values of TDF. The TDF is generally required to be wire free to minimize potential feeding complications, especially jamming within the feed system which can result from the steel wires in the tire belts.

Hog fuel varies substantially in moisture and Btu content. Therefore, fuels with high heat values, such as coal, are often used as a supplement to hog fuel. Because scrap tires also have high heat values and essentially no moisture content, TDF has recently gained acceptance as an auxiliary fuel in this industry. Table 4-4 lists pulp and paper mills which have tested or are regularly combusting tires as an auxiliary fuel in their boilers.

4.2.3 ELECTRIC UTILITIES

Scrap tires can be combusted at electric utility plants in either wet-bottom boilers (whole tires) or cyclone boilers (wire free, 1" x 1" TDF). Table 4-5 presents a summary of experiences at electric utility facilities which have conducted test burns. Depending on the boiler size and ash-handling system, whole scrap tires or TDF can be combusted in existing U.S. utility boilers with little modification. The major modification needed to combust tires would include the construction of a secondary fuel feed system to deliver tires to the boiler.

Cyclone boilers require finely shredded TDF (1" x 1" or less), which can make combusting the TDF uneconomical. However, on a Btu basis, TDF can be cheaper than coal. The Ottertail Power Company's Big Stone Plant in South Dakota has test-burned TDF and determined that in the proper coal/TDF ratio, TDF can offer a cyclone-fired boiler improved flame stabilization compared to coal alone. The Wisconsin Power & Light

Company operates two cyclonic boilers which have test-burned TDF in Rock River, Wisconsin. Results indicate a decrease in NO_x and SO_2 emissions with only a slight increase in opacity.

4.2.4 DEDICATED TIRE-TO-ENERGY FACILITY

One tire-to-energy facility is currently operating in the U.S., and, a second facility is currently under construction in Sterling, Connecticut. The Modesto Energy Company, owned by Oxford Energy, Inc., operates two mass burn waterwall boilers in Westley, California. Oxford Energy, Inc. obtained the technology from Gummi-Mayer KG (Landau), a German tire retreader. Modesto Energy scaled up the technology developed by Gummi-Mayer to handle eight times as many tires and increased the emission control system to comply with the environmental regulations in the U.S. At this facility, whole scrap tires are fed to each boiler on a gravity roller conveyor-belt assembly. The tire feed rate is approximately 3.97 tons/hour (700 tires/hour), but it is varied to optimize the energy input rate.

Tires are fed into both boilers and combusted on a reciprocating stoker grate located in each unit. This reciprocating grate allows air to flow between the metal grate bars, and moves ash and slag down onto a conveyor, which removes the wet ash. To achieve and maintain proper combustion temperatures, several auxiliary gas-fired burners are used during periods of startup and when tire feed is interrupted. The high boiler temperature (2500°F) is designed to minimize air emissions of organic compounds.

The heat generated during the combustion process at the Modesto facility is used to convert boiler water to steam. Output from the two boilers is 125,000 pounds per hour of 930 psig steam. Hot offgases, produced during the combustion process, pass through a superheater section and then through an economizer section to preheat the water being supplied to the boiler. This steam is 930°F when it is transported to a 14 megawatt turbine generator to produce electricity. The electricity is sold to the Pacific Gas and Electricity Company and provides power to 15,000 homes in Modesto. Figure 4-2 is a schematic diagram of the Modesto Energy Company Plant.

The facility's air pollution control system consists of three stages. The first stage, ammonia injection (Thermal De-NO_x™), reduces the emissions of nitrogen oxides. Ammonia injectors, located on the boiler walls in the economizer section, mix ammonia with the hot flue gases reducing nitrogen oxides. The second stage includes a fabric filtration system (baghouse), which collects particulate matter from the flue gases in a baghouse.

Finally, after leaving the baghouse, the flue gases enter a spray tower, where a lime slurry in a wet scrubber absorbs sulfur gases and hydrogen chloride (HCl). The remaining gas is then exhausted through a 120 ft. stack. The air emissions testing at the Modesto Energy Company's tire-to-energy facility is summarized in Section 6.

All by-products and ash produced at the plant are sold for recycling. The ferrous slag goes to cement factories; the zinc is recovered from the fly ash, which is mostly zinc calcines; and gypsum is used as a soil conditioner by local farmers or sold to cement kilns.

The Modesto plant is located near the world's largest known tire dump with an estimated 40 million discarded tires. The plant charges a tipping fee for each new scrap tire received; but pays the owner of the pile for each tire withdrawn from the pile. Tires with high treads suitable for retreading with useable casings are sold to tire retreaders. The remaining tires are combusted to generate electricity which is sold to utilities.

Oxford Energy's second plant in Sterling, Connecticut is scheduled to begin combusting tires by mid-1991 (Valenti, 1991). This plant, which is anticipated to cost approximately $100 million (Oxford Energy Co., 1989 Annual Report), is designed to combust up to 11 million tires per year (compared to Modesto's 5 million tires per year). An anticipated 30 megawatts of electricity, enough to serve 28,000 homes, will be sold to Connecticut Power and Light.

SCRAP TIRE USE

COMPANY NAME: Roanoke Cement Co.
PLANT NAME: Same
ADDRESS: PO Box 27
Glasgow, VA 24475
PHONE NO.: (703) 992-1501
ENVIRONMENTAL ENGINEER/CONTACT: RANDY RAKES

OF KILNS: 5 Kilns — Only 1 Burning Tires
CAPACITY OF EACH: 550 000 TPY
HEAT RATE OF EACH: 325,000,000 BTU/HR

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED (WHOLE) SLIT

MAXIMUM TIRE PIECE:
OTHER FUELS:
% TIRE OF TOTAL FUEL: 20%

POLLUTION CONTROL EQUIPMENT:
No New Equipment Required

CONTINUOUS EMISSION MONITORING EQUIPMENT:
DATA TEST Single Pass model 900-A

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
Installed Elevator + Conveyors to handle Tires

WASTE TIRE SUPPLY PROBLEMS? YES ____ (NO) ____
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ (NO) ____
IF YES, PLEASE EXPLAIN:

AIR EMISSION DATA:
Pending

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? (YES) ____ NO ____
IF YES, WHAT TYPE OF MODIFICATION?
Simple Feds modification

166

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: SOUTHDOWN, INC. *
PLANT NAME: LYONS PLANT
ADDRESS: P.O. BOX 529
LYONS, COLORADO 80540
PHONE NO.: (303) 534-4206
ENVIRONMENTAL ENGINEER/CONTACT: RANDY WILEY, PLANT ENGINEER

OF KILNS: 1
CAPACITY OF EACH: 1400 TON/DAY CLINKER
HEAT RATE OF EACH 4.8 MBTU/TON

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

(SHREDDED) WHOLE SLIT

MAXIMUM TIRE PIECE: 3" X 3"
OTHER FUELS: WASTE OIL, NATURAL GAS, COAL, #6 FUEL OIL(haven't used in yrs)
% TIRE OF TOTAL FUEL: 1/2 TON/HR, @ 5%

POLLUTION CONTROL EQUIPMENT:
BAGHOUSE

CONTINUOUS EMISSION MONITORING EQUIPMENT:
OPACITY
HC MONITOR AND SO_2 – INTERMITTENTLY

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
ADDED HOPPER, SCALE, AND BELT CONVEYOR

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:
FROM DENVER, DELIVERED SHREDDED

ANY COMBUSTION/OPERATING PROBLEM: YES ____ NO X
IF YES, PLEASE EXPLAIN: SOME FEEDING PROBLEMS, PLUGGING OF RUBBER SHREDS TO HOPPER – IF SHREDS HAVE BELTS AND BEADS

AIR EMISSION DATA:
SEND WRITTEN REQUEST FOR DATA

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?
NO FINAL PERMIT – HAVE SOME NEW LIMITS.

* Information obtained by phone.

QUESTIONNAIRE

SCRAP TIRE USE

COMPANY NAME: Southwestern Portland Cement Co.
PLANT NAME: Quarry Plant
ADDRESS: 506 E. Xenia Drive, P. O. Box 191
Fairborn, OH 45324
PHONE NO.: (513) 878-8651
ENVIRONMENTAL ENGINEER/CONTACT: Daniel A. Willis

OF BOILERS: N/A
CAPACITY OF EACH:
HEAT RATE OF EACH:

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 36 inches diameter
OTHER FUELS: Fossil fuels, hazardous waste fuel
% TIRE OF TOTAL FUEL: 10 - 15%

POLLUTION CONTROL EQUIPMENT:

Fabric filter dust collectors

CONTINUOUS EMISSION MONITORING EQUIPMENT:
Altech system for NO, SO_2, CO_2, CO O_2, HC

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
Added conveyors, elevator, scale, double tipping valve air lock, electric eyes, misc. hardware and software

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES X NO ____
IF YES, PLEASE EXPLAIN: Limited to 18% of total heat input

AIR EMISSION DATA:
Bypass Stack: PM = .03 gr/dscf @ 7% O_2
Main Stack: PM = .02 gr/dscf @ 7% O_2

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION? RAPCA and OEPA require operating permit for each type of fuel burned.

SCRAP TIRE USE

COMPANY NAME: Wisconsin Power and Light Co
PLANT NAME: Rock River Plant
ADDRESS: 150 Townline Road
Beloit, WI
PHONE NO.: (608) 252-3084
ENVIRONMENTAL ENGINEER/CONTACT: Greg Eirschele, Chem Eng

OF BOILERS: 2; tests in 1
CAPACITY OF EACH: 75 Megawatts
HEAT RATE OF EACH: 10,600 Btu/KW hr

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 1" x 1"
OTHER FUELS: Coal - Low sulfur western
% TIRE OF TOTAL FUEL: 7%

POLLUTION CONTROL EQUIPMENT:
ESP - one on each unit

CONTINUOUS EMISSION MONITORING EQUIPMENT:
opacity

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
Added hopper, separate portable blending conveyor, and scale

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO ✓
IF YES, PLEASE EXPLAIN: 100% of tire supply provided by WI
pays $20.00-25.00/ton

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ NO ✓
IF YES, PLEASE EXPLAIN: Fuel Feed system problems = ① too much volume of rubber at one time ② bad quality of TDF - TDF not w/in specifications: lger size than requested and bad out of TDF n wires stick out + jams coal feed system.

AIR EMISSION DATA:
Not available yet - plan to receive 3/31/91

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES ____ NO X
IF YES, WHAT TYPE OF MODIFICATION? WE OWR - exempt modif under definition - considers tires as minor modification as "test phase". Will pursue permanent operating per if results are good.

TABLE 6–2

SUMMARY OF RETURNED QUESTIONNAIRES FROM COMPANIES WHICH HAVE TEST–BURNED OR ARE BURNING SCRAP TIRES

COMPANY NAME	LOCATION	# BLRS KILNS	CAPACITY	HEAT RATE	TIRE SIZE	OTHER FUELS	% TIRE	POLL. CONTROL EQUIPMENT	CONT. EMISSION MONITORING
Arizona Portland Cement	Rillito, AZ	1			2" X 2"	coal	5–20	fabric collectors	opacity
Ash Grove Cement West, Inc.	Durkee, OR	1	500,000 ton/yr				10	ESP*	opacity, CO, O_2, NOx
Boxcrow Cement Co.	Midlothian, TX	1	3100 tons/day	3.5 MBtu/ton	2" x 6"	coal	10–12	baghouse	SO_2, NOx, opacity
Calif. Portland Cement Co.	Mojave, CA	1	3250 tons/day	3.3 MBtu/ton	2.5" x 2.5"	coal	30	filter baghouse	opacity
Calaveras Cement Co.	Redding, CA	1	650,000 tons/yr		shredded	coal	20	baghouse	NOx, CO, O_2
Champion International	Bucksport, ME	1	500,000 lb/hr	814 MBtu	2" X 2"	oil, coal, biomass, sludge	10	ESP	opacity, CO_2, SO_2, NOx
Fort Howard Corp.	Green Bay, WI	5			1" x 1"	coal, pet. coke, RDF	3	baghouse	opacity, SO_2
Georgia Pacific	Cedar Springs, GA	2	690 x 10^6 Btu/hr	22,000 Btu/hr/ft^3	1.5" x 1.5"	coal, woodwaste, peanut hulls, No. 6 oil, gas	5	multicyclones followed by venturi scrubbers	no gas analyzers
HOLNAM, Inc.	Seattle, WA	1	1500 stpd**	5.3 MBtu/st	2" x 2"	coal	15	ESP	O_2, opacity, CO
				6.0 MBtu/st	2" x 2"	gas	20	ESP	O_2, opacity
Kosmos Cement Co.	Louisville, KY	1	2160 tons/day	302,650,000 Btu/hr		coal	12	baghouse	opacity
Roanoke Cement Co.	Roanoke, VA	***5(1)	550,000 tons/yr	325 MBtu/hr	whole		20		
Southdown, Inc	Lyons, CO	1	1400 tons/day	4.8 MBtu/ton	3" x 3"	waste oil, gas, coal	5	baghouse	opacity
Southwestern Portland Cem. Co.	Fairborn, OH				wh–36"	fossil, haz wst.	10–15	fabric filter dust collector	NO, SO_2, CO_2,
Uniroyal Goodrich	Eau Claire, WI	1	100,000 lb/hr		3 sq. in.	coal	5	particle collectors on stack	O_2
Willamette Industries	Albany, OR	1	180,000 lbs/hr	3,400 MBtu/day	2" X 4"	hog fuel	2 by wt	wet scrubber	opacity
Wisconsin Power & Light	Beloit, WI	2(1)	75 Mwatts	10,000 Btu/kwhr	1" x 1"	coal	7	ESP	opacity

* ESP = electrostatic precipitator

** stpd = standard tons per day

*** Number in parentheses indicates number of boilers burning tires.

TABLE 6–3

SUMMARY OF AIR EMISSION RESULTS FOR NEKOOSA PACKAGING

POLLUTANT	UNITS	WITH TIRES	WITHOUT TIRES	LIMIT
Particulate Matter	lb/Mbtu	0.092	0.082	0.38
SO_2	lb/Mbtu	1.13	1.1	5.5
NO_x	lb/Mbtu	0.49	0.5	NL
NO_x	lb/hr	221	230	720
CO	lb/hr	301	223	1155
THC	lb/hr	8.89	3.23	NL
Arsenic	lb/yr	43.8	52.6	25
Cadmium	lb/yr	<43.8	<35	25
Lead	lb/hr	0.037	0.038	0.00349
Nickel	lb/yr	<158	<140	250
Zinc	lb/yr	15234	12553	NL
Mercury	lb/hr	0.0012	0.001	0.017
Chromium VI	lb/yr	649	227	2
Chromium VI	lb/hr	0.0741	0.0259	0.017
HCl	lb/hr	3.63	1.95	1.368
Benzene	lb/yr	<978	<843	300
PCB	lb/yr	0.159	0.098	0.1
PAH	lb/hr	0.017	0.012	17.472
Dioxins	lb/yr	0.00009	0.00013	0.0001

(From Wisconsin Department of Natural Resources, 1990, and Clean Air Engineering, 1989)

TABLE 6–4

EMISSIONS OF PNAs AND METALS FROM BURNING AUXILIARY FUELS PORT TOWNSEND PAPER COMPANY

(Measured in ug/m^3 at 7% O_2)

POLLUTANT	BURNING TIRES	BURNING OIL	DIFFERENCE WITH TIRE BURNING	
ZINC	274000	16700	257000	INCREASE
VANADIUM	10	1017	−1007	DECREASE
NICKEL	65	778	−713	DECREASE
LEAD	145	681	−536	DECREASE
PHENANTHRENE*	846	473	373	INCREASE
CHROMIUM	38	62	−24	DECREASE
CADMIUM	34	48	−14	DECREASE
ANTHRACENE*	29	11	18	INCREASE

* Polynuclear Aromatic Hydrocarbons (PNA)

(From Washington Department of Ecology, 1986)

TABLE 6–5

SUMMARY OF AIR EMISSION RATES FROM BURNING TIRES GREAT SOUTHERN PAPER COMPANY

POLLUTANT	DATE	POWER BOILER #	TDF FEED RATE (LB/HR)	EMISSION RATE (LB/MBTU)	EMISSION LIMIT (LB/MBTU)
PARTICULATE MATTER	11/89	1	2585	0.14	0.30
	10/90	1	4480	0.14	0.30
	11/89	2	2584	0.08	0.29
	10/90	2	4870	0.15	0.28
NOx	3/88	1	0	0.67	NONE
	10/90	1	4837	0.20	NONE
	10/90	2	6480	0.29	NONE

(From Georgia Department of Natural Resources, 1989 and 1990)

TABLE 6–6

SUMMARY OF EMISSIONS FROM THE TDF–SLUDGE TEST–BURN INLAND–ROME, INC., ROME, GEORGIA

POLLUTANT	DATE	TDF FEED RATE (TONS/DAY)	HEAT RATE (MBTU/HR)	EMISSIONS*
TOTAL SUSPENDED PARTICULATES (TSP)	8/5/89	0	810	33.76 lb/hr
	8/11/89	**25	754	36.76 lb/hr
NOx	9/11/87	0	NOT AVAILABLE	315.3 mg/m^3
	1/31/89	**25	NOT AVAILABLE	338 mg/m^3

* Emissions are combined rates from two boilers.
** Approximately 25 tons of sludge and 25 tons of TDF were fed concurrently to each boiler.

(From Georgia Department of Natural Resources, 1991)

TABLE 6–7

SUMMARY OF AIR EMISSIONS FROM BURNING TIRES CROWN ZELLERBACH PULP MILL

POLLUTANT	TIRES, OIL, AND WOOD FIRED	OIL AND WOOD FIRED	DIFFERENCE WITH TIRES	LIMIT
PARTICULATE MATTER (@ 12% CO_2)	0.056 GR/DSCF	0.03 GR/DSCF	0.026 – INCREASE	0.10 GR/DSCF @ 12% CO_2
ZINC (@ 7% O_2)	28400 ug/m3	3600 ug/m3	14800 – INCREASE	NOT LISTED
ARSENIC (@ 7% O_2)	11.3 ug/m3	4.5 ug/m3	6.8 – INCREASE	NOT LISTED
PNA	–	–	– NO DIFFERENCE	NOT LISTED

(From Washington Department of Ecology, 1986)

TABLE 6–8

AVERAGE EMISSION DATA FROM BURNING TDF AND COAL*
WILLAMETTE INDUSTRIES, INC., PORTLAND, OREGON

POLLUTANT	UNITS	HOGGED FUEL ONLY	HOGGED FUEL WITH 6% TDF	HOGGED FUEL WITH 13% COAL
PARTICULATE MATTER	gr/sdcf	0.0328	0.0692	0.0339
OPACITY (pre–drier)	%	36	40	22
SO_2	ppm**	0	16	6
ZINC	lb/day	7.3	114.9	26.3

* All values adjusted to a steaming rate of 160,000 lb/hr.
** parts per million

(From Vosler, 1985)

TABLE 6–9A

SUMMARY OF AVERAGE AIR EMISSIONS FOR EACH TEST CONDITION CHAMPION INTERNATIONAL, SARTELL, MINNESOTA

TEST TYPE	UNITS	TEST 1 0% TDF	TEST 2 15% TDF	TEST 3 30% TDF	EMISSION LIMIT (LB/MBTU
PARTICULATE MATTER	LB/MBTU	0.05	0.09	0.22	0.1
SULFUR DIOXIDE	LB/MBTU	0.25	0.33	0.45	1.2
NOx	LB/MBTU	0.64	0.67	0.47	0.7
METALS:					
CADMIUM		0.000005	0.000015	0.000026	NONE
CHROMIUM		0.000023	0.000005	0.00024	NONE
LEAD		0.000071	0.00022	0.00032	NONE
ZINC		0.00025	0.039	0.086	NONE
TOTAL HYDROCARBONS	ppm* – (AS CARBON)	959	16	3	NONE
	LB/HR – (AS CARBON)	165	2.7	0.6	NONE
PAH**	–	–	–	–	–

* ppm – parts per million
** PAH – All polynuclear aromatic hydrocarbons were below detection levels.

(From Pace Laboratories, 1988)

TABLE 6–9B

EMISSION RATES OF MATERIALS MEASURED IN TESTS CHAMPION INTERNATIONAL, BUCKSPORT, MAINE

TEST TYPE	UNITS	TDF FEED RATE			
		1.5 TPH	2.5 TPH	3.5 TPH	0 TPH
TOTAL PARTICULATE MATTER	LB/MBTU	0.054	0.047	0.056	0.053
SULFUR DIOXIDE	LB/MBTU	0.466	0.483	0.510	0.508
METALS:					
BERYLLIUM	LB/MBTU	0.00000111	0.00000087	0.00000073	0.00000106
CADMIUM	LB/MBTU	0.00000149	0.00000084	0.00000078	0.00000060
CHROMIUM	LB/MBTU	0.0000147	0.00000667	0.00000636	0.0000121
LEAD	LB/MBTU	<.000010	<.000010	<.000010	<.000010
ZINC	LB/MBTU	0.000981	0.001380	0.002560	0.000260
HYDROCARBONS AS PROPANE	LB/MBTU	0.00118	0.00118	0.00118	0.00117
OXIDES OF NITROGEN	LB/MBTU	0.273	0.280	0.273	0.274

TPH – Tons per hour

(From Woodman Engineering, Inc., 1989)

TABLE 6–10

AVERAGE EMISSION TEST RESULTS
SMURFIT NEWSPRINT, NEWBERG, OREGON

POLLUTANT	TEST DAY 1 WOOD ONLY	TEST DAY 2 1% TDF	TEST DAY 3 1 1/2% TDF	EMISSION LIMIT
PARTICULATE MATTER gr/scfd @ 12% CO_2	0.022	0.0374	0.0459	0.04 gr/scfd
VOLATILE ORGANIC COMPOUNDS (VOC) tons/yr @ 8760 hr/yr	110	35.1	306	189 tons/yr

(From Horizon Engineering, 1987)

TABLE 6–11

SUMMARY OF AVERAGE AIR EMISSIONS RESULTS FROM STUDY I
UNITED POWER ASSOCIATION, ELK RIVER, MINNESOTA

POLLUTANT*	TEST DAY 1 100% COAL	TEST DAY 2 6.3% TDF	TEST DAY 3 10.4% TDF	EMISSION LIMIT (lb/MBtu)
PARTICULATE MATTER**	0.021	0.015	0.009	0.6
SO_2	1.41	1.8	1.53	4
SULFURIC ACID (SO_3 & H_2SO_4)	0.015	0.014	0.012	NOT LISTED
NOx	0.78	0.58	0.3	NOT LISTED
Cl^- ***	0.029	0.029	0.027	NOT LISTED

* All emission rates in lb/MBtu
** Includes back–half catch
*** Average from inlet

(From O'Brien, M.V., and Hanson, W.C., 1983)

TABLE 6–12A

MODESTO ENERGY COMPANY
SUMMARY OF MEASURED EMISSIONS, 1988

PARAMETER	ACTUAL EMISSIONS	LB/DAY	PERMIT LIMIT
PCDD	0.515 ng/sec	9.81E–08	**** TCDD = 2.60×10^{-7} g/sec
PCDF	1.692 ng/sec	3.22E–07	–
PAH	61.6 ug/sec	1.17E–02	**** 9.42×10^{-5} g/sec
PCB*	3 ug/sec	5.71E–04	**** 1.93×10^{-5} g/sec
THC**	0.239 ppmv @ 12% CO_2	0.646	148.4 lb/day
NH_3	63.9 ppmv @12% CO_2	181.8	50 ppmv
NOx	49.54 ppmv @ 12% CO_2	384.3	500 lb/day
SOx –			250 lb/day
– SO_3 (CCS)	4.5 ppmv @ 12% CO_2	55.4	
– SO_2 (Method 8)	4.2 ppmv @ 12% CO_2	45.4	
– SO_2 (CEM)	3.76 ppmv @ 12% CO_2	40.6	
HCl	< 3.5 ppmv @ 12% CO_2	< 22.3	–
CO	52.59 ppmv @ 12% CO_2	247.8	346.4 lb/day
PM –			
– FRONT HALF	0.00190 grains/dscf	25.5	
– BACK HALF	0.000418 grains/dscf	5.7	
– TOTAL	0.0023 grains/dscf	31.2	113 lb/day
TOTAL METALS***	48.4 mg/sec	9.2	–
Al***	1,464 ug/sec		2.02×10^{-3} g/sec
As***	13.7 ug sec		4.61×10^{-4} g/sec
Ca***	609 ug/sec		NR
Cd***	9.38 ug/sec		2.22×10^{-3} g/sec
Cr***	6.00 ug/sec		8364×10^{-5} g/sec
Cu***	77.8 ug sec		2.30×10^{-3} g/sec
Hg***	<0.17 ug/sec		5.76×10^{-4} g/sec
Mg***	122 ug/sec		2.30×10^{-3} g/sec
Na***	655 ug/sec		$<2.88 \times 10^{-4}$ g/sec
Pb***	138 ug/sec		1.15×10^{-3} g/sec
Fe***	3,244 ug/sec		2.24×10^{-2} g/sec
K***	1,341 ug/sec		$<2.88 \times 10^{-4}$ g/sec
Zn***	40,706 ug/sec		2.10×10^{-1} g/sec

NOTE: 1 mg = 0.001 g; 1 ug = 1×10^{-6} g; 1 ng = 1×10^{-9} g

* Data obtained from Engineering–Science.

** Expressed as parts per million methane.

*** Estimated based on inlet concentrations and particulate reduction.

**** Permit Limit obtained from Modesto Tire Incinerator Health Risk Assessment.

NR – Not Reported

(Data from Radian Corporation, 1988)

1737–01–1

REV. 2, May 3, 1991

TABLE 6-1 (Page 1 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
Alamo Cement Company San Antonio, Texas	Yes	No
Alaska Basic Industries, Inc. Anchorage, Alaska	Yes	No - No Kilns
Allentown Cement Company, Inc. Blandon, Pennsylvania	Yes	No
Arizona Portland Cement Company Rillito, Arizona	Yes	Yes - Burns 10% tires
Armstrong Cement & Supply Corporation Cabot, Pennsylvania	Yes	No
Ash Grove Cement Company Overland Park, Kansas (Corp. H.Q.)	Yes	Yes
Plants:		
Chanute, Kansas;	No	Yes
Louisville, Nebraska;	No	Can burn tires
Foreman, Arkansas	No	Can burn tires
Ash Grove Cement West, Inc.		
Plants:		
Durkee, Oregon;	Yes	Yes - test burned, in permitting process
Inkom, Idaho;	Yes	No
Seattle, Washington;	Yes	No
Clancy, Montana;	Yes	No
Leamington, Utah;	Yes	No, have discussed with state.
Blue Circle Atlantic, Inc.	Yes	Test Burned in England.
Plants:		
Ravena, New York;	Yes	No
Sparrows Point, Maryland	Yes	No kilns.
Blue Circle, Inc.		
Plants:		
Calera, Alabama;	Yes	No
Atlanta, Georgia;	Yes	Test Burned
Tulsa, Oklahoma	Yes	No - Too Expensive

TABLE 6-1 (Page 2 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
BCW, Inc. Phoenix, Arizona	Yes	No Kilns
Boxcrow Cement Company, L.P. Midlothian, Texas	Yes	Yes - One Day
Calmat Company Los Angeles, California	Yes	No - No Kilns
California Portland Cement Company (Subsidiary of Calmat Company)		
Colton, California	Yes	No
Mojave, California;	Yes	Yes - Test burned.
Rillito, Arizona	No	
Capitol Aggregates, Inc. San Antonio, Texas	Yes	No
Capitol Cement Corporation Martinsburg, West Virginia	Yes	No
CBR Cement - Calaveras Cement Company Redding, California	Yes	Yes - Burns 20% tire
CBR Cement Corporation Monolith, California	Yes	No
CBR Cement, Calaveras Cement Company Sparks, Nevada	No	
CBR Cement, Tilburn Cement Company Seattle, Washington	Yes	No - Distribution Oni
Centex Cement Enterprises, Inc. Dallas, Texas	No	
Citadel and Florida Marketing Groups Atlanta, Georgia	No	
Citadel Brand Atlanta, Georgia	No	

TABLE 6-1 (Page 3 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
Coastal Cement Corporation Boston, Massachusetts	Yes	No - Distribution Only
Continental Cement Company, Inc.		
Chicago, Illinois;	No	
Hannibal, Missouri	Yes	No
Davenport Cement Company Davenport, Iowa	Yes	No
Dixon-Marquette Cement, Inc. Dixon, Illinois	Yes	No
Dragon Products Company Thomaston, Maine	Yes	No
Dundee Cement Company Dundee, Michigan (Corp H.Q.)	Yes	Yes - Test-burned
Essroc Cement Group		
Plants:		
Egypt, Pennsylvania;	Yes	Yes - many plants burning
Nazareth, Pennsylvania (Corp. H.Q.);	Yes	Sent request letter
Frederick, Maryland;	No	
Speed, Indiana;	No	
Logansport, Indiana;	No	
Essexville, Michigan;	No	
Federal White Cement, Inc. Oil City, Pennsylvania	Phone # out of order.	
Florida Crushed Stone Company Brooksville, Florida	Yes	Yes - have test burned.
Giant Cement Company Harleyville, South Carolina	Yes	Yes - burn unsuccessful
Gifford-Hill and Company, Inc.		
Midlothian, Texas;	No	
Riverside, California;	No	
Oro Grande, California	No	
Dallas, Texas	No	

TABLE 6-1 (Page 4 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
Gulf Coast Portland Cement Company Houston, Texas	Yes	No
Hawaii Cement Honolulu, Hawaii	Yes	No
Heartland Cement Company Independence, Kansas	No	
Hercules Cement Company Stockertown, Pennsylvania	Yes	No
Ideal Basic Industries, Inc. Fort Collins, Colorado; Florence, Colorado; Superior, Nebraska	 Yes No No	 Yes
Illinois Cement Co. LaSalle, Illinois	Yes	Has test-burn plannec
Independent Cement Corporation Catskill, New York Hagerstown, Maryland	 Yes Yes	 No No
Kaiser Cement Corporation Cupertino, California	Yes	No
Keystone Cement Company Bath, Pennsylvania	Yes	No
Lafarge Corporation Reston, Virginia (Corp. H.Q.) Plants: Demopolis, Alabama; New Braunfels, Texas; Fredonia, Kansas	 No Yes Yes Yes	 No Yes Test burn planned
Masonry Grinding and Color Blending Birmingham, Alabama	No	
Florida Brand Tampa, Florida	No	

TABLE 6-1 (Page 5 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
Trinity Marketing Group		
Dallas, Texas		
Metaline Falls, Washington	No	
Whitehall, Pennsylvania;	No	
Alpena, Michigan;	No	
Paulding, Ohio	No	
Lehigh Portland Cement Company		
Allentown, Pennsylvania (Corp. H.Q.)	Yes	Sent request letter
Buffington-Gary, Indiana;	No	
Mason City, Iowa;	No	
Union Bridge, Maryland;	No	
Waco, Texas;	No	
York, Pennsylvania	No	
Lone Star Industries, Inc.		
Cape Girardeau, Missouri;	Yes	No
Pryor, Oklahoma;	Yes	No
Bonner Springs, Kansas;	No	
Greencastle, Indiana;	Yes	No
Nazareth, Pennsylvania;	Yes	No
Maryneal, Texas;	Yes	No
Oglesby, Illinois	Yes	No
Medusa Cement Company		
Cleveland, Ohio; (Main Office)	Yes	Yes - Sent letter.
Charlevoix, Michigan;	Yes	Yes - Test-burned
Clinchfield, Georgia;	No	Yes
Wampum, Pennsylvania;	No	No
Manitowoc, Wisconsin;	No	
Milwaukee, Wisconsin;	No	
Detroit, Michigan;	No	
Chicago, Illinois;	No	
Green Bay, Wisconsin;	No	
Toledo, Ohio;	No	
Ferrysburg, Michigan;	No	
Plover, Wisconsin;	No	
Rhinelander, Wisconsin;	No	
Doraville, Georgia;	No	
Orlando, Florida	No	

TABLE 6-1 (Page 6 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
Miron/U.S.A Ltd. Glens Falls, NY	Disconnected number.	
Missouri Portland Cement Company Grand Chain, Illinois; Independence, Missouri	Yes Yes	No No
The Monarch Cement Company Humboldt, Kansas; Des Moines, Iowa	Yes Yes	Yes - Test-burned No - No kilns
Mountain Cement Company Laramie, Wyoming	Yes	No
National Cement Company, Inc. Encino, California	Yes	No
National Cement Company, Inc. (Southeast Division) Ragland, Alabama	Yes	No
National Cement Company of California, Inc. Lebec, California	Yes	No
National Portland Cement Company Palmetto, Florida	Yes	No
Nevada Cement Company Fernley, Nevada	Yes	No - No Kilns
Northwestern States Portland Cement Company Mason City, Iowa	Yes	No
RC Cement Company, Inc. St. Louis, Missouri	Yes	No - No Kilns
Roanoke Cement Co. Roanoke, Virginia Test Burn	Yes	Yes - Preliminar
Rinker Materials Corporation Miami, Florida	Yes	No

TABLE 6-1 (Page 7 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
River Cement Company St. Louis, Missouri Plant: Festus, Missouri	Yes	Yes - Test-burned
Riverton Corporation Riverton, Virginia	Yes	No
RMC Lone Star Davenport, California	Yes	Yes - Test-burned
St. Mary's - New York Cement Company, Inc. Buffalo, New York	Yes	No - No kilns
St. Mary Peerless Cement Company Detroit, Michigan	Yes	No
St. Mary's Wisconsin Cement, Inc. Detroit, Michigan	Yes	No
Santee Portland Cement Corporation Holly Hill, South Carolina	Yes	No
Signal Mountain Cement Company Chattanooga, Tennessee	Yes	No
South Dakota Cement Rapid City, South Dakota	Yes	No
Southdown, Inc. Houston, Texas; Victorville, California; Odessa, Texas; Lyons, Colorado; Fairborn, Ohio;	 Yes No Yes Yes Yes	 No No Test Burned Permit Expired October, 1990
Brooksville, Florida	No	
Dixie Cement Company Knoxville, Tennessee	Yes	No

TABLE 6-1 (Page 8 of 8)

CEMENT COMPANIES LISTED IN
"THE AMERICAN CEMENT DIRECTORY, 1990"

	Contacted?	Burn Tires?
Kosmos Cement Company		
Kosmosdale, Kentucky;	Yes	Test Burned
Pittsburgh, Pennsylvania	No	
Texas Industries, Inc.		
Midlothian, Texas;	Yes	No
Artesia, Missouri;	Does not own.	
New Braunfels, Texas	Yes	No
Texas-Lehigh Cement Company		
Buda, Texas	Yes	Yes - Test-burned
Texas Sunbelt Cement (Distribution Only)		
Corpus Christi, Texas	Yes	No - Distribution only

5.1 REGULATORY REQUIREMENTS

Typically, in order for a facility to combust scrap tires on a regular basis, either as a supplemental or primary fuel, an air permit modification is required by the state or local regulatory agency. Modifications usually include additional emission testing or continuous emission monitoring (CEM) requirements. Changes in air emission limits are usually not required by the state agency. Most state agencies require that the air emissions from facilities combusting scrap tires comply with the existing air emission limits presently allowed by the applicable air permit. Emissions testing by an approved testing contractor are often required to determine the impact of combusting scrap tires on air emissions.

5.2 TYPES OF AIR EMISSIONS

Ambient Air Quality Standards have been established by the U.S. Environmental Protection Agency. The standards establish maximum ground level concentrations of criteria pollutants in the ambient air which the agency determines to be adequate to protect the health and welfare of the public. There are both primary and secondary standards. Primary standards are those required to protect the public health; secondary standards, which are more restrictive, establish levels to protect the public welfare from any known or anticipated adverse effects. Presently air quality standards have been adopted by the EPA for six pollutants, otherwise known as criteria pollutants: particulate matter, sulfur dioxide, ozone, oxides of nitrogen, carbon monoxide and lead.

In addition to these criteria pollutants, the air emissions associated with the combustion of scrap tires may contain non-criteria pollutants. The non-criteria pollutants tend to be the pollutants of greater concern to the public and regulatory agencies when combusting non-traditional fuels. Based upon the reviewed data, the non-criteria pollutant emissions data base is limited to the following pollutants: polynuclear aromatic hydrocarbons, volatile organic compounds (VOCs), dioxins, furans, total hydrocarbons, arsenic, cadmium, nickel, zinc, mercury, chromium, vanadium, hydrogen chloride, benzene, and PCBs. While this listing is lengthy, only two facilities have been tested for the majority of these pollutants.

5.3 AIR POLLUTION CONTROL EQUIPMENT

Air pollution control equipment typically utilized by facilities combusting tires include: cyclones, baghouses, electrostatic precipitators, fabric filter collectors, and scrubbers. All are primarily used to remove particulate matter. However, scrubbers will also reduce gaseous emissions. The mechanics and efficiencies of the pollution control equipment vary from facility to facility.

Cyclones are devices that use centrifugal force, generated by a spinning gas stream, to collect the particulate matter (liquid or solid) from the carrier gas. A fabric filter (baghouse) is a porous structure composed of granular or fibrous material, which collects the particulate dust as the carrier gas passes through the voids of the filter. The filter is constructed of material which is compatible with the carrier gas and particulate, and may be arranged in deep beds, mats, or fabric. Electrostatic precipitators (ESP) collect particulates from the mutual attraction between particles of one electrical charge and a collecting electrode of opposite polarity. In a wet scrubber, a liquid, usually water, is used to capture particulate matter. A venturi is a rectangular or circular flow channel, which converges to a narrow throat section and then diverges back to its original cross-sectional area. Venturi scrubbers are primarily used to remove fine particulate matter, but also removes acid gases: SO_2, HCl and HF.

Emissions test results from several combustion sources show an increase in some emissions in the form of fly ash or fine particulate matter when combusting scrap tires, which can only be collected by high efficiency air pollution control equipment. Emission data indicate that electrostatic precipitators have had success in collecting particulate matter or suspended particulates, especially zinc oxide (ZnO) due to the charge on ZnO (Robinson, 1991). A tire burn test conducted at Monsanto Chemical revealed an increase in the performance of the ESP when combusting tires.

The migration velocity is an empirically derived value and is a function of the electrical field characteristics, inlet particle size and resistivity, and ESP design. Migration velocity depends on the voltage strength of both the charging and collection fields. The migration velocity also depends on the particle size; larger particles have higher migration velocities and are collected more easily than smaller ones. Resistivity also affects the migration velocity; the higher the dust resistivity is, the lower will be the migration velocity. Dust resistivity is a term describing the resistance of a collected dust layer to the flow of electric current. Resistivity can generally be reduced by adjusting the temperature and

moisture content of the flue gas.

Drabek and Willenberg (1987) suggest that the efficiency of the air pollution control equipment be reviewed prior to combusting tire chips as a supplemental fuel. In general, wet scrubbers are not as efficient in collecting fine particulate matter as electrostatic precipitators when combusting scrap tires (Hope, 1991). Other emissions such as VOCs are usually not dependent on the pollution control equipment. VOC emissions are usually a function of the combustion process (Hope, 1991).

Ultimately, the state agency determines what emission rates the pollution control equipment must achieve for a facility. Environmental, energy, and economic impacts of the pollution control equipment are factors which must be considered when determining the appropriate type of pollution control equipment for a facility.

5.3.1 Dry Scrubbers

The flue gas containing fly ash and acid gases (SO_2, HCl, HF, and CO) enters the dry scrubber and is contacted with a finely atomized lime slurry. The slurry can be injected into the dry scrubber through dual phase nozzles or mechanical atomizers. Acid gases rapidly dissolve into the liquid phase of the droplets and react with the absorbent to form solid phase salts. Simultaneously, the solid particles are dried by the heat of the flue gas. During the approximate 10 second residence time in the scrubber, the flue gas is cooled as the water in the lime slurry is evaporated.

5.3.2 Wet Scrubbers

If wet scrubbers are applied for acid gas control, a high-efficiency particulate control device usually precedes the scrubber to ensure compliance with the particulate matter emission standards applicable to new facilities. Electrostatic precipitators have been used in combination with wet scrubbers as flue gas desulfurization (FGD) systems for coal-fired utility boilers. The most widely used scrubber in these applications is an open spray tower using limestone as the absorbent. Removal efficiencies equivalent to those of dry scrubbers have been achieved.

In an ESP/wet scrubber system, the particulate-laden gases first pass through an ESP designed to meet the required particulate matter limitations. The cleaned gases then enter the wet scrubber where SO_2 and HCl are absorbed from the gas stream. The overall reactions of gaseous SO_2 with limestone ($CaCO_3$) as the absorbent results in the formation of calcium sulfite ($CaSO_3$) with some oxidation to calcium sulfate ($CaSO_4$). The current

technology of wet scrubbers at utility facilities is a forced oxidation process. During this process, sulfur oxidizes to calcium sulfate or gypsum.

Existing wet scrubber installations in Europe and Japan which have demonstrated good acid gas removal capabilities have used an ESP/wet scrubber combination, with addition of alkaline reagent (CARB, 1984). Corrosion and scaling have been the major problems encountered in wet scrubbers using alkaline reagents. These problems can be minimized by special design measures and by constructing the scrubber with special corrosion resistant materials.

5.3.3 Fabric Filters (Baghouse)

Fabric filters are typically highly efficient particulate control devices. Collection of particles is accomplished through filtration by fabric filter media. The basic components of a baghouse include a filter medium (tubular bag), a cage to support the bag, a gas-tight enclosure, and a mechanism to remove accumulated particulates. In one typical baghouse design, gases enter the lower portion of the baghouse near the collection hoppers. The gases enter one of a number of separate baghouse compartments where they are directed upward through a cell plate, a sheet of perforated metal with the thimbles protruding from each cell, and into contact with the tube-shaped bag, or fabric filter. The tubular bags are contained in multiple modular units comprising the total baghouse system. When the particulate laden gas reaches the filter medium, the gases pass through while greater than 99 percent of the particulate matter is collected on the filter medium. Initial collection forms a thick porous cake of collected particulate on the bags. The cake then acts as the filtration medium while the bags support the cake.

Periodically the accumulated dust cake layer is removed from the bags. Baghouses are categorized according to the method used for cleaning the bags: shaker, reverse-air and pulse jet. The reverse-air baghouse uses an external centrifugal blower. A large volume of gas from the blower is introduced through a reverse gas damper. This gas gently collapses the bags, cracking the dust cake, and blows it down into the hopper. The pulse jet baghouse uses high-pressure compressed air. The short (50-100 milliseconds) pulse of compressed air forms an energy bubble that travels down the bag, rapidly distending the bag and dust cake. When the fabric reaches its stretch limit, its motion abruptly stops and the dust cake, which has been cracked and broken during transition, is thrown from the fabric and falls into the hopper below.

When used with a dry scrubber, the baghouse also serves as an "acid gas reactor"

because any unspent sorbent will coat the bags and absorb acid gas not absorbed in the dry scrubber. Thus, the fabric filter has a greater capability of handling peaks in acid gas concentrations since the efficiency of reagent utilization is increased. In addition, the fabric filter will remove a greater percentage of heavy metals in the low temperature environment.

5.3.4 Electrostatic Precipitators

Electrostatic precipitators are designed to remove particulate matter from gas streams. An electrostatic precipitator collects particulates by producing an electrical charge on the particles and then attracting the particles to collection surfaces of opposite polarity. A typical ESP consists of an alternating array of negatively charged wires or grids and positively charged collection plates. The incoming particles are given an electrical charge through contact with gas ions produced by a high voltage corona discharge. The charged particles pass through a strong electric field causing migration of particles to a collection electrode of opposing polarity. The particulates are dislodged periodically by rappers and fall by gravity into hoppers.

The discharge electrodes are usually small metal wires tensioned by weights or by rigid frames. Collection electrodes are usually flat plates. The electrical system consists of high voltage components used to control the strength of the electric field between the discharge and collection electrodes.

The collection efficiency of an ESP system is affected by several factors. These include the following:

- Collection plate area per unit gas flow;
- Gas velocity through collectors;
- Particle size distribution and properties of the particles;
- Number, width and length of gas passages;
- Electrical field strength;
- Particle in-field residence time; and
- Resistivity of fly ash.

ESP performance is highly dependent on the electrical characteristics of fly ash particles. The critical property affecting ESP performance is the resistivity of the particle. Particles with very low resistivities give up their charge and are re-entrained in the flue gas. Particles with very high resistivities will adhere to the collection plates making them difficult to dislodge. The three major factors that affect the resistivity of the fly ash are: (1) fuel characteristics, (2) particle size distribution and (3) flue gas stream characteristics.

Fuel characteristics, such as ash, chloride and metals, affect the characteristics of fly ash formed. Large fluctuations in the quantity and type of fly ash significantly affect the resistivity and the ESP collection efficiency. A high concentration of fine particulates reduces the corona discharge which reduces the overall collection efficiency. Reductions in ESP collection efficiencies occur in the submicron particle size range.

Flue gas stream characteristics (such as temperature, moisture content, and volumetric flow rate) affect the resistivity and performance of the ESP. At high flue gas temperatures, resistivity is more predictable. Moisture can encapsulate fly ash particles, significantly altering electrical characteristics resulting in a reduction of collection efficiency. High flue gas flow rates reduce the residence time of the fly ash in the ESP thereby reducing the collection efficiency.

5.3.5 Selective Non-Catalytic Reduction

Selective Non-Catalytic Reduction (SNCR) is a system used to control NO_x emissions. It is based on the gas phase homogeneous reaction between NO_x in the flue gas and NH_3, which produces innocuous nitrogen and water. This reaction is effective to varying degrees within the temperature range of 1300°F to 2200°F. At high temperatures, additional NO_x may form, while at lower temperatures the reaction falls off drastically. In practice, the optimal temperature for NO_x reduction is 1750°F, with an effective temperature range for NO_x reduction of 1600°F to 2000°F. In general, NH_3 is injected into the hot flue gas by means of either air or steam (carrier gas) at a zone in the flue gas path specifically selected to provide optimum reaction temperature and residence time. Typically, injection will be carried out by wall injectors, usually arranged in multiple zones in the furnace.

There are two known patented processes of SNCR available for resource recovery facility applications. The first process is called Thermal De-NO_x and is licensed by Exxon Research and Engineering. The second, called the NO_x-OUT process, was developed under EPRI sponsorship, and is now licensed by Fuel-Tech. The former process utilizes ammonia injection into the flue gas stream and the latter process utilizes aqueous urea injection. The Modesto Energy Company's tire-to-energy facility is the only tire combusting facility that uses this Thermal De-No_x process.

6.0 SUMMARY OF AIR EMISSIONS DATA BY COMBUSTION SOURCE

6.1 SOURCES OF INFORMATION

All cement kilns listed in "The American Cement Directory" (1990) were contacted to determine whether their facility had experience in combusting scrap tires. Table 6-1 is a list of all the cement companies contacted in the U.S. with information on their level of experience with combusting scrap tires. Several state agencies were also contacted to obtain names of other companies that have test-burned or are currently combusting tires.

Each company that indicated they had test-burned or are combusting tires was requested to complete a questionnaire to obtain some information regarding their facility and conditions when combusting scrap tires. In addition, air emissions data was requested from each company. A copy of this questionnaire is provided in Appendix A; the request letters and a list of recipients is provided in Appendix B; and completed questionnaires are included in Appendix C. Table 6-2 is a list of companies which returned questionnaires and a summary of their responses. No air emissions testing information was received with questionnaires from the cement companies listed in Table 6-2. Some of the questionnaires have some air emission data, however, no air emission limits were included for comparison. In addition, no information regarding the testing conditions during the collection of air emissions data were provided and thus, were not included in the following section.

6.2 AIR EMISSIONS DATA FROM KILNS

According to Kearney (1990), combustion of scrap tires in cement kilns reduces NO_x by approximately 10 percent. In general, the nitrogen (N) content is much lower than in coal (TDF = 0.24 percent N versus coal = 1.76 percent N). SO_2 and CO emissions on the average do not show significant changes.

BOISE CASCADE

Boise Cascade's plant in Wallula, Washington is a pulp and paper mill; however, a source test was conducted on their lime kiln on May 20-21, 1986. Particulate matter emissions were measured when combusting natural gas and with natural gas supplemented with approximately 15 percent heat input from shredded tires (approximately 87 Mbtu/hr). Pollution control equipment consists of an Air Pol variable throat venturi scrubber. A 64

percent increase in particulates was observed from combusting tires with gas (from 0.037 gr/dscf corrected to 10% O_2 to 0.058 gr/dscf corrected to 10% O_2). Although the measured emissions increased when combusting tires as a co-fuel, the emission rates were still below the allowable limit of 0.067 gr/dscf corrected to 10% O_2 (Drabeck, 1986).

6.3 AIR EMISSIONS DATA FROM PULP AND PAPER MILLS

Air emissions from combusting scrap tires at pulp and paper mills have generally resulted in mixed data. Increased particulate emissions of 38 percent - 93 percent have been observed while combusting TDF in hog fuel boilers (Kearney, 1990). Hog fuel, or wood waste, is considered a "clean fuel". Increased emissions would not be unexpected when adding TDF due to the relative characteristics of tire material versus wood. Data has revealed increases in zinc by 1500 percent (Kearney, 1990). No significant differences have been observed with polynuclear aromatic hydrocarbons (PAHs).

Lower emissions of several metals including chromium, cadmium, and lead have been observed. Lower emissions in SO_2 and NO_x have been observed when the primary fuels at these pulp and paper mills are coal or oil. Again, because of the relative characteristics of TDF versus coal, decreases in emission in SO_2 and NO_x would be expected.

Air emissions testing was conducted at a stationary grate, wood-fired boiler to measure VOC emissions. The location of the wood-fired boiler is not specified by Caron (1985). During the test, 10 percent of the total heat input was shredded rubber tire chips. The results indicate that emission rates were essentially the same as those measured when no rubber chips were combusted (Caron, 1985). At another site, CO emissions were measured from a boiler combusting shredded rubber tire chips. Emissions were essentially the same as those measured when rubber chips were not combusted. Because both CO and VOCs are by-products of incomplete combustion, emissions of these pollutants should follow the same trend when combusting tires.

Some wood-residue fired boilers can combust controlled amounts of rubber tire chips without increasing VOC emission rates. However, the feed rates of tires which can be combusted without influencing emissions of VOCs need to be established. It would be expected that these levels would vary from boiler to boiler and depend on flexibility in the control of primary to secondary air to the unit, as well as grate design.

NEKOOSA PACKAGING

On August 4 through 11, 1989 Nekoosa Packaging conducted air emissions testing at their Tomahawk Mill in Tomahawk, Wisconsin. The purpose of the tests was to determine differences in air emissions from combusting coal and bark versus combusting coal, bark, and rubber in the form of scrap tires (TDF). Emissions from boilers are controlled by an electrostatic precipitator. A summary of the air emission results is provided in Table 6-3.

Test results indicated increased emissions in SO_2, CO, HCl, polychlorinated biphenyls (PCBs), total hydrocarbons (THC), zinc, and hexavalent chromium. Decreased emissions were observed in particulate matter and NO_x. Arsenic, lead, chromium (as chrome VI), and benzene were high for both conditions. Dioxin emissions were nearly the same for both conditions.

PORT TOWNSEND PAPER COMPANY

Air emissions were measured from power boiler No. 10 at the Port Townsend Paper Company Kraft Pulp Mill in Port Townsend, Washington. On February 25, 1986, tires and hog fuel were combusted, and on March 5, oil and hog fuel were combusted. Pollution control equipment consists of a multi-clone followed by a venturi scrubber.

The average measured particulate concentration emitted when tires were combusted was 0.149 gr/dscf. The average concentration on the day when tires were not combusted was 0.117 gr/dscf. Both measured emissions were above the allowable emission of 0.1 gr/dscf. All measurements were corrected to 7% O_2.

Emissions of PNAs and metals were measured when tires were combusted as an auxiliary fuel and when only oil was used as the auxiliary fuel. Table 6-4 presents the results of the air emission tests. A large increase in zinc emissions resulted when combusting tires. Emissions of lead, nickel, and vanadium increased when oil was combusted. Slight increases in emissions of PNAs, phenanthrene and anthracene, and decreases in chromium and cadmium were observed when tires were combusted.

GREAT SOUTHERN PAPER COMPANY

Results from air emission testing at Great Southern Paper Company in Georgia are presented on Table 6-5. In general, particulate matter increased, but the emission rates were all below the emission limit stated in the air permit. NO_x levels were more than one-half the emission rate of NO_x from combusting coal. In addition, NO_x emissions decreased

as TDF feed rate increased. Although Georgia does not have a standard for NO_x, comparison of NO_x emissions from combusting coal and coal with TDF indicated that NO_x emissions did not increase when combusting TDF.

INLAND-ROME, INC.

The Inland-Rome paper mill test-burned TDF-sludge fuels in two of its four boilers. TSP emissions were measured on August 11, 1989 and NO_x emissions were measured on January 1, 1990. The purpose of these test-burns was to determine if a significant increase in emissions would occur when combusting tires. The pollution control equipment for all four boilers is an ESP.

The results of the TDF-sludge test are listed in Table 6-6. A feed rate of 25 tons per day of TDF was measured during the test burns. Increases in TSP and NO_x were measured when combusting the TDF. However, according to calculations from 40CFR60, Appendix C by the Georgia Department of Natural Resources, no significant increases in TSP or NO_x emissions were detected due to the combustion of the TDF-sludge fuel. In addition, 25 tons per day of sludge were also fed into the boilers concurrently with the TDF. Thus, the increase in the emissions may be partially or solely due to the sludge. The increase in the air emissions caused by the TDF alone cannot be determined from these tests.

CROWN ZELLERBACH

On June 10 and 11, 1986, hog fuel and oil and hog fuel, oil, and tires were combusted, respectively, at Crown Zellerbach's Port Angeles, Washington facility. The purpose of the test-burn was to measure particulate emissions from the #8 wood-fired boiler. The #8 boiler was originally designed to combust oil, but was converted to combust hog fuel with oil used as an auxiliary fuel to increase combustion efficiency. Tires have been used at Crown Zellerbach as an alternate fuel to supplement the oil. Approximately 2 percent of the total heat input on June 11 was contributed by tires and 11 percent of heat input was contributed by oil. Pollution control equipment consists of a multi-clone followed by a venturi scrubber. Table 6-7 presents air emission results from the combustion of tires. Average measured concentration of particulate matter increased from 0.030 gr/dscf to 0.056 gr/dscf when tires were combusted. Both were below the allowable emission of 0.10 gr/dscf. All measurements were corrected to 12 percent CO_2. On a lb/hr basis, emissions increased from 9.9 lb/hr (0.069 lb/MBtu) to 16.3 lbs/hr (0.14 lbs/MBtu) with tires. Opacity

increased from zero percent to 13 percent with tires. Authors of this source test indicated that although opacity increased while combusting tires, opacity during previous tests (April 24, 1986) and during the first run was zero percent, and thus, this increase in opacity during the combustion of tires is not attributed to the burning of tires (Washington Department of Ecology, 1986).

Zinc emissions increased seven-fold when tires were combusted to supplement the oil. A slight increase in arsenic also occurred when tires were used. Emissions of other metals and PNAs from combusting tires as two percent of the total fuel were not measurably different than when oil was used as the auxiliary fuel.

WILLAMETTE INDUSTRIES

In order to determine the environmental impact of combusting rubber as an alternate fuel to hog fuel, source tests were conducted at the Albany Paper Mill in Oregon to analyze the hogged fuel boiler emissions. Emissions from the 185,000 lb/hr [illegible]ed fuel boiler are maintained by a series of multi-clones followed by a fuel dryer and two wet scrubbers. Emissions testing was performed when 6 percent rubber and 13 percent coal by weight was combusted as a supplemental fuel to the hogged fuel.

Table 6-8 lists emission rates while combusting the hogged fuel and rubber tires, and hogged fuel and coal. Particulate matter emissions increased by 53 percent when combusting tires. According to Vosler (1985), the maximum rate of particulate matter discharged occurred while combusting tires, but was only 84 percent of the permitted discharge rate. The opacity did not exceed the limit of 20 percent after the wet scrubbers at any time. The rate of zinc discharges increased by 108 lbs/day, and SO_2 emissions increased from zero to 16 ppm when combusting tires.

When coal was combusted with hogged fuel, the only significant increase was in SO_2 emissions (from zero to 6 ppm). In addition, the rate of zinc discharges increased slightly, and particulate emissions remained essentially the same. Opacity decreased by 39 percent when coal was combusted.

Permit limits were not exceeded at any time during the test burns. However, an increase of 113 tons/year in particulate matter emissions were determined when combusting 6 percent rubber. Guidelines state that a significant increase in particulate emissions is more than 25 tons/year. Thus, particulate matter emissions when combusting 6 percent rubber were well in excess of these guidelines. Increases in SO_2 emissions while combusting 6 percent rubber or 13 percent coal were both considered insignificant.

After modifications of the scrubbers, changes in the air flows to the boiler, and the installation of a solid state steam control system were completed, additional trials were conducted. Trial burns determined that up to 2 percent rubber by weight would be combusted with no measurable increase in particulate matter, and that up to 5 percent rubber could be combusted with no significant increase in particulate matter emissions.

CHAMPION INTERNATIONAL, SARTELL, MINNESOTA

Emission compliance testing was conducted at the Champion International Mill in Sartell, Minnesota on October 28 through 30, 1987 for the Unit 3 stack to measure particulate matter, NO_x, SO_x, metals, PAHs, and THC for each of three test conditions. Test conditions included combusting 0, 15, and 30 percent TDF, respectively. Continuous monitoring of CO_2 and CO was also performed during testing.

Unit 3 is a stoker-fired boiler with a traveling grate. Pollution control consists of facilitated by a multi-clone as a pre-separator followed by a wet scrubber. The boiler operated at approximately 90 percent of capacity for Test Day 1 and part of Test Day 2. The load was gradually increased to 100 percent on Test Day 2.

Test results for particulate matter, SO_x, and NO_x are presented in Table 6-9A. Average particulate matter emissions increased from 0.05 lb/MBtu with no tires to 0.09 lb/MBtu with 15 percent TDF and 0.22 lb/MBtu with 30 percent TDF combusted as fuel. The particulate matter emission limit allowed by the state is 0.1 lb/MBtu. SO_2 emissions increased from 0.25 lb/MBtu to 0.33 lb/MBtu and 0.45 lb/MBtu when combusting 0%, 15%, and 30 percent TDF, respectively. Although emissions increased, SO_2 was still below the limits allowed by the state. NO_x emissions remained the same when combusting 15 percent tires, but decreased to 0.47 lb/MBtu when 30 percent TDF was combusted. All values were below the 0.7 lb/MBtu emission limit allowed by the state. Analyses of PAH samples indicate all samples were below detectable levels for Method 610 compounds. Results of the metals analyses indicate that zinc was the most significant metal emission. Zinc emissions averaged 0.08 lb/hr, 12.3 lb/hr, and 31.0 lb/hr for 0, 15, and 30 percent TDF runs, respectively. Emissions limitations are not established for PAHs, metals, and total hydrocarbons. These emissions are regulated on a case by case basis in Minnesota. In Minnesota, particulate matter compliance, by state rule, requires both the front and back-half catch to be included in the Method 5 test method results.

201

CHAMPION INTERNATIONAL, BUCKSPORT, MAINE

Air emissions testing was performed at the Champion International Corporation Steam Plant in Bucksport, Maine during September 27 to October 3, 1989. Two tests were conducted at a feed rate of 0 tons per hour (TPH) 1.5 TPH, 2.5 TPH, and 3.5 TPH. The TDF was added to the flow of biomass entering the fuel feeders to boiler Number 8. Emission rates of hydrocarbons, SO_2, NO_x total particulate matter, and selected metals (beryllium, cadmium, chromium, lead and zinc) were measured by sampling two breechings leading from the electrostatic precipitator to the stack.

The results of the air emission tests are presented in Table 6-9B. Hydrocarbon emissions (as propane) were not affected by the combustion of TDF. Beryllium, cadmium, and chromium emissions decreased as the quantity of TDF increased. Cadmium and zinc emissions increased during all three test conditions when TDF was combusted. Zinc emissions increased almost ten-fold with the maximum TDF input of 3.5 TPH. SO_2 emissions and NO_x emissions were affected only slightly, as TDF input increased.

SMURFIT NEWSPRINT

Source tests for particulate matter and VOCs were conducted on the No. 10 boiler stack at Smurfit Newsprint's plant at Newberg, Oregon. Emissions from the No. 10 stoker-grate boiler is controlled by a multi-clone and a venturi scrubber. The tests were performed to fulfill air contaminant discharge permit requirements for annual compliance and to determine if normal wood fuel could be supplemented with rubber tire chips without violating the emission standards. On May 28, 1987, only wood was combusted, and on June 3 and July 16, 1987 tire chips were added as 1 percent and 1-1/2 percent by weight of the total fuel, respectively.

The average results from three test runs for the three testing conditions are summarized on Table 6-10. Particulate matter test results with only wood fuel were all below the emission standards. Two of the three particulate tests were below the standard at 1 percent and 1-1/2 percent tires. The average of the three tests at 1 percent tires was in compliance, but the average was not in compliance at 1-1/2 percent tires. VOC emissions from runs with 1-1/2 percent tires were also over the permitted amounts, whereas VOC emissions from the first two test conditions were below the allowable limits.

In general, decreases in NO_x and SO_2 emissions have been observed from combusting scrap tires at utility boilers (Kearney, 1990). However, opacity has been observed to increase in some utility boilers from combusting TDF (Kearney, 1990).

Overall, the compiled air emissions data from combusting scrap tires/TDF as a supplemental fuel for energy recovery does not show an adverse impact on air emissions.

UNITED POWER ASSOCIATION

United Power Association in Elk River, Minnesota conducted a study on two boilers to co-fire shredded tires and subbituminous coal. Pollution control for these two stoker-fired boilers is a baghouse. Two studies were conducted: the first used non-steel belted, two inch tire chips, and the second used mostly two to six inch shredded steel-belted radial tires.

During Study I (May, 1979), tire chips were mixed with coal at 0, 6.4, and 10.4 percent proportions, respectively. The feeders operated normally while combusting up to 10.4 percent rubber, but less fuel was fed to the boilers for the same output when the mix went to 6.3 percent rubber. the flames were longer and hotter at the 6.3 percent rubber test and more black smoke than normally for western coal was observed.

Emission rates from Study I are presented in Table 6-11. Overall, SO_2 and particulate matter emission rates remained below the emission limit. Both particulate matter and NO_x decreased as the percentage of tire chips increased.

During study II, the percentage of shredded tires in the fuel was varied for the tests, from 5% to 65% by weight, for one month to evaluate the long-term effects of combusting tires. A 50/50 mixture of coal and rubber appeared to combust the best. Once again, the particulate matter results include both the front and back-half catch.

TRAVERSE CITY LIGHT AND POWER

Traverse City Light and Power (TCL&P) received permission to combust 25 tons per day of tire chips from the Michigan Department of Natural Resources (DNR). Pollution control for the boiler includes a multiple cyclone with sidestream baghouse. Air emission limits allowed by the air permit are presented below:

Pollutant	Allowable Limit
SO_2	1.67 lb/MBtu
Particulate Matter	0.30 lbs/1,000 lbs of exhaust gasses, corrected to 50% excess air.
Opacity	20%

Due to emission problems, no test data on air emissions was collected. The superintendent of TCL&P indicated that too many tires were combusted initially, causing the opacity monitor to increase to 80% within the first hour. They were combusting approximately 30% tires with coal. However, since their test burn, TCL&P has combusted 2% to 5% tires with wood without opacity problems. TCL&P has burned up their scrap tire pile, and has decided not to pursue combusting tires again.

WISCONSIN POWER AND LIGHT

The Wisconsin Power and Light Company test-burned TDF in one of the two boilers February through March, 1991. The shredded tires were approximately 1" x 1" in size, and were combusted to supplement low sulfur western coal, the primary fuel. Approximately 7% TDF was combusted during the test-burn. Pollution control for the boiler is an electrostatic precipitator. Air emission test results from the test-burn are currently under review by the Wisconsin DNR. The Wisconsin Power and Light Company plans to pursue an operating modification permit if the air quality results are favorable (Eirschele, personal communication).

OHIO EDISON COMPANY

See Section 7.5 for discussion.

6.5 AIR EMISSIONS DATA FROM A DEDICATED TIRE-TO-ENERGY FACILITY

Tables 6-12A and 6-12B are summaries of measured emissions at the Modesto tire-to-energy plant. The emission tests were conducted on January 9 through 14, 1988 and March 2 through 4, 1988 by Radian Corporation, and on October 9 through 10, 1990 by The Almega Corporation. Test parameters include: particulate matter (PM), dioxins and furans, polynuclear aromatic hydrocarbons (PAH), polychlorinated biphenyls (PCB), ammonium (NH_3), hydrochloric acid (HCl), sulfur oxides (SO_2, SO_3), nitrogen oxides (NO_x), carbon monoxide (CO), total hydrocarbons (THC), metals and particle size distribution. In

summary, NH_3 levels, which averaged 63.9 ppm corrected to 12 percent CO_2, exceeded the permitted level of 50 ppm during the 1988 emissions testing. All other test parameter results were below the levels allowed by the air permit. The average emission for dioxins (PCDD) and furans (PCDF) combined was 2.21 x 10^{-9} g/sec. This average emission rate is less than one percent of the permitted level. The average emission rate for PAHs was 6.2 x 10^{-5} g/sec. Only one species, (benzo(b)fluoranthene) of the 17 PAHs analyzed was detected. None of the 7 PCB aroclors tested were detected. The listed emission for PCB aroclors in Table 6-12A is the detection limit. PM ranged from 0.0017 to 0.0033 gr/dscf, and averaged 0.0023 gr/dscf or approximately 31 lbs/day. These emission rates are about 25 percent of the permitted level of 113 lbs/day.

6.6 AIR EMISSIONS DATA FROM OTHER INDUSTRIES

DOW CORNING

An emission study was conducted from March 9 through 29, 1989 on Dow Corning Corporation's wood-fired boiler in Midland, Michigan during a tire chip trial burn to determine the total particulate and PM-10 (particulate matter ten microns or less) emissions from the boiler. Pollution control for the boiler is an electrostatic precipitator. Tire chips are purchased in approximately 2-3 inches in diameter sizes with wires.

Samples were collected under four operating conditions: tire chips as 0%, 5%, 10%, and 15 percent of the fuel. In addition, sampling for metals (cadmium, total chromium, zinc, and beryllium) was performed during the 0% and 15% tire chip loading conditions. SO_2, NO_x, and opacity were measured using continuous emission monitors (CEMs) on the stack. Table 6-13 provides the air emission results for each of the four operating conditions. In general, particulate emissions increased with increasing tire percentage. The PM emission limit allowed by the DNR (0.035 lbs/MBtu corrected to 12% CO_2) was exceeded only when 15 percent tires of the total fuel were combusted. One sample exceeded the PM limit at 10 percent, but the average of the three samples was just below the limit.

SO_2 and NO_x emissions were below the established emission limits allowed by the air permit. SO_2 increased with an increase in tire percentage, but was still under the limit. SO_2 doubled with 15 percent tires, but were insignificant. No significant trend with NO_x was observed, but NO_x decreased by almost one-half with 15 percent tires.

Opacity increased with increasing percentage of tire chip fuel. The permit limit for opacity is 20%. Averages for test periods are as follows:

% Tire Chip Fuel	Average Opacity (%)
0	5.89%
5	6.90%
10	7.46%
15	15.80%

Table 6-14 lists the metal emission results for the four metals analyzed. The most significant change in emissions observed was zinc, which increased more than 150 times when combusting tires. Cadmium emissions increased approximately five times when combusting tires. Chromium emissions increase slightly, but were statistically insignificant. Beryllium was below detection limits in both cases.

UNIROYAL GOODRICH TIRE COMPANY

Air emission compliance testing was conducted on September 27 through 29, 1990 on the No. 2 boiler at the Uniroyal Goodrich Plant near Eau Claire, Wisconsin. Tests included particulate, carbon monoxide, trace metals, and polyaromatic hydrocarbons (PAHs) determinations. Particulate matter emissions are controlled by a Zurn mechanical collector. Air emissions were tested at two different firing conditions: 11.5% TDF and 0% TDF. The TDF consisted of a mixture of waste oil, rubber dust, and hog scrap tires.

The results of the emission tests are provided in Table 6-15. The average particulate matter emission rate when combusting coal was 0.35 lb/MBtu, whereas for coal and tires it was 0.42 lb/MBtu. The State limit for particulate matter emissions is 0.6 lb/MBtu. The emission rates of all the trace metals are quite low, except for zinc. However, the low emission rates may be due to the low volumetric flow rate of exhaust gas. Arsenic and cadmium emissions exceed the State standards. CO concentrations measured were very low. In addition, the concentrations of THC, benzene, and PAHs were extremely low. Because CO and PAHs are both byproducts of incomplete combustion, their concentrations are usually positively correlated.

VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY

Stack emissions were measured at the Virginia Polytechnic Institute on the number 6 stoker-fired boiler while firing coal and coal mixed with shredded tires. Emissions from this boiler are controlled by multicyclones. Shredded tire sizes varied from 1/4" to 8" long and 1/2" to 2" wide. Particulate matter and carbon monoxide emissions were determined

26

while combusting coal-tire mixtures consisting of 0, 10, and 20 percent tire chips by weight. NOx and SO_2 emissions could not be determined due to absorption of these compounds by the gas analyzer sample train. PAHs quantified were benzene, phenol, crysene, and benzo(a)pyrene.

A summary of the air emissions testing results are provided in Table 6-16. Particulate matter emissions measured for 0, 10, and 20 percent tire mixtures were 0.88, 2.32, and 2.13 lb/MBtu, respectively. Carbon monoxide (CO) emission results were 0.17, 0.22, and 0.33 lb/MBtu for 0, 10, and 20 percent tire mixtures, respectively. Both particulate matter and CO emissions increased when combusting tires. Opacity readings taken during the testing increased to as high as 50 percent with the combustion of tires. Some of this opacity increase is thought to be due to zinc oxide emissions. Because the sulfur content in tires is generally the same as Virginia coal, the SO_2 emissions were not expected to change substantially when combusting tires. Furthermore, because tires have a higher heating value than this coal, SO_2 emissions on a lb/MBtu basis, should be less as the percent of TDF combusted increases.

Phenol and chrysene emissions increased with increasing tire percent. No trends in benzene or benzo(a)pyrene were observed for increased or decreased emissions with the amount of tire mixture.

After reviewing the test conditions of the trial burn, the Virginia Department of Air Pollution Control considers the test data inconclusive.

MONSANTO CHEMICAL

On December 18 and 19, 1990, a series of tests were conducted to determine air emissions and the operating efficiency of Boiler #8 at Monsanto Company in Sauget, Illinois. All emission test data were collected at the exhaust of the electrostatic precipitator (ESP) during 100% coal use and a 80% and 20% mixture of coal and TDF, respectively. Particulate matter emissions were also tested at the inlet to the ESP.

Table 6-17 presents a summary of the results of these tests. Metals and dioxin data are not available and are not included in Table 6-17. In summary, the coal/TDF mixture significantly reduced O_2, particulate matter, VOCs, NO_x, HCl, and HF emissions. NO_x emmisions decreased by 30 percent, particulate matter emissions decreased by 50 percent, and the accompanying ESP performance increased by 4 percent when combusting coal and TDF. Only CO and SO_2 emissions increased when combusting the coal/TDF fuel. The CO emission rate increased from 0.38 lb/hr to 0.53 lb/hr, and the SO_2 emission rate increased

from 83.0 lb/hr to 109.0 lb/hr. The increase in CO emissions is considered negligible in either case (Almega Corporation, 1991).

6.7 ADDITIONAL OBSERVATIONS

Generally, the sulfur content in tires is moderate, and co-firing with coal can result in both increases or decreases in SO_2 emissions depending on the sulfur content of the original coal or primary fuel. For example, the Big Stone Plant, operated by the Ottertail Power Company in South Dakota, combusts North Dakota lignite. An initial evaluation of the lignite reveals that it has approximately one-half the sulfur of TDF (lignite = 0.85% S; TDF = 1.6% S). However, TDF has 2.5 times the heating value per pound than lignite, and thus, TDF actually has 25 percent less sulfur than lignite on a Btu basis (Schreurs, 1991). The effect on air emissions while combusting TDF is dependent on the type of primary fuel, and is relative to the fuel compared to TDF.

Energy Product of Idaho, Inc. constructed a 3' x 3' pilot plant with a fluidized-bed combustor to test burn tires, refuse-derived fuel (RDF) and a variety of other fuels (Pope, 1991). Emission tests were conducted while combusting the tires. Results of the emission tests from combusting tires and RDF are shown on Table 6-18. Test data revealed that the emission levels of dioxins and furans were not detectable (detection limit = 25 picograms) (Pope, 1991). SO_2 gases released during the combustion process are reduced by the injection of limestone into the combustor and captures SO_2 gases. The gases are removed from the gas stream by the pollution control equipment in collected fly ash. This limestone injection method has resulted in 90% removal of SO_2 gas.

The production of Nitrogen Oxide (NO_x) emissions is low due to the extremely high temperatures in the combustor. Reduction of up to 80% NO_x emissions have been observed when operating the Selective Non-Catalytic NO_x Reduction Technology, which injects ammonia into the vapor space of the combustor. Modesto Energy Company uses this technology to control NO_x emissions at their tire-to-energy facility.

Several other factors influence air emissions when combusting scrap tires, but all of these factors have not been thoroughly studied. Drabek and Willenberg reported that PAH emissions would not increase if the combustion conditions are properly maintained. Other factors such as pollution control equipment, boiler-type, size of TDF, and quality of TDF may also influence the rate and type of air emissions. However, the amount of influence that each factor has on air emissions has not been determined. In general, modern pollution

control equipment, especially electrostatic precipitators and baghouses, is more effective in capturing particulate matter than scrubbers. The amount of increased efficiency of ESPs, relative to scrubbers, is not known when combusting tires. Pope (1991) states that a fluidized-bed boiler is the "best bet" for complete combustion, which is the key to efficiently converting tires into energy in a clean and environmentally sound manner. Thus, based upon these findings, it appears that the combustion technology may be the dominant factor that allows for the incineration of 100% tires in a clean and efficient manner.

TABLE 4–1

TYPES OF COMBUSTION SOURCES

	COMBUSTION SOURCES			
	CEMENT KILNS	PULP/PAPER MILLS	ELECTRIC UTILITIES	TIRE–TO–ENERGY FACILITIES
GEOGRAPHIC LOCATION	240 in US Europe Japan	United States	United States	United States– Modesto Energy Co. W. Germany – Gummi–Mayer KG
WASTE TIRE SPECIFICATIONS	Depends on configuration of kiln. Steel in tires supplements iron for cement. Whole or shredded tires.	Must be dewired. Less than 10 % tires of total fuels on Btu Basis	Whole or shredded tires.	Whole tires.
FUEL HANDLING REQUIREMENTS	Separate fuel feed system design.	Install metering system capable of handling high temperatures.	Modification of fuel feed system.	Uses gravity roller conveyor–belt system
WASTE TIRE SUPPLY PROBLEMS	None.	May have problems due to remote locations of many pulp and paper mills.	Concerned with quality of TDF.	None. U.S. facility is located near world's largest known tire dump.

(Modified from Kearney, 1990)

TABLE 4–2

MAJOR CHEMICAL ELEMENTS IN ASH OF COAL AND THREE RUBBER SAMPLES

ASH ANALYSIS (%)	COAL	RUBBER 1/2" "FUZZ"	RUBBER 2" W/O METAL	RUBBER 2" W/METAL
Silicon as SiO_2	47.98	18.21	22.00	5.16
Aluminum as Al_2O_3	20.70	6.99	9.09	1.93
Iron as Fe_2O_3	18.89	30.93	1.45	0.35
Titanium as TiO_2	0.82	6.01	2.57	0.14
Calcium as CaO	3.30	5.99	10.64	0.56
Magnesium as MgO	0.79	0.73	1.35	0.10
Sodium as Na_2O	0.48	1.07	1.10	0.13
Potassium as K_2O	2.06	0.55	0.92	0.14
Sulfur as SO_3	4.33	8.35	15.38	0.99
Phosphorous as P_2O_5	0.62	0.56	1.03	0.10
Zinc as ZnO	0 02	20.60	34.50	5.14
Metal				85.28
Total	100.00	100.00	100.00	100.00
Base/Acid Ratio	0.37	1.26	0.46	*11.98

* Counting metal as Fe_2O_3

All values normalized to 100%

Ash and coal samples laboratory–prepared.

(From Granger and Clark, 1991)

TABLE 4–3

CEMENT FACILITIES WHICH HAVE TEST–BURNED OR ARE BURNING TIRES

COMPANY NAME	PLT/MILL	CITY	STATE	APPX. SIZE TIRE BURNED
Arizona Portland Cement Co.	Rillito	Rillito	Arizona	2" X 2"
Ash Grove Cement West, Inc.	Durkee	Durkee	Oregon	2", wire free
Blue Circle, Inc	Atlanta	Atlanta	Georgia	
Box Crow Cement Co.	Boxcrow	Midlothian	Texas	2" X 6"
California Portland Cement	Mojave	Mojave	California	2.5" X 2.5"
CBR Cement–Calaveras Cement Co.	Redding	Redding	California	shredded
Dundee Cement		Dundee	Michigan	
Essroc Materials, Inc.		Nazareth	Pennsylvania	
Florida Crushed Stone Co.		Leesburg	Florida	
Giant Resource Recovery		Harleyville	South Carolina	
Gifford Hill Cement Co		Harleyville	South Carolina	whole
Gifford Hill Cement Co.		Midlothian	Texas	
HOLNAM, Inc.	Main office	Dundee	Michigan	
HOLNAM, Inc. for Ideal Basic Ind., Inc.		Dundee	Michigan	2" X 2"
Ideal Cement		Seattle	Washington	2", wire free
Illinois Cement Co.		LaSalle	Illinois	
Kosmos Cement Co.		Kosmosdale	Kentucky	shredded
LaFarge Corp.	Main ofc.	Dallas	Texas	
LaFarge Corp.	Balcones	New Braunfels	Texas	2", wire free
LeHigh Portland Cement Co.		Allentown	Pennsylvania	
Medusa Cement		Charlevoix	Michigan	
Medusa Cement Co.		Cleveland	Ohio	
Medusa Concrete		Clinchfield	Georgia	
Monarch Cement Co		Humboldt	Kansas	
St. Marys Peerless Cement		Detroit	Michigan	
River Cement Co.	Selma	Festus	Missouri	
RMC Lone Star		Davenport	California	
Roanoke Cement Co.		Roanoke	Virginia	whole
Southdown, Inc. (Southwestern)	Lyons	Lyons	Colorado	3" x 3"
Southwestern Portland Cement Co.		Fairborn	Ohio	whole–36"
FOREIGN FACILITIES:				
Heidelberger Cement Plant			W. Germany	
Blue Circle Dry Process Cement Works		Hope	England	whole
Sumitomo Cement Co.			Japan	
Onada Cement Co.			Japan	
Chichibu Cement Co.			Japan	
Osaka Cement Co.			Japan	

TABLE 4–4

PULP AND PAPER MILLS WHICH HAVE TEST–BURNED OR ARE BURNING TIRES

COMPANY NAME	PLANT/MILL	CITY	STATE	APPX. SIZE TIRE BURNED
Champion International	Bucksport	Bucksport	Maine	
Champion International		Sartell	Minnesota	TDF
Crown Zellerbach		Port Angeles	Washington	
Fort Howard Corp.	Green Bay	Green Bay	Wisconsin	
Great Southern Paper		Cedar Springs	Georgia	TDF
Inland–Rome Paper		Rome	Georgia	TDF
Port Townsend Paper Company		Port Townsend	Washington	shredded
Rome Kraft Pulp and Paper Mill		Rome	Georgia	
Smurfit Newsprint		Newburg	Oregon	tire chips
Sonoco Products Co.		Hartsville	South Carolina	
Willamette Industries	Albany Paper	Albany	Oregon	

TABLE 4–5

UTILITY FACILITIES WHICH HAVE TEST–BURNED OR ARE BURNING TIRES

COMPANY NAME	PLANT/MILL	CITY	STATE	APPX. SIZE TIRE BURNED
Illinois Power	Baldwin	Baldwin	Illinois	1" X 1"
Manitowoc Public Utilities		Manitowoc	Wisconsin	shredded
Ohio Edison Company	Toronto	Toronto	Ohio	whole
Ottertail Power Co.	Big Stone	Big Stone City	So. Dakota	2" X 2"
Southern Electric International		Niagra Falls	New York	shredded
Traverse City Light & Power		Traverse City	Michigan	
United Power Association, UPA	Elk River	Elk River	Minnesota	shredded
Wisconsin Power & Light	Rock River	Beloit	Wisconsin	1" X 1"

(Source: EPRI)

An estimated 120,000 tons of scrap tires, or 15 million tires, are generated in Ohio annually. Approximately 40 percent or 6 million scrap tires are reused or recycled, which is a higher rate than the national average of 25 to 30 percent. The remaining 60 percent or 9 million or more scrap tires are disposed at landfills, and frequently at illegal dumpsites. An estimated 80 million scrap tires are already stockpiled in Ohio. This estimate appears low, especially when considering that 26 million scrap tires are estimated to be in Wyandot County (midway between Toledo and Columbus) alone (Blumenthal, personal communication).

Although the annual generation of scrap tires represents only about one percent of the Ohio solid waste stream, scrap tires in Ohio cause significant disposal problems as in any other state. Because scrap tires buried in landfills cause structural, health, and environmental problems, many landfill owners are refusing to accept tires. This has caused an increase in the number of tires disposed in tire stockpiles and illegal dumpsites.

7.1 MOSQUITOES

Lyons, Parsons, and Collart (1986) and Parsons (1987) studied mosquitoes in Ohio, including the effects of mosquitoes on humans and animals. The following is a summary of their studies.

At least 63 different species of mosquitoes have been identified in Ohio. Six of the 63 mosquito species are considered pathogenic to humans and animals. Four of these six disease vector species are known to breed in tires. In general, data suggest that the geographic spread of vector mosquitoes and thus, the diseases borne by them, are significantly increased by scrap tires (Parsons, 1987). Imported vectors are non-native species which carry these diseases. Indicator species are mosquitoes which are not necessarily vectors, but occur in Ohio only through the interstate transport of tire casings. Studies by the Ohio Department of Health indicate that any humans living, working, visiting, or playing near used tires and tire piles are at a greater risk of exposure to mosquitoes than those who live in or enter areas without tires, even in environments where the vector mosquitoes naturally occur (Parsons, 1987). Mosquito eggs hatch only if they are in water; and removing standing water, if possible, is essential in preventing mosquito breeding. Disposing of old tires is an essential element in effectively controlling mosquito populations.

Although only a few species interfere with human activities, mosquitoes are ubiquitous. Mosquitoes which attack house pets and farm animals can cause weight loss and decreased milk production, and can transmit diseases. Malaria to humans, encephalitis to humans and horses, and heartworm to dogs are all transmitted through mosquitoes.

Birds are the normal hosts of St. Louis encephalitis which is transmitted by the Northern House Mosquito (Culex pipiens). In 1975, 416 cases of St. Louis encephalitis were diagnosed in Ohio resulting in 29 deaths. This was the worst epidedemic of St. Louis incephalitis in Ohio history. Between 1964 and 1985, 439 cases of St. Louis encephalitis were diagnosed in Ohio with 32 associated deaths.

Animals of the squirrel family are the normal hosts of LaCrosse (formerly California) encephalitis which is transmitted by the Tree Hole Mosquito (Aedes triseriatus) and the Asian Tiger Mosquito (Aedes albopictus). Between 1963 and 1985, 617 cases of LaCrosse encephalitis with five deaths were reported in Ohio.

Dengue and yellow fever are transmitted by the Yellow Fever Mosquito (Aedes aegypti) and the Asian Tiger Mosquito. Between 1976 and 1980, 83 cases of imported malaria were reported in Ohio.

Other species of mosquitoes which have been found breeding in tires in Ohio include: Culex restuans, salinarius, and territans; Anopheles barberi and punctipennis; Orthopodomyia alba and signifera; and Toxorhynchites rutilis septentrionalis.

7.2 SCRAP TIRE LEGISLATION

In order to address the solid waste generated within the state of Ohio, including the handling of scrap tires, House Bill 592 (H.B. 592) was approved in 1989. The purpose of H.B. 592 is to ensure that all solid waste generated in the state of Ohio is planned, accounted for, and disposed of in an acceptable manner.

H.B. 592 requires each county, or each joint county district, to prepare a Solid Waste Management Plan (SWMP) which includes provisions for compliance with the objectives established in the State SWMP and the rules/guidelines of the Ohio Environmental Protection Agency (OEPA). Ohio has placed the responsibility for solid waste management planning at the county level. As part of their SWMP, each county district, or regional district must first identify all existing tire dumps, then develop a plan that includes strategies for managing waste tires. This plan requires a schedule for implementation and purchase of equipment to manage waste tires. Each county has the ultimate responsibility for all

216

wastes inside its boundaries. Thus, provisions must be included in each SWMP to allow for the county to assess a levy for wastes disposed at its disposal facility. For scrap tires, a tip fee could be instituted, if not already in place.

The Ohio Solid Waste Management Plan (SWMP), which was approved through H.B. 592 in June, 1989, requires:

- Effective January 1, 1993, waste tires must be shredded or processed (cut, sliced, etc.) prior to disposal. Disposal of whole scrap tires at landfills will no longer be allowed.
- Effective January 1, 1995, neither whole nor shredded tires will be accepted for disposal at sanitary landfills. Tires will only be accepted at tire monofills or monocells (shredded) or at legitimate recycling facilities.

Anyone planning to construct a shredded tire monofill, or purchasing an abandoned strip mine to be used as a monofill, must first submit an application to the State EPA for a permit-to-install. Although regulations for the monofilling of waste tires were not completed in 1990, the agencies expect to redraft monofill regulations in 1991 (Scrap Tire News, 1991). The primary objective regarding scrap tire management by the Ohio EPA is to remove existing tires stockpiled at landfills and prevent further tires from entering into landfills. The current emphasis for disposal methods of existing scrap tires is to place them into tire monofills where they can be readily mined when technologies for utilizing scrap tires is more advanced and economical.

In order to reduce and minimize the threats posed by outdoor storage of scrap tires, the OEPA and Department of Natural Resources (DNR) have completed draft rules regarding the storage of waste tires. According to these draft rules, the storage of tire piles is limited to 2500 sq. ft., with minimum of 50 ft. fire lanes between tire piles.

The Ohio Tire Recycling and Recovery Act was originally proposed in House Bill 847 (H.B. 847) in 1990, but was not enacted. This Act was re-introduced in the 1991 legislature. The bill was assigned a house and senate number of H.B. 293 and S.B. 115, respectively. In addition to tire recycling and recovery, this proposed bill would also require licensing of scrap tire transporters, collectors, and processors, and set up a system to track waste tires from collection through disposal. The following statement is taken from the pending legislation:

> The director may use moneys credited to the fund in excess of those needed to implement, administer, and enforce this chapter for research and development regarding waste tire management and for promoting or assisting in the development of markets for materials or energy recovered form waste tires.

217

One of the strategies recommended in the State SWMP is energy recovery from waste tires. This can occur in one of two ways: shredding scrap tires and using them as a supplemental fuel, or constructing a dedicated waste tire-to-energy facility. According to Natalie Farber (personal communication) of the OEPA, there has been very little development of scrap tire combustion within Ohio's industrial sector. Although there was considerable interest in combusting scrap tires as a supplemental fuel in the past, most industries concluded that it was not cost effective. As industries studied the process involved in combusting tires as a supplemental fuel for their boilers, most companies found that significant modifications to their existing fuel feed system would be necessary. In addition, these facilities would require either a shredder or shredded tires, as well as specifications as to the size and quality of TDF. As the industries added the costs required for tire specifications, the modifications necessary for their pollution control equipment to comply with allowable air emissions, and testing of air emissions, they determined that combusting scrap tires would not be as cost effective as originally anticipated. Some type of financial incentive could increase the usage of scrap tires as a supplemental fuel by these industries. However, the state of Ohio has not initiated any such incentives. As noted in Section 7.4, Minnesota, Wisconsin, and Illinois have established grant/loan programs for companies recycling, reusing, or processing scrap tires. Therefore, unless disposal costs increase significantly or electrical costs become high enough to warrant some type of change in fuel, most facilities capable of combusting scrap tires will remain with their primary fuel source, usually coal (Farber, 1991).

7.3 COAL RESERVES

Approximately 17 coal seams are currently mined in Ohio. Table 7-1 lists the heat content, ash and sulfur percent of these 17 coal seams. The average heat content ranges from 10,472 to 13,796 Btu/lb. The average percent ash in moisture-free Ohio coals ranges from 6.43% to 28.3%. Many more coal seams are present in Ohio. However, some are not persistent and others, such as the Dunkard Group, have high ash and sulfur contents and correspondingly low Btu content, and are mined only on a small scale for local use.

Sulfate sulfur, pyritic sulfur, and organic sulfur comprise the total sulfur content in the coal. There is less sulfate sulfur in the coal than the other two types of sulfur. The pyritic sulfur makes up the largest portion of the total sulfur. Coal is "washed" after it is recovered and then ground down to a particular size. The coal is then subjected to a float/sink wash

215

with liquids of varying densities. During this process, most of the pyritic sulfur and some of the sulfate sulfur is removed. The organic sulfur, or the sulfur which was in the plant when it died, cannot be extracted from the coal.

Of the coal seams mined in Ohio, three are relatively low in sulfur content. Two of these seams, the Sharon and Quakertown, were heavily mined in the 1950's and 1960's, and have essentially been "mined out". Approximately 30 million tons of the Sharon seam are estimated to remain in the mines. The Harlem seam is also a very low-sulfur coal, with approximately 0.46 percent organic sulfur. The Harlem seam is currently being mined, but its reserves are minimal. Thus, the majority of Ohio's minable coal reserves are made up of high-sulfur coals, and a large variability in the grade of coal can exist within the same seam and over a given area.

Approximately 30 million tons of coal are mined in Ohio every year. Prior to the Clean Air Act Amendments of 1970, Ohio was mining approximately 55 million tons per year. Because the majority of Ohio coals have a high sulfur content, several mines in Ohio have closed, or are in the process of closing down operations. Peabody owns two mines in Ohio, both of which will be shut down. American Electric Power (AEP), which is the largest utility company in Ohio, owns Southern Ohio Coal. This coal company mines 5 million tons of coal per year, or one-sixth of the total tonnage of coal mined in Ohio. Southern Ohio Coal mines primarily the Clarion (No. 4A) (Line 13 in Table 7-1) for American Electric Power to combust in their utility boilers. However, because AEP does not have scrubbers and the boilers are old, combusting the Clarion coals exceeds the regulatory emission standard for SO_2, which is 1.2 lb/MBtu of coal. The alternatives for AEP are to install modern pollution control equipment (scrubbers) or switch to a low-sulfur coal. According to initial AEP estimates, the pollution control equipment will cost approximately $800 million, whereas a fuel switch will cost $200 million. Unless other alternatives are discovered, a fuel switch would significantly decrease Ohio's coal production.

7.4 INDUSTRIES CURRENTLY COMBUSTING SCRAP TIRES FOR ENERGY RECOVERY

Two facilities in Ohio have some experience with combusting scrap tires as a supplemental fuel in their process furnaces: the Southwestern Portland Cement Company Quarry Plant facility at Fairborn, Ohio (Southwestern), and the Ohio Edison Company Toronto Plant facility at Toronto, Ohio (Ohio Edison). Southwestern is a cement

manufacturer that has combusted scrap tires in the past and is planning to conduct extensive compliance testing in March, 1991 as part of the application for a Permit-to-Operate. Ohio Edison successfully completed compliance testing in May, 1990 and anticipates receiving their Permit-to-Install and Permit-to-Operate from the Ohio EPA in the near future. Other cement kiln facilities located in Ohio, such as LaFarge Corporation and Medusa, have conducted scrap tire test burns at facilities located outside of Ohio but have not yet begun using scrap tires at their facilities in Ohio. Although preliminary reports from test burns at Ohio Edison indicate overall positive results when using scrap tires as 5 to 20 percent of the total fuel (including higher Btu and lower emissions of particulates, lead, SO_2, and NO_x), scrap tire usage is not being fully utilized as a viable supplemental fuel source in private industry. The environmental issues to be addressed by industrial facilities when considering scrap tire combustion include the laws regulating waste tire collection, public perception, storage, and recovery facilities and the transportation of scrap tires.

According to the Lockwood-Post's Directory (1991), 35 pulp and paper mills are located in Ohio. Table 7-2 lists these pulp and paper mills and their locations. All but three of these mills were contacted to determine if they had experience in combusting scrap tires in their boilers. None had such experience. Champion International, however, had experience in combusting tires at several plants outside of Ohio, but has decided not to pursue combusting tires at their Ohio facility. Of the mills contacted, thirteen are not equipped to combust solid fuels, two are currently idle, one has closed down, and one does not have boilers. Only nine mills have considered combusting tires, but due to modification requirements, and economic, fuel quality, and permitting problems, these mills have decided not to combust tires in their boilers (Table 7-2). The remaining six mills have never considered or never heard of combusting tires as a primary or supplementary fuel source.

Proposed Ohio regulations concerning the storage of waste tires may generate questions regarding the pricing of waste tires. For example, this position was stated by the owner of a nursery and greenhouse complex who considered combusting waste tires in his boilers but feared that such regulations may make high-sulfur Ohio coal more attractively priced. Proposed state regulations define a "waste tire storage facility" as a site or facility for the storage of whole waste tires having at least 1,000 tires on-site on any day. These regulations would require that such facilities, in order to be permitted, must submit engineering and contingency plans to be approved by the OEPA. It is feared by some that very stringent permitting governing the storage and handling of waste tires may reduce the quantity of facilities interested in combusting tires. Some of the facilities interviewed stated

that, although they were very interested in combusting tires, they were anticipating some technical and regulatory problems that would have to be confronted by the pioneering facilities such as Ohio Edison.

7.5 SUMMARY OF AIR EMISSIONS TESTS AT OHIO EDISON COMPANY

On May 21 through 25, 1990, test burns of a mixture of coal and whole tires were conducted at the Ohio Edison Toronto Plant. Their #9 pulverized coal-fired boiler was modified so that whole tires could be added to the boiler at varying feed rates. Specifically, an additional opening was created in the boiler wall to feed whole tires into the boiler. Pollution control equipment for this facility is an electrostatic precipitator, and the stack is continuously monitored for opacity.

Table 7-3 lists the feed rates of coal and tires selected for the five test days. Stack gas samples were collected and analyzed to quantify SO_2, NO_x, particulates, and lead emissions. Both the fly ash and bottom ash were analyzed for heavy metals. Three test runs were conducted daily and averaged for each day. Average emission rates for all variables are provided in Table 7-4.

Results of the stack tests are as follows:

1. Particulate and SO_2 emission rates were less than the compliance limits (Table 7-4). There are no emission limits for NO_x and lead for Ohio Edison Toronto Plant.

2. Emission rates for SO_2, NO_x, particulates, and lead decreased as the percent of tires as fuel increased.

3. While the maximum percent of tires as fuel were combusted (20 % of total Btu input),

   a) SO_2 emission rates were equivalent to non-tire emission rates;
   b) lead emission rates were 5% lower;
   c) particulate emission rates were 28% lower; and
   d) NO_x emission rates were 36% lower.

4. The higher emission rates at lower tire feed rates are assumed to be related to the non-uniform Btu supply associated with slower whole tire feed rates.

One bottom ash transport water grab sample was collected each day and analyzed for total and dissolved RCRA heavy metals. Results of the analyses indicate that all dissolved metals and total metals from the bottom ash transport water during the tire combustion test

were below drinking water standards. Tables 7-5 and 7-6 list the dissolved and total metal analyses, respectively, for the tire burn bottom ash transport water.

Fly ash and bottom ash samples were also collected and analyzed for RCRA heavy metals using the USEPA toxic characteristic leachate procedure. All TCLP leachate results for fly ash and bottom ash from the tire combustion test were below drinking water standards.

Ohio Edison plans to conduct a second test burn while cofiring coal and up to 40 % whole tires (Gillen, personal communication). At this rate, the Toronto Plant has the potential to combust approximately 6 million tires per year in its boilers.

7.6 SOUTHWESTERN PORTLAND CEMENT COMPANY

According to a completed questionnaire received by Southwestern Portland Cement Company's Quarry Plant (Southwestern) in Fairborn, Ohio, Southwestern combusts whole tires in their cement kilns. Pollution control equipment includes fabric filter dust collectors and the facility is continuously monitored for NO, SO_2, CO_2, CO, O_2, and HCl. Figure 7-1 provides a copy of the completed questionnaire by Southwestern. In order to combust whole tires in its kilns, Southwestern added conveyors, an elevator, scale, double tipping valve air lock, electric eyes, and miscellaneous hardware and software. Southwestern produces 10 to 15 percent of its total heat using tires as fuel with an upper limit of 18 percent. Particulate emissions in the bypass and main stacks are 0.03 gr/dscf corrected to 7% O_2 and 0.02 gr/dscf corrected to 7% O_2, respectively. As mentioned previously, Southwestern plans to conduct extensive air emissions testing in March, 1991.

221

B - 8

Akmenes Cementas
Company Background

8.0 SUMMARY

Significant numbers of scrap tires are presently stored in numerous locations around the United States, and each year more tires are added to the storage piles. These scrap tires are a solid waste management concern, and are contributing to both public health and safety problems.

Scrap tires, however, have an attractive heat content and, as a result, are a potential energy resource. Under the appropriate operating conditions, feed rates and pollution control equipment configurations, these scrap tires have a significant potential as a supplemental or dedicated fuel. A number of industries use the combustion of scrap tires for energy recovery, for varied economic reasons.

The feasibility of combusting scrap tires has been demonstrated to be both environmentally and technically sound. However, the feasibility typically is state- and site-specific in nature. State regulatory requirements range from silence to imposition of extensive emissions testing and air pollution control equipment. The air emissions testing specifications also vary from state to state. For example, some regulatory agencies require that the Method 5 testing include both front and back-half catch for particulate matter compliance demonstrations. The back-half catch requirement results in a more restrictive particulate matter permit emission limit. These types of differences cause a difficulty in interpreting data results and developing any technical comparisons of test results at different facilities.

Regardless of these data limitations, the combustion of scrap tires, either whole or chips, is occurring and is a permitted option available to mitigate a solid waste problem that is also a public health and safety concern.

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: Southwestern Portland Cement Co.
PLANT NAME: Quarry Plant
ADDRESS: 506 E. Xenia Drive, P. O. Box 191
Fairborn, OH 45324
PHONE NO.: (513) 878-8651
ENVIRONMENTAL ENGINEER/CONTACT: Daniel A. Willis

OF BOILERS: N/A
CAPACITY OF EACH:
HEAT RATE OF EACH:

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 36 inches diameter
OTHER FUELS: Fossil fuels, hazardous waste fuel
% TIRE OF TOTAL FUEL: 10 - 15%

POLLUTION CONTROL EQUIPMENT:

~~Fabric filter dust collectors~~

CONTINUOUS EMISSION MONITORING EQUIPMENT:
Altech system for NO, SO_2, CO_2, CO O_2, HC

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
Added conveyors, elevator, scale, double tipping valve air lock, electric eyes, misc. hardware and software

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES X NO ____
IF YES, PLEASE EXPLAIN: Limited to 18% of total heat input

AIR EMISSION DATA:
Bypass Stack: PM = .03 gr/dscf @ 7% O_2
Main Stack: PM = .02 gr/dscf @ 7% O_2

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION? RAPCA and OEPA require operating permit for each type of fuel burned.

MALCOLM PIRNIE

Completed Questionnaire
Southwestern Portland Cement Company

1737-01-1 REV. 2, May 3, 1991

FIGURE 7-1

TABLE 6–12B (Page 1 of 2)

MODESTO ENERGY COMPANY
SUMMARY OF MEASURED EMISSIONS, 1990

PARAMETER	ACTUAL EMISSIONS (lb/hr)	PERMIT LIMIT
TOTAL NON–METHANE ORGANICS	0.0	–
THC*	NR	148.4 lb/day
Benzene	0.0	–
NOx	17.69	500 lb/day
SOx –		250 lb/day
– SO_3	2.58	
– SO_2	NR	
– H_2SO_4	0.0	
VINYL CHLORIDE	0.0	–
CO	12.98	346.4 lb/day
PARTICULATE MATTER	3.88	113 lb/day
METALS:		
Al	4.21×10^{-3}	2.02×10^{-3} g/sec
As	0.00	4.61×10^{-4} g/sec
Be	0.00	–
Cd	0.67×10^{-3}	2.22×10^{-3} g/sec
Cd (Method 429)	0.64×10^{-3}	–
Cr(Total)	0.84×10^{-3}	8364×10^{-5} g/sec
Cr (Hexavalent)	0.0	–
Cu	1.35×10^{-3}	2.30×10^{-3} g/sec
Fe	13.15×10^{-3}	–
Hg	NR	5.76×10^{-4} g/sec
Mg	0.12×10^{-3}	2.30×10^{-3} g/sec
Mn	0.28×10^{-3}	–
Na	NR	$<2.88 \times 10^{-4}$ g/sec
Ni	1.14×10^{-3}	–
Pb	0.23×10^{-3}	1.15×10^{-3} g/sec
Fe	NR	2.24×10^{-2} g/sec
K	NR	$<2.88 \times 10^{-4}$ g/sec
Sn	0.76×10^{-3}	–
Zn	25.96×10^{-3}	2.10×10^{-1} g/sec

NOTE: 1 lb/hr = 24 lb/day; 1 lb/hr = 0.126 g/sec

NR – Not Reported

* Expressed as parts per million methane.

** Permit Limit obtained from Modesto Tire Incinerator Health Risk Assessment.

(Data from The Almega Corporation, 1990)

1737–01–1

REV. 2, May 3, 1991

226

TABLE 6–12B (Page 2 of 2)

MODESTO ENERGY COMPANY
SUMMARY OF MEASURED EMISSIONS, 1990

PARAMETER	ACTUAL EMISSIONS (lb/hr)	PERMIT LIMIT
Phenol	0.000	–
Formaldehyde	30.61×10^{-3}	–
PCDD	NR	** TCDD = 2.60×10^{-7} g/sec
PCDF	NR	–
PAHs		** 9.42×10^{-5} g/sec
Naphthalene	0.207×10^{-3}	
Acenaphthylene	0.000	
Acenaphthene	0.001×10^{-3}	
Fluorene	0.003×10^{-3}	
Phenanthrene	0.010×10^{-3}	
Anthracene	0.002×10^{-3}	
Fluoranthene	0.003×10^{-3}	
Pyrene	0.004×10^{-3}	
Benz(a)anthracene	0.000	
Chrysene	0.000	
Benzo(b)fluoranthene	0.001×10^{-3}	
Benzo(k)fluoranthene	0.000	
Benzo(a)pyrene	0.000	
Indeno(1,2,3–cd)pyrene	0.000	
Dibenzo(ah)anthracene	0.000	
Benzo(ghi)perylene	0.000	
Monochlorobiphenyl	0.000	–
PCBs		** 1.93×10^{-5} g/sec
Dichlorobiphenyl	0.000	
Trichlorobiphenyl	0.000	
Tetrachlorobiphenyl	0.000	
Pentachlorobiphenyl	0.000	
Hexachlorobiphenyl	0.000	
Heptachlorobiphenyl	0.000	
Octochlorobiphenyl	0.000	
Nonachlorobiphenyl	0.000	
Decachlorobiphenyl	0.000	

NOTE: 1 lb/hr = 24 lb/day; 1 lb/hr = 0.126 g/sec

NR – Not Reported

* Expressed as parts per million methane.

** Permit Limit obtained from Modesto Tire Incinerator Health Risk Assessment.

(Data from The Almega Corporation, 1990)

TABLE 6–13

AIR EMISSIONS SUMMARY FROM BURNING TDF
DOW CORNING CORPORATION, MIDLAND, MICHIGAN

POLLUTANT	UNITS	0% TDF*	5% TDF*	10% TDF*	15% TDF*	EMISSION LIMIT
TOTAL PARTICULATE MATTER @ 12% CO_2	LB/MBTU	0.0117	0.0196	0.0313	0.0114	0.035
PM–10 @ 12% CO_2	LB/MBTU	0.0078	0.0174	0.0244	**	**
OPACITY	%	5.89	6.9	7.46	15.8	**
SOx	LB/MBTU	0.026	0.028	0.037	0.059	0.8
NOx	LB/MBTU	0.153	0.162	0.133	0.081	0.7

* Balance of fuel is wood
** – Not Listed

(From EDI Engineering & Science, 1989)

TABLE 6–14

METAL EMISSIONS SUMMARY FROM BURNING TDF
DOW CORNING CORPORATION, MIDLAND, MICHIGAN

METAL	UNITS	0% TDF*	15% TDF*	INCREASE/ DECREASE
CADMIUM	LB/HR	0.00049	0.0028	INCREASE
TOTAL CHROMIUM	LB/HR	0.00128	0.0019	INCREASE
ZINC	LB/HR	0.0634	11.32	INCREASE
BERYLLIUM	LB/HR	ND**	ND**	NO CHANGE

* Balance of fuel is wood.

** ND = Not detected at a detection limit of 0.16 ug/m^3 and 7.3 x 10^{-5} lbs/hr.

(From EDI Engineering & Science, 1989)

TABLE 6–15

SUMMARY OF EMISSION COMPLIANCE TEST RESULTS
UNIROYAL GOODRICH TIRE COMPANY, EAU CLAIRE, WISCONSIN

PARAMETER	RUN 1 11.5% TDF	RUN 2 (SOOT BLOWN)	RUN 3 COAL ONLY	ALLOWABLE LIMIT
PARTICULATE MATTER (LB/MBTU)	0.417	0.938	0.35	0.6
CARBON MONOXIDE (LB/HR)	1.1	2.2	3.1	NL
TOTAL GASEOUS HYDROCARBONS (LB C/HR*)	0.28	0.24	0.19	NL
BENZENE (10^{-3} LB/HR)	<0.029	<0.029	<0.030	NL
PAH** (10^{-6} g/sec)				
Benzo–a–anthracene	14	12	14	
Benzo–b–fluoranthene	7.7	6.9	7.7	
Benzo–a–pyrene	3	2.7	3	
Dibenzo–a,h–anthracene	6.9	6.1	6.8	
Indeno,1,2,3–pyrene	7	6.2	7	
Dibenzo–a,h–acridine	117	104	116	
Dibenzo–a,j–acridine	117	104	116	
7H–Dibenzo–c,g–carbazole	7.8	6.9	7.7	
Dibenzo–a,h–pyrene	156	139	155	
Dibenzo–a,i–pyrene	156	139	155	
METALS (10^{-3} LB/HR)				
ARSENIC	7.9	21.9	9.6	2.85
BERYLLIUM	0.14	0.44	0.14	2.85
CADMIUM	5	53	9.2	2.85
CHROMIUM	3.3	6.6	2.4	1.7
COPPER	33	61.9	30.2	336
LEAD	15.9	36.6	15.1	R
MERCURY	0.19	0.16	0.12	33.6
NICKEL	4.8	10.4	5	28.5
SELEMIUM	4.8	38	3.7	67.2
ZINC	8630	13000	5800	UR

* LB C/HR = Pounds Carbon per hour
** ALL PAH CONCENTRATIONS WERE BELOW THE DETECTION LIMIT
NL = Not Listed
UR = Unregulated
R = Regulated by DNR on a case by case basis

(From Interpoll Laboratories, Inc., 1990)

TABLE 6–16

SUMMARY OF AVERAGE EMISSION RESULTS
VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY

POLLUTANT		COAL ONLY	10% TIRES	20% TIRES	BLANKS
PARTICULATE MATTER	(lb/MBtu)	0.88	2.29	2.08	
CO	(lb/MBtu)	0.17	0.21	0.32	
PAH**	(mg/MBtu)				
	Phenol	*	14.00	11.00	13.00
	Benzene	47.00	25.00	37.00	25.00
	Chrysene	*	*	0.41	0.00
	Benzo(a)pyrene	3.68	3.87	2.10	0.00

* Below detection limits
** Average calculations included * and negative (after blank corrections) values as 0.

(From Virginia Polytechnic Institute and State University,
Departments of Civil Engineering and Mechanical Engineering, 1990)

TABLE 6–17

SUMMARY OF PRELIMINARY AVERAGE EMISSION RATES
MONSANTO COMPANY

POLLUTANT	FUEL TYPE		% DIFFERENCE 90% COAL/10% TDF AS COMPARED TO 100% COAL
	100% COAL	90% COAL/ 10% TDF	
VOLUME FLOW (scfm)	41000	37000	−11
PARTICULATE MATTER–OUTLET (lb/hr)	3.6	1.79	−50
ESP CONTROL EFFICIENCY (%)	92.8	96.1	4
O_2 (%)	10.1	9.6	−5
CO (lb/hr)	0.38	0.53	40
VOC (as CH_4) (lb/hr)	1.04	0.73	−30
SO_2 (lb/hr)	83	109	31
NOx (lb/hr)	34.7	24.3	−30
HCl (lb/hr)	13.5	9.59	−29
HF (lb/hr)	0.93	0.84	−10

(From The Almega Corporation, 1991)

TABLE 6–18

EMISSIONS DATA FROM TIRE AND REFUSE DERIVED FUEL (RDF) COMBUSTION TESTING

PARAMETER	TIRES (PPM)	RDF (PPM)
CO	30	20
NOx	222	412
NOx w/DeNOx	46	47
SO_2	630	–
SO_2 w/lime	60	0
VOC	ND*	ND*
HCl	0	250
HCl w/lime	0	25

* ND = NONE DETECTED

(From Pope, 1991)

9.0 CONCLUSIONS AND RECOMMENDATIONS

As a result of reviewing the literature associated with testing of scrap tires as either a supplemental fuel or at a dedicated waste tire combustion facility, several recommendations are provided regarding the combustion of scrap tires for energy recovery:

- Scrap tires should be considered a resource rather than a waste material. State regulatory agencies should begin an education program which presents waste tires as a resource. This should be a cooperative effort, with local and state health departments and public service agencies involved.

- Tires in either a shredded, chipped, or whole condition can be combusted in an environmentally sound manner. State waste management programs should modify their rules pertaining to unacceptable waste definitions.

- Scrap tires have a significant heat content, and under controlled conditions this heat can be extracted for a beneficial use. State and federal energy agencies should evaluate the effect of combusting scrap tires as part of an overall energy policy.

- Specific controlled test burns should be conducted at each of the combustion facility types to determine optimum feed rates, fuel specifications, operational conditions, air pollution control equipment collection efficiencies, and resultant air emissions. These test burns are necessary for public acceptance of the combustion of scrap tires. The availability of grant programs for off-setting some of the costs of these test burns should be evaluated.

- A standard list of pollutants, both criteria and non-criteria, for air emissions testing needs to be established on a national level. This development would reduce the amount of time and expense to the next potential user. A national data base could possibly preclude each proposer from developing a separate data base.

- Standardized air emission test methods need to be established for the non-criteria pollutants. These methods should include both inlet and outlet testing such that air pollution control system efficiencies may be determined.

- The federal EPA should provide some uniform guidance to state agencies for permitting existing industrial and electric utility facilities to combust scrap tires. Consideration to combust scrap tires is an economic decision, and efforts to establish uniform guidance would enhance the economic decision making process.

- Efforts to allow fuel switching and fuel cleaning, by combusting a fuel mix of scrap tires, should be considered for existing industrial and electric utility facilities for complying with federal and state regulatory requirements. The

1990 Clean Air Act Amendments need to be analyzed as to how scrap tire combustion may affect permitting and compliance demonstrations.

- Facilities interested in combusting scrap tires may need to add air pollution control equipment due, in part, to the 1990 Clean Air Act Amendments. Since a national solid waste problem is addressed in an environmentally sound manner, the possibility of a tax incentive for the installation of pollution control equipment should be evaluated.

- Further evaluation of tire processing technologies and ash characteristics should be conducted. The ability of chipping and shredding equipment to consistently meet fuel specifications appears to be uncertain. Ash characterization needs to be evaluated in order to facilitate storage at permitted landfills.

10.0 REFERENCES

Almega Corporation, The. Boiler Emissions and Efficiency Testing TDF/Coal Mixed Fuel Project, December 18 and 19, 1990. Prepared for Monsanto Company, Project I-6845. February, 1991.

—, Summary of Emission Rates for the Oxford Energy Company, Westley, CA. October, 1990.

American Cement Directory, The, Bradley Pulverizer Company, Allentown, PA. June, 1990.

American Electric Power. Personal Communication. March, 1991.

Bakkom, T.K., and Felker, M.R., Tire Shredding and the Property of Tire-Derived Fuel." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Basic, Sr., J.N., "Steam and Electrical Energy Accomplished by Burning Whole Tires", Basic Environmental Engineering, Inc., Glen Ellyn, IL. December, 1989.

Blumenthal, M. Person Communication, March, 1991.

Burger, C., "Illinois Scrap Tire Management Study Summary." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

California Air Resources Board (CARB). Air Pollution Control at Resource Recovery Facilities. May, 1984.

Caron, A.L., 1985. "Comparative TGNMO Emission Data from a Wood-Residue Fired boiler on a Trial Rubber Tire Chip Burn." NCASI Bulletin Board, vol. 10, no. 16, July: 14-16.

Chapman, D. Personal Communication, April, 1991.

Clean Air Engineering. Report on Diagnostic Testing Performed at Nekoosa Packaging, Tomahawk Mill, Units 7,8, and 10, Tomohawk, Wisconsin, vol. 1. November, 1989.

Crowell, D. Personal Communication. March, 1991.

Culviner, P., 1990. "From Energy to Roads: New Uses for Old Tires." World Wastes, October: 50-51.

Drabek, J., and Willenberg, J. "Measurement of Polynuclear Aromatic Hydrocarbons and Metals from Burning Tire Chips for Supplementary Fuel." Presented at the TAPPI Environmental Conference, Portland, Oregon. April 26-29, 1987.

EDI Engineering & Science. Source Emission Testing at Dow Corning Corporation, Midland, Michigan. March, 1989.

Farber, N. Personal Communication. March, 1991.

"Fire Rages at Gigantic Tire Pile in Ontario." Tire Business, 1990.

Gaglia, N., Lundqvist, R., Benfield, R., and Fair, J., "Design of a 470,000 lb/hr Coal/Tire-Fired Circulating Fluidized Bed Boiler for United Development Group." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Georgia Department of Natural Resources, Amendment to Air Quality Permit No. 2631-049-4527-0 and No. 2631-049-4528-0 to Great Southern Paper Company. January, 1989.

---, Source Test Report Review for Power Boilers 1 and 2, Great Southern Paper Company. November, 1989 and October, 1990.

---, "Inland-Rome, Inc.: Test Results TDF and Sludge Burning in No. 1 and No. 3 Power Boilers". September, 1987, and January and August, 1989.

Gillen, J., Personal Communication. March, 1991.

Granger, J.E., and Clark, G.A., "Fuel Characterization of Coal/Shredded Tire Blends." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Haas, T.O., Personal Communication. July, 1990.

Haley, C.A., "The Blue Circle Technical Experience." Presented at the Scrap Tire Fuel for Cement Kilns Exchange Meeting Summary, Chicago, Illinois. October, 1984.

Hansen, E., Personal Communication. February, May, 1991.

Herald-Star, The. "Edison Seeks Full-Scale Tire Burning." December 6, 1991, Pg. 19.

Hope, M.W., 1985. "Waste Tire Utilization in Solid Fuel Boilers: An Alternative Fuel and It's Emissions." NCASI Bulletin Board, vol. 10, no. 16. July: 1-8.

---, Personal Communication. March, 1991.

Horizon Engineering. Stack Emissions Test Report: Smurfit Newsprint's No. 10 Hogged Fuel Fired Boiler Tire Chip Supplement Trials, Newberg, Oregon, May-July, 1987. August, 1987.

Horvath, M., "Whole Tire and Coal Cofiring Test in a Pulverized Coal-Fired Boiler." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Howe, W.C., "Fluidized Bed Combustion Experience with Waste Tires and Other Alternate Fuels." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Hutchinson, W., Eirschele, G., and Newell, R. "Experience with Tire-Derived Fuel in a Cyclone-Fired Utility Boiler." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

"Illinois Tests Tire Fuel." World Wastes. November, 1990.

Interpoll Laboratories, Inc. Results of the September 1990 Air Emission Compliance Test on the No. 2 Boiler at the Uniroyal Goodrich Tire Company. November, 1990.

Juell, G., "Experiences Burning Rubber Tires at Genstar Cement, Redding, California." Presented at the Scrap Tire Fuel for Cement Kilns Exchange Meeting Summary, Chicago, Illinois. October, 1984.

Kearney, A.T., "Scrap Tire Use/Disposal Study - Final Report." Scrap Tire Management Council. September, 1990.

Kosmos Cement Company Conditional Construction Permit. Permit NO. 48-90. Air Pollution Control District of Jefferson County. April, 1990.

Kramer, W., "The Tiger Mosquito has invaded America!" Lincoln Center Kiwanis Club and The State Department of Health, Lincoln, Nebraska. 2p.

Luybli, M., Personal Communication. January, 1991.

Lyon, W.F., Parsons, M.A., and Collart, M., 1986. "Mosquito Control." Ohio Cooperative Extension Service (OSU) and the Ohio Department of Health. Columbus, Ohio 43210. 9 p.

Malcolm Pirnie. Application for Solid Waste and Air Emission Facility Permit for the Dakota County Resource Recovery Facility. November, 1989.

McGowin, C.R., "Alternate Fuel cofiring with Coal in Utility Boilers." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Michigan Department of Natural Resources. Medusa Cement Company Air Use Permit Application. 1990.

Michigan Department of Natural Resources. Traverse City Light and Power Air Permit Application. March, 1984.

Modesto Energy Company Permit. Stanislaus County Department of Environmental Resources Air Pollution Control District. March, 1988.

Monroe, M., 1990, "Tire Fires Prevented through Recycling." Environmental Waste Management Magazine, May: 5.

National Institute for Occupational Safety and Health (NIOSH), Rhinehart Tire Fire, Winchester, VA. March, 1984. HETA document #84-044-1441, 18 p.

O'Brien, M.V., and Hanson, W.C. "Shredded Tires for Electric Generation." Presented at the Air Pollution Control Association 76th annual Meeting. June, 1983.

Ohio Edison Company. Results of The Ohio Edison Tire Burn Test at Ohio Edison Company Toronto Plant, Toronto, Ohio, May 21 through 25, 1990. August, 1990.

Oxford Energy Company. 1989 Annual Report.

Pace Laboratories, Inc. Results of the October 28-30, 1987 Criteria and Non-Criteria Emission Compliance Testing on the Unit 3 Stack at the Champion International Facility Located in Sartell, Minnesota, Volume 1 of 2 - Results. February, 1988.

Parsons, M.A., and Collart, M., 1986. Ohio Department of Health, Vector-borne Disease Unit, P.O. Box 2568, Columbus, Ohio 43266-0068. Presentation given at the Used Tire Recovery and Disposal Task Force Seminar, Columbus, Ohio. 1987.

Phalen, J., Libal, A.B., and Taylor, T., "Manitowoc Coal/Tire Chip-Cofired Circulating Fluidized Bed Combustion Project." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Pillsbury, H., Personal Communication. March, 1991.

Pope, K.M., "Tires to Energy in a Fluidized Bed Combustion System." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Radian Corporation, "Modesto Energy Company Waste Tire to Energy Facility, Westley, CA, Final Emission Test Report." April, 1988.

Rittenhouse, R.C., 1983. "Handling and Firing Nonconventional Fuels." Power Engineering. December: 34-42.

Robinson, W., Personal Communication. February, 1991.

Rolfus, M., Personal Communication. March, 1991.

Rouge, J.D., and Lowe, J., 1986. "Air Toxics Impacts from Resource Recovery Projects: A Comparison of Health Risk Assessment Methodologies and Emission Factors." Presented at the 79th Annual Meeting of the Air Pollution Control Association, Minneapolis, Minnesota. June 22-27, 1986.

Ryan, J.V., Characterization of Emissions from the Simulated Open Burning of Scrap Tires. United States Environmental Protection Agency, EPA/600/S2-89/054. October, 1989: 61 p.

Schreurs, S.T., "Tire-Derived Fuel and Lignite Co-Firing Test in a Cyclone-Fired Utility Boiler." Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

Sladek, T.A., 1989. "...and Your Old Tire in Trade." Resource Recovery, vol. 3, no. 2. April: 29-30.

Stopek, D.J., Millis, A.K., Stumbaugh, J.A., and Diewald, D.J. "Testing of Tire-Derived Fuel at a 560 MW Cyclone Boiler" Presented at the EPRI Conference, Waste Tires as a Utility Fuel, San Jose, California. January, 1991.

"Third Annual Legislative Update." Scrap Tire News, vol. 5, no. 1, pp.1-15. January, 1991.

"Tire Economics: Oil Prices Down, Disposal Prices Up." Fire Engineering, p. 24. June, 1988.

"Tires Fuel Yokohama Plant." Scrap Tire News, vol. 4, no. 5, pp. 5. September, 1990.

Valenti, M., "Burning Rubber." Mechanical Engineering, vol. 113, no. 2, pp. 108. February, 1991.

Virginia Polytechnic Institute and State University. "Measurement of Polynuclear Aromatic Hydrocarbons and other Combustion Products from Burning Tire-Derived Fuel and Coal in a Conventional Boiler". November, 1990.

Vosler, G.L., 1985. "Hog Fuel Boiler Alternate Fuels Project." NCASI Bulletin Board, vol. 10, no. 16, July: 9-13.

Wark, K., and Warner, C.F., Air Pollution, Its Origin and Control, Second Edition, Harper & Row, Publishers, New York, NY, 1981, 526p.

Washington Department of Ecology. Source Test - Summary of Emissions to Atmosphere: Boise Cascade Lime Kiln. Report No. 86-08. July, 1986.

——. Source Test - Summary of Emissions to Atmosphere: Crown Zellerbach Pulp Mill. Report No. 86-10. December, 1986.

——. Source Test - Summary of Emissions to Atmosphere: Port Townsend Paper Company. Report No. 86-01. July, 1986.

——. Polynuclear Aromatic Hydrocarbons and Metals Emitted from the Burning of Tires at Crown Zellerbach, Port Angeles, June 10 and 11, 1986. Ecology Source Test 86-10a. November, 1986.

——. Polynuclear Aromatic Hydrocarbons and Metals Emitted from the Burning of Tires at the Port Townsend Paper Company, February 25 and March 5, 1986. Ecology Source Test 86-01a. June, 1986.

Wisconsin Department of Natural Resources. Review of Stack Tests Performed at Nekoosa Packaging, Tomahawk, Wisconsin. File Ref: 4530. February, 1990.

——. Air Pollution Control Permit for Owens-Illinois Tomahawk and Timber STS, Inc., Tomahawk, Wisconsin. Permint No. 735008010-J01. June, 1987.

Woodman Engineering, Inc., "Champion International Corporation - TDF Tests". Prepared for Champion International Corporation, Bucksport, Maine. October, 1989.

Zimmer, J., Personal Communication. April, 1991.

RECEIVED

MAR 06 1991

QUESTIONNAIRE

March 4, 1991

Steven M. Jeske
Malcolm Pirnie, Inc.
6161 Busch Blvd.
Columbus, OH 43229

Dear Steven:

We are presently in the process of seeking a Permit-to-Install (PTI) and a Permit-to-Operate (PTO) a whole waste tire burning system at our Toronto plant. Additional information may be available if you can wait until the EPA completes their review and rules on our application which is expected early-to-mid April, 1991.

QUESTIONNAIRE RESPONSE:

OHIO EDISON Co

PLANT NAME:	TORONTO
ADDRESS:	TORONTO, OHIO
CONTACT:	WILLIAM J. KOLOSI
PHONE NO.:	216-384-5833
# BOILERS:	1
CAPACITY:	418,000 #/HR STEAM
TIRE SPEC:	WHOLE
MAXIMUM SIZE:	PASSENGER/LIGHT COMMERCIAL
% TIRE FUEL:	20% BY BTU INPUT
PC EQUIPMENT:	ESP
CEM:	OPACITY
MODIFICATIONS:	MINIMAL; CONVEYORS & BOILER PENETRATION
SUPPLY PROBLEMS:	NONE
EMISSION DATA:	LEAD DOWN 5%; PARTICULATE DOWN 28%; NITROGEN OXIDES DOWN 36%; SULFUR EMISSION DOWN APPROXIMATELY 13%.
PERMITS:	WAIVER FOR 7 DAY TEST BURN OBTAINED FROM OEPA

Sincerely,

W. J. Kolosi

24

QUESTIONNAIRE

SCRAP TIRE USE

COMPANY NAME: KOSMOS CEMENT COMPANY
PLANT NAME:
ADDRESS: 15301 DIXIE HIGHWAY
LOUISVILLE, KY 40272
PHONE NO.: 502-935-7331
ENVIRONMENTAL ENGINEER/CONTACT: JAMES D. PARKER

OF BOILERS: ONE CEMENT KILN
CAPACITY OF EACH: 2160 TONS/DAY
HEAT RATE OF EACH: 302,650,000 BTU/HOUR, 14 TONS OF COAL/HOUR

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 28 INCH OUTER DIAMETER
OTHER FUELS: COAL
% TIRE OF TOTAL FUEL: 12%

POLLUTION CONTROL EQUIPMENT:
BAGHOUSE

CONTINUOUS EMISSION MONITORING EQUIPMENT:
OPACITY

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
USING OUR OWN DESIGN FOR TIRES CONVEYING AND FEEDING WITH DOUBLE AIRLOCKS AT ENTRY TO KILN.

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

AIR EMISSION DATA:
PARTICULATE = 2.32 LB/HR.; SO_2 = 116.6 LB/HR; NOx = 444.7 LB/HR.
CO = 114.4 LB/HR.; TOTAL HYDROCARBON = 5.6 LB/HR.; HCl = 3.36/LB

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION? TEST BURN PERMIT REQUIRED BY THE AIR POLLUTION CONTROL DISTRICT OF JEFFERSON COUNTY, KENTUCKY.

*THE EPA HAS ACKNOWLEDGED THE POSSIBILITY OF ANOMALOUS RESULTS DUE TO CATION INTERFERENCE WHEN EPA METHOD 26 IS USED TO DETERMINE HYDROGEN CHLORIDE EMISSIONS FROM CEMENT KILNS.

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: HOLNAM INC.
PLANT NAME: SEATTLE PLANT (DEVIL'S SLIDE PLANT)
ADDRESS: 3400 W. MARGINAL WAY SW / 6055 E. CROYDON RD.
SEATTLE, WA 98106 / MORGAN UT 84050
PHONE NO.: 206-937-8025 / 801-829-6821
ENVIRONMENTAL ENGINEER/CONTACT: SCOTT HEARD / LEVIN OVARD

# CEMENT KILNS:	1	2
CAPACITY OF EACH:	1500 STPD	600 STPD EACH
HEAT RATE OF EACH:	~ 5.3 MM Btu/ST	~ 6.0 MM Btu/ST

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE:		2" TOPSIZE BOTH PLANTS
OTHER FUELS:	COAL (SEATTLE)	GAS (DEVIL'S SLIDE)
% TIRE OF TOTAL FUEL:	15% PERMITTED	20% SOVEREIGN

POLLUTION CONTROL EQUIPMENT:

ESP / ESP'S

CONTINUOUS EMISSION MONITORING EQUIPMENT:

O_2, OPACITY, CO. / O_2, OPACITY PLANNED POSSIBLY CO

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:

HOPPER TO SCREW TO PNEUMATIC CONVEYING / PLAN TO USE COALS

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO ✓
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ NO ✓
IF YES, PLEASE EXPLAIN: IN FACT, COMBUSTION AT SEATTLE IS IMPROVED

AIR EMISSION DATA:

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES ✓ NO ____
IF YES, WHAT TYPE OF MODIFICATION? AIR PERMIT FOR BOTH PLANTS

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: GEORGIA PACIFIC
PLANT NAME: CEDAR SPRINGS OPERATIONS
ADDRESS: P.O. BOX 44 HIGHWAY 273 WEST
CEDAR SPRINGS, GA. 31732
PHONE NO.: (912) 372-5104
ENVIRONMENTAL ENGINEER/CONTACT: DONALD J. MILLER

 # OF BOILERS: TWO B&W COMBINATION FUEL BOILERS
CAPACITY OF EACH: DESIGN 690 X10^6 BTU/HR
HEAT RATE OF EACH: HEAT RELEASE RATE ~28,000 BTU/HR/FT^3

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

(SHREDDED) WHOLE SLIT (WITH METAL REMOVED)

MAXIMUM TIRE PIECE: NOMINAL 1 1/2" x 1 1/2"
OTHER FUELS: COAL, WOOD WASTE, PEANUT HULLS, NO. 6 OIL, GAS
% TIRE OF TOTAL FUEL: ~5%

POLLUTION CONTROL EQUIPMENT:
BARON MECHANICAL COLLECTORS (MULTICYCLONES) FOLLOWED BY AERAL VENTURI SCRUBBERS

CONTINUOUS EMISSION MONITORING EQUIPMENT:
NO GAS ANALYZERS, CONTINUOUS MONITORING OF SCRUBBER FLOW AND DIFFERENTIAL PRESSURE

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
INSTALLED SEPARATE FEEDER SYSTEM FOR TIRE FUEL HAS RECORDING WEIGHTOMETER. TIRE FUEL METERED IN TO WOODWASTE FUEL FEED

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEM: YES X NO ____
IF YES, PLEASE EXPLAIN: HAS TO BE FED WITH WOOD WASTE FUEL BECAUSE HIGH TEMPERATURE OF TIRE FUEL ALONE WILL DAMAGE BOTTOM GRATES, ALSO HIGH METAL CONTENT WILL AFFECT FEED BELTS, GRATES, AND PLUG ASH REMOVAL LINES

AIR EMISSION DATA:
PARTICULATES 0.10 - 0.14 #/MMBTU
NOx 0.28 #/MMBTU

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES ✓ NO ____
IF YES, WHAT TYPE OF MODIFICATION? MODIFICATION TO ALLOW ALTERNATIVE FUEL, EMISSIONS INCREASE INSIGNIFICANT

1737-01-1

REV. 0, MARCH 22, 1991

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: FORT HOWARD CORPORATION *
PLANT NAME: GREEN BAY MILL
ADDRESS: 1919 S. BROADWAY
P.O. BOX 19130, GREEN BAY, WISCONSIN 54307-9130
PHONE NO.: (414) 435-8821
ENVIRONMENTAL ENGINEER/CONTACT: AL TOMA

OF BOILERS: 5; 1 IS USED 20 DAYS/YR
CAPACITY OF EACH: 100,000; 250,000; 375,000; 500,000; 189,000 LBS STEAM/HR
HEAT RATE OF EACH:

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 2" X 2", NORMALLY 1' X 1', BUT COMES LARGER
OTHER FUELS: COAL, PET. COKE, SOME RDF (SMALL AMT)
% TIRE OF TOTAL FUEL: 30 TONS TIRES / 1000 TONS COAL PER DAY; @ 3%

POLLUTION CONTROL EQUIPMENT:
ALL 5 BOILERS TIED INTO 1 BAGHOUSE
BACKUP OF PRECIPITATOR ONLY – NO SULFUR OR NOx CONTROL

CONTINUOUS EMISSION MONITORING EQUIPMENT:
OPACITY – SIEGLER
SO_2 – KVB

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
MIX WITH COAL, INCLINE VALVE TO SILOS AND RUN TO COAL CRUSHER

WASTE TIRE SUPPLY PROBLEMS? YES _____ NO X
IF YES, PLEASE EXPLAIN:
WISCONSIN HAS EXCELLENT PROGRAM FOR CLEANING TIRE DUMPS.

ANY COMBUSTION/OPERATING PROBLEMS? YES _____ NO _____
IF YES, PLEASE EXPLAIN: OPERATIONAL PROBLEMS ONLY
500,000 LB CYCLONE BOILER, NO GOOD WAY TO INPUT TIRES, TRIED W/AIR, BUT HAVEN'T ACCOMPLISHED. CHAIN DRIVE OR STOKER BOILERS ARE JAMMED BY **

AIR EMISSION DATA:
NONE. NO PROBLEMS WITH ASH, EP TOXICIY ON ASH FOR METALS – BELOW LIMITS.

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES _____ NO X
IF YES, WHAT TYPE OF MODIFICATION? TIRES ADDED AS AN ALTERNATE FUEL* IF BOILERS ARE CAPABLE OF BURNING.

* Information obtained by phone
** STEEL (BELTS AND BEADS) IF TIRES ARE NOT SHREDDED WELL. ADDITIONAL REQUIREMENT – INCREASE FREQUENCY OF BLASTING GRATES ON STOKER BOILERS TO 4X/YR DUE TO STEEL MELTING ON GRATES.

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME CHAMPION INTERNATIONAL *
PLANT NAME: BUCKSPORT MILL
ADDRESS: RIVER ROAD
P.O. BOX 1200, BUCKSPORT, MAINE 04416
PHONE NO.: (207) 469-1700
ENVIRONMENTAL ENGINEER/CONTACT: STEVE JOSE

OF BOILERS: 4; 3 BURNS ONLY OIL, 4th BURNS MULTIFUELS
CAPACITY OF EACH: 500,000 LB/HR STEAM (MULTIFUEL BOILER)
HEAT RATE OF EACH: 814 MBTU

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 2" OR LESS, METAL REMOVED
OTHER FUELS: #6 OIL, PULV. COAL, BIOMASS, PAPER SLUDGE
% TIRE OF TOTAL FUEL: PERMITTED UP TO 3.5 TONS/HR, OPERATES AT 2.5 TONS/HR (@ 10%

POLLUTION CONTROL EQUIPMENT:
FIVE-STAGE ELECTROSTATIC PRECIPITATOR

CONTINUOUS EMISSION MONITORING EQUIPMENT:
KIKO MONITORS - OPACITY, ELECTRON 400, CO_2, SO_2, NO_x

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
FEEDER UNIT = CUT HOLE IN CONVEYOR GELDER

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:
USES ONE COMPANY TO SHRED TIRES. TIRES SHIPPED FORM TEXAS AND ATLANTA

ANY COMBUSTION/OPERATING PROBLEM: YES ____ NO X
IF YES, PLEASE EXPLAIN:
TIRES DECREASE AIR; SLOW GRATE SPEED TO ALLOW FOR MORE AIR

AIR EMISSION DATA:
WILL SEND

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION? ASH TESTING REQUIRED
AIR LICENSE - ADD SOLID WASTE, NO CHANGE IN LIMITS.

* Information obtained by phone.
1737-01-1

REV. 0, MARCH 22, 1991

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: CALIF PORTLAND CEMENT CO
PLANT NAME: MOJAVE
ADDRESS: PO BOX 910
MOJAVE, CA 93502
PHONE NO.: (805) 824-2401
ENVIRONMENTAL ENGINEER/CONTACT: Michael L Dwyer

CEMENT KILNS: 1 Precalciner
CAPACITY OF EACH: 3250 TON/DAY
HEAT RATE OF EACH: 3.3 MMBtu/TON

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 2½" x 2½"
OTHER FUELS: COAL
% TIRE OF TOTAL FUEL: 30%

POLLUTION CONTROL EQUIPMENT:
FILTER BAGHOUSES

CONTINUOUS EMISSION MONITORING EQUIPMENT:
TWO OPACITY MONITORS ONE EACH ON KILN STACK & COOLER STACK

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

AIR EMISSION DATA:
NONE

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE ~~STATE~~ County Air District REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION? SIMPLY TO USE SHREDDED TIRES AS A FUEL SOURCE

We operated on tires twice. Once for 5 days and the other 3 days

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: Bridgestone / Firestone, Inc. *
PLANT NAME:
ADDRESS: 2500 N. 22nd Street
Decatur, IL 62526
PHONE NO.: (217) 428-2141
ENVIRONMENTAL ENGINEER/CONTACT: Pete Brinkoetter, Mech. Engineer

OF BOILERS: 1
CAPACITY OF EACH: 22,000 lb/hr steam
HEAT RATE OF EACH 29 MBtu/hr

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED (WHOLE) SLIT

MAXIMUM TIRE PIECE:
OTHER FUELS: wood, cardboard, paper, some plastics, nat. gas as fuel supplement
% TIRE OF TOTAL FUEL: 15 % to 16 %

POLLUTION CONTROL EQUIPMENT:
none, has secondary combustion chamber

CONTINUOUS EMISSION MONITORING EQUIPMENT:
opacity

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
modifications to secondary combustion chamber.

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:
manufactures tires on-site.

ANY COMBUSTION/OPERATING PROBLEM: YES X NO ____
IF YES, PLEASE EXPLAIN: Proprietary

AIR EMISSION DATA:
measures particulate matter, CO, and CO_2 only

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES ____ NO ____
IF YES, WHAT TYPE OF MODIFICATION? Permit limits number of operating hours.
Can burn 100% tires.

* Information obtained by phone.
1737-01-1

REV. 0, MARCH 22, 1991

249

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: CALAVERAS CEMENT CO.
PLANT NAME: REDDING PLANT
ADDRESS: 8750 WONDERLAND BLVD.
REDDING, CA 96003
PHONE NO.: 916 275 1581 EXT 141
ENVIRONMENTAL ENGINEER/CONTACT: GREGORY JUELL (PROCESS SUPERINTENDENT)

CEMENT KILNS: ONE
CAPACITY OF EACH: 650,000 TONS / YR
HEAT RATE OF EACH: PROPRIETARY

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

(SHREDDED) WHOLE SLIT

MAXIMUM TIRE PIECE: PROPRIETARY
OTHER FUELS: COAL 80%
% TIRE OF TOTAL FUEL: 20%

POLLUTION CONTROL EQUIPMENT:
FABRIC FILTER BAG HOUSE

CONTINUOUS EMISSION MONITORING EQUIPMENT:
NO_x, CO, O_2 (TOTAL HC SPRING 1991)

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

AIR EMISSION DATA:
EMISSIONS NOT SIGNIFICANTLY DIFFERENT THAN BURNING COAL

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION? USE PERMIT MODIFICATION FROM THE COUNTY AGENCIES. NOT FROM STATE

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: BOXCROW CEMENT COMPANY *
PLANT NAME: BOXCROW PLANT
ADDRESS: 700 DOVE LANE P.O. DRAWER 1170
MIDLOTHIAN, TEXAS 76065
PHONE NO.: (214) 299 – 6350
ENVIRONMENTAL ENGINEER/CONTACT: ROY CLICK, ENV. ENGINEER

OF KILNS: 1
CAPACITY OF EACH: 3100 TONS CLINKER PER DAY
HEAT RATE OF EACH: 3 1/2 MBTU PER TON OF CLINKER

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: 2" X 6"
OTHER FUELS: COAL
% TIRE OF TOTAL FUEL: 10 % – 12 %

POLLUTION CONTROL EQUIPMENT:
BAGHOUSE

CONTINUOUS EMISSION MONITORING EQUIPMENT:
SO_2, NOx, OPACITY

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
NONE

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO x
IF YES, PLEASE EXPLAIN: PRESHREDDED WHEN DELIVERED

ANY COMBUSTION/OPERATING PROBLEM: YES ____ NO x
IF YES, PLEASE EXPLAIN:

AIR EMISSION DATA:
ONLY CONTINUOUS MONITORING DATA.
PLAN TO COLLECT DURING NEXT TEST–BURN.

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES x NO ____
IF YES, WHAT TYPE OF MODIFICATION?
NOT SURE YET.

* Information obtained by phone.

QUESTIONNAIRE
SCRAP TIRE USE

FEB 04 1991

COMPANY NAME: Ash Grove Cement west, Inc.
PLANT NAME: Durkee Cement Plant
ADDRESS: P.O. Box 5
Durkee, Oregon 97905
PHONE NO.: 503-877-2411
ENVIRONMENTAL ENGINEER/CONTACT: Douglas Y. Hale

CEMENT KILNS: One Four Stage Preheater Type
CAPACITY OF EACH: 500,000 ton/year
HEAT RATE OF EACH:

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE:
OTHER FUELS:
% TIRE OF TOTAL FUEL: 10%

POLLUTION CONTROL EQUIPMENT:
Electrostatic Precipitator

CONTINUOUS EMISSION MONITORING EQUIPMENT:
Opacity, CO, O_2, NOx

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

ANY COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

AIR EMISSION DATA:
Extensive testing for particulates, SOx, metals, total hydrocarbons showed no significant increase.

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?
Minor air quality

Arizona Portland Cement
a division of California Portland Cement
P.O. Box 338
Rillito, Arizona, 85654
(602)622-3503

January 29, 1991

Mr. Michael V. O'Brien
Project Environmental Scientist
Malcom Pirnie, Inc.
5001 W.80th Street, Suite 770
Minneapolis, MN 55437

FEB 04 1991

Dear Mr. O'Brien

Arizona Portland Cement has successfully used tire-derived fuel (TDF) in our production process. The following comments are provided in response to your letter of January 18, 1991.

1. TDF has been used only in our #4 Kiln, a suspension pre-heater with pre-calciner.

2. Our main solid fuel, coal, averages 12,500 BTU/lb. Our TDF has a value of about 14,300 BTU/lb. We use 2"x2" shredded tires. TDF use, on a BTU basis, runs from 5 to 20 percent of the total fuel.

3. Fabric collectors are used to remove particulate emissions from the process. The stack opacity is continuously monitored.

4. A front-end loader dumps the TDF into a hopper which has a twin screw feeder discharging onto a conveyor belt. The belt dumps into a bucket elevator that carries the tire chips to a duct through which they enter the calciner. This equipment was all expressly installed for the TDF.

5. The availability of shredded tires is a concern to management. The TDF does not burn as efficiently as pulverized coal, so its use is limited in order to optimize the process. TDF also presents some handling, storage and housekeeping problems that make it less desirable as a fuel source. Its chief benefit is a low cost. Emission rates do not seem to be significantly altered by the use of TDF.

If you have any further questions please contact me at the Rillito plant.

Sincerely,

Steven A. Regis

Steven A. Regis
Process Engineer

APPENDIX A

QUESTIONNAIRE

SCRAP TIRE USE

COMPANY NAME: _____
PLANT NAME: _____
ADDRESS: _____
_____

PHONE NO.: _____
ENVIRONMENTAL ENGINEER/CONTACT: _____

OF BOILERS: _____
CAPACITY OF EACH: _____
HEAT RATE OF EACH: _____

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MAXIMUM TIRE PIECE: _____
OTHER FUELS: _____
% TIRE OF TOTAL FUEL: _____

POLLUTION CONTROL EQUIPMENT:

_____
_____

CONTINUOUS EMISSION MONITORING EQUIPMENT:

_____
_____

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:

_____
_____

WASTE TIRE SUPPLY PROBLEMS? YES _____ NO _____
IF YES, PLEASE EXPLAIN: _____
_____

ANY COMBUSTION/OPERATING PROBLEMS? YES _____ NO _____
IF YES, PLEASE EXPLAIN: _____
_____

AIR EMISSION DATA:

_____
_____

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES _____ NO _____
IF YES, WHAT TYPE OF MODIFICATION? _____
_____

APPENDIX B

REQUEST FOR INFORMATION

APPENDIX B

REQUEST FOR INFORMATION

Mr. Ladd Parsons
Vice President-Operations
Medusa Cement Company
P.O. Box 5668
Cleveland, OH 44101

Mr. Greg Juell, Process Superintendent
CBR Cement - Calaveras Cement Company
Redding Plant
8750 Wonderland Boulevard
Redding, CA 96003

Mr. Mike Dwyer, Process Engineer
Mojave Plant
CALMAT Company
P.O. Box 910
Mojave, CA 93501

Mr. John Frye, Plant Manager
Arizona Portland Cement Company
Rillito Plant
P.O. Box 338
Rillito, AZ 85654

Mr. Mike Cawthray
Essroc Materials, Inc.
P.O. Box 32
Nazareth, PA 10864

Mr. Al Asaro
Giant Resource Recovery
P.O. Box 352
Harleyville, SC 29448

Mr. Hank Gross, Vice President-Production
Illinois Cement Company
P.O. Box 442
LaSalle, IL 61310

Mr. Roy Harris, Plant Chemist
Monarch Cement Company
Humboldt, KS 66748

Mr. Greg Carrigan, Production Manager
LaFarge Corporation
Balcones Plant
P.O. Box 311507
New Braunfels, TX 78131

Mr. Tom Donaldson
Lab Production Superintendent
River Cement Company
Selma Plant
Festus, MO 63028

Mr. Doug Hale, Corporate Environmental Manager
Ash Grove Cement West, Inc.
Durkee Plant
P.O. Box 5
Durkee, OR 97905

Mr. Harold Bordon
Environmental Affairs
HOLNAM, Inc.
P.O. Box 122
Dundee, MI 48131

Dr. Greg Miller
HOLNAM, Inc. for Ideal Basic Industries, Inc.
P.O. Box 122
Dundee, MI 48131

Ms. Elizabeth Mikols
Lehigh Portland Cement Company
718 Hamilton Mall
Allentown, PA 18105

Mr. John Whitmore
Lafarge Corporation
P.O. Box 324
Dallas, TS 75221

Mr. Randy Rakes, Environmental Engineer
Roanoke Cement Company
P.O. Box 27
Cloverdale, VA 24077

Eric Hansen, V.P.
Ash Grove Cement Co.
Tel No: (913) 451-8900
Fax No: (913) 451-8324

Mr. Don Miller, Process Engineer
Georgia Pacific Company
Cedar Springs, GA
FAX No: (912) 372-5163

Mr. Randy Thompson
Florida Crushed Stone Company
P.O. Box 490300
Leesburg, FL 34749-0300

Ms. Diedra Vance, Process Engineer
Blue Circle, Inc.
Atlanta Plant
2520 Paul Avenue, N.W.
Atlanta, GA 30318

Mr. Daniel A. Willis
Division Process/Environmental Engineer
Southdown, Inc.
Eastern Division
P.O. Box 191
Fairborn, Ohio 45324

Mr. Jim Parker
Special Projects Manager
Kosmos Cement Company
Kosmosdale Plant
15301 Dixie Highway
Kosmosdale, KY 40272

Mr. Randy Wiley, Plant Engineer
Southdown, Inc.
Lyons Plant
P.O. Box 529
Lyons, CO 80540

Ms. Annette White
Inland-Rome Paper
P.O. Box 1551
Rome, GA 30161

Mr. Charles Wright, Process Engineer
RMC Lone Star
Highway 1
Davenport, CA 95017

Mr. Pete Gruene
Sonoco Products Company
P.O. Box 160
Hartsville, South Carolina 29550

Mr. Chris Nigren
Willamette Industries
P.O. Box 339
Albany, OR 97321

REGULATORY AGENCY REQUESTS

Department of Air Pollution Control
P.O. Box 10089
Richmond, VA 23240

Mr. Gene Drew
Georgia Department of Natural Resources
205 Butler Street SE
Floyd Tower - 1162 East
Atlanta, GA 30334

Mr. Gary Reed, Inspector
Stanislaus County
Air Pollution Control District
1716 Morgan Road
Modesto, CA 95351

Mr. Dave Ferrier
Michigan Department of Natural Resources
Air Quality Division
P.O. Box 30028
Lansing, MI 48909

Ms. Pat Dennis
Permit Section
Illinois EPA
Division of Air Pollution Control
1340 North 9th
Springfield, IL 62702

Paul Castagno
Air Pollution Control District
Jefferson County
850 Barret Avenue
Louisville, KY 40204-1745

OTHER REQUESTS / CONTACTS:

Mr. Lacy Hinther, Permit Engineer
Kansas Department of Air Quality
(913) 296-1576

Su Shant
Arizona Department of Environmental Quality
(602) 257-6956

Mr. Bill Robinson
Virginia Department of Solid Waste Management
Roanoke, Virginia
(804) 371-8714

Ms. Natalie Farber
Ohio Environmental Protection Agency
Office of Solid Waste
Columbus, Ohio
(614) 466-7220 #3135

Mr. Ray Potts
Oregon Department of Environmental Quality
(503) 229-5630

Mr. Mike Stansfield
Missouri Department of Natural Resources
Division of Environmental Quality
Jefferson City, Missouri
(314) 751-4817

Mr. Bob Hudson
South Carolina Department of Air Quality Analysis, State Park
(803) 935-7015

Mr. Stan Miller
Smurfit Newsprint
Newburg, Oregon
(503) 538-2151

Ms. Kathy Leone
Tacoma Public Utilities
Tacoma, Washington
(206) 593-8322

Mr. Robert Wood
South Carolina Permit Division
(803) 734-4750

Mr. Doug Crowell, Coal Geologist
Ohio Geological Survey
Columbus, Ohio
(614) 265-6594

Mr. John Heinrich
Wisconsin Department of Natural Resources
(608) 267-7547

Mr. Mark Harder
Wisconsin Department of Natural Resources
(608) 267-2016

Mr. Ron Milikin
California Air Resources Board
(818) 572-6206

Mr. James Rouge
Radian Corporation
(916) 362-5332

Mr. Jim Gillen
Ohio Edison Co.
(216) 384-7959

Mr. Allan Justice
Mr. Paul Purseglove
Illinios Environmental Protection Agency
Department of Energy
(217) 782-6760

Mr. Chris Burger
Illinios Department of Energy and Natural Resources
(217) 524-5459

Mr. John Mitchell
Pennsylvania Bureau of Air Quality
(717) 787-9702

Mr. Mark Hope
Waste Recovery
(503) 283-2261

Mr. Jim Jarrell
Heartland Industries of Dexter
Missouri
(314) 246-2523

Mr. Joe Otto
Minnesota Pollution Control Agency
Office of Solid Waste
(612) 296-8411

Mr. P.J. (Pete) Brinkoetter, Mech. Engineer
Bridgestone/Firestone, Inc.
Decatur, Illinois
(217) 428-2141

Mr. Greg Eirschele, Chem. Engineer
Wisconsin Power & Light Co.
Beloit, Wisconsin
(608) 252-3084

Mr. Mark Wadell, Chief Engineer
Eastern Illinois University
(217) 581-5941

Mr. Barry Henderson, Environmental Engineer
Reynolds Tobacco
Winston-Salem, North Carolina
(919) 741-5000

Mr. Ben Ziesmen (via McGowin)
Northern Indiana Public Service Company (NIPSCO)
Hammond, Indiana

TABLE 7-1

SULFUR AND ASH DATA FOR THE MOST PRODUCTIVE COAL BEDS IN OHIO

COAL SEAMS	NO. OF ANALYSES	AVERAGE PERCENT					AVERAGE HEAT RATE (BTU/LB)	ESTIM RECOV RESI (BILLIO
		ASH	TOTAL SULFUR	SULFATE SULFUR	PY_ITIC SULFUR	ORGANIC SULFUR		
WASHINGTON (NO. 12)	6	28.30	2.41	0.08	1.42	0.82	10,427	
WAYNESBURG (NO. 11)	34	17.31	2.93	0.12	1.64	1.12	11,825	
MEIGS CREEK (NO. 9)	100	13.04	4.00	0.07	1.69	1.85	12,425	
REDSTONE (NO. 8A)	27	12.34	3.52	0.10	2.44	1.15	12,451	
PITTSBURGH (NO. 8)	188	10.58	4.24	0.15	2.56	1.67	12,948	
HARLEM	5	8.72	0.97	0.01	0.50	0.49	13,369	
ANDERSON	9	12.94	3.73	0.01	2.56	1.03	12,504	
MAHONING (NO. 7A)	5	8.73	2.65	NL	NL	NL	13,796	
UPPER FREEPORT (NO. 7)	110	11.01	3.11	0.05	2.21	0.91	12,952	
LOWER FREEPORT (NO. 6A)	51	11.82	3.72	0.15	2.51	1.19	13,155	
MIDDLE KITTANNING (NO. 6)	272	9.12	3.48	0.10	2.07	1.47	12,969	
LOWER KITTANNING (NO. 5)	162	11.19	4.50	0.11	3.16	1.44	12,772	
CLARION (NO. 4A)	73	12.89	4.19	0.24	2.41	1.59	12,367	
BROOKVILLE (NO 4)	36	12.60	3.15	0.08	1.87	1.35	12,634	
TIONESTA (NO. 3B)	6	14.64	4.45	0.02	3.87	1.17	12,176	
QUAKERTOWN (NO. 2)	11	6.43	1.28	0.05	0.59	0.47	13,364	
SHARON (NO. 1)	14	10.01	0.84	0.30	0.50	0.38	12,884	

COAL SEAMS LISTED STRATIGRAPHICALLY

(From Ohio Geology, 1989; and Ohio Geological Survey)

TABLE 7-2

PULP AND PAPER MILLS IN OHIO

CITY	COMPANY NAME	ADDRESS	BURN TIRES?	REMARKS
Avery	CertainTeed Corp	POBox 600	NO	Cannot burn solid fuels
Baltimore	Fairfield Paper Co, L.P.	310 Water St.	NO	Has not considered.
Chagrin Falls	IVEX Corp	218 Cleveland St.	NO	Cannot burn solid fuels
Chillicothe	Mead Corp	401 S. Paint St.		Unable to contact.
Cincinnati	Cincinnati Paperboard Corp.	5500 Wooster Rd.	NO	Cannot burn solid fuels
Cincinnati	Ohio Pulp Mills Inx.	2100 Losantiville Rd	NO	Does not have boilers
Cincinnati	Rock-Tenn Co.	3347 Madison Rd.	NO	Never heard of burning tires.
Circleville	Container Corp. of America	401 W. Mill St.	NO	Worried about quality control.
Columbus	DuPont Specialty Imaging Media Inc.	785 Frebis Av.	NO	Cannot burn solid fuels
Coshocton	Stone Container Corp.	500 N. 4th St.	NO	Worried about env. issues.
Dayton	Howard Paper Mills, Inc.	115 Columbia St.	NO	Never considered burning tires
Franklin	Cheney Pulp & Paper Co.	P.O. Box 215	NO	Cannot burn solid fuels
Franklin	Franklin Boxboard Corp.	50 E. 6th St.	NO	Cannot burn solid fuels
Franklin	Georgia-Pacific Corp.	125 No. River St.	NO	Cannot burn solid fuels
Franklin	IKO Industries	1200 S. Main ST.	NO	Cannot burn solid fuels
Gypsum	USG Industries, Inc.	NL	NO	Too much modif. in fuel feed syst. req
Hamilton	The Beckett Paper Co.	400 Dayton St.	NO	Cannot burn solid fuels
Hamilton	Champion International	601 North B St.	NO	Permitting is concern.
Lancaster	Sonoco Products Co.	831 S. Columbus St.	NO	Have not considered burning tires at this time
Lockland	Erving Paper Mills	NL	-	Paper Mill is idle
Lockland	Jefferson Smurfit Corp./Container Corp. of America	S. Cooper Av.	NO	Fuel feed system is not right. Have pulverized boiler.
Massillon	Cleaners Hanger Co.	670 17th ST. NW	NO	Cannot burn solid fuels
Massillon	Greif Board Corp	9420 Warmington St.		Unable to contact.
Middletown	Crystal Tissue Co.	3120 S. Verity Pkwy.	NO	Fuel feed system is not right.
Middletown	Middletown Paperboard Co.	427 Vandervoer St.	NO	Cannot burn solid fuels
Middletown	Packaging Corp. of America	806 Centeral Av.	-	Paper Mill is idle
Middletown	Simpson Paper Co.	S. Main St.	NO	Closed down.
Middletown	Jefferson Smurfit Corp./Container Corp. of America	407 Charles St.	NO	Has not considered. Set up to burn coal only.
Middletown	Sorg Paper Co.	901 Manchester Av.	NO	Needs pulverized coal.
Munroe Falls	Sonoco Products Co.	59 N. Main St.	NO	Cannot burn solid fuels
Rittman	Packaging Corp. of America	100 Industrial Av.	NO	Has contemplated only.
Toronto	Valley Converting Co.	405 Daniels St.	NO	Cannot burn solid fuels
Urbana	Howard Paper Mills, Inc.	W. Church St.	NO	Never considered.
West Carrollton	Appleton Papers, Inc.	P.O. Box 68		Unable to contact.
West Carrollton	Miami Paper Corp.	P.O. Box 66	NO	Too much modif. and permitting req.

NL - NOT LISTED

(From Lockwood-Post's Directory, 1991)

TABLE 7–3

TIRE FEED RATES FOR TEST BURNS AT
THE OHIO EDISON TORONTO PLANT

DAY	TIRE FEED RATE	FUEL COMPOSITION	
		COAL	TIRES
1	NONE (BASELINE)	100	0
2	1 PER 34 SECONDS	95	5
3	1 PER 17 SECONDS	90	10
4	1 PER 11.3 SECONDS	85	15
5	1 PER 8.5 SECONDS	80	20

(From Horvath, 1991)

TABLE 7–4

EMISSION RATES DURING THE OHIO EDISON TIRE BURN TEST

POLLUTANT	DAY 1	DAY 2	DAY 3	DAY 4	DAY 5	PERMIT LIMIT (lb/MBtu)
SO_2	5.30	5.73	5.71	5.47	5.34	8.10
NOx	0.601	0.57	0.436	0.443	0.387	NONE
PARTICULATE MATTER	0.0631	0.0717	0.0564	0.0815	0.0453	0.10
LEAD	0.0000963	0.0000993	0.0000963	0.0000966	0.0000912	NONE

All emission rates measured in lbs/MBtu

(From Horvath, 1991)

TABLE 7–5

TIRE BURN BOTTOM ASH TRANSPORT WATER
DISSOLVED METALS ANALYSIS *
OHIO EDISON TORONTO PLANT

PARAMETERS	DRINKING WATER LIMITS	DAY 1 0% TIRES AS FUEL	DAY 2 5% TIRES AS FUEL	DAY 3 10% TIRES AS FUEL	DAY 4 15% TIRES AS FUEL	DAY 20% TI AS FU
ARSENIC	0.05	**ND	ND	ND	ND	
BARIUM	1	0.04	0.04	0.04	0.04	
CADMIUM	0.01	ND	ND	ND	ND	
CHROMIUM	0.05	ND	ND	ND	ND	
LEAD	0.05	ND	ND	ND	ND	
MERCURY	0.002	ND	ND	ND	ND	
SELENIUM	0.01	ND	ND	ND	ND	
SILVER	0.05	ND	ND	ND	ND	

* In mg/l
** ND – None Detected

(From Horvath, 1991)

TABLE 7–6

TIRE BURN BOTTOM ASH TRANSPORT WATER TOTAL METALS ANALYSIS * OHIO EDISON TORONTO PLANT

PARAMETERS	DRINKING WATER LIMITS	DAY 1 0% TIRES AS FUEL	DAY 2 5% TIRES AS FUEL	DAY 3 10% TIRES AS FUEL	DAY 4 15% TIRES AS FUEL	DAY 5 20% TIRES AS FUEL
ARSENIC	0.05	**ND	ND	ND	ND	ND
BARIUM	1	0.05	0.04	0.05	0.04	0.04
CADMIUM	0.01	ND	ND	ND	ND	ND
CHROMIUM	0.05	0.04	ND	0.05	ND	ND
LEAD	0.05	ND	ND	ND	ND	ND
MERCURY	0.002	ND	ND	ND	ND	ND
SELENIUM	0.01	ND	ND	ND	ND	ND
SILVER	0.05	ND	ND	ND	ND	ND

* In mg/l
** ND – None Detected

(From Horvath, 1991)

SCRAP TIRE USE

PANY NAME: Willamette Industries
T NAME: Albany Paper Mill
RESS: P.O. Box 335
Albany OR 97321
NE NO.: (503) 926-2281
RONMENTAL ENGINEER/CONTACT: Chris Nygren

MENT KILNS: None (1) Hog Fuel Boiler
CITY OF EACH: 180,000 lb steam/hr
RATE OF EACH: 3,400 mBTU/day

TE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MUM TIRE PIECE: 2" x 4"
R FUELS: Hog Fuel (Wood Bark and Sawdust)
RE OF TOTAL FUEL: 28% by weight

UTION CONTROL EQUIPMENT:
Wet scrubber only

TINUOUS EMISSION MONITORING EQUIPMENT:
Opacity only now although

HANDLING REQUIREMENTS/MODIFICATIONS:
None, fed directly into the boiler with the fuel

TE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

MISSION DATA:

Zinc levels in our primary sludge treatment is a concern. No other problems have been noticed.

AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?
No limits were changed but now the amount of tires burned must be reported

270

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: UNIROYAL GOODRICH *
PLANT NAME: EAU CLAIRE
ADDRESS: 799 WISCONSIN ST.
EAU CLAIRE, WI 54703
PHONE NO.: (715) 836-6200
ENVIRONMENTAL ENGINEER/CONTACT: BILL HABLE -PROCESSING
JOHN GLENZ - ENG. MGR. OF PLANT
OF BOILERS: 1 BURNING TIRES - STOKER TYPE
CAPACITY OF EACH:
HEAT RATE OF EACH 100,000 LB/HR - MAX

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

(SHREDDED) WHOLE SLIT

MAXIMUM TIRE PIECE: 3 SQ. INCH
OTHER FUELS: COAL - LOW S, HIGH BTU EASTERN COAL
% TIRE OF TOTAL FUEL: 5%

POLLUTION CONTROL EQUIPMENT:
PARTICLE COLLECTORS ON STACK (NO ESPs)

CONTINUOUS EMISSION MONITORING EQUIPMENT:
O_2

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
NEED EVEN DISTRIBUTION OF TIRE AND COAL
UNDERFED STOKERS

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:
INTERNAL SUPPLY - MAKES TIRES AT SITE, SCRAP BAD TIRES

ANY COMBUSTION/OPERATING PROBLEM: YES ____ NO X
IF YES, PLEASE EXPLAIN: WIRES STICKING OUT OF TIRES CAN PLUG
STOKERS WITH BASD SHREDS, NO PROBLEMS WITH GOOD SHREDS

AIR EMISSION DATA:
NO PREVIOUS TESTING ON COAL - HIGH EMISSION RATES MAY BE DUE TO COAL, NOT RUBBER. ARSENIC IS PROBLEM (Limit-25 lb/hr, Test-70lb/hr) - NOT SURE IF DUE TO COAL OR RUBBER.

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?

* Information obtained by phone.

1737-01-1

REV. 0, MARCH 22, 1991

SCRAP TIRE USE

ANY NAME: Willamette Industries
NAME: Albany Paper Mill
ESS: P.O. Box 335
Albany OR 97321
E NO.: (503) 926-2281
ONMENTAL ENGINEER/CONTACT: Chris Nyren

ENT KILNS: None (1) Hog Fuel Boiler
CITY OF EACH: 180,000 lb steam/hr
RATE OF EACH: 3,400 mBTU/day

E TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

IUM TIRE PIECE: 2" x 4"
R FUELS: Hog Fuel (Wood Bark and Sawdust)
E OF TOTAL FUEL: 2% by weight

ITION CONTROL EQUIPMENT:
Wet scrubber only

NUOUS EMISSION MONITORING EQUIPMENT:
Opacity meter only now although

HANDLING REQUIREMENTS/MODIFICATIONS:
None, fed directly into the boiler with the fuel

E TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

MISSION DATA:

Zinc levels in our primary sludge treatment is a concern. No other problems have been noticed.

AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?
No limits were changed but now the amount of tires burned must be reported

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: UNIROYAL GOODRICH *
PLANT NAME: EAU CLAIRE
ADDRESS: 799 WISCONSIN ST.
EAU CLAIRE, WI 54703
PHONE NO.: (715) 836-6200
ENVIRONMENTAL ENGINEER/CONTACT: BILL HABLE -PROCESSING
JOHN GLENZ - ENG. MGR. OF PLANT
OF BOILERS: 1 BURNING TIRES - STOKER TYPE
CAPACITY OF EACH:
HEAT RATE OF EACH 100,000 LB/HR - MAX

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

(SHREDDED) WHOLE SLIT

MAXIMUM TIRE PIECE: 3 SQ. INCH
OTHER FUELS: COAL - LOW S, HIGH BTU EASTERN COAL
% TIRE OF TOTAL FUEL: 5%

POLLUTION CONTROL EQUIPMENT:
PARTICLE COLLECTORS ON STACK (NO ESPs)

CONTINUOUS EMISSION MONITORING EQUIPMENT:
O_2

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
NEED EVEN DISTRIBUTION OF TIRE AND COAL
UNDERFED STOKERS

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:
INTERNAL SUPPLY - MAKES TIRES AT SITE, SCRAP BAD TIRES

ANY COMBUSTION/OPERATING PROBLEM: YES ____ NO X
IF YES, PLEASE EXPLAIN: WIRES STICKING OUT OF TIRES CAN PLUG STOKERS WITH BASD SHREDS, NO PROBLEMS WITH GOOD SHREDS

AIR EMISSION DATA:
NO PREVIOUS TESTING ON COAL - HIGH EMISSION RATES MAY BE DUE TO COAL, NOT RUBBER. ARSENIC IS PROBLEM (Limit-25 lb/hr, Test-70lb/hr) - NOT SURE IF DUE TO COAL OR RUBBER.

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?

* Information obtained by phone.

1737-01-1

REV. 0, MARCH 22, 1991

SCRAP TIRE USE

ANY NAME: Willamette Industries
NAME: Albany Paper Mill
ESS: P.O. Box 339
Albany OR 97321
E NO.: (503) 926-2281
ONMENTAL ENGINEER/CONTACT: Chris Nyren

ENT KILNS: None (1) Hog Fuel Boiler
CITY OF EACH: 180,000 lb steam/hr
RATE OF EACH: 3,400 mBTU/day

E TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

SHREDDED WHOLE SLIT

MUM TIRE PIECE: 2" x 4"
R FUELS: Hog Fuel (Wood Bark and Sawdust)
E OF TOTAL FUEL: 2% by weight

UTION CONTROL EQUIPMENT:
Wet scrubber only

INUOUS EMISSION MONITORING EQUIPMENT:
Opacity meter only now although

HANDLING REQUIREMENTS/MODIFICATIONS:
None, fed directly into the boiler with the fuel

E TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

COMBUSTION/OPERATING PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:

MISSION DATA:

Zinc levels in our primary sludge treatment is a concern ~~now~~. No other problems ~~were noted~~ have been noticed.

AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?
No limits were changed but now the amount of tires burned must be reported

QUESTIONNAIRE
SCRAP TIRE USE

COMPANY NAME: UNIROYAL GOODRICH *
PLANT NAME: EAU CLAIRE
ADDRESS: 799 WISCONSIN ST.
EAU CLAIRE, WI 54703
PHONE NO.: (715) 836-6200
ENVIRONMENTAL ENGINEER/CONTACT: BILL HABLE – PROCESSING
JOHN GLENZ – ENG. MGR. OF PLANT
OF BOILERS: 1 BURNING TIRES – STOKER TYPE
CAPACITY OF EACH:
HEAT RATE OF EACH 100,000 LB/HR – MAX

WASTE TIRE SPECIFICATIONS: (CIRCLE THOSE WHICH APPLY)

(SHREDDED) WHOLE SLIT

MAXIMUM TIRE PIECE: 3 SQ. INCH
OTHER FUELS: COAL – LOW S, HIGH BTU EASTERN COAL
% TIRE OF TOTAL FUEL: 5%

POLLUTION CONTROL EQUIPMENT:
PARTICLE COLLECTORS ON STACK (NO ESPs)

CONTINUOUS EMISSION MONITORING EQUIPMENT:
O_2

FUEL HANDLING REQUIREMENTS/MODIFICATIONS:
NEED EVEN DISTRIBUTION OF TIRE AND COAL
UNDERFED STOKERS

WASTE TIRE SUPPLY PROBLEMS? YES ____ NO X
IF YES, PLEASE EXPLAIN:
INTERNAL SUPPLY – MAKES TIRES AT SITE, SCRAP BAD TIRES

ANY COMBUSTION/OPERATING PROBLEM: YES ____ NO X
IF YES, PLEASE EXPLAIN: WIRES STICKING OUT OF TIRES CAN PLUG STOKERS WITH BASD SHREDS, NO PROBLEMS WITH GOOD SHREDS

AIR EMISSION DATA:
NO PREVIOUS TESTING ON COAL – HIGH EMISSION RATES MAY BE DUE TO COAL, NOT RUBBER. ARSENIC IS PROBLEM (Limit–25 lb/hr, Test–70lb/hr) – NOT SURE IF DUE TO COAL OR RUBBER.

WAS AN OPERATING PERMIT MODIFICATION REQUIRED FROM THE STATE REGULATORY AGENCY? YES X NO ____
IF YES, WHAT TYPE OF MODIFICATION?

* Information obtained by phone.

1737-01-1

REV. 0, MARCH 22, 1991


AKMENĖS CEMENTAS
Lietuvos Respublikos valstybinė įmonė
ŽMONĖS. METAI. DARBAS
ZEMENT VON AKMENĖ
Staatsunternehmen
Der Litauischen Republik
MENSCHEN. JAHRE. ARBEIT

Lietuvos Respublika - sena, iš naujo atgimstanti valstybė, gražus kraštas rytinėje Baltijos jūros pakrantėje. Čia derlingi laukai, žydri ežerai ir upės, nedideli tvarkingi miestai. Gyvena čia darbštūs ir nuoširdūs žmonės, svetingi savo šalies šeimininkai.

Tokia Lietuva po penkių inkorporavimo į buvusią TSRS deimtmečių grįžta į pasaulio tautų šeimą. Ji nori ir siekia pažinti pasaulį ir jame pritapti, siekia, kad ir pasaulis ją pažintų

Šis iliustruotas pasakojimas - apie vieną iš stambiausių ir stabiliausiai dirbančių Lietuvos statybinių medžiagų gamyklų - Akmenės valstybinę įmonę „Akmenės cementas", esančią pačioje Lietuvos šiaurėje.

Įmonės produkcija padėjo atstatyti po II Pasaulinio Karo sugriautą Lietuvos ūkį, įmonės žmonių darbas įamžintas ne tik Lietuvos, bet ir kitų kraštų miestų pastatuose, kaimų sodybose.

Lithuanian Republic is an old and beautiful state near the Baltic sea going through the period of rebirth. One can see fertile soil, blue lakes and rivers, small neat towns here. There live diligent and sincere people in Lithuania who are well known for their hospitality.

Lithuania is coming back to Europe and to the family of the world nations after fifty years of Soviet incorporation. It is eager to know the world and to find its place there. At the same time Lithuania wants the world to know it.

Here is s story about one of the largest Lithuanian plants of building materials - „Akmenė Cement". It is one of the most stable working plants, situated in Akmenė, in the north of Lithuania.

The plant's production helped too restore Lithuania after the 2nd World War. Its production can be seen not only in Lithuania but in other countries as well.

Litauische Republik ist ein alter neuerstehender Staat, ein schönes Land auf der östlicher Ostseeksüte. Fruchtbare Felder himmelblaue Seen und Flüsse, kleine, ordentliche Städte. Hier leben fleissige und herzliche Menschen, tüchtige Gastgeber.

Nach fünf Inkorporationsjahrzehnten in die ehemalige SU kehrt also das Litauen in Freieuropa und in die Familie der Weltvölker zurück. Es strebt nach Welterkenntnis, wünscht sich in sie einzuschalien, strebt nach Weltanerkennung.

Diese illustrierte Erzählung stellt einen der grössten und stabilsten Baumaterialienbetriebe Litauens vor - Akmenėer Staatsunternehmen „Zement von Akmenė", das sich im Norden Litauens befindet.

Betriebsproduktion trug zum Aufbau der zerstörten Volkswirtschaft Litauens nach dem 2. Weltkrieg bei. Tätigkeit der Fabrikarbeiter wurde nicht nur in Litauen, sondern auch in Stadtgebäuden und Bauernhöfen anderer Regionen verewigt.

211



CEMENTAS PASAULYJE

vienas kraštas negali išsiversti statybų. Kuo statybos sudėtinės, tuo patikimesnių reikia mujų medžiagų. ypač aštriai problemą iškėlė spartėjanti lizacijos raida, poreikis statylidelius tvirtus tiltus, pastatus engimus vandenyje.

III a. Anglijoje iš molingų ačių (mergelio) imta degti raulines kalkes. 1796 m. lų technikas Parkeris atrado lą iš mergelio gaminti cemen- 1824 m. tas pats išradėjas, štoje temperatūroje degdas klinčių ir molio mišinį, panino naują rišamąją džiagą, spalva primenančią tlando provincijos uolienas, avadino ją portlandcemen- Jo gamyba greitai plito Ange ir Prancūzijoje, o nuo 1856 - ir kitose Vakarų Europos tybėse, Rusijoje, JAV.

XX a. pradžios cementas - biausia ir plačiausiai nau-

CEMENT IN THE WORLD

No land can exist without constructions. The more complicated the construction, the more reliable materials it demands. The development of civilazition showed how acute this problem was in building bridges, houses and construction in the water.

In 18 c. in England hydraulic lime was made from marl. In 1796 the English technician Parker discovered how to make cement from marl. In 1824 the same inventor made a new binding material, burning clay and limestone at very high temperature. The new material was called portlandcement because its colour reminded of the rocks in the province of Portland. Its production was rapidly spreading in England and France. Since 1856 it has been produced in Western

ZEMENT IN DER WELT

Kein Land kann ohne Bau auskommen. Je komplizierter der Bau, desto zuverlässigere Bindemittel werden gebraucht. Mit der intensiven Zivilisationsentwicklung, dem Bedürfniss nach Bau von grossen und festen Brücken, Gebäuden und Einrichtungen im Wasser tauchte dieses Problem besonders scharf auf.

Im 18. Jahrhundert begann man in England aus kalkhaltigen Tonen (Mergel) hydraulische Kalke zu brennen. 1726 hat der englische Techniker Parker Zementherstellungsmethode aus Mergel gefunden. 1824 erzeugte derselbe Erfinder durch Brennen der Mischung von Kalkstein und Ton ein neues Bindemittel, das den Gesteinen der Provinz Portland ähnelt, und nannte es Portlandzement. Seine Herstellung verbreitete sich rasch in England und Frakreich, vom Jahre 1856 auch in anderen Ländern Westeuropas, Russland, USA.



dojama rišamoji statybų medžiaga. 1929 m. pasaulyje jo pagaminta 68 mln. t.
Cemento gamyba didžiausiose pasaulio valstybėse
1990 m. (mln.t)

Kinija	*203,O*
TSRS	*137,3*
JAV	*75,5*
Japonija	*84,45*
Italija	*41,69*
VFR	*39,26*
Prancūzija	*26,98*
Didžioji Britanija	*14,O*

CEMENTAS LIETUVOJE

Grupė Lietuvos verslininkų 1912 m. įkūrė „Lietuvos portlandcemento bendrovę". Jos įgaliotas inžinierius ir mokslininkas P.Jodelė suprojektavo ir savo žemėje, tarp Varėnos ir Valkininkų, pastatė fabriką, kuris 1914 m. iš čia kasamų kreidos ir molio pradėjo gaminti cementą. Pirmojo pasaulinio karo metais

Europian countries and in Russia as well as in the USA.
Since the beginning of the 20 c. cement has been one of the main and most used binding materials. In 1929 the world produced 68 milion tons of cement.
The production of cement in the largest countries of the world in 1990 (mln. t.)

China	*203,0*
USSR	*137,3*
USA	*75,5*
Japan	*84,45*
Italy	*41,69*
GFR	*30,26*
France	*26,98*
Great Britain	*14,0*

CEMENT IN LITHUANIA

In 1912 a group of Lithuania businessmen founded the company „Lithuanian portlandcement". It supported P. Jodelė, an engineer and

Vom Anfang des 20. Janhrhunderts ist Zement das Wichtigste und gebräuchlichste Bindemitte im Bau. 1929 wurden 68 Mill. Zement in der Welt hergestellt.
Zementherstellung in den grössten Staaten der Welt
i.J. 1990 (mill. t)

SU	*137,3*
USA	*75,5*
Japan	*84,45*
Italien	*41,69*
BRD	*30,26*
Frankreich	*26,98*
China	*203,0*
Grossbritanien	*14,0*

ZEMENT IN LITAUEN

Eine Gruppe von litauischen Unternehmern grundete 1912 „Gesellschaft des Portlandzements Litauens". Ihre Vertrauensperson Ingenieur und Wissenschaftler P. Jodelė projektierte und baute in seinem Heimatland, zwischen Varėna und Druskininkai, eine Fabrik, in der

onė buvo sugriauta, įrengimai aikinti.

priklausoma Lietuvos Respublika 1918-1940 m. cementą portuodavo iš Didžiosios Britanijos, Belgijos, Danijos, Latvi-, Norvegijos, TSRS bei kietijos.

mento įvežimas Lietuvos spubiikoje (tūkst. t.)

26 m.	31
28 m.	47
38 m.	124

mento gamyklos statybos usimas ne kartą keltas 1930 940 metais, bet Lietuvos Respublika stokojo tam lėšų, o užnio firmos, bręstant II sauliniam Karui, nesiryžo intuoti Lietuvoje kapitalo. Vis o 1940 m. pradėtas statyti nento fabrikas ties Skirsne-ne, bet prasidėjęs karas staty- nutraukė. Diskutuota ir imybė statyti cemento gamyk- Akmenės apylinkėse, kur jau o išžvalgyti dideli klinčių klo-.

siritus į Vakarus II Pasauli- Karo bangai, iškilo reikalas greičiau atstatyti sugriautą . Griuvėsiais buvo paversti gelis miestų ir miestelių, ga- klų ir fabrikų. Lietuvą vėl pavusios TSRS partinė ir tybinė valdžia ieškojo gali- bių Pabaltijo ir Baltarusijos ir iningrado srities atstatymui ientą gaminti čia pat, panau- nt gausius darbo jėgos iš- ius.

dydama centrinės valdžios ktyvas, tuometinė Lietuvos

scientist, who on his own piece of land between the towns of Varėna and Valkininkai, built a factory which produced cement from local chalk and clay. During the 1st World War this factory was destroyeted.

Independent lithuanian Republic imported cement from Great Britain, Belgium, Denmark, Latvia, Norway, USSR and Germany in the period of 1918 - 1940.

Import of cement to Lithunia (thousand tons)

In 1926 31
In 1928 47
In 1938 124

The guestion of building a cement plant was discussed several times in 1930 - 1940, but Lithuanian Republic was poor and couldn't afford it, and foreign firms didn't risk to invest their money on the verge of the 2th World War. In 1940 the construction of a cement plant near Skirsnemunė began, but the war stopped it. There began a discussion about building a cement plant in Akmenė district, because huge resources of limestone had been explored there.

The wave of the war moving to the West, there arose a great demand to restore the devasted aconomy. A number of towns, factories and plants became ruins. The occupant power of the USSR in Lithuania wanted to produce cement using cheap

man 1914 aus den hiesigen Ton und Kreide die Zementherstellung begann. In den Jahren des 1. Weltkriegs wurde der Betrieb zerstort, die Einrichtugengen vernichtet.

1918-1940 importierte die unabhangige Litauische Republik Zement aus Grossbritanien, Belgien, Danemark, Lettland, Norwegen, SU und Deutschland.

Zementeinfuhr in der Litauischen Republik (tausend t)

i. J. 1926 31
i. J. 1928 47
i. J. 1938 124

Die Frage eines Zementbetriebsbaus wurde mehrmals in den Jahren 1930-1940 aufgeworfen, Litauische Republik aber empfand Bedurfniss nach den Geldmitteln und auslandische Firmen konnten sich nicht entschliessen, ihr Kapital in Litauen anzulegen, indem der 2. Weltkrieg heranreifte. 1940 wurde immeerhin der Bau eines Zementbetriebs bei Skirsnemunė begonnen, der Krieg aber hatte den Bau unterbrochen. Besprochen wurde auch die Moglichkeit einen Betrieb in der Umgebung Akmenė zu bauen, wo grosse Kalksteinschichten gefunden wurden.

Nach dem 2. Weltkrieg entstand das Bedurfniss so schnel wie moglich die zerstorte Wirtschaft wiederherzustellen. Der Krieg hinterliess d meisten Stadte und Stadt Betriebe und Fabriken in inen. Besatzungsbehorden der USSR suchten nach Moglichkeiten,



SR liaudies komisarų taryba 945 m. liepos 27 d. priėmė nu-rimą statyti Lietuvoje cemento mykląą. Statybai šį kartą pasi-ktas Akmenės regionas, ku-me jau buvo ištirti gausūs mento gamybai tinkamų klin-ų ir molio klodai. Pirmąjį pro-ktą rengė Leningrado stitutas „Giprocement". 1947 pradėti statybos darbai. Pir-oji cemento gamybos techno-ginė linija paleista 1952 m. gsėjo 20 d.

LIETUVOS RESPUBLIKOS VALSTYBINĖ ĮMONĖ „AKMENĖS CEMENTAS"

Iš įmonės vizitinės kortelės

rendimas pradėti statybą: 945 m. liepos 27 d.
ojektavimo pradžia: 1946 m. gsėjo 11 d.
atybos darbų pradžia: 1947 m.
kurta pirmoji sukamoji kros-s: 1952 m. rugsėjo 20 d.

ĮMONĖS DIREKTORIAI

tinas JURAGA (1947 - 1949)
vlas PURMALIS (1949 - 951)
onidas ZASEDATELIS 951 - 1954)
eksandras ANDROSOVAS 954 - 1956)
ktoras MARKEVIČIUS 956 - 1959)
eksandras SPUDULIS (1959 962)
opoldas PETRAVIČIUS 962 - 1990)
nonas Vytis ANUŽIS (nuo 90)

labour force, whish was wery necessary not only for rebuilding Lithuanian towns, but other republics as well.
Under the directions of central power, the Comissars' Soviet of Lithuanian SSR issude an order to build a cement plant. It was decided to choose Akmenė district, as it was rich in limestone and clay that was good for making cement. The first project was made by institution „Giprocement" in Leningrad. In 1947 the construction of plant was started. The first technological line of cement production began to operate on September 20, 1952.

LITHUANIAN STATE PLANT „AKMENĖ CEMENT"

Important data:

The decision to build the plant: July 27,1945
The beginning of the project: September 11, 1946
The beginnig of construction: 1947
The first rotating kiln started to work: September 20, 1952

MANAGERS OF THE PLANT

Justinas JURAGA (1947-1949)
Pavlas PURMALIS (1949-1951)
Leonidas ZASEDATELIS (1951-1954)
Aleksandras ANDROSOVAS (1954-1956)
Viktoras MARKEVIČIUS (1956-1959)
Aleksandras SPUDULIS (1959-1962)

Baltikum, Belorussland und Gebiet Kaliningrad mit Hilfe der Zementherstellung an Ort und Stelle Verwedung der ergiebigen Arbeitskrafte aufzubauen.
Der damalige Rat der Volkskommissare der Litauischen SSR hielt sich an die Richtlinien der Zentralregierung und fasste den Beschluss, einen Zementherstellungsbetrieb in Litauen zu bauen. Fur den Bau wurde Gebiet Akmenė gewahlt, wo grosse fur Zementherstellung notige Kalkstein-und Tonschichten gefunden wurden. Den ersten Bauentwurf machte das Institut „Giprocement" von Lenengrad. 1947 begannen die Bauarbeiten. Die erste technologische Linie der Zementherstellung wurde am 20. September 1952 in Betrieb gesetzt.

STAATSUNTERNEHMEN DER LITAUISCHEN REPUBLIK

„ZEMENT VON AKMENĖ"

Aus der Visitenkarte des Unternehmens:
Beschluss zum Baubeginn: der 27. Juli 1945
Projektierungsanfang: der 11. September 1946
Anfang der Bauarbeiten: 1947
Der 1. Drehrohrofen in Betrieb gesetzt: am 20. September 1952

DIREKTOREN DES UNTERNEHMENS

Ustinas JURAGA (1947-1949)
Pavlas PURMALIS (1949-1951)
Leonidas ZASEDATELIS (1951-1954)



STEBĖTOJŲ TARYBA

Išrinkta 1990 m. gruodžio 27 d.
Stebėtojų tarybos pirmininkas
Valerijus ZAVJALOVAS
sekretorius Klemas RIMUTIS
nariai Dalia BINKULIENĖ
Vytautas Jonas BORUSEVIČIUS
Edmundas DIMITREVIČIUS
Edmundas KRIPAS
Julius UŠPARAS

DIREKTORIŲ VALDYBA

Patvirtinta 1991 m. sausio 29 d.

Simonas Vytis ANUŽIS - direktorius, valdybos pirmininkas
Vincas MONTVILA - direktorius pavaduotojas, valdybos narys
Leopoldas PETRAVIČIUS (1962-1990)
Simonas Vytis ANUŽIS (since 1990)

SUPERVISORS COUNCIL

Elected on December 27, 1990.
The head of the council
Valerijus Zavjalovas
Secretary Klemas Rimutis
Members Dalia Binkulienė
Jonas Borusevičius
Eimundas Dimitrevičius
Julius Užparas

THE COUNCIL OF MANAGERS

Aproved on January 29, 1991
Simonas Vytis Anužis - manager, the head of the council
Aleksandras ANDROSO
(1954-1956)
Viktoras MARKEVIČ
(1956-1959)
Aleksandras SPUDULIS (
1962)
Leopoldas PETRAVIČ
(1962-1990)
Simonas Vytis ANUŽIS /AI
HIS/ (vom 1990 an)

AUFSICHTSRAT

Am 27. Dezember 1990 gew
Vorsitzende des Aufsichts
Valerijus ZAVJALOVAS
Sekretär Klemas RIMUTIS
Müglieder Dalia BINKULI
Vytautas Jonas BORUS
ČIUS
Edmundas DIMITREVIČI















lbinas KLIMAS - direktorius avaduotojas, valdybos narys
)lius DANYLA - direktoriaus avaduotojas, valdybos narys
:omualdas NORKUS - direkto-'aus pavaduotojas, valdybos arys
lgimantas MITUZAS - vyriau-asis inžinierius, valdybos narys

Valstybinėje įmonėje „Akmenės cementas"

ıgaminta 1991 m.:
'mento - 3125,5 tūkst. tonų,
ınguoto šiferio (asbestcemen-o) - 695O1 tūkst. sutartinių kštų,
·bestcementinių vamzdžių (su-rtinio diametro) - 1885,2 km.

Vincas Montvila - assistant manager, council member
Albinas Klimas - assistant manager, council member
Olius Danyla - assistant manager, council member
Romualdas Norkus - assistant manager, council member
Algimantas Mituzas - chief engineer, council member
The state plant „Akmenė Cement" produced in 1991:
cement - 3125,5 thousand tons
ruffled slate (asbestos cement) - 69501 thousand leaves
pipes made of asbestos cement (set diameter) - 1885,2 km

Edmundas KRIPAS
Julius UŠPARAS

DIREKTORIUM

Am 29. Januar 1991 bestätigt.
Simonas Vytis ANUŽIS - der Direktor, Vorsitzende des Direktoriums
Vincas MONTVILA - der stellvertretende Direktor, Mitglied des Direktoriums
Albinas KLIMAS - der stellvertretende Direktor, Mitglied des Direktoriums
Olius DANYLA - der stellvertretende Direktor, Mitglied des Direktoriums

PAGRINDINIAI GAMYBOS PADALINIAI

1-OJI CEMENTO GAMYKLA: 4 sukamosios krosnys. Gamykloje yra trupinimo ir rūšiavimo bei pakavimo skyriai, žaliavų, degimo, malimo, dulkių surinkimo, mechaninis, elektros, remonto ir statybos, laboratorijos cechai.

Gamykloje dirba 778 žmonės, iš jų 700 darbininkų, 78 specialistai, meistrai vadovai.

1991 m. pagaminta:

portlandcemenčio M400 - 149000 t,

greit kietėjančio portlandcemenčio M400 - 430000 t,

smėlinio portlandcemenčio - 143000 t,

cemento kelių dangai - 39000 t.

2-OJI CEMENTO GAMYKLA: 4 didžiosios (185 m. ilgio, 5 m. diametro) sukamosios krosnys. Gamykloje 3 barai - degimo, malimo, energetikos. Dirba 405 žmonės, iš jų 373 darbininkai, 32 vadovai, specialistai, meistrai.

1991 m. pagaminta:

portlandcemenčio M400 - 125000 t,

greit kietėjančio portlandcemenčio M400 - 1634000 t,

M500 - 605000 t.

ASBESTCEMENČIO GAMYKLA: dirba 293 žmonės, iš jų 271 darbininkas, 22 specialistai, meistrai ir vadovai.

Gamina: banguotus asbestcemenčio (šiferio) lakštus (1750x1130x5,8 mm), įvairaus diametro asbestcementinius vamzdžius ir movas slėginiams ir beslėgiams vamzdynams.

THE MAIN PRODUCING SECTION

CEMENT PLANT 1: 4 rotatory kilns. In the plant there are crushing, sorting and packing devisions, raw materials, burning, milling, dust collecting, mechanical, electric, repair building, laboratory departments.

There work 778 people at the plant, 700 are workers, the rest 78 are specialists, masters and chiefs.

In 1991 it produced:

portlandcement M400 - 149000 t

fast hardening portlandcement M400 - 430000 t

sand portlandcement - 143000 t

cement for road cover - 39000 t.

CEMENT PLANT 2: 4 big (185 m. long, 5 m. diameter) rotatory kiln. There are 3 sections - burning, grinding, energetics. There work 405 people - 373 workers, 32 chiefs, specialists, masters.

ASBESTOS CEMENT PLANT: there work 293 people 271 workers, 22 specialists, amsters and chiefs.

It produces:

ruffled asbestos cement (slate) leaves (1750x130x5,8 mm)

pipes and cluthces of variuos diameter made of asbestos cement for using under pressure and without pressure.

RAW MATERIALS AND THEIR PROVIDERS

Data of 1991

Limestone (local pit Karpėnai) - 4321,7 th. t

Romualdas NORKUS - der st lvertretende Direktor, Mitgli des Direktoriums

Algimantas MITUZAS - a Chefingenieur, Mitglied des I rektoriums

Produktion des Staatsunterne mens „Zement von Akmenė" i. J. 1991

Zement - 3125,5 tausend t,

Wellschiefer (Asbestzement) 69501 tausend Vertragsplatten

Asbestzementröhren (im ve raglichen Durchmesser) - 1885 km.

HAUPTUNTERABTEILUNGI

Der 1. Zementbetrieb: 4 Drel rohröfen. Im Betrieb sinc Zerkrümelung-, Sortier-un Verpackungsabteilungen, Rol stoff-, Brenn-, Mühl-, Staul sammlung-, Maschinen Elektro-, Reparatur-und Bau Laborabteilungen.

Beschäftigtenzahl: 778 (700 sin Arbeiter, 78 sind Fachleut Werkmeister, Leiter)

Herstellungsprogramm i. 1991:

Portlandzement M400 - 149000 schnell verhärtender Portlandze ment M 400 - 430000 t,

Sandportlandzement - 143000 Zement fur Strassenbelag 39000 t.

Der 2.Zementbetrieb: 4 Rie sendrehrohrofen (185 m lang, m Diameter). Im Betrieb gibt e Brenn-, Mühl-und Energiepro duktionsbereiche. 405 Leut sind beschaftigt, 373 unter ihne sind Arbeiter, 32 Leiter, Fach leute, Werkmeister.

ŽALIAVOS IR JŲ TIEKĖJAI

1991 m. duomenys
Klintys (vietinis Karpėnų karjeras) - 4321,7 tūkst. t;
Molis (Šaltiškių molio karjeras) - 1315,8 tūkst. t;
Gipsas (Sauriešo kasykla Latvijoje) - 5 tūkst. t;
Pirito degenos (Kingisepo gamybinis susivienijimas „Fosforit") - 70,3 tūkst. t;
Opoka (Stoniškių karjeras) - 46,6 tūkst. t;
Fosfogipsas (Kėdainių chemijos gamykla) - 52,1 tūkst. t;
Fosfogipsas (Gomelio chemijos kombinatas Baltarusijoje) - 23,8 tūkst. t.

KURO IR ENERGIJOS ŠALTINIAI

1991 m. duomenys
Mazutas (pagrindinė tiekėja - Mažeikių naftos perdirbimo gonė) - 469,2 tūkst. t,
Gamtinės dujos (gamybinei kalinei) - 54776 tūkst. kub. m,
Elektros energija (gaunama 2 maitinimo 110 kv linijomis iš Lietuvos energtinės sistemos) - 97257 mln kWh,
Mazuto ūkį aptarnauja 28 Darbuotojai.

AUTOTRANSPORTO ŪKIS

Gonė turi 146 įvairių markių ir paskirties automašinas, iš jų 76 krovinvartes, 14 autobusų.
1991 m. pervežta 5353 tūkst. krovinių. Autotransporto ūkį aptarnauja 105 darbuotojai.

GELEŽINKELIO ŪKIS

Geležinkeliu 1991 m. išsiųsta:
Clay (Šaltiškiai clay pit) - 1315,8 th. t
Gyps (Siauries pit in Latvia) - 5 th. t
Pyrite (Kingisisep plant „Phosphorite") - 70,3 th. t
Opoka (Staniškiai pit) - 46,6 th .t
Phosphogyps (Kėdainiai chemical plant) - 52, 1 th. t
Phosphogyps (Gomel chemical plant in Bielorussia) - 23,8 th. t

SOURCES OF FUEL AND ENERGY

Data of 1991
Oil (the main provider is Mažeikiai oil plant) - 469,2 th. t
Natural gas (for boilers) - 54776 th. cubic m.
Electric energy (it comes in 2 lines 110 kV from Lithuanain energetic system) - 397257 mln. kwh
28 workers are in charge of oil.

MOTOR TRANSPORT SERVICE

The plant possesses 146 vehicles of all kinds, among them - 76 trucks, 14 buses.
1991 they caried 5353, 1 th. t of load. 105 workers are in charge of transport service.

RAILWAY

In 1991 there were sent by railway: 44732 carriages of cement (among them 1645 carriages were exported), 972 cariages with slate, 1258 carriages with asbestos cement pipes. The plant has 11 steam engines. 287 workers are in charge of railway.

Heerstellungsprogramm i.J. 1991:
Portlandzement M 400 - 125000 t,
schell verhartender Portlandzement M 400 - 1634000 t,
M 500 - 605000 t.
Asbestzementbetrieb:
Beschäftigtenzahl 293 (271 Arbeiter, 22 Fachleute, Werkmeister, Leiter)
Produktion:
Wellschieferplatten (Asbestzement) (1750x1130x5,8 mm)
Asbestzementröhren und-muffen mit unterschiedlichem Durchmesser für Druck-und drucklose Leitung.

ROHSTOFFE UND LIEFERANTEN

Angaben fürs Jahr 1991
Kalkstein (hiesige Kalksteingrube von Karpenai) - 4321,7 tausend t,
Ton (Tongrube von Šaltiškiai) - 1315,8 tausend t,
Piritushorst (Produktionsvereinigung „Fosforit" von Kingisep) - 70,3 tausend t,
Kieselkalkton (Grube von Stoniškiai) - 46,6 tausend t,
Fosfogips (Chemiewerk von Kėdainiai) - 52,1 tausend t,
Fosfogips (Chemiewerk von Gomel in Belorussland) - 23,8 tausend t.

BRENNSTOFF-UND ENERGIEQUELLEN

Angaben fürs 1991
Masut (Hauptanlieferer-Erdölraffinerie von Mažeikiai) - 469,2 tausend t,





44732 vagonai cemento (tame tarpe 1645 vagonai - eksportui), 972 vagonai šiferio, 1258 vagonai asbestcementinių vamzdžių. Įmonė turi 11 šilumvežių. Geležinkelio ūkį aptarnauja 287 darbuotojai.

ŠILUMOS ŪKIS

Per metus įmonė pagamina 419 tūkst. gigakalorijų šilumos.
Asbestcementčio gamyklai ir valstybinei gelžbetonio įmonei „Karpėnai" 1991 m. patiekta 66,9 tūkst. Gcal garo.
Karšto vandens 16000 Gcal sunaudota įmonėje. Naujosios Akemenės miestui patiekta 66,4 Gcal šilumos (šildymas ir karštas vanduo).

VANDENS ŪKIS

Technologinėms reikmėms 1991 m. sunaudota 2622 tūkst. kubinių metrų vandens iš Agluonos upės ir 1333 tūkst. kubinių metrų - iš Sablauskių tvenkinio.

THERMAL SERVICE

Every year the plant produces 419 thousand Gcal of heat. In 1991 the plant of asbestos cement and the state concentrate plant „Karpėnai" recieved 66,9 Gcal of steam.
The plant consumed 16000 Gcal of hot water. It supplies the town of Naujoji Akmenė with 66,4 Gcal of heat (heating and hot water).

WATER SUPPLY

In 1991 technological processes demanded 2622 th cubic metres of water that came from the river Agluona and from the Sablauskiai pond.
The area of Sablauskiai pond is 123,8 ha, its size is 2 mln cubic metres.
Drinking water supplies reach 3044 th cubic metres per year. In 1991 the town of Naujoji Akmenė got 3021 th cubic metres of drinking water.

Erdgas (für den Betriebskesselraum) - 54776 tausend Kubikmeter,
Elektroenergie (Versorgung durch zwei 110-kv-Leitungen vom Verbundsysthem Litauens) - 397257 kwh.
Masutwirtschaft wird von 28 Werktätigen bedient.

TRANSPORTWESEN

Das Unternehmen verfüng über 146 verschiedenartige Kraftfahrzeuge, darunter 76 Kippautos 14 Autobusse.
Gütertransport fürs Jahr 1991: 5353,1 tausend t.
Beschäftigtenzahl 105.

EISENBAHNWESEN

Bahntransport im Jahre 1991: 44732 Güterwagen mit Zement (darunter 1645 Wagen zur Ausfuhr), 972 Güterwagenmit Schiefer, 1258 Güterwagen mit Asbestzementröhren. Das Unternehmen verfügt über 11 Die-



Sablauskių tvenkinio plotas 123,8 ha, tūris - 2 mln kubinių metrų.
Geriamo vandens verslovės pajėgumas 3044 tūkst. kubinių metrų per metus. 1991 m. Naujosios Akmenės miestui patiekta 3021 tūkst. kubinių metrų geriamo vandens.

EKOLOGINIS ŪKIS

Įmonės eksploatuojamų vandens valymo įrengimų pajėgumas 10 tūkst. kubinių metrų vandens per parą. Per metus išvaloma 2,5 mln kubinių metrų vandens.
Per metus sugaudoma 1125 tūkst. t klinkerio dulkių. Įrengti 22 elektros filtrai. Prie cemento malūnų, cemento ir klinkerio silosų bei pakavimo mašinų įrengti per 40 rankovinių filtrų. Sugaudytos dulkės grąžinamos į rotacinę krosnis

EKOLOGICAL SERVICE

The cleaning eguipment used by the plant has industral capacity of 2,5 mln cubic metres of water per year.
Every year 1125 th t of clinker dust is caught. There are 22 electric filters. There are over 40 sleevelike filters near the cement mills, cement and clinker silo, packing machines. The caught dust is turned back to the rotatory kilns.

TRAINING OF SPECIALISTS

Every year the state plant „Akmenė Cement" trains 200 new workers on average, 350 workers improve their qualifications, 2000 workers are tested anew. Every year about 100-120 engineers and technologists improve their qualifications in their professional sphere as well in safety engineering.

sellokomotiven, Beschäftigtenzahl 287.

WÄRMEWIRTSCHAFT

Jährliche Wärmeerzeugung: 419 Gcal.
Dampfanlieferung dem Asbestzementbetrieb und dem Staatsbetrieb „Karpėnai" i.J. 1991: 66,9 tausend Gcal.
Heisswassergebrauch: 16000 Gcal. Wärmeanlieferung für die Stadt Naujoji Akmenė: 66,4 Gcal Wärme (Heizung und Heisswasser).

WASSERWIRTSCHAFT

1991 hat man 2622 tausend m3 Wasser aus dem Fluss Agluona und 1333 tausend m3 Wasser aus dem Teich Sablauskiai für technologische Ziele gebraucht.
Der Teich Sablauskiai mit einer Fläche von 123,8 ha, Fassungsvermögen von 2 Mill.m3.
Kapazität der Wasserwirtschaft: 3044 tausend m3 pro Jahr. Anlieferung der Stadt Naujoji Ak-



DARBUOTOJŲ RENGIMAS IR MOKYMAS

Per metus valstybinėje įmonėje „Akmenės cementas" parengiama vidutiniškai po 200 naujų darbuotojų, kvalifikaciją pakelia 350 darbuotojų, peratestuojama 2000 darbuotojų. Kasmet 100-120 inžinerijos technikos darbuotojų pakelia profesinę kvalifikaciją, atnaujina ir pagilina saugumo technikos, darbo apsaugos žinias.

DARBO APSAUGOS SISTEMA

Kolektyvinė sutartis ir kiti susitarimai įmonės administraciją įpareigoja užtikrinti sveikas ir saugias darbo sąlygas. Sveikatai kenksmingiausi faktoriai yra vibracija, įrenginių triukšmas, dulkėtumas, aukšta temperatūra gamybos patalpose. Darbo saugos profilaktika, priežiūra, kontrole, darbuotojų konsultavimu ir medicininiu aptarnavimu rūpinasi įmonės darbo apsaugos ir saugumo technikos skyrius.

THE SYSTEM OF LABOUR PROTECTION

Collective and other agreements oblige the administration of the plant to garantee safe working conditions. The factors harmful for health are the following: vibration, noise, dust, high temperature in working places. The departament of labour protection is in charge of the workers medical check up, medical service, safe labour conditions and their control.

The workers of this departament measure the noise, vibration, dust, lighting, instruction workers on safe methods of work, check up the equipments in working places.

The rate of the worker's illnesses and professional diseases is stable. During the year every worker is ill for 10 days.

HEALT PROTECTION

The plant „Akmenė Cement" has created a reasonable health

menė i.J. 1991: 3021 tausend m3 Trinkwasser.

ÖKOLOGIEWIRTSCHAFT

Kapazität der Wassereinrichtungen für Reinigung: 10 tausend m3 Wasser pro Tag und Nacht. Jährlich wird 2,5 Mill.m3 Wasser gereinigt.

Jährlich wird 1125 tausend t Klinkerstaub aufgefangen. Es sind 22 Elektrofilter eingerichtet. An den Zementmühlen, Zement-und Klinkersilos, Verpackungsmaschinen sind mehr als 40 Ärmelfilter eingerichtet. Aufgefangener Staub wird in die Drehrohröfen zurückgegeben.

BESCHÄFTIGTENSCHULUNG

Jahrlich werden durchschnittlich 200 neue Arbeitstätige im staatlichen Unternehmen „Akmenės cementas" angelernt, 350 Beschäftigte weiterausgebildet, 2000 Werktätige umgeschult. Jährlich bekommen 100-120 Ingenieure und Techniker Weite-

yriaus darbuotojai tikrina ukšmo, vibracijos, dulkėtumo, švietimo parametrus darbo ıtose, rengia instruktažus ir ıgių darbo metodų mokymo siėmimus, kelimo ir šildymo ngimų eksploatavimo patikrinus bei kitas kontrolės priemes.

onėje stabilus bendrasis bei fesinis darbuotojų sergamus. Per metus vienas įmonės buotojas serga vidutiniškai dienų.

SVEIKATOS APSAUGA

onėje „Akmenės cementas" urta patogi ir visiems darbuoms prieinama sveikatos apgos sistema.

ioje įmonėje veikia sveikatos ktas. Jame pacientus aptarja gydytojas ir 6 medicinos onalo darbuotojai. Atliekavisos fizioterapinės proceos, injekcijos, veikia ıatologinis kabinetas.

josios Akmenės mieste veimonės sanatorija profilakumas. Čia ligonius maıja 34 darbuotojai, iš jų lytojai. Veikia fizioterapinis, o, vandens procedūrų skygydomosios fizkultūros, inacijų, stomatologinis ir edūrų kabinetai, yra poilsio lpos. 1991 m. sanatorija laktoriumas aptarnavo žmonių iš „Akmenės ceo" bei kitų miesto įmonių ir ų.

protection system, which is accessible to all the workers.

Health service operates at the very plant. A doctor and 6 nurses take care of the patients. All kinds of physiotherapic treatment, injections, stomatological service are available here.

The plant has a propohylactic sanatorium in the town of Naujoji Akmenė. 34 medical workers take care of patients here, among them there are 3 doctors. There one can find all sorts of procedures: physiotherapic, mud, water, gymnastics, inhalations. The prophylactic sanatorium in 1991 treated 1480 people from „Akmenė Cement" and from other enterprises.

CONDITIONS FOR WORKERS' REST AND REHABILITATION

For the worker's summer rest the plant „Akmenė Cement" has its own residence near the Baltic sea and in the health resort Druskininkai. There is a beautiful place for for weekends near the river Virvytė, 30 km from town of Naujoji Akmenė.

The plant has the places for rest in the following health resorts near the Baltic Sea:

In Palanga - 80 places

In Pervalka (Neringa) - 20 places

In rucava (Latvia) - 40 places

In healt resort Druskininkai 16 places

rausbildung, erneuern und vertiefen ihre Arbeitsschutzkenntnisse.

ARBEITSSCHUTZSYSTHEM

Vertrag der Belegschaft und andere Verabredungen verpflichten die Administration des Unternehmens gesunde und sichere Arbeitsbedingungen zu garantieren. Gesundheitschädlichste Faktoren sind Vibration, Einrichtungenlärm, Staubigkeit, hohe Temperatur in Betriebsraumen. Die Arbeitsschutzabteilung des Unternehmens sorgt für Sicherheitstechnikprophylaxe, - aufsich und - kontrolle, Beschäftigtenberatung und medizinische Betreuung.

Die Mitarbeiter der Abteilung prüfen Lärm-, Vibration-, Staubigkeits-, Beleuchtungsparameter an Arbeitsstellen, veranstalten Belehrungen, unterrichten in Betriebssicherheitsmethoden, kontrollieren den Hebe-und Heizeinrichtungenbetrieb u.a.

Stabile Allgemein-und Be, ıfsmorbidität der Beschäftigten. Jahrlich ist ein Arbeiter im Durchschnitt 10 Tage krank.

GESUNDHEITSSCHUTZ

Das Gesundheitsschutzsysthem des Unternehmens „Zement von Akmenė" ist bequem und für alle Arbeiter zugänglich.

Es funktioniert eine Sanitätsstelle. Da bedient die Patienten ein Arzt, ihm helfen 6 Mitarbeiter des Gesundheitswesens. Es werden alle Physiotherapieheilverfahren durchgeführt,

DARBUOTOJŲ POILSIO IR REABILITACIJOS SĄLYGOS

Darbuotojų vasaros poilsiui įmonė „Akmenės cementas" turi nuosavas bazes Baltijos pajūryje ir Druskininkų kurorte ir trumpam savaitgalio poilsiui - prie Virvytės upės, už 30 km nuo Naujosios Akmenės miesto.

Baltijos pajūryje veikia šios poilsio bazės:

Palangoje - 80 vietų,

Pervalkoje (Neringa) - 20 vietų,

Rucavoje (Latvija) - 40 vietų.

Poilsio bazė Druskininkų kurorte turi 16 vietų.

Trumpalaikio poilsio bazė „Virvytė" - 160 vietų.

Poilsio bazės veikia pamainomis nuo birželio 1 iki rugsėjo 1 d.

Aktyviai sportuojantiems įmonės darbuotojams bei jų šeimoms skirti „Akmenės cemento" sporto rūmai. Juose yra 983 kv. m ploto sporto žaidimų salė, 25x14 m plaukymo baseinas. Įmonė turi šaudymo sporto bazę. Ji remia aviacijos technikos sporto klubą, rengiantį sklandymo ir parašiutizmo sporto entuziastus. Lietuvos ir Akmenės rajono pirmenybėse dalyvauja įmonės krepšinio, futbolo, tinklinio, šaudymo, šachmatininkų komandos.

EKONOMIKA IR FINANSAI

Įstatinio kapitalo struktūra

Įmonės bendras įstatinis kapitalas 100 proc.

tame tarpe: valstybinis kapitalas 90 proc.

akcinis kapitalas 10 proc.

For short rest in „Virvytė" - 160 places.

The places for rest operate in 9 shifts from June till September.

„Akmenės Cement" has a sports palace for its workers and their families. There is a big hall (983 sq. m.) for games, a swimming pool (25x14 m). It has a place for shooting. It suppors the aviation club training glider pilots and parachute jumpers. There are good basketball, football and voleyball teams, many chessplayers at the plant.

ECONOMICS AND FINANCE

Genaral regulations capital of the plant 100 %

including: state capital 90 %

capital of shares 10 %

PROFITABLENESS

1991 indexes

The profitableness of plant according to production costs 37 %

The profitableness of the plant's regulations capital 33 %

INCOME STRUCTURE AND RESOURCES 1991

Income resources	Income in thousand roubles	Income structure %
General income	274448,8	100
for cement	212161,3	77,3
for slate	18623,1	6,79
for asbestos cement pipes	16951,4	6,18
for other production	26713,0	9,73

EXPENSES STRUCTURE 1991 (%)

Expense	%
The whole costs	100
raw and basic materials	8
additional materials	5

Injektionen gemacht, zur Verfügung steht ein Stomatologe.

In der Stadt Naujoji Akmenė gibt es das Betriebssanatorium. Die Kranken werden hier von 34 Mitarbeitern des Gesundheitswesens (3Ärzten) bedient. Es funktionieren Physiotherapiezimmer, Moorbäder, Wasserheilverfahrenabteilung, Kabinette für kurative Körperkultur, Stomatologie, Heilverfahren, Entspannungsräume. 1991 hat das Betriebssanatorium 1480 Menschen aus „Zement von Akmenė" und anderen Betrieben der Stadt behandelt.

ERHOLUNGS-UND REHABILITATIONSBEDINGUNGEN DER WERKTÄTIGEN

Zur Erholung im Sommer hat das Unternehmen eigene Erholungsheime an der Ostsee und im Kurort Druskininkai, zur Erholung am Wochenende - am Fluss Virvytė, 30 km von Naujoji Akmenė entfernt.

Am Ostseestrand funktionieren folgende Erholungsstationen:

in Palanga - 80 Plätze,

in Pervalka (Neringa) - 20 Plätze,

in Rucava (Lettland) - 40 Plätze.

Im Kurort Druskininkai gibt es 16 Plätze, in „Virvytė" 160 Plätze. Erholugsstationen sind vom 1.Juni bis zum 1.September in 9 Schichten in Betrieb.

Für aktive Sportler steht der Sportpalast zur Verfügung. Da gibt es eine 983 m3 grosse Turnhalle , ein 25x14 m grosses Hal-

Rentabilumas

1991 m. rodikliai·

Įmonės rentabilumas pagal produkcijos savikainą 37 proc.

Įmonės įstatinio kapitalo rentabilumas 33 proc.

PAJAMŲ STRUKTŪRA IR ŠALTINIAI 1991 m.

Pajamų šaltiniai	Pajamų kiekis tūkst. rb	Pajamų struktūra proc.,
Bendrosios pajamos iš jų:	274448,8	100,
už cementą	212161,3	77,3
už šiferį	18623,1	6,79
už asbestcementinius vamzdžius	16951,4	6,18,
už kitą produkciją	26713,0	9,73

IŠLAIDŲ STRUKTŪRA 1991 m. (proc.)

Išlaidų pobūdis	Proc.
Visa įmonės savikaina tame tarpe	100
aliavos ir pagrindinės medžiagos	8
pagalbinės medžiagos	5
energetiniai resursai	60
darbo apmokėjimo lėšos	15
amortizacija	3
remonto ir kitos piniginės lėšos	6
negamybinės išlaidos	3

PELNAS IR JO PASKIRSTYMAS 1991 m.

Iš viso gauta pelno 1991 metais 73766 tūkst. rublių

Pelno panaudojimo tikslas	Proc.
Visi valstybiniai mokesčiai į biudžetą	40
pelno mokestis	30
palūkanos už valstybinio kapitalo naudojimą	12
Įmonei likęs pelnas	58
priskaičiuoti dividentai akcininkams	2
panaudotos labdaai,naujos technikos įsigijimui,projektavimo darbams	2
išmokėta premijų, įtjemų darbuotojams	10
sources of energy	60
wages	15
amortization	3
repair & other expenses	6
nonproduction expenses	3

PROFIT AND ITS DISTRIBUTION 1991

The whole profit in 1991 was 73766 thousand roubles

use of profit	%
All state tax for budget	42
including:	profit tax
interest for using state capital	12
The profit remaining at the plant	58
including: dividends for shareholders	2
charity,new technical devices,projects	2
premiums and bounties for workers	10
for social and cultural programms	8
reserve fund	14
reserve fund of share capital	22

TRADE UNIONS OF WORKERS

There is the trade union of construction workers at the state plant „Akmenė Cement". It consist of 1700 members. There are 29 organizations at differents departments.

The highest organ of the union is conference, taking place every 3 years.

Committees of primary organizations make reports on their work and are elected every 2 years.

The committee of trade union of the plant consists of 27 members, delegated by primary trade union organizations of other departments.

The chairman of the committee of plant's trade union Drąsutis

lenschwimmbad, einen Schiessplatz. Das Unternehmen unterstützt den Lufttechnikklub, der Segelflieger und Fallschirmspringer ausbildet. An Meisterschaften Litauens und des Bezirks Akmenė nehmen Fussball-, Basketball-, Volleyball-, Schiess-, Schachspielermannscnaften teil.

ÖKONOMIK UND FINANZEN

Struktur des Grundkapitals

Grundkapital des Unternehmens 100%
darunter:
Staatskapital 90%
Aktienkapital 10%

Einträglichkeit 1991

Einträglichkeit des Unternehmens
nach Produktionsselbstkosten 37%
Einträglichkeit des Grundkapitals 33%

STRUKTUR UND QUELLEN DER EINNAHMEN 1991

Quellen der Einnahmen	Einnahmenmenge tausend Rbl.	Struktur der Einnahmen %
Allgemeine Einnahmen	274448,8	100
darunter: für Zement	212161,3	77,3
für Schiefer	18623,3	6,79
für Asbestzementröhren	16951,4	6,18
für andere Produktionsarten	26713,0	9,73

AUSGABENSTRUKTUR 1991 (%)

Ausgabencharakter	%
Selbstkostenpreis des Unternehmens	100
darunter: Rohstoffe u. Hauptmaterialen	8
Hilfsmaterialien	5

panaudota įmonės socialinėms ir kultūrinėms programoms realizuoti	8
atsargos pelno rezervo fondas	14
akcinio kapitalo rezervo fondas	22

DARBUOTOJŲ PROFESINĖ SĄJUNGA

Valstybinėje įmonėje „Akmenės cementas" veikia Statybos ir statybinių medžiagų pramonės darbuotojų profsąjungos organizacija. Joje 1700 profesinės sąjungos narių. Įkurtos 29 pirminės (cechų, barų) organizacijos.

Aukščiausias profesinės sąjungos organizacijos organas - konferencija, šaukiama kas 3 metai. Pirminių organizacijų komitetai atsiskaito ir renkami kas 2 metai. Įmonės profesinės sąjungos komitete 27 nariai, deleguoti pirminių (cechų, barų) profsąjungos organizacijų.

Įmonės profsąjungos komiteto pirmininkas Drąsutis LAKAVIČIUS, išrinktas 1991 m. kovo 12 d.

ĮMONĖ IR MIESTAS

Darbininkų gyvenvietė 3 km nuo cemento gamyklos per 4 dešimtmečius išaugo į Naujosios Akmenės miestą, kuriame dabar gyvena 14 tūkstančių žmonių. Įmonės ir miesto ūkis glaudžiai susiję. Per daugelį metų įmonė pastatė 3180 butų ir individualių namų. Įmonė miestui tiekia šilumą ir karštą vandenį, eksploatuoja geriamo vandens verslovę. Daugelį metų „Akmenės cementas" atlieka arba finan-

LAKAVIČIUS was elected on March 12, 1991.

THE PLANT AND THE TOWN

The workers' settlement, 3 km from cement plant, grew into the town of Naujoji Akmenė during 4 decades. the population is 14 thousand at present. The economics of the plant and the town are tied together. In the period of years the plant has built 3180 flats and individual houses. The plant supplies the town with heat and hot water, operates drinking water enterprise.

In 1958 the plant built a palace of culture which became the center of the town's cultural life. All kinds of banks, folk music groups, choirs, performers, children's art studio find place for work, rehearsals and shows under its roof.

The plant „Akmenė Cement" operates a number of engineering networks, supports 3 secondary schools and the central hospital. The people of the town are allowed to make use of the plant's resting places. The town and people living in the vicinity can watch TV programms broadcasted via the transmitter set up by the plant.

The activity of the „Akmenė Cement" keeps in line with the directions of activity of other plants in the town. The state plant of construction materials in Naujoji Akmenė supplies the cement production with lime and clay, operates the pits and

Energiequellen	60
Mittel des Leistungslohnes	15
Amortisierung	3
Remont-und andere Geldmittel	6
nichtbetriebliche Ausgaben	3

DER ERTRAG UND VERTEILUNG 1991

Ertrag fürs Jahr 1991: 73766 tausend Rbl.

Ziel der Ertragsverwendung	%
Alle Staatssteuern des Budgets	42
darunter: Gewinnsteuer	30
Lombard-Zins für Gebrauch des Staatskapitals	12
Dem Unternehmen gebliebener Gewinn	58
darunter: Dividenden für Aktionäre	2
Wohltätigkeit, Automatisierung u. Mechanisierung, Projektierarbeiten u. Gratiszugaben den Mitarbeitern	10
Sozial-und Kulturprogramm	8
Gewinnreservefonds	14
Reservefonds des Aktienkapitals	22

GEWERKSCHAFT DER WERKTÄTIGEN

Im Unternehmen wirkt Gewerkschaft der Bau-und Baumaterialienindustrie. Sie umfasst 1700 Mitglieder. Es sind 29 Grundorganisationen gegründet.

Höchstes Organ der Gewerkschaft ist Konferenz (alle 3 Jahre).

Komitees der Grundorganisationen werden alee 2 Jahre gewählt Imm Komitee der Unternehmensgewerkschaft sind 27 Mitglieder aus Grundorganisationen.

suoja miesto valymo, gatvių asfaltavimo darbus, apšvietimą.
1958 metais įmonės pastatyti kultūros rūmai yra miesto kultūrinio gyvenimo centras, juose repetuoja ir koncertuoja choras, liaudies kapela, vokaliniai ansambliai, spektaklius ir koncertus rengia atvykstantys profesionalūs meniniai kolektyvai, veikia liaudies teatras, vaikų dailės studija.
„Akmenės cemento" įmonė nutiesė ir eksploatuoja daug miesto inžinerinių tinklų, teikia paramą mieste esančioms 3 vidurinėms mokykloms, rajono centrinei ligoninei. Miesto gyventojai turi galimybių naudotis cementininkų sanatorijos prifilaktoriumo paslaugomis, miesto ir jo apylinkių gyventojams iš cementininkų įrengto retransliatoriaus transliuojamos televizijos programos.
„Akmenės cemento" gamybinė veikla susijusi su kitų miesto įmonių veiklos profiliu. Naujosios Akmenės valstybinė statybinių medžiagų įmonė tiekia gamybai klintis ir molį, eksploatuoja karjerus ir atlieka daug rengimų remonto darbų. Valstybinė autotransporto įmonė specialiomis mašinomis cementą pristato Lietuvos teritorijoje esantiems klientams.
Keletas įmonės darbuotojų išrinkti Akmenės rajono Tarybos deputatais.

ĮMONĖ IR LIETUVA

„Akmenės cementas" jau daug metų yra viena iš didžiausių ir viena iš stabiliausiai dirbančių

provides repair of the equipments. The state transportation plant provides secial trucks for carrying cement to different places all over Lithuania.

THE PLANT AND LITHUANIA

For many years „Akmenė Cement" has been one of the biggest stable working plants in Lithuania, having a big importance to the economics of the whole state. The production of the plant can be met in different corners of Lithuania. Everything built or restored in Lithuania during the past 40 years couldn't do without Akmenė cement. One can mention Kaunas and Elektrėnai power stations, restoration of old towns, churches, theatres, health resorts, Klaipėda's port etc.
„Akmenė Cement" was one of the first plants in Lithuania that freed itself from the direct the Moscow rule. The plant gave financial help to Lithuanian SĄJUDIS and donated 20 thousand dollars to Lithuanian TV, destroyed by the Soviet army which occupied the TV tower on January 13, 1991.

THE PLANT AND THE WORLD

Since the very begining up to 1990 „Akmenė Cement" was integrated into the industry of building materials of former USSR and was one of the most progressive plants according to the Soviet standards. That's why

Der Vorsitzende des Gewerkschaftskomitees ist Drąsutis LAKAVIČIUS - LAKAVITSCHJUS, am 12.März 1991 gewählt.

DAS UNTERNEHMEN UND DIE STADT

Arbeitersiedlung in 3 km vom Zementherstellungsunternehmen ist in 4 Jahrzehnten zur Stadt Naujoji Akmenė geworden, die heutzutage 14 tausend Menschen zählt. Die Wirtschaft der Stadt und des Unternehmens sind eng verbunden. In den vielen Jahren hat das Unternehmen 3180 Wohnungen und Einfamilienhäuser gebaut. Es liefert Heizung und Heisswasser der Stadt. Seit vielen Jahren führt es durch und finanziert die Arbeiten der Stadtreinigung, Strassenasphaltierung und- beleuchtung.
Der 1958 vom Unternehmen gebaute Kulturpalast ist zum Zentrum des Kulturlebens der Stadt geworden. Dort arbeiten: Chor, Volkskapelle, Vokalensembles, Volkstheater, Kinderkunstschule. Ihre Vorstellungen und Konzerte veranstalten zur Gastrolle kommende Schauspielerkollektive, Kulturgruppen.
Das Unternehmen hat das Ingenieurnetz der Stadt gebaut und betreibt es, leistet den 3 Mütelschulen, dem Zentralkrankenhaus des Bezirks Beihilfe. Die Stadteinwohner dürfen das Betriebssanatorium besuchen, Fernsehsendungen beobachten, die vom Unternehmen eingerichteter Fernsehzubringer überträgt.

Lietuvos gamyklų, reikšminga visos valstybės ekonomikai. Akmenės cementininkų darbo pėdsakus šiandien aptiksi visuose Lietuvos kampeliuose. Kauno hidroelektrinė ir Elektrėnų šiluminė elektrinė, restauruoti senų miestų kvartalai ir bažnyčios, teatrai ir kurortai, Klaipėdos uostas - visa, kas per pastaruosius 40 metų Lietuvoje pastatyta ar restauruota, daryta naudojant Akmenės cementą.

„Akmenės cementas" buvo viena iš pirmųjų tiesiogiai Maskvai pavaldžių Lietuvos įmonių, išsivadavusių iš TSRS diktato ir perėjusių į Lietuvos reguliavimo sferą. Įmonė materialiai parėmė Lietuvos Sąjūdį jo kūrimosi metais, skyrė 20 tūkst. dolerių okupacinės TSRS kariuomenės nuniokotai po 1991 m. sausio 13 - osios Lietuvos televizijai.

ĮMONĖ IR PASAULIS

Nuo pat pradžios iki 1990 metų „Akmenės cementas" buvo tvirtai integruotas į buvusios TSRS statybinių medžiagų pramonę kaip viena stambiausių ir pagal TSRS lygi viena pažangiausių cemento gamyklų. Suprantama, kad įmonėje dirba TSRS pagaminti įrengimai, iš ten iki šiol gaunama žaliavų, remonto medžiagų. Savo ruožtu ilgą laiką daugiau kaip pusė Akmenėje pagaminto cemento buvo tiekiama kitoms buvusioms TSRS respublikoms ir sritims. Atkūrus nepriklausomą Lietuvos valstybę, su buvusios TSRS įmonėmis for-

there work eguipments made in the USSR and some raw materials or the materials used for repair are brought from there. For a long time more than a half of the cement produced in Akmenė had been sent to other republics of the former USSR. After the restoration of the independent Lithuanian State useful trade and exchange are encouraged on both sides.

A number of workers from cement plants of Cuba, Vietnam, Iraq and other states used to work probation or improve their skills at „Akmenė Cement". At the same time 37 workers from the plant worked in cement produstion in Egypt, Cuba, Iraq, Bulgaria, Poland, Mali, Yemen, Mongolia.

Small quantities of „Akmenė Cement" production has been exported to Poland and Yugoslavia for a long time. Since 1988 its cement has been exported to Finland, later - to Sweden. There are connections with German cement plants and firms, Export of cement from Akmenė has all the possibilities to expand.

THE MOST IMPORTANT MOMENTS FROM THE HISTORY OF „AKMENĖ CEMENT"

27. 12 1945 - decision to build a cement plant in Lithuania

11. 09. 1946 - the beginning of the project

1947 - beginning of construction in the village of Karpėnai, building of the railway

Die Betriebstätigkeit ist eng mit den anderen Stadtbetrieben verbunden. „Zement von Akmenė" bekommt Kalkstein und Ton vom Baumaterialienbetrieb, der auch Einrichtungenreparatur durchführt, Gruben betriebt. Staatliches Transportunternehmen liefert den Kunden Litauens Zement.

Einige Werktätige sind Deputierte des Bezirksowjets von Akmenė.

AS UNTERNEHMEN UND LITAUEN

„Zement von Akmenė" zählt seit vielen Jahren zu den grössten und stabilsten Unternehmen Litauens, das auch für die Staatswirtschaft bedeutend ist. Die Arbeitsspuren der Mitarbeiter kann man überall in Litauen finden. Pumpspeicherwerk von Kaunas, Wärmekraftwerk von Elektrėnai, restaurierte Kirchen, Theater, Wohnviertel der alten Städte und Kurorte, Hafen von Klaipėda - das ist alles, was mit Zement von Akmenė in 40 Jahren geleistet wurde.

„Zement von Akmenė" war eines der ersten Unternehmen, das sich von der Zustandigkeit Moskaus befreit hat. Es hat der nationalen Befreiunsbewegung Litauens „Sąjūdis" in ihren Gründungsjahren materiell geholfen, 20 tausend Dollar dem am 13. Januar 1991 von der Sowjetarmee verwüsteten Fernsehen ausgezahlt.

DAS UNTERNEHMEN UND DIE WELT

Vom Bauanfang an bis zum Jahre 1990 war „Zement von

ıuojasi abipusiškai naudingi rekybos ir mainų santykiai.
lkmenėje yra stažavęsi ir kėlę valifikaciją Irako, Kubos, Vietamo ir kitų valstybių cemento ımyklų darbininkai bei speciastai. Savo ruožtu 37 „Akmenės ɜmento" darbininkai ir speciastai yra dirbę įsisavinant ceento gamybos pajėgumus gipto, Mali, Kubos, Irako, 'ongolijos, Jemento, Bulgaris, Lenkijos gamyklose.
u seniau „Akmenės cemento" odukcija nedideliais kiekiais ɜvo eksportuojama į Jugoslavi- Lenkiją. Nuo 1988 metų Akenėje pagamintas cementas sportuojamas į Suomiją, vėu - į Švediją. Dalykiniai ryšiai megzti su Vokietijos cemento myklomis ir firmomis. Ceɜnto eksportas iš Amenės turi 'imybių plėstis.

SVARBESNI „AKMENĖS CEMENTO" ISTORIJOS PUSLAPIAI

15. VII. 27 - priimtas nutari's statyti cemento gamyklą 'tuvoje.
16. IX. 11 - įmonės darbų pra- ı.
17 m. - pradėti statybos darbai pėnų kaime, tiesiamas gele- ɛelis.
'O m. - pradėti Karpėnų klinkarjero atidengimo darbai.
2. IX. 2O - paleista pirmoji ımoji krosnis.
3. XI - paleista antroji suka- 'i krosnis.
6 m. - atlikta abiejų techno- ıių linijų rekonstrukcija, na-

1950 - beginning to operate Karpėnai limestone pit
20. 09. 1952 - the first rotatory furnace starts working
1956 - reconstruction of both technological lines, increase of efficiency 40 %, the plant starts stable operation
09. 1959 - the construction of the 3rd cement production line is finished
15. 07. 1961 - the 4th rotatory furnace started working
1963 - the plant of asbestos cement is built, producing ruffled slate
1964 - beginning to produce asbestos cement tubes. Oil is used for fuel instead of shale
02. 1967 - the beginning of the construction of 5th and 6th cement technological lines
10. 1969 - the construction of 5th technological line is finished
06. 1970 - 6th rotatory furnace begins to work
08. 1974 - 7th rotatory furnace begins to work
11. 1974 - 8th rotatory kiln begins to work, construction of 2nd cement plant is over
1975 - the plant reaches the efficiency of 3 mln. tons a year
1988 - Akmenė starts cement export to Finland
1990 - the plant gets into Lithuanian jurisdiction

Akmenė" fest die Baumaterialienwirtschaft der SU intergriert, als eines der grössten und besten in der damalige UdSSR. Selbstverständlich werden hier die in der SU hergestellte Einrichtungen und Anlagen betrieben, Rohstoffe benutzt. Lange Zeit ging die Hälfte der Zementlieferungen an ehemalige Sowjetrepubliken. Beim Wiederaufbau des unabhängigen Litauens bilden sich eiträgliche Handels- und Umtauschbeziehungen heraus.
In Akmenė haben Arbeiter der Zementherstellungsunternehmen und Fachleute aus Irak, Kuba, Vietnam u.a. Staaten Weiterausbildung bekommen. 37 Mitarbeiter aus dem litauischen Betrieb haben in Ägypten, Mali, Kuba, Mongolei, Jemen, Bulgarien, Polen gearbeitet.
Schon früher hat man die Produktion von „Zement von Akmenė" in kleinen Mengen an Jugoslawien, Polen, vom Jahr 1988 an Finnland, später an Schweden geliefert.
Das Unternehmen hat Fachbeziehungen mit Zementherstellungunternehmen und Firmen Deutschlands aufgenommen. Zementausfuhr hat gute Möglichkeiten.

WICHTIGERE SEITEN DER GESCHICHTE „ZEMENT VON AKMENĖ"

1945.07.27 - Beschluss zum Bau des Zementherstellungsunternehmens in Litauen.
1946.09.11 - Anfang der Projektierungsarbeiten.

šumas padidėja 40 proc., įmonė pradeda dirbti stabiliai.
1959. IX - baigta 3-iosios technologinės cemento gamybos linijos statyba.
1961. VII. 15 - paleista 4-oji sukamoji krosnis.
1963 m. - pastatyta asbestcemenčio gamykla, pradėta banguoto šiferio gamyba.
1964 m. - pradėti gaminti asbestcemenčio vamzdžiai. Kurui vietoj skalūnų imtas naudoti mazutas.
1967. II - pradėta 5-osios ir 6-osios cemento technologinių linijų statyba.
1969. X - baigta 5-osios technologinės linijos statyba.
1970, VI - paleista 6-oji sukamoji krosnis.
1974. VIII - baigta montuoti ir paleista 7-oji sukamoji krosnis.
1974. XI - paleista 8-oji sukamoji krosnis, baigta 2-osios cemento gamyklos statyba.
1975 m. - įmonė pasiekia 3 mln. tonų cemento per metus našumą.
1988 m. - Akmenės cementas pradedamas eksportuoti į Suomiją.
1990 m. - įmonė tampa pavaldi Lietuvos Respublikai.

1947 - Beginn der Bauarbeiten im Dorf Karpėnai, Eisenbahnlegung.
1950 - Eröffnung der Kalksteingrube von Karpėnai.
1952.09.20 - Anlassen des ersten Drehrohrofens,
1953.11 - Anlassen des zweiten Drehrohrofens.
1956 - Rekonstruktion der beiden Technologielinien. Hebung der Arbeitsproduktivität zu 40%.
1959.09 - Ende der bauarbeiten der 3. technologischen Linie.
1961.07.15 - Anlassen des ė. Drehrohrofens.
1963 - Bauende des Asbestzementbetriebs, Anfang der Wellenschieferherstellung
1964 - Beggin der Herstellung von Asbestzementröhren. Masut gebrauch man als Brennstoff.
1967.02 -Baubeginn der 5. und 6. Zementherstellungslinien.
1969.10 - Anlassen der 5. technologischen Linie.
1970.06 - Anlassen des 6. Drehrohrofens.
1974.08 - Anlassen des 7. Drehrohrofens.
1974.11 - Anlassen des 8. Drehrohrofens, des 2. Zementbetriebs.
1975 - Hebung der Arbeitsproduktivität bis 3 Mill. t Zement pro Jahr.
1988 - Zementausfuhrbeginn nach Finnland.
1990 - Zuständigkeit des Unternehmens der Lit. Republik.

"AKMENĖS CEMENTAS", Naujoji Akmenė, 5464, Lithuania Tel. (8 - 295) 54140, 54995, 54097, Fax (8 - 295) 52198

Printed in Finland by Erweko 1992

B-9

Curriculum Vitae For
F.C. Stevens and F.A. Phillips

Frank C. Stevens
President
Stevens Consulting Company
13688 Oak Mountain Drive
Yucalpa, California, 92399
Tel: 909-790-4033 Fax: 909-790-4031

SUMMARY

Qualified and experienced for consulting world wide on all phases of businesses connected with cement, concrete, construction, industrial minerals, alternative fuels, enviromental and energy. Handled mergers and acquisitions. Managed as President and CEO, companies connected with aggregates,cement concrete, oil and gas exploration, coal mining, transportation, and waste fuels.

RESUME

January 1991
To Present

CEMEX, Monterrey México

Consultant and technical adviser to CEMEX, fourth largest cement company in the world with 19 plants in Mexico, 12 plants in Spain, and large cement and concrete activities in the United States. Performed many assignments in transfer and use of cement manufacturing technology, and enviromental improvements. First in Mexico to use alternatives and waste fuels in cement kilns. Developed the Department of Energy covering fuels, electricity and enviromental, Trained personnel, in all phases including engineering, construction, procurement, and studies. Worked with other divisions for activities in Mexico, Spain and United States.

January 1985
to December 1990

Continental Cement Company, Hannibal Missouri

President and CEO of 650,000 tons per year cement plant with four distribution terminal on inland water ways. Turned company around, reduced costs, and increased sales. Started the first waste fuel facility in Missouri in 1986, utilizing latest and new technology for using liquids, sludges and solids fuels in wet process kiln. In 1990 as a consultant, started a waste fuel facility in Australia.

September 1980
to December 1984

Stanford Research Institute (SRI)
Menlo Park California

Senior Management Consultant and Senior Industrial Economist for one of the best consulting organizations in the world. Performed many studies and assisted clients around the world including United States, Europe and Asia. Scope of reports and assignments covered manufacturing plants, energy projects (fuel and electricity), industrial minerals, enviromental projects, cement, concrete, construction, mergers, and acquisitions. Performed in-house management and improvement studies that resulted in increased profits for clients.

January 1980 to
August 1980

Special Assigment Activities for Unicem, Turin Italy

July 1970 to
December 1980

River Cement Company, St. Louis, Missouri

President, CEO, and Director of River Cement Company, Vice president of Missouri Pacific Corporation (Parent Company), Chariman and CEO of four ready-mix concrete companies and Chairman of River Corporation (gas and oil exploration and development). River Cement had annual production of 1.2 million tons per year using 2 dry process kilns in a highly automated, low cost, and profitable company with five distribution terminals on inland water system. Parent company owned the Misssouri Pacific Railroad, and Mississippi River Gas Transmission Company. Built the cement plant and terminals when Vice President Operations of River Cement in1963 to 1968.

September 1968 to
July 1970

Medusa Corporation, Cleveland Ohio

Vice President Operations and Engineering in charge of 6 cement plants producing grey cement, white cement, expansive cement and special products, and limestone aggregates. Expanded the facilities, reduced costs and increased production.

Other major Activities
1945 to 1968

- Build River Cement Company in Missouri

- Vice President Operations Lake Ontario Cement Company, Toronto Canada. Rebuilt and expanded cement plant and aggregate plant.

- Started career at Riverside Cement Company in research and quality control. Production manager. Built waste heat power plant (15 megawatts).Added kilns and mills to plants. Conducted other special assignments resulting in cost reduction and production increases.

Personal and other Information

- Married to Elisabeth with three grown children.
- Graduate Harvard Business Schools, Advanced Management Program in 1975.
- Graduate Texas A & M Electrical Engineering and U.S. Navy Electronics Program in 1943 and 1944.
- Graduate Riverside City College in Chemical Engineering in 1942.
- Aviation Electronics Officer in U.S. Navy (active duty and organized reserve) 1942 to 1947.
- Active in community affairs including President of Rotary Clubs in California and Canada.
- Participated in Portland Cement Association as Chairman of Research and Development Committee1976 through 1978, Chairman General Technical Committee 1974 through 1976. Member of Waste Management Task Force, Washington Affairs, Energy Task Force and on the Board of Directors 1970 through 1978.

FCS.
Nov.1993

Franklin A. Phillips

Education

B.S. Physiology (Pre-Medical) from Southern Illinois University at Carbondale.

Graduate studies in Chemistry at the University of Houston, Texas.

Masters in Business Administration from Lindenwood College in St. Charles, Missouri,

Current Position

President of Phillips Environmental Training and Resource Associates Inc., a firm specializing in hazardous waste, emergency response, safety, and transportation programs and training for industry compliance with regulations

Mr. Phillips is certified as an Environmental Trainer, and as a Hazardous Materials Manager.

Experience

Background of hazardous waste treatment, storage, and disposal facility services including permitting, waste analysis plans, trial burns, emergency response training, air quality, stormwater best management practices plans , corrective action cleanups, and risk assessments. Positions included Environmental Manager, Safety Director , and Chemist.

Technical liaison with EPA Region & for RCRA hazardous waste industrial incineration trial burn and Part B Permit at McDonnell Douglas Corporation.

30